

Package ‘AQuadtree’

July 21, 2025

Title Confidentiality of Spatial Point Data

Version 1.0.4

Date 2023-07-12

Depends R (>= 3.3.2), methods, stats, sp (>= 2.0-0), dplyr,

Description Provides an automatic aggregation tool to manage point data privacy, intended to be helpful for the production of official spatial data and for researchers. The package pursues the data accuracy at the smallest possible areas preventing individual information disclosure. The methodology, based on hierarchical geographic data structures performs aggregation and local suppression of point data to ensure privacy as described in Lagonigro, R., Oller, R., Martori J.C. (2017) <[doi:10.2436/20.8080.02.55](https://doi.org/10.2436/20.8080.02.55)>. The data structures are created following the guidelines for grid datasets from the European Forum for Geography and Statistics.

License MIT + file LICENSE

Suggests sf, knitr, devtools, rmarkdown

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

VignetteBuilder knitr

NeedsCompilation no

Author Raymond Lagonigro [aut, cre] (ORCID: <<https://orcid.org/0000-0002-8091-4296>>),
Ramon Oller [aut] (ORCID: <<https://orcid.org/0000-0002-4333-0021>>),
Joan Carles Martori [aut] (ORCID: <<https://orcid.org/0000-0002-8400-5487>>)

Maintainer Raymond Lagonigro <raymond.lagonigro@uvic.cat>

Repository CRAN

Date/Publication 2023-07-19 08:50:06 UTC

Contents

AQuadtree-package	2
-----------------------------	---

AQuadtree-class	3
area.QT	6
BarcelonaCensusTracts	6
BarcelonaPop	7
CharlestonCensusTracts	7
CharlestonPop	8
createAQuadtree	8
createGrid	11
joinAQuadtree	12
merge,AQuadtree,data.frame-method	13
plot,AQuadtree,missing-method	14
pointsToAQuadtree	15
print,AQuadtree-method	16
show,AQuadtree-method	16
spatialPointsCellCodes	17
splitCellNum	18
spplot,AQuadtree-method	20
summary,AQuadtree-method	20
[,AQuadtree-method	21
[<-,AQuadtree-method	22
Index	23

AQuadtree-package	<i>AQuadtree: A package to anonymise spatial points data.</i>
-------------------	---

Description

This package provides an S4 class for creating, manipulating and exporting spatial quadtree varying size grids, and for methods including print/show, plot, spplot, subset, [, [[, names, dim, summary, write.

Introduction

The quadtree functions and class provide the tools to build a varying size quadtree grid performing a bottom-up aggregation considering a minimum threshold for each the cell. The main goal of the package is the anonymization of a set of spatial point data by an aggregation process as in a k-anonymity model. The grid created follows the INSPIRE Specification on Geographical Grid Systems.

Author(s)

Maintainer: Raymond Lagonigro <raymond.lagonigro@uvic.cat> ([ORCID](#))

Authors:

- Ramon Oller <ramon.oller@uvic.cat> ([ORCID](#))
- Joan Carles Martori <martori@uvic.cat> ([ORCID](#))

References

D2.8.I.2 INSPIRE Specification on Geographical Grid Systems – Guidelines https://inspire.ec.europa.eu/documents/Data_Specifications/INSPIRE_Specification_GGS_v3.0.1.pdf

EEA reference grid dataset https://data.europa.eu/euodp/data/dataset/data_eea-reference-grids-2

AQuadtree-class	Class "AQuadtree".
-----------------	--------------------

Description

An S4 class representing a Quadtree hierarchical geographic Grid to anonymise spatial point data.

Objects can be created by calls to the function [AQuadtree](#)

Wrapper function AQuadtree.

Usage

```
AQuadtree(
  points,
  dim = 1000,
  layers = 5,
  colnames = NULL,
  threshold = 100,
  thresholdField = NULL,
  funs = NULL,
  ineq.threshold = 0.25,
  loss.threshold = 0.4
)
```

Arguments


points	object of class "SpatialPoints" or "SpatialPointsDataFrame".
dim	a single integer specifying the initial cell sizes in meters, defaults to 1000.
layers	a single integer specifying the number of divisions of the initial cells, defaults to 5.
colnames	character string or character string vector specifying the columns to summarise in the resulting quadtree.
threshold	number. The threshold minimum value each cell must have in the column thresholdField.
thresholdField	character string specifying the column at which the threshold value will apply.
funs	character string or character string vector specifying the summary functions for each of the colnames. If vector, the size must be the same as colnames.
ineq.threshold	inequality threshold value to be considered on the disaggregation process. Forces disaggregation under the given inequality threshold.
loss.threshold	loss threshold value to be considered on the disaggregation process. Forces aggregation when there's much loss (i.e loss rate > ineq.threshold).

Details

Given a set of points, the AQuadtree class represents a varying size Quadtree grid created performing a bottom-up aggregation considering a minimum threshold for each cell. Cells with a value under the threshold for the thresholdField are aggregated to the upper level in a quadtree manner.

When no thresholdField is given, total number of points in the cell will be used, and so, given a threshold of k, none of the cells in the resulting grid have a value less than k individuals as in a k-anonymity model.

The Quadtree produced balances information loss and accuracy. For instance, for the set of cells in the left image, where numbers in the cells represent the values in the thresholdField, using a threshold value of 100, the resulting Quadtree will be the one on the right. As we can see, some cells will be discarded, and some aggregated to maintain as much information as possible, keeping at the same time as much disaggregation as possible



The INSPIRE coding system for cell identifiers will be used to generate a CellCode and CellNum for each cell in the Quadtree. The objective of the coding system is to generate unique identifiers for each cell, for any of the resolutions.

The cellCode is a text string, composed of cell size and cell coordinates. Cell codes start with a cell size prefix. The cell size is denoted in meter (m) for cell sizes below 1000 m and kilometre (km) for cell sizes from 1000 m and above.

Example: a 100 meter cell has an identifier starting with “100m”, the identifier of a 10000 meter cell starts with “10km”.

The coordinate part of the cell code reflects the distance of the lower left grid cell corner from the false origin of the CRS. In order to reduce the length of the string, Easting (E) and Northing (N) values are divided by 10^n (n is the number of zeros in the cell size value). Example for a cell size of 10000 meters: The number of zeros in the cell size value is 4. The resulting divider for Easting and Northing values is $10^4 = 10000$.

The CellNum is a sequence of concatenated integers identifying all the hierarchical partitions of the main cell in which the point resides. For instance, the CellNum of the top right cell would be 416 (fourth in first partition, sixteenth in second partition)

The input object must be projected and units should be in 'meters' because the system uses the INSPIRE coding system.

function to create an object of class AQuadtree

Value

AQuadtree object representing a varying size Quadtree aggregation for the given points.

Slots

```
dim = "numeric"
layers = "numeric",
colnames = "character",
threshold = "numeric",
thresholdField = "character",
loss = "numeric"
```

See Also

- D2.8.I.2 INSPIRE Specification on Geographical Grid Systems – Guidelines https://inspire.ec.europa.eu/documents/Data_Specifications/INSPIRE_Specification_GGS_v3.0.1.pdf
- EEA reference grid dataset https://data.europa.eu/euodp/data/dataset/data_eea-reference-grids-2

Examples

```
data("BarcelonaPop", "BarcelonaCensusTracts")
aquadtrees.Barcelona<-AQuadtree(BarcelonaPop, layers = 3)
plot(aquadtrees.Barcelona)

aQuadtree.Charleston<-AQuadtree(CharlestonPop, colnames="sex", threshold=17,
  thresholdField=c("sex.male", "sex.female"))

## Not run:
## spatial object not projected
sp.not.projected<-spTransform(CharlestonPop,CRS("+proj=longlat +datum=NAD27"))
is.projected(sp.not.projected)
aqt<-AQuadtree(sp.not.projected)

## not an SpatialPoints object
aqt<-AQuadtree(CharlestonCensusTracts)

## too many subdivisions
aqt<-AQuadtree(CharlestonPop, layers=15)

## End(Not run)
```

area.QT	<i>area.QT AQuadtree-method</i>
---------	---------------------------------

Description

Method area.QT

Usage

```
area.QT(obj, residual = TRUE, ...)

## S4 method for signature 'AQuadtree'
area.QT(obj, residual = FALSE, ...)
```

Arguments

- obj an object of class AQuadtree.
- residual logical; if TRUE cells marked as residual cells are included
- ... passed through.

Details

Get the areas of the Quadtree grid cells in square meters

Value

area of Quadtree grid cells in square meters

BarcelonaCensusTracts	<i>Census tract borders of Barcelona city in Catalonia.</i>
-----------------------	---

Description

A SpatiaPolygons object containing the Census tract borders of Barcelona city in Catalonia.

Usage

BarcelonaCensusTracts

Format

A SpatialPolygons object

BarcelonaPop

Radomly created population points for Barcelona city in Catalonia.

Description

A dataset containing randomly created population for the Barcelona city in Catalonia for the year 2018. Population has been created randomly with the real distributions of census tracts from the dataset dividing the total population by 20 (https://ajuntament.barcelona.cat/estadistica/catala/Estadistiques_per_temes/Poblacio_i_demografia/Poblacio/Padro_municipal_habitants/a2018/edat/index.htm).

Usage

BarcelonaPop

Format

A SpatialPointsDataFrame with 81359 rows and 2 attributes:

age age the individual

sex sex of the individual as a factor with levels: "man", "woman"

CharlestonCensusTracts

Census tract borders of Charleston, SC MSA, USA.

Description

A SpatialPolygons object containing the Census tract borders of Charleston, SC MSA, USA.

Usage

CharlestonCensusTracts

Format

A SpatialPolygons object with 117 polygons

CharlestonPop

Radomly created population points for Charleston, SC MSA, USA.

Description

A dataset containing randomly created population for Charleston, SC MSA, USA. Population has been created randomly with distributions of census tracts from the dataset Charleston1, 2000 Census Tract Data for Charleston, SC MSA and counties

Usage

```
CharlestonPop
```

Format

A SpatialPointsDataFrame with 54619 rows and 3 attributes:

age group age the individual as a factor with levels: "under16", "16_65", "over65"

sex sex of the individual as a factor with levels: "male", "female"

origin origin of the individual as a factor with levels: "asian", "black", "hisp", "multi_ra", "white"

See Also

<https://spatial.uchicago.edu/sample-data>

createAQuadtree

Create a Quadtree grid to anonymise spatial point data

Description

createAQuadtree returns a SpatialPointsDataFrame representing a Quadtree hierarchical geographic dataset. The resulting grid contains varying size cells depending on a given threshold and column. with identifiers A cellCode and cellNum is created for each cell as in INSPIRE Specification on Geographical Grid Systems.

Usage

```
createAQuadtree(
  points,
  dim = 1000,
  layers = 5,
  colnames = NULL,
  threshold = 100,
  thresholdField = NULL,
  funs = NULL,
```



```

    as = "Spatial",
    ineq.threshold = 0.25,
    loss.threshold = 0.4
  )

```

Arguments


points	object of class "SpatialPoints" or "SpatialPointsDataFrame".
dim	a single integer specifying the initial cell sizes in meters, defaults to 1000.
layers	a single integer specifying the number of divisions of the initial cells, defaults to 5.
colnames	character or character vector specifying the columns to summarise in the resulting quadtree. For columns of class factor, a column for each factor level will be created.
threshold	number. The threshold minimum value each cell must have in the column thresholdField.
thresholdField	character or character vector specifying the columns to which the threshold value will apply. If not specified, threshold value will be applied over the total cell points number. ThresholdField must be one of the colnames.
funcs	character or character vector specifying the summary functions for each of the colnames. If vector, the size must be the same as colnames.
as	character indicating return type, if "AQuadtree" a quadtree class element will be returned, otherwise a SpatialPolygonsDataFrame will be returned. Defaults to "Spatial".
ineq.threshold	inequality threshold value to be considered on the disaggregation process. Forces disaggregation under the given inequality threshold.
loss.threshold	loss threshold value to be considered on the disaggregation process. Stops disaggregation when there's much loss (i.e loss rate > ineq.threshold).

Details

Given a set of points a varying size Quadtree grid is created performing a bottom-up aggregation considering a minimum threshold for each cell. Cells with a value under the threshold for the thresholdField are aggregated to the upper level in a quadtree manner.

When no thresholdField is given, total number of points in the cell will be used, and so, given a threshold of k, none of the cells in the resulting grid have a value less than k individuals as in a k-anonymity model.

The Quadtree produced balances information loss and accuracy. For instance, for the set of cells in the left image, where numbers in the cells represent the values in the thresholdField, using a threshold value of 100, the resulting Quadtree will be the one on the right. As we can see, some cells will be discarded, and some aggregated to maintain as much information as possible, keeping at the same time as much disaggregation as possible



The INSPIRE coding system for cell identifiers will be used to generate a cellCode and cellNum for each cell in the Quadtree. The objective of the coding system is to generate unique identifiers for each cell, for any of the resolutions.

The cellCode is a text string, composed of cell size and cell coordinates. Cell codes start with a cell size prefix. The cell size is denoted in meter (m) for cell sizes below 1000 m and kilometre (km) for cell sizes from 1000 m and above.

Examples: a 100 meter cell has an identifier starting with “100m”, the identifier of a 10000 meter cell starts with “10km”.

The coordinate part of the cell code reflects the distance of the lower left grid cell corner from the false origin of the CRS. In order to reduce the length of the string, Easting (E) and Northing (N) values are divided by 10^n (n is the number of zeros in the cell size value). Example for a cell size of 10000 meters: The number of zeros in the cell size value is 4. The resulting divider for Easting and Northing values is $10^4 = 10000$.

The cellNum is a sequence of concatenated integers identifying all the hierarchical partitions of the main cell in which the point resides. For instance, the cellNum of the top right cell would be 416 (fourth in first partition, sixteenth in second partition)

The input object must be projected and units should be in 'meters' because the system uses the INSPIRE coding system.

Value

SpatialPolygonsDataFrame representing a varying size Quadtree aggregation for the given points.

See Also

- D2.8.I.2 INSPIRE Specification on Geographical Grid Systems – Guidelines https://inspire.ec.europa.eu/documents/Data_Specifications/INSPIRE_Specification_GGS_v3.0.1.pdf

- EEA reference grid dataset https://data.europa.eu/euodp/data/dataset/data_eea-reference-grids-2

Examples

```
data("CharlestonPop")
aQuadtree.Charleston<-createAQuadtree(CharlestonPop, threshold=10,
  colnames="sex", thresholdField=c("sex.male", "sex.female"))
```

createGrid

Create a Grid grid covering a given geographic zone.

Description

createGrid returns a SpatialPolygons object representing a grid covering a given geographic zone following the INSPIRE Specification on Geographical Grid Systems. Each polygon will be identified with it's CellCode code.

Usage

```
createGrid(zone, dim = 1000, intersect = TRUE, outline = FALSE)
```

Arguments

zone	object of class "SpatialPoints", "SpatialPointsDataFrame", "SpatialPolygons" or "SpatialPolygonsDataFrame" specifying the zone to be covered by the grid.
dim	a single integer specifying the initial cell sizes in meters, defaults to 1000.
intersect	logical, if TRUE the resulting grid will be intersected with the given zone. If zone is of class SpatialPoints, only cells containing points will be kept on the resulting grid. If zone is of class SpatialPolygons, only cells inside or partially inside polygons in zone will be kept on the resulting grid. Defaults to TRUE
outline	logical, if TRUE the resulting grid will be clipped with the outlines of the given zone. Only applicable if zone is of class SpatialPolygons. Defaults to FALSE

Details

INSPIRE Specification on Geographical Grid Systems

The objective of the coding system is to generate unique identifiers for each point, for any of the recommended resolutions.

The cellCode is a text string, composed of cell size and cell coordinates. Cell codes start with the cell's size prefix. The cell size is denoted in meter (m) for cell sizes below 1000m and kilometre (km) for cell sizes from 1000m and above.

Examples: a 100 meter cell has an identifier starting with "100m", the identifier of a 10000 meter cell starts with "10km".

The coordinate part of the cell code reflects the distance of the lower left grid cell corner from the false origin of the CRS. In order to reduce the length of the string, Easting (E) and Northing (N) values are divided by 10^n (n is the number of zeros in the cell size value). Example for a cell size

of 10000 meters: The number of zeros in the cell size value is 4. The resulting divider for Easting and Northing values is $10^4 = 10000$.

Value

SpatialPolygons dataset representing a grid with squared cells of the given size.

See Also

- D2.8.I.2 INSPIRE Specification on Geographical Grid Systems – Guidelines https://inspire.ec.europa.eu/documents/Data_Specifications/INSPIRE_Specification_GGS_v3.0.1.pdf
- EEA reference grid dataset https://data.europa.eu/euodp/data/dataset/data_eea-reference-grids-2

Examples

```
data("BarcelonaPop")
BarcelonaPop.INSPIRE_GRID<-createGrid(BarcelonaPop)
plot(BarcelonaPop.INSPIRE_GRID)

## Not run:
BarcelonaPop.INSPIRE_GRID.10km<-createGrid(BarcelonaPop, 10000, intersect=FALSE)
plot(BarcelonaPop.INSPIRE_GRID.10km)

data("BarcelonaCensusTracts")
Barcelona.INSPIRE_GRID<-createGrid(BarcelonaCensusTracts, outline=TRUE)
plot(Barcelona.INSPIRE_GRID)

## End(Not run)
```

joinAQuadrees

Join two AQuadtree objects from the same area, to compare their data

Description

Given two objects of class AQuadtree for the same area, wich, for instance, may contain data from two different periods, joinAQuadrees returns a new object of class AQuadtree with the common zones at the lowest shared level, summarising the data from both AQuadrees.

Usage

```
joinAQuadrees(qt1, qt2, withResiduals = FALSE, mean.1 = NULL, mean.2 = NULL)
```

Arguments

qt1	object of class "AQuadtree" containing the first object to join.
qt2	object of class "AQuadtree" containing the second object to join.
withResiduals	logical indicating if residual cells should be maintained (TRUE) or not (FALSE, default).
mean.1	character or character vector specifying the columns in the first AQuadtree to which a weighted mean should be computed. By default the aggregation function used is sum.
mean.2	character or character vector specifying the columns in the first AQuadtree to which a weighted mean should be computed. By default the aggregation function used is sum.

Details

The function `joinAQuadtrees` creates a new AQuadtree object from two given AQuadtree objects with data from the same area. The data of the two given objects is summarised at the smallest possible cells shared by both given objects. All the input data is maintained on the new created object. This function can be used to join the different attributes from the same area or information from different periods.

Value

AQuadtree with the information of the two given objects summarised at the lowest level shared by both objects.

Examples

```
data("CharlestonPop")
CharlestonPop.AQT_1<-AQuadtree(CharlestonPop, layers = 2)
CharlestonPop.AQT_2<-AQuadtree(CharlestonPop, colnames="sex",
                               thresholdField=c("sex.male", "sex.female"), layers = 2)
CharlestonPop.AQT_1_2<-joinAQuadtrees(CharlestonPop.AQT_1, CharlestonPop.AQT_2)

## Not run:
## non AQuadtree objects
joinAQuadtrees(CharlestonPop, CharlestonCensusTracts)

## End(Not run)
```

merge,AQuadtree,data.frame-method

Merge an AQuadtree object with a data.frame

Description

Method merge.

Usage

```
## S4 method for signature 'AQuadtree,data.frame'
merge(x, y)
```

Arguments

x	an object of class AQuadtree.
y	an object of class data.frame

Details

Merges the AQuadtree object data with the data.frame on the columns "cellCode" and cellNum"

Value

An AQuadtree object where the data is extended with the input data.frame

plot,AQuadtree,missing-method
plot AQuadtree-method

Description

Method plot

Usage

```
## S4 method for signature 'AQuadtree,missing'
plot(x, ..., residual = TRUE, add = FALSE, col)
```

Arguments

x	an object of class AQuadtree.
...	passed through.
residual	logical; if TRUE cells marked as residual cells are included
add	logical. TRUE to add plot to the current existing plot
col	default plotting color

Details

Plot an object of class AQuadtree.

Value

none

pointsToAQuadtree	<i>Add SpatialPoints to an AQuadtree object.</i>
-------------------	--

Description

Given an object of class AQuadtree and an object of class SpatialPoints or SpatialPointsDataFrame for the same area, pointsToAQuadtree returns a new object of class AQuadtree aggregating the data from the points to the cells where each point fall.

Usage

```
pointsToAQuadtree(qt, points)
```

Arguments

qt	object of class "AQuadtree".
points	object of class "SpatialPoints" or "SpatialPointsDataFrame".

Details

The function pointsToAQuadtree returns a new AQuadtree object with the input set of points aggregated to the input AQuadtree object. The function creates a “p.total” attribute to compute the total number of points aggregated to each cell of the input AQuadtree. If points is an object of class SpatialPointsDataFrame, the function summarises numeric attributes in the dataframe using the mean function, and deploys factor attributes creating a new attribute for each label of the factor to calculate the count. The attributes added to the resulting AQuadtree object are prefixed with “p.”.

Value

AQuadtree with the information of the given set of points aggregated at each corresponding cell of the given AQuadtree.

Examples

```
data("BarcelonaPop")
Barcelona.QT<-AQuadtree(BarcelonaPop)
BcnWomen75yPop<-BarcelonaPop[BarcelonaPop$sex=='woman' & BarcelonaPop$age>=75, 'age']
Barcelona.extended.QT<-pointsToAQuadtree(Barcelona.QT, BcnWomen75yPop)

## Not run:
## not an AQuadtree object
pointsToAQuadtree(CharlestonCensusTracts, CharlestonPop)

## spatial object not projected
sp.not.projected<-spTransform(CharlestonPop,CRS("+proj=longlat +datum=NAD27"))
is.projected(sp.not.projected)
pointsToAQuadtree(AQuadtree(CharlestonPop), sp.not.projected)
```

```
## End(Not run)
```

```
print,AQuadtree-method  
    print AQuadtree-method
```

Description

Method print.

Usage

```
## S4 method for signature 'AQuadtree'  
print(x, ...)
```

Arguments

- x an object of class AQuadtree.
- ... passed through.

Details

Prints the AQuadtree object

Value

none

```
show,AQuadtree-method  show AQuadtree-method
```

Description

Method show.

Usage

```
## S4 method for signature 'AQuadtree'  
show(object)
```

Arguments

- object an object of class AQuadtree.

Details

Display the AQuadtree object

Value

A data.frame showing the information attributes contained in the AQuadtree object.

spatialPointsCellCodes

Add cell identifiers to SpatialPoints as in INSPIRE Specification

Description

spatialPointsCellCodes returns a SpatialPointsDataFrame with identifiers (CellCode and Cell-Num) for each point as in INSPIRE Specification on Geographical Grid Systems.

Usage

```
spatialPointsCellCodes(points, dim = 1000, layers = 1)
```

Arguments

points	object of class "SpatialPoints" or "SpatialPointsDataFrame".
dim	a single integer specifying the initial cell sizes, defaults to 1km.
layers	a single integer specifying the number of divisions of the initial cells, defaults to 1.

Details

INSPIRE coding system for point identifiers

The objective of the coding system is to generate unique identifiers for each point, for any of the recommended resolutions.

The cellCode is a text string, composed of cell size and cell coordinates. Cell codes start with a cell size prefix. The cell size is denoted in meter (m) for cell sizes below 1000 m and kilometre (km) for cell sizes from 1000 m and above.

Examples: a 100 meter cell has an identifier starting with "100m", the identifier of a 10000 meter cell starts with "10km".

The coordinate part of the cell code reflects the distance of the lower left grid cell corner from the false origin of the CRS. In order to reduce the length of the string, Easting (E) and Northing (N) values are divided by 10^n (n is the number of zeros in the cell size value). Example for a cell size of 10000 meters: The number of zeros in the cell size value is 4. The resulting divider for Easting and Northing values is $10^4 = 10000$.

The cellNum is a sequence of concatenated integers identifying all the hierarchical partitions of the main cell in which the point resides. For instance, the cellNum of the top right cell would be 416 (fourth in first partition, sixteenth in second partition)

13	14	15	16
9	10	11	12
5	6	7	8
1	2	3	4

The input object must be projected and units should be in 'meters' because the system uses the INSPIRE coding system.

Value

A "SpatialPointsDataFrame" containing all the points given. For each point a cellCode and cellNum identify the cell to which the point belongs.

CellCode is a text string, composed of cell size and cell coordinates. Cell codes start with a cell size prefix. The cell size is denoted in meter (m) for cell sizes below 1000 m and kilometer (km) for cell sizes from 1000 m and above.

The cellNum is a sequence identifying the different partitions of the main cell in which the point resides.

See Also

- D2.8.I.2 INSPIRE Specification on Geographical Grid Systems – Guidelines https://inspire.ec.europa.eu/documents/Data_Specifications/INSPIRE_Specification_GGS_v3.0.1.pdf
- EEA reference grid dataset https://data.europa.eu/euodp/data/dataset/data_eea-reference-grids-2

Examples

```
data("BarcelonaPop")
BarcelonaPop.IDs<-spatialPointsCellCodes(BarcelonaPop)
BarcelonaPop.IDs.10km<-spatialPointsCellCodes(BarcelonaPop, 10000, 3)

## Not run:
## spatial object not projected
sp.not.projected<-spTransform(CharlestonPop,CRS("+proj=longlat +datum=NAD27"))
is.projected(sp.not.projected)
spatialPointsCellCodes(sp.not.projected)

## End(Not run)
```

Description

createQuadtree returns a vector decomposing the given CellNum into the sequence of the different cell numbers for each level.

Usage

```
splitCellNum(x)
```

Arguments

x a character or character vector containing a sequence of cell numbers or an R object with a field named 'cellNum'

Details

CellNum is an integer with the concatenated sequence of hierarchical cell positions inside a main cell. splitCellNum splits that sequence into a vector. For instance, the CellNum of the top right cell would be 416 (fourth in first partition, sixteenth in second partition)

13	14	15	16
9	10	11	12
5	6	7	8
1	2	3	4

Diagram illustrating a 4x4 grid of cells. The grid is partitioned into four quadrants by a vertical red line and a horizontal red line. The top-left quadrant is labeled '3', the top-right quadrant is labeled '4', the bottom-left quadrant is labeled '1', and the bottom-right quadrant is labeled '2'. The cells are numbered 1 through 16 in a row-major order, with the top row containing 13, 14, 15, 16, the second row 9, 10, 11, 12, the third row 5, 6, 7, 8, and the bottom row 1, 2, 3, 4.

Value

integer vector or list of integer vectors with the sequence CellNums splitted

See Also

- D2.8.I.2 INSPIRE Specification on Geographical Grid Systems – Guidelines https://inspire.ec.europa.eu/documents/Data_Specifications/INSPIRE_Specification_GGS_v3.0.1.pdf
- EEA reference grid dataset https://data.europa.eu/euodp/data/dataset/data_eea-reference-grids-2

Examples

```
data("CharlestonPop")
CharlestonPop.IDs<-spatialPointsCellCodes(CharlestonPop, layers=2)
splitCellNum(CharlestonPop.IDs)
```

spplot,AQuadtree-method

spplot AQuadtree-method

Description

Method spplot

Usage

```
## S4 method for signature 'AQuadtree'
spplot(obj, zcol = NULL, by.density = TRUE, residual = TRUE, ...)
```

Arguments

obj	an object of class AQuadtree.
zcol	character; attribute name(s) or column number(s) in attribute table
by.density	logical; if TRUE cell values specified in zcol are divided by cell areas
residual	logical; if TRUE cells marked as residual cells are included
...	passed through.

Details

Plots a AQuadtree object as a spatial object with its data

Value

Creates a lattice plot of class "trellis" created with the spplot method in the sp package

summary,AQuadtree-method

summary AQuadtree-method

Description

Method summary.

Usage

```
## S4 method for signature 'AQuadtree'
summary(object, ...)
```

Arguments

object an object of class AQuadtree.
 ... passed through.

Details

summarize information of an object of class AQuadtree

Value

An object of class "table" with summarising information in the AQuadtree input object

[,AQuadtree-method [AQuadtree-method

Description

Method [

Usage

```
## S4 method for signature 'AQuadtree'
x[i, j, ..., drop = TRUE]
```

Arguments

x an object of class AQuadtree.
 i, j elements to extract.
 ... passed through.
 drop passed on to [indexing operator.

Details

Extract a part of a AQuadtree object

Value

An AQuadtree object with the selected subset of rows or columns from the input object.

[<-,AQuadtree-method [*<- AQuadtree-method*

Description

Method [<-

Usage

```
## S4 replacement method for signature 'AQuadtree'  
x[i, j, ...] <- value
```

Arguments

x	an object of class AQuadtree.
i, j	elements to extract or replace.
...	passed through.
value	value to set.

Details

An AQuadtree object cannot be assigned directly

Value

none

Index

* datasets

- BarcelonaCensusTracts, [6](#)
- BarcelonaPop, [7](#)
- CharlestonCensusTracts, [7](#)
- CharlestonPop, [8](#)
- [([,AQuadtree-method), [21](#)
- [,AQuadtree-method, [21](#)
- [<-,AQuadtree-method, [22](#)
- [<- ([<-,AQuadtree-method), [22](#)
- _PACKAGE (AQuadtree-package), [2](#)
- AQuadtree, [3](#)
- AQuadtree (AQuadtree-class), [3](#)
- AQuadtree-class, [3](#)
- AQuadtree-package, [2](#)
- area.QT, [6](#)
- area.QT, AQuadtree-method (area.QT), [6](#)
- BarcelonaCensusTracts, [6](#)
- BarcelonaPop, [7](#)
- CharlestonCensusTracts, [7](#)
- CharlestonPop, [8](#)
- createAQuadtree, [8](#)
- createGrid, [11](#)
- joinAQuadtrees, [12](#)
- merge
 - (merge,AQuadtree,data.frame-method), [13](#)
- merge,AQuadtree,data.frame-method, [13](#)
- plot (plot,AQuadtree,missing-method), [14](#)
- plot,AQuadtree,missing-method, [14](#)
- pointsToAQuadtree, [15](#)
- print (print,AQuadtree-method), [16](#)
- print,AQuadtree-method, [16](#)
- show (show,AQuadtree-method), [16](#)
- show,AQuadtree-method, [16](#)
- spatialPointsCellCodes, [17](#)
- splitCellNum, [18](#)
- spplot (spplot,AQuadtree-method), [20](#)
- spplot,AQuadtree-method, [20](#)
- summary (summary,AQuadtree-method), [20](#)
- summary,AQuadtree-method, [20](#)