

Package ‘AutoWMM’

July 21, 2025

Type Package

Title Perform the Weighted Multiplier Method on Trees

Version 1.0.2

Maintainer Mallory J Flynn <mallory.flynn@stat.ubc.ca>

Description When many possible multiplier method estimates of a target population are available, a weighted sum of estimates from each back-calculated path can be achieved with this package. Variance-minimizing weights are used and with any admissible tree-structured data. The methodological basis used to create this package can be found in Flynn (2023) <<http://hdl.handle.net/2429/86174>>.

License GPL (>= 2)

URL <https://github.com/malfly/AutoWMM>

Depends R (>= 4.3.0)

Imports data.tree, DiagrammeR, dplyr, gtools, MASS, rlang, magrittr, tidyselect

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Encoding UTF-8

LazyData true

RoxygenNote 7.3.1

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Mallory J Flynn [cre, aut]

Repository CRAN

Date/Publication 2025-05-20 09:10:02 UTC

Contents

confInts	2
countTree	3

drawTree	3
estTree	4
ko.weights	5
logEstimates	5
makeTree	6
mmEstimate	7
Nhats	7
root.confInt	8
sampleBeta	9
ss.confInts	9
ssEstimate	10
treeData1	11
treeData2	11
wmmTree	12
Index	14

confInts	<i>confInts</i>
----------	-----------------

Description

Estimation helper function: Method that takes samples and generates confidence intervals for nodes other than the root. Assume raw data (not log), with normal distributed log data for confidence interval construction

Usage

```
confInts(v)
```

Arguments

v A vector

Value

Returns a confidence interval. For non-root nodes

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
message("note - longer run time example")
Zhats <- wmmTree(tree, sample_length = 10)
confInts(Zhats$estimates)
```

countTree	<i>countTree</i>
-----------	------------------

Description

Visualize post-wmmTree tree with root estimate and marginal counts Also displays average of probability samples on each branch

Usage

```
countTree(tree)
```

Arguments

tree	A makeTree object
------	-------------------

Value

Returns a tree plot

Examples

```
message("note - longer run time example")
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
countTree(tree)
```

drawTree	<i>drawTree</i>
----------	-----------------

Description

Visualize tree with descriptions and probabilities; can be used pre-WMM analysis

Usage

```
drawTree(tree, probs = TRUE, desc = TRUE)
```

Arguments

tree	A makeTree object
probs	A logical with default TRUE to specify whether to display probabilities on branches
desc	A logical with default TRUE to specify whether to display node descriptions

Value

Returns a descriptive tree plot

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
drawTree(tree)
```

estTree

estTree

Description

Visualize post-wmmTree tree with root estimate given by each branch, and weighted sum at the root (for post-analysis). Also displays average of probability samples on each branch.

Usage

```
estTree(tree)
```

Arguments

tree A makeTree object

Value

Returns a tree plot

Examples

```
message("note - longer run time example")
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
estTree(tree)
```

ko.weights	<i>ko.weights</i>
------------	-------------------

Description

Estimation helper function: Calculating variance minimizing weights. Only assigns weights to informative paths

Usage

```
ko.weights(tree)
```

Arguments

tree	A makeTree object
------	-------------------

Value

Returns vector of variance-minimizing weights on informative paths

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
ko.weights(tree)
```

logEstimates	<i>logEstimates</i>
--------------	---------------------

Description

Estimation helper function: Creates a vector of mean estimate values given by each informative path

Usage

```
logEstimates(tree)
```

Arguments

tree	A makeTree object
------	-------------------

Value

Returns a vector of mean log estimate values of the root population size from each informative path

Examples

```
message("note - longer run time example")
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
logEstimates(tree)
```

makeTree

makeTree

Description

Assuming a specific structure, create a tree with the following columns: from (node label), to (node label), Estimate (+ integer), Total (+ integer), and Count (for terminal nodes with marginal counts). 'from' and 'to' describe the edge for that row of data, where 'Estimate' and 'Total' are assumed to come from surveys of size 'Total' (a sample of the population at node 'from'), and observe 'Estimate' number of those individuals at 'Total' which move to the node described by 'to'. 'Estimate' and 'Total' columns are used for branching probabilities only. 'Count' column is NA for rows where 'to' nodes are not leaves; and also for all leaves without a marginal count. A Population (logical) column is not needed, but can be added if 'Estimate' and 'Total' come from population numbers, rather than samples. A 'Description' column (string) is also possible to include if particulars are desired on the tree diagram. 'TerminalCount' (binary) will be created for functional purposes, where marginal counts are included on leaves.

Usage

```
makeTree(data)
```

Arguments

data A dataframe object

Value

Returns a makeTree object

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
```

`mmEstimate`*mmEstimate*

Description

Helper function: Performs the multiplier method from a single terminal node (o) and returns the root estimate given that path, and the probabilities of each branch on that path.

Usage

```
mmEstimate(o)
```

Arguments

o A node from a makeTree object

Value

Returns node with modified attributes

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
mmEstimate(tree$A)
mmEstimate(tree$B)
tree$A$targetEst
tree$B$targetEst
```

`Nhats`*Nhats*

Description

Estimation helper function: Returns Nhat for each sample from the WMM (rather than the aggregate value given by the average, this calculates weights and applies the weighted sum to each of the samples)

Usage

```
Nhats(tree)
```

Arguments

tree A makeTree object

Value

Returns a vector of root population size estimates from each sample run of the wmmTree function

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
Nhats(tree)
```

root.confInt

root.confInt

Description

Estimation helper function: Method for generating confidence interval for root node. Assumes unlogged input data and normally distributed logged data. Completes conversion internally.

Usage

```
root.confInt(tree, int.type = "quantiles")
```

Arguments

tree	A makeTree object
int.type	A string specifying interval type, passed from the wmmTree function.

Value

Returns a confidence interval for the root population size estimate in un-logged form.

Examples

```
message("note - longer run time example")
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
root.confInt(tree)
```

sampleBeta

sampleBeta

Description

Helper function: Method for sampling from a Beta distribution given the survey estimates

Usage

```
sampleBeta(x, n, pop, node)
```

Arguments

x	An integer; typical use case is survey numerator
n	An integer; typical use case is survey sample size
pop	A logical value which takes TRUE if sample size is population size
node	A node from a makeTree object; carried forever from

Value

Returns sample from Beta distribution with parameters dependent on x, n

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
sampleBeta(10, 55, pop = FALSE, tree$A)
```

ss.confInts

ss.confInts

Description

Estimation helper function: Method that takes samples and generates confidence intervals for nodes in single source sibling tree (single.source = TRUE)

Usage

```
ss.confInts(o, digits = 3)
```

Arguments

o	A node of a makeTree object
digits	The number of significant digits to report

Value

A confidence interval for nodes of the tree that only use a single source of sibling data.

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
ss.confInts(tree$B)
```

ssEstimate	<i>ssEstimate</i>
------------	-------------------

Description

Helper function: Performs the closed form calculation of variances and means based on a "single-source sibling" tree. Engages when single.source = TRUE in wmmTree function. See documentation for further details.

Usage

```
ssEstimate(o)
```

Arguments

o A node from a makeTree object

Value

Returns node with modified attributes

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)
ssEstimate(tree$B)
```

treeData1*Simple Tree Data*

Description

Small, artificially generated toy data set to demonstrate package functionality

Usage

```
data(treeData1)
```

Format

An object of class "data.frame"

from A node label and started point of directed edge (parent node)

to A node label and endpoint of directed edge (child node)

Estimate A numerical value assumed to be survey count belonging to 'to' node (integer)

Total A numerical value assumed to be survey sample size (integer)

Count A numerical value for marginal count if leaf node (integer)

Population A boolean value for if survey size is entire population (logical)

Description A string describing 'to' node (string)

References

This data set was artificially created for the AutoWMM package.

Examples

```
data(treeData1)
head(treeData1)
```

treeData2*Larger Tree Data*

Description

Larger artificially generated toy data set to demonstrate package functionality

Usage

```
data(treeData2)
```

Format

- An object of class "data.frame"
- from** A node label and started point of directed edge (parent node)
- to** A node label and endpoint of directed edge (child node)
- Estimate** A numerical value assumed to be survey count belonging to 'to' node (integer)
- Total** A numerical value assumed to be survey sample size (integer)
- Count** A numerical value for marginal count if leaf node (integer)

References

This data set was artificially created for the AutoWMM package.

Examples

```
data(treeData2)
head(treeData2)
```

wmmTree	<i>wmmTree</i>
---------	----------------

Description

Main function. Generate weighted estimates using the weighted multiplier method.

Usage

```
wmmTree(
  tree,
  sample_length = 10,
  method = "mmEstimate",
  int.type = "quants",
  single.source = FALSE
)
```

Arguments

- tree** A makeTree object
- sample_length** An integer for number of samples
- method** Method specifying weighting. Only default compatible with 'mmEstimate' at this time
- int.type** A string specifying interval type. Default "quants" generates the interval using the quantiles giving the central 95% of the samples. Alternatively, "var" can be used to generate a variance-weighted confidence interval, and "cox" generates a Cox interval.
- single.source** Set to TRUE if all data comes from single, fully informed source. Default is FALSE.

Value

Returns a makeTree object with branches and nodes now associated with estimates and samples generated with the weighted multiplier method

Examples

```
data(treeData1)
tree <- makeTree(treeData1)
Zhats <- wmmTree(tree, sample_length = 3)

message("Another example with a larger tree")
message("note - longer run time example")
data(treeData2)
tree2 <- makeTree(treeData2)
Zhats <- wmmTree(tree2, sample_length = 3)
Zhats$estimates # print the estimates of the root node generated by the 15 iterations
Zhats$weights # prints the weights of each branch
Zhats$root # prints the final estimate of the root node by WMM
Zhats$uncertainty # prints the final rounded estimate of the root with conf. int.

message(paste("show the average root estimate with 95% confidence interval,",
              "as well as average estimates with confidence interval for each parameter"))
tree2$Get('uncertainty')

message("show the samples generated from each path which provides root estimates")
tree2$Get('targetEst_samples')

message("show the probabilities sampled at each branch leading into the given node")
tree2$Get('probability_samples')
```

Index

- * **datasets**
 - treeData1, [11](#)
 - treeData2, [11](#)
- confInts, [2](#)
- countTree, [3](#)
- drawTree, [3](#)
- estTree, [4](#)
- ko.weights, [5](#)
- logEstimates, [5](#)
- makeTree, [6](#)
- mmEstimate, [7](#)
- Nhats, [7](#)
- root.confInt, [8](#)
- sampleBeta, [9](#)
- ss.confInts, [9](#)
- ssEstimate, [10](#)
- treeData1, [11](#)
- treeData2, [11](#)
- wmmTree, [12](#)