

Package ‘CAOP.RAA.2024’

July 21, 2025

Title Official Administrative Map of the Azores (CAOP 2024)

Version 0.0.5

Description Provides the official administrative boundaries of the Azores (Região Autónoma dos Açores (RAA)) as defined in the 2024 edition of the Carta Administrativa Oficial de Portugal (CAOP), published by the Direção-Geral do Território (DGT). The package includes convenience functions to import these boundaries as 'sf' objects for spatial analysis in R.
Source: <https://geo2.dgterritorio.gov.pt/caop/CAOP_RAA_2024-gpkg.zip>.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 3.5)

Imports sf, tibble, dplyr, readr, stringi, glue

Suggests testthat (>= 3.0.0), roxygen2, knitr, rmarkdown, ggplot2

RoxygenNote 7.3.2

URL <https://github.com/patterninstitute/CAOP.RAA.2024>,
<https://www.pattern.institute/CAOP.RAA.2024/>

BugReports <https://github.com/patterninstitute/CAOP.RAA.2024/issues>

Config/Needs/website patterninstitute/chic

NeedsCompilation no

Author Ramiro Magno [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5226-3441>>),
Pattern Institute [cph, fnd]

Maintainer Ramiro Magno <rmagno@pattern.institute>

Repository CRAN

Date/Publication 2025-03-13 13:00:11 UTC

Contents

boundary_segments	2
districts	3
eez	4
islands	5
laea_azores_proj	6
municipalities	7
nuts	8
parishes	9
Index	10

boundary_segments	<i>Azorean boundary segments</i>
-------------------	----------------------------------

Description

[boundary_segments\(\)](#) returns the boundary segments that separate administrative entities or borders with the Atlantic Ocean in the Azores.

[boundary_segments_25N\(\)](#) returns the boundary segments in the meter-based projection PTRAO8 / UTM zone 25N, i.e. those boundary segments in the western-most part of the archipelago: *Ilha das Flores* and *Ilha do Corvo*.

[boundary_segments_26N\(\)](#) returns the boundary segments in the meter-based projection PTRAO8 / UTM zone 26N, i.e. those boundary segments in the Central and Eastern groups of the archipelago.

Usage

```
boundary_segments(crs = laea_azores_proj())

boundary_segments_25N()

boundary_segments_26N()
```

Arguments

`crs` Coordinate reference system (CRS) passed on to [st_transform\(\)](#). Defaults to a custom CRS centered on the Azores, see [laea_azores_proj\(\)](#) for more details. Other possible options are "EPSG: 3035" for ETRS89-extended / LAEA Europe or "EPSG: 4326" for WGS 84.

Value

A simple features ([sf](#)) object with seven fields:

`id` An unique UUID identifier for the segment.

`id_at_right` Identifier for the entity at the right side of the boundary.

`id_at_left` Identifier for the entity at the left side of the boundary.

`is_confirmed` Boundary segment whose acceptance by the parties has not yet been officially communicated.

`boundary_type` Boundary type: land or coast.

`boundary_level` Boundary level: administrative level.

`length` Boundary segment length in kilometers.

Examples

```
boundary_segments()
boundary_segments_25N()
boundary_segments_26N()
```

`districts`

Azorean districts

Description

`districts()` returns the boundaries of districts (islands) in the Azores.

`districts_25N()` returns the districts in the meter-based projection PTR08 / UTM zone 25N, i.e. those districts in the western-most part of the archipelago: *Ilha das Flores* and *Ilha do Corvo*.

`districts_26N()` returns the districts in the meter-based projection PTR08 / UTM zone 26N, i.e. those districts in the Central and Eastern groups of the archipelago.

Usage

```
districts(crs = laea_azores_proj())
```

```
districts_25N()
```

```
districts_26N()
```

Arguments

`crs` Coordinate reference system (CRS) passed on to `st_transform()`. Defaults to a custom CRS centered on the Azores, see `laea_azores_proj()` for more details. Other possible options are "EPSG: 3035" for ETRS89-extended / LAEA Europe or "EPSG: 4326" for WGS 84.

Value

A simple features ([sf](#)) object with six fields:

`id` An unique identifier for the district. Follows the format `[DT][MN][FR]`: DT is a two-digit id for the district, MN for the municipality and FR for the district (freguesia in Portuguese).

`district` Name of the civil district.

`municipality` Name of municipality.

`district` Name of district, coincides with the name of the island.

`area` District area in hectares (ha).

`perimeter` District perimeter in kilometers.

`n_municipalities` Number of municipalities in the district.

`n_parishes` Number of parishes in the district.

Examples

```
districts()
districts_25N()
districts_26N()
```

 eez

Compute the Exclusive Economic Zone (EEZ) for the Azores

Description

This function calculates the Exclusive Economic Zone (EEZ) boundary for the Azores by buffering each island by a specified distance (default 200 nautical miles) and merging the resulting buffers to create a single EEZ polygon.

Usage

```
eez(crs = laea_azores_proj(), distance = 200)
```

Arguments

<code>crs</code>	Character or CRS object. The target coordinate reference system (CRS) for the EEZ output. Defaults to <code>laea_azores_proj()</code> (a custom Lambert Azimuthal Equal-Area projection centered on the Azores).
<code>distance</code>	Numeric. The buffer distance in nautical miles (NM) around each island. Defaults to 200 (200 NM, the standard EEZ definition). If another value is provided, it will be converted to meters.

Details

The EEZ is defined as the area **200 nautical miles from the nearest baseline of each island**. This function:

- Buffers each island by distance $\times$ 1,852 meters (default: **370,400 meters**).
- Merges overlapping buffers into a single EEZ boundary.
- Transforms the final EEZ to the specified crs.

Value

An sf object representing the EEZ as a single POLYGON.

Examples

```
library(ggplot2)
ggplot() +
  geom_sf(data = eez(), fill = NA, linewidth = 1, col = "gray") +
  geom_sf(data = districts(), mapping = aes(fill = district), col = "white") +
  guides(fill = "none")

# WGS 84 projection
ggplot() +
  geom_sf(data = eez(crs = "EPSG:4326"), fill = NA, linewidth = 1, col = "gray") +
  geom_sf(data = districts(crs = "EPSG:4326"), mapping = aes(fill = district), col = "white") +
  guides(fill = "none")
```

islands	<i>Azorean islands</i>
---------	------------------------

Description

A brief dataset of the nine Azorean islands.

Usage

```
islands()
```

Value

A [tibble](#) with columns:

group Island group.

is_triangle Due to their proximity, Pico, Faial and São Jorge form the so-called *Triangle* of the Central Group of islands.

name Island's name.

Examples

```
islands()
```

laea_azores_proj	<i>Lambert Azimuthal Equal-Area (LAEA) projection centered on the Azores</i>
------------------	--

Description

`laea_azores_proj()` creates a PROJ string for a custom Lambert Azimuthal Equal-Area (LAEA) projection, centered on the Azores. It allows flexibility in setting the latitude and longitude center, datum, and units.

Usage

```
laea_azores_proj(lat_0 = 38.5, lon_0 = -28, datum = "WGS84", units = "m")
```

Arguments

lat_0	Numeric. Latitude of the projection's center. Defaults to 38.5 (Central Azores).
lon_0	Numeric. Longitude of the projection's center. Defaults to -28 (Central Azores).
datum	Character. The geodetic datum used for the projection. Defaults to "WGS84". Other options include "ETRS89", "NAD83", etc.
units	Character. Measurement units for the projection. Defaults to "m" (meters). Can be set to "ft" (feet) if needed.

Value

A character string representing the PROJ definition for the custom LAEA projection.

Examples

```
# Default Azores-centered LAEA projection
laea_azores_proj()

# Custom projection centered at a different location
laea_azores_proj(lat_0 = 38, lon_0 = -27, datum = "ETRS89")
```

municipalities	<i>Azorean municipalities</i>
----------------	-------------------------------

Description

`municipalities()` returns the boundaries of municipalities in the Azores.

`municipalities_25N()` returns the municipalities in the meter-based projection PTR08 / UTM zone 25N, i.e. those municipalities in the western-most part of the archipelago: *Ilha das Flores* and *Ilha do Corvo*.

`municipalities_26N()` returns the municipalities in the meter-based projection PTR08 / UTM zone 26N, i.e. those municipalities in the Central and Eastern groups of the archipelago.

Usage

```
municipalities(crs = laea_azores_proj())
```

```
municipalities_25N()
```

```
municipalities_26N()
```

Arguments

<code>crs</code>	Coordinate reference system (CRS) passed on to <code>st_transform()</code> . Defaults to a custom CRS centered on the Azores, see <code>laea_azores_proj()</code> for more details. Other possible options are "EPSG: 3035" for ETRS89-extended / LAEA Europe or "EPSG:4326" for WGS 84.
------------------	--

Value

A simple features (`sf`) object with six fields:

`id` An unique identifier for the municipality. Follows the format [DT][MN]: DT is a two-digit id for the district and MN for the municipality.

`municipality` Name of municipality.

`district` Name of district, coincides with the name of the island.

`area` Municipality area in hectares (ha).

`perimeter` Municipality perimeter in kilometers.

`n_parishes` Number of parishes in municipality.

Examples

```
municipalities()
municipalities_25N()
municipalities_26N()
```

nuts

*Azorean NUTS***Description**

`nuts()` returns the boundaries of the Nomenclature of Territorial Units for Statistics (NUTS).

`nuts_25N()` returns the NUTS boundaries in the meter-based projection PTTRA08 / UTM zone 25N, i.e. the NUTS area in the western-most part of the archipelago: *Ilha das Flores* and *Ilha do Corvo*.

`nuts_26N()` returns the NUTS boundaries in the meter-based projection PTTRA08 / UTM zone 26N, i.e. the NUTS area in the Central and Eastern groups of the archipelago.

Usage

```
nuts(crs = laea_azores_proj())
```

```
nuts_25N()
```

```
nuts_26N()
```

Arguments

`crs` Coordinate reference system (CRS) passed on to `st_transform()`. Defaults to a custom CRS centered on the Azores, see `laea_azores_proj()` for more details. Other possible options are "EPSG: 3035" for ETRS89-extended / LAEA Europe or "EPSG: 4326" for WGS 84.

Value

A simple features (`sf`) object with seven fields:

`nuts_code` NUTS code.

`nuts_level` NUTS level.

`nuts_name` NUTS name.

`area` NUTS area in hectares (ha).

`perimeter` NUTS perimeter in kilometers.

`n_municipalities` Number of municipalities in the NUTS.

`n_parishes` Number of parishes in the NUTS.

Examples

```
nuts()
nuts_25N()
nuts_26N()
```

parishes	<i>Azorean civil administrative parishes</i>
----------	--

Description

`parishes()` returns the boundaries of civil parishes in the Azores.

`parishes_25N()` returns the parishes in the meter-based projection PTR08 / UTM zone 25N, i.e. those parishes in the western-most part of the archipelago: *Ilha das Flores* and *Ilha do Corvo*.

`parishes_26N()` returns the parishes in the meter-based projection PTR08 / UTM zone 26N, i.e. those parishes in the Central and Eastern groups of the archipelago.

Usage

```
parishes(crs = laea_azores_proj())
```

```
parishes_25N()
```

```
parishes_26N()
```

Arguments

<code>crs</code>	Coordinate reference system (CRS) passed on to <code>st_transform()</code> . Defaults to a custom CRS centered on the Azores, see <code>laea_azores_proj()</code> for more details. Other possible options are "EPSG: 3035" for ETRS89-extended / LAEA Europe or "EPSG: 4326" for WGS 84.
------------------	---

Value

A simple features (`sf`) object with six fields:

`id` An unique identifier for the parish. Follows the format [DT][MN][FR]: DT is a two-digit id for the district, MN for the municipality and FR for the parish (freguesia in Portuguese).

`parish` Name of the civil parish.

`municipality` Name of municipality.

`district` Name of district, coincides with the name of the island.

`area` Parish area in hectares (ha).

`perimeter` Parish perimeter in kilometers.

Examples

```
parishes()
parishes_25N()
parishes_26N()
```

Index

boundary_segments, [2](#)
boundary_segments(), [2](#)
boundary_segments_25N
 (boundary_segments), [2](#)
boundary_segments_25N(), [2](#)
boundary_segments_26N
 (boundary_segments), [2](#)
boundary_segments_26N(), [2](#)

districts, [3](#)
districts(), [3](#)
districts_25N(districts), [3](#)
districts_25N(), [3](#)
districts_26N(districts), [3](#)
districts_26N(), [3](#)

eez, [4](#)

islands, [5](#)

laea_azores_proj, [6](#)
laea_azores_proj(), [2](#), [3](#), [6–9](#)

municipalities, [7](#)
municipalities(), [7](#)
municipalities_25N(municipalities), [7](#)
municipalities_25N(), [7](#)
municipalities_26N(municipalities), [7](#)
municipalities_26N(), [7](#)

nuts, [8](#)
nuts(), [8](#)
nuts_25N(nuts), [8](#)
nuts_25N(), [8](#)
nuts_26N(nuts), [8](#)
nuts_26N(), [8](#)

parishes, [9](#)
parishes(), [9](#)
parishes_25N(parishes), [9](#)
parishes_25N(), [9](#)

parishes_26N(parishes), [9](#)
parishes_26N(), [9](#)

sf, [2](#), [4](#), [7–9](#)
st_transform(), [2](#), [3](#), [7–9](#)

tibble, [5](#)