

Package ‘CVXR’

July 21, 2025

Type Package

Title Disciplined Convex Optimization

Version 1.0-15

VignetteBuilder knitr

URL <https://cvxr.rbind.io>, <https://www.cvxgrp.org/CVXR/>

BugReports <https://github.com/cvxgrp/CVXR/issues>

Description An object-oriented modeling language for disciplined convex programming (DCP) as described in Fu, Narasimhan, and Boyd (2020, <[doi:10.18637/jss.v094.i14](https://doi.org/10.18637/jss.v094.i14)>). It allows the user to formulate convex optimization problems in a natural way following mathematical convention and DCP rules. The system analyzes the problem, verifies its convexity, converts it into a canonical form, and hands it off to an appropriate solver to obtain the solution. Interfaces to solvers on CRAN and elsewhere are provided, both commercial and open source.

Additional_repositories <https://bnaras.github.io/drat>

Depends R (>= 3.4.0)

Imports methods, Matrix, Rcpp (>= 0.12.12), bit64, gmp, Rmpfr, ECOSolveR (>= 0.5.4), scs (>= 3.0), stats, osqp, cli, utils

Suggests knitr, rmarkdown, testthat, nnls, slam, covr

LinkingTo Rcpp, RcppEigen

License Apache License 2.0 | file LICENSE

LazyData true

Collate 'CVXR-package.R' 'data.R' 'globals.R' 'generics.R' 'interface.R' 'canonical.R' 'expressions.R' 'constant.R' 'variable.R' 'lin_ops.R' 'atoms.R' 'affine.R' 'problem.R' 'constraints.R' 'elementwise.R' 'coeff_extractor.R' 'reductions.R' 'reduction_solvers.R' 'complex2real.R' 'conic_solvers.R' 'clarabel.R' 'eliminate_pwl.R' 'dcp2cone.R' 'dgp2dcp.R' 'sparse_utils.R' 'qp2quad_form.R' 'qp_solvers.R' 'utilities.R' 'coll_utils.R' 'solver_utilities.R'

'transforms.R' 'exports.R' 'rcppUtils.R' 'LinOp.R'
 'LinOpVector.R' 'RcppExports.R' 'CVXcanon.R' 'canonInterface.R'

RoxygenNote 7.3.2

Encoding UTF-8

Enhances Rplex, gurobi, rcbc, cccp, Rmosek, Rglpk, clarabel (>= 0.9.0)

NeedsCompilation yes

Author Anqi Fu [aut, cre],
 Balasubramanian Narasimhan [aut],
 David W Kang [aut],
 Steven Diamond [aut],
 John Miller [aut],
 Stephen Boyd [ctb],
 Paul Kunsberg Rosenfield [ctb]

Maintainer Anqi Fu <anqif@alumni.stanford.edu>

Repository CRAN

Date/Publication 2024-11-07 19:40:02 UTC

Contents

*,Expression,Expression-method	11
+,Expression,missing-method	11
-,Expression,missing-method	13
.build_matrix_0	14
.build_matrix_1	15
.decomp_quad	15
.LinOpVector__new	16
.LinOpVector__push_back	16
.LinOp__at_index	16
.LinOp__args_push_back	17
.LinOp__get_dense_data	17
.LinOp__get_id	18
.LinOp__get_size	18
.LinOp__get_slice	19
.LinOp__get_sparse	19
.LinOp__get_sparse_data	20
.LinOp__get_type	20
.LinOp__new	21
.LinOp__set_dense_data	21
.LinOp__set_size	21
.LinOp__set_slice	22
.LinOp__set_sparse	22
.LinOp__set_sparse_data	23
.LinOp__set_type	23
.LinOp__size_push_back	24

.LinOp__slice_push_back	24
.ProblemData__get_const_to_row	25
.ProblemData__get_const_vec	25
.ProblemData__get_I	26
.ProblemData__get_id_to_col	26
.ProblemData__get_J	27
.ProblemData__get_V	27
.ProblemData__new	28
.ProblemData__set_const_to_row	28
.ProblemData__set_const_vec	29
.ProblemData__set_I	29
.ProblemData__set_id_to_col	30
.ProblemData__set_J	30
.ProblemData__set_V	31
.p_norm	31
/,Expression,Expression-method	32
<=,Expression,Expression-method	33
==,Expression,Expression-method	35
abs,Expression-method	36
Abs-class	37
accepts	38
AffAtom-class	39
are_args_affine	40
Atom-class	41
AxisAtom-class	43
BinaryOperator-class	44
bmat	45
CallbackParam-class	46
Canonical-class	46
Canonicalization-class	48
canonicalize	49
CBC_CONIC-class	49
cdiac	51
Chain-class	52
CLARABEL-class	53
CLARABEL.dims_to_solver_dict	55
CLARABEL.extract_dual_value	55
complex-atoms	56
complex-methods	56
Complex2Real-class	57
Complex2Real.abs_canon	57
Complex2Real.add	58
Complex2Real.at_least_2D	58
Complex2Real.binary_canon	59
Complex2Real.canonicalize_expr	59
Complex2Real.canonicalize_tree	60
Complex2Real.conj_canon	61
Complex2Real.constant_canon	61

Complex2Real.hermitian_canon	62
Complex2Real.imag_canon	62
Complex2Real.join	63
Complex2Real.lambda_sum_largest_canon	64
Complex2Real.matrix_frac_canon	64
Complex2Real.nonpos_canon	65
Complex2Real.norm_nuc_canon	65
Complex2Real.param_canon	66
Complex2Real.pnorm_canon	67
Complex2Real.psd_canon	67
Complex2Real.quad_canon	68
Complex2Real.quad_over_lin_canon	68
Complex2Real.real_canon	69
Complex2Real.separable_canon	70
Complex2Real.soc_canon	70
Complex2Real.variable_canon	71
Complex2Real.zero_canon	71
cone-methods	72
ConeDims-class	72
ConeMatrixStuffing-class	73
ConicSolver-class	73
ConicSolver.get_coeff_offset	74
ConicSolver.get_spacing_matrix	75
Conjugate-class	76
Constant-class	77
ConstantSolver-class	79
Constraint-class	81
construct_intermediate_chain,Problem,list-method	83
construct_solving_chain	83
constr_value	84
conv	84
Conv-class	85
CPLEX_CONIC-class	86
CPLEX_QP-class	88
CumMax-class	90
cummax_axis	91
CumSum-class	92
cumsum_axis	93
curvature	94
curvature-atom	94
curvature-comp	96
curvature-methods	96
CvxAttr2Constr-class	98
CVXOPT-class	98
cvxr_norm	100
Dcp2Cone-class	101
Dcp2Cone.entr_canon	101
Dcp2Cone.exp_canon	102

Dcp2Cone.geo_mean_canon	102
Dcp2Cone.huber_canon	103
Dcp2Cone.indicator_canon	103
Dcp2Cone.kl_div_canon	104
Dcp2Cone.lambda_max_canon	104
Dcp2Cone.lambda_sum_largest_canon	105
Dcp2Cone.log1p_canon	105
Dcp2Cone.logistic_canon	106
Dcp2Cone.log_canon	106
Dcp2Cone.log_det_canon	107
Dcp2Cone.log_sum_exp_canon	107
Dcp2Cone.matrix_frac_canon	108
Dcp2Cone.normNuc_canon	108
Dcp2Cone.pnorm_canon	109
Dcp2Cone.power_canon	109
Dcp2Cone.quad_form_canon	110
Dcp2Cone.quad_over_lin_canon	110
Dcp2Cone.sigma_max_canon	111
Dgp2Dcp-class	111
Dgp2Dcp.add_canon	112
Dgp2Dcp.constant_canon	113
Dgp2Dcp.div_canon	113
Dgp2Dcp.exp_canon	114
Dgp2Dcp.eye_minus_inv_canon	114
Dgp2Dcp.geo_mean_canon	115
Dgp2Dcp.log_canon	115
Dgp2Dcp.mulexpression_canon	116
Dgp2Dcp.mul_canon	116
Dgp2Dcp.nonpos_constr_canon	117
Dgp2Dcp.norm1_canon	117
Dgp2Dcp.norm_inf_canon	118
Dgp2Dcp.one_minus_pos_canon	118
Dgp2Dcp.parameter_canon	119
Dgp2Dcp.pf_eigenvalue_canon	119
Dgp2Dcp.pnorm_canon	120
Dgp2Dcp.power_canon	120
Dgp2Dcp.prod_canon	121
Dgp2Dcp.quad_form_canon	121
Dgp2Dcp.quad_over_lin_canon	122
Dgp2Dcp.sum_canon	122
Dgp2Dcp.trace_canon	123
Dgp2Dcp.zero_constr_canon	123
DgpCanonMethods-class	124
Diag	124
diag,Expression-method	125
DiagMat-class	125
DiagVec-class	127
Diff	128

diff,Expression-method	129
DiffPos	130
dim_from_args	130
domain	131
dspop	132
dssamp	132
dual_value-methods	133
ECOS-class	133
ECOS.dims_to_solver_dict	134
ECOS_BB-class	135
Elementwise-class	136
EliminatePwl-class	137
EliminatePwl.abs_canon	137
EliminatePwl.cummax_canon	138
EliminatePwl.cumsum_canon	138
EliminatePwl.max_elemwise_canon	139
EliminatePwl.max_entries_canon	139
EliminatePwl.min_elemwise_canon	140
EliminatePwl.min_entries_canon	140
EliminatePwl.norm1_canon	141
EliminatePwl.norm_inf_canon	141
EliminatePwl.sum_largest_canon	142
entr	142
Entr-class	143
EvalParams-class	144
exp,Expression-method	145
Exp-class	145
ExpCone-class	147
Expression-class	148
expression-parts	152
extract_dual_value	153
extract_mip_idx	154
EyeMinusInv-class	154
eye_minus_inv	156
FlipObjective-class	156
format_constr	157
GeoMean-class	158
geo_mean	160
get_data	161
get_dual_values	162
get_id	162
get_np	163
get_problem_data	163
get_sp	164
GLPK-class	164
GLPK_MI-class	166
grad	167
graph_implementation	168

group_constraints	169
GUROBI_CONIC-class	169
GUROBI_QP-class	171
HarmonicMean	172
harmonic_mean	173
hstack	173
HStack-class	174
huber	175
Huber-class	176
id	178
Imag-class	179
import_solver	180
installed_solvers	180
InverseData-class	181
invert	181
inv_pos	182
is_dcp	182
is_dgp	183
is_mixed_integer	183
is_qp	184
is_stuffed_cone_constraint	184
is_stuffed_cone_objective	185
is_stuffed_qp_objective	185
KLDiv-class	186
kl_div	187
Kron-class	188
kronecker,Expression,ANY-method	189
LambdaMax-class	190
LambdaMin	191
LambdaSumLargest-class	192
LambdaSumSmallest	193
lambda_max	193
lambda_min	194
lambda_sum_largest	195
lambda_sum_smallest	195
leaf-attr	196
Leaf-class	196
linearize	200
ListORConstr-class	201
log,Expression-method	201
Log-class	202
Loglp-class	204
LogDet-class	205
logistic	206
Logistic-class	207
LogSumExp-class	208
log_det	210
log_log_curvature	211

log_log_curvature-atom	211
log_log_curvature-methods	212
log_sum_exp	212
make_sparse_diagonal_matrix	213
MatrixFrac-class	214
MatrixStuffing-class	215
matrix_frac	216
matrix_prop-methods	217
matrix_trace	218
MaxElemwise-class	218
MaxEntries-class	220
Maximize-class	222
max_elemwise	223
max_entries	224
mean.Expression	225
MinElemwise-class	226
MinEntries-class	227
Minimize-class	229
min_elemwise	230
min_entries	230
mip_capable	231
MixedNorm	232
mixed_norm	232
MOSEK-class	233
MOSEK.parse_dual_vars	235
MOSEK.recover_dual_variables	235
multiply	236
Multiply-class	236
name	238
Neg	238
neg	239
NonlinearConstraint-class	239
NonPosConstraint-class	240
Norm	241
norm,Expression,character-method	241
norm1	242
Norm1-class	243
Norm2	245
norm2	246
NormInf-class	247
NormNuc-class	249
norm_inf	250
norm_nuc	251
Objective-arith	252
Objective-class	253
OneMinusPos-class	254
one_minus_pos	256
OSQP-class	256

Parameter-class	258
perform	260
PfEigenvalue-class	260
pf_eigenvalue	262
Pnorm-class	263
Pos	265
pos	266
Power-class	266
Problem-arith	269
Problem-class	270
problem-parts	274
ProdEntries-class	274
prod_entries	276
project-methods	277
Promote-class	278
PSDWrap-class	279
psd_coeff_offset	280
psolve	280
p_norm	282
Qp2SymbolicQp-class	284
QpMatrixStuffing-class	284
QpSolver-class	284
QuadForm-class	285
QuadOverLin-class	287
quad_form	289
quad_over_lin	289
Rdict-class	290
Rdictdefault-class	291
Real-class	292
reduce	293
Reduction-class	293
ReductionSolver-class	295
resetOptions	297
Reshape-class	297
reshape_expr	298
residual-methods	300
retrieve	300
scaled_lower_tri	301
scaled_upper_tri	301
scalene	302
SCS-class	302
SCS.dims_to_solver_dict	304
SCS.extract_dual_value	305
setIdCounter	305
SigmaMax-class	306
sigma_max	307
sign,Expression-method	308
sign-methods	308

sign_from_args	309
size	310
size-methods	310
SizeMetrics-class	311
SOC-class	312
SOCAxis-class	313
Solution-class	315
SolverStats-class	315
SolvingChain-class	316
sqrt,Expression-method	317
square,Expression-method	318
SumEntries-class	318
SumLargest-class	319
SumSmallest	321
SumSquares	321
sum_entries	322
sum_largest	323
sum_smallest	324
sum_squares	324
SymbolicQuadForm-class	325
t.Expression	327
TotalVariation	327
to_numeric	328
Trace-class	328
Transpose-class	329
triu_to_full	330
tri_to_full	331
tv	331
UnaryOperator-class	332
unpack_results	333
updated_scaled_lower_tri	334
UpperTri-class	335
upper_tri	336
validate_args	337
validate_val	337
value-methods	338
Variable-class	338
vec	340
vectorized_lower_tri_to_mat	340
vstack	341
VStack-class	342
Wrap-class	343
ZeroConstraint-class	344
[,Expression,index,missing,ANY-method	345
[,Expression,missing,missing,ANY-method	346
%*%,Expression,Expression-method	348
%>>%	350
^,Expression,numeric-method	351

Index**353**

*,Expression,Expression-method
Elementwise multiplication operator

Description

Elementwise multiplication operator

Usage

```
## S4 method for signature 'Expression,Expression'
e1 * e2

## S4 method for signature 'Expression,ConstVal'
e1 * e2

## S4 method for signature 'ConstVal,Expression'
e1 * e2
```

Arguments

e1, e2 The [Expression](#) objects or numeric constants to multiply elementwise.

+,Expression,missing-method
The AddExpression class.

Description

This class represents the sum of any number of expressions.

Usage

```
## S4 method for signature 'Expression,missing'
e1 + e2

## S4 method for signature 'Expression,Expression'
e1 + e2

## S4 method for signature 'Expression,ConstVal'
e1 + e2

## S4 method for signature 'ConstVal,Expression'
e1 + e2
```

```
## S4 method for signature 'AddExpression'
dim_from_args(object)

## S4 method for signature 'AddExpression'
name(x)

## S4 method for signature 'AddExpression'
to_numeric(object, values)

## S4 method for signature 'AddExpression'
is_atom_log_log_convex(object)

## S4 method for signature 'AddExpression'
is_atom_log_log_concave(object)

## S4 method for signature 'AddExpression'
is_symmetric(object)

## S4 method for signature 'AddExpression'
is_hermitian(object)

## S4 method for signature 'AddExpression'
copy(object, args = NULL, id_objects = list())

## S4 method for signature 'AddExpression'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

e1, e2	The Expression objects or numeric constants to add.
x, object	An AddExpression object.
values	A list of arguments to the atom.
args	An optional list of arguments to reconstruct the atom. Default is to use current args of the atom.
id_objects	Currently unused.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `dim_from_args(AddExpression)`: The dimensions of the expression.
- `name(AddExpression)`: The string form of the expression.
- `to_numeric(AddExpression)`: Sum all the values.
- `is_atom_log_log_convex(AddExpression)`: Is the atom log-log convex?

- `is_atom_log_log_concave(AddExpression)`: Is the atom log-log convex?
- `is_symmetric(AddExpression)`: Is the atom symmetric?
- `is_hermitian(AddExpression)`: Is the atom hermitian?
- `copy(AddExpression)`: Returns a shallow copy of the `AddExpression` atom
- `graph_implementation(AddExpression)`: The graph implementation of the expression.

Slots

`arg_groups` A list of [Expressions](#) and numeric data.frame, matrix, or vector objects.

-,Expression,missing-method
The NegExpression class.

Description

This class represents the negation of an affine expression.

Usage

```
## S4 method for signature 'Expression,missing'
e1 - e2

## S4 method for signature 'Expression,Expression'
e1 - e2

## S4 method for signature 'Expression,ConstVal'
e1 - e2

## S4 method for signature 'ConstVal,Expression'
e1 - e2

## S4 method for signature 'NegExpression'
dim_from_args(object)

## S4 method for signature 'NegExpression'
sign_from_args(object)

## S4 method for signature 'NegExpression'
is_incr(object, idx)

## S4 method for signature 'NegExpression'
is_decr(object, idx)

## S4 method for signature 'NegExpression'
is_symmetric(object)
```

```
## S4 method for signature 'NegExpression'
is_hermitian(object)

## S4 method for signature 'NegExpression'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

e1, e2	The Expression objects or numeric constants to subtract.
object	A NegExpression object.
idx	An index into the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `dim_from_args(NegExpression)`: The (row, col) dimensions of the expression.
- `sign_from_args(NegExpression)`: The (is positive, is negative) sign of the expression.
- `is_incr(NegExpression)`: The expression is not weakly increasing in any argument.
- `is_decr(NegExpression)`: The expression is weakly decreasing in every argument.
- `is_symmetric(NegExpression)`: Is the expression symmetric?
- `is_hermitian(NegExpression)`: Is the expression Hermitian?
- `graph_implementation(NegExpression)`: The graph implementation of the expression.

.build_matrix_0	<i>Get the sparse flag field for the LinOp object</i>
-----------------	---

Description

Get the sparse flag field for the LinOp object

Usage

```
.build_matrix_0(xp, v)
```

Arguments

xp	the LinOpVector Object XPtr
v	the id_to_col named int vector in R with integer names

Value

a XPtr to ProblemData Object

<code>.build_matrix_1</code>	<i>Get the sparse flag field for the LinOp object</i>
------------------------------	---

Description

Get the sparse flag field for the LinOp object

Usage

```
.build_matrix_1(xp, v1, v2)
```

Arguments

<code>xp</code>	the LinOpVector Object XPtr
<code>v1</code>	the <code>id_to_col</code> named int vector in R with integer names
<code>v2</code>	the <code>constr_offsets</code> vector of offsets (an int vector in R)

Value

a XPtr to ProblemData Object

<code>.decomp_quad</code>	<i>Compute a Matrix Decomposition.</i>
---------------------------	--

Description

Compute sgn , $scale$, M such that $P = sgn * scale * dot(M, t(M))$.

Usage

```
.decomp_quad(P, cond = NA, rcond = NA)
```

Arguments

<code>P</code>	A real symmetric positive or negative (semi)definite input matrix
<code>cond</code>	Cutoff for small eigenvalues. Singular values smaller than <code>rcond * largest_eigenvalue</code> are considered negligible.
<code>rcond</code>	Cutoff for small eigenvalues. Singular values smaller than <code>rcond * largest_eigenvalue</code> are considered negligible.

Value

A list consisting of induced matrix 2-norm of P and a rectangular matrix such that $P = scale * (dot(M1, t(M1)) - dot(M2, t(M2)))$

.LinOpVector__new	Create a new LinOpVector object.
-------------------	----------------------------------

Description

Create a new LinOpVector object.

Usage

.LinOpVector__new()

Value

an external ptr (Rcpp::XPtr) to a LinOp object instance.

.LinOpVector__push_back	Perform a push back operation on the args field of LinOp
-------------------------	--

Description

Perform a push back operation on the args field of LinOp

Usage

.LinOpVector__push_back(xp, yp)

Arguments

xp	the LinOpVector Object XPtr
yp	the LinOp Object XPtr to push

.LinOp_at_index	Return the LinOp element at index i (0-based)
-----------------	---

Description

Return the LinOp element at index i (0-based)

Usage

.LinOp_at_index(lvec, i)

Arguments

lvec	the LinOpVector Object XPtr
i	the index

`.LinOp__args_push_back`

Perform a push back operation on the args field of LinOp

Description

Perform a push back operation on the args field of LinOp

Usage

`.LinOp__args_push_back(xp, yp)`

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>yp</code>	the LinOp Object XPtr to push

`.LinOp__get_dense_data`

Get the field dense_data for the LinOp object

Description

Get the field dense_data for the LinOp object

Usage

`.LinOp__get_dense_data(xp)`

Arguments

<code>xp</code>	the LinOp Object XPtr
-----------------	-----------------------

Value

a MatrixXd object

.LinOp__get_id	<i>Get the id field of the LinOp Object</i>
----------------	---

Description

Get the id field of the LinOp Object

Usage

.LinOp__get_id(xp)

Arguments

xp the LinOp Object XPtr

Value

the value of the id field of the LinOp Object

.LinOp__get_size	<i>Get the field size for the LinOp object</i>
------------------	--

Description

Get the field size for the LinOp object

Usage

.LinOp__get_size(xp)

Arguments

xp the LinOp Object XPtr

Value

an integer vector

<code>.LinOp__get_slice</code>	<i>Get the slice field of the LinOp Object</i>
--------------------------------	--

Description

Get the slice field of the LinOp Object

Usage

```
.LinOp__get_slice(xp)
```

Arguments

xp	the LinOp Object XPtr
----	-----------------------

Value

the value of the slice field of the LinOp Object

<code>.LinOp__get_sparse</code>	<i>Get the sparse flag field for the LinOp object</i>
---------------------------------	---

Description

Get the sparse flag field for the LinOp object

Usage

```
.LinOp__get_sparse(xp)
```

Arguments

xp	the LinOp Object XPtr
----	-----------------------

Value

TRUE or FALSE

`.LinOp__get_sparse_data`

Get the field named sparse_data from the LinOp object

Description

Get the field named sparse_data from the LinOp object

Usage

`.LinOp__get_sparse_data(xp)`

Arguments

xp the LinOp Object XPtr

Value

a [dgCMatrix-class](#) object

`.LinOp__get_type`

Get the field named type for the LinOp object

Description

Get the field named type for the LinOp object

Usage

`.LinOp__get_type(xp)`

Arguments

xp the LinOp Object XPtr

Value

an integer value for type

.LinOp__new	Create a new LinOp object.
-------------	----------------------------

Description

Create a new LinOp object.

Usage

```
.LinOp__new()
```

Value

an external ptr (Rcpp::XPtr) to a LinOp object instance.

.LinOp__set_dense_data	Set the field dense_data of the LinOp object
------------------------	--

Description

Set the field dense_data of the LinOp object

Usage

```
.LinOp__set_dense_data(xp, denseMat)
```

Arguments

xp	the LinOp Object XPtr
denseMat	a standard matrix object in R

.LinOp__set_size	Set the field size of the LinOp object
------------------	--

Description

Set the field size of the LinOp object

Usage

```
.LinOp__set_size(xp, value)
```

Arguments

xp	the LinOp Object XPtr
value	an integer vector object in R

<code>.LinOp__set_slice</code>	<i>Set the slice field of the LinOp Object</i>
--------------------------------	--

Description

Set the slice field of the LinOp Object

Usage

```
.LinOp__set_slice(xp, value)
```

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>value</code>	a list of integer vectors, e.g. <code>list(1:10, 2L, 11:15)</code>

Value

the value of the slice field of the LinOp Object

<code>.LinOp__set_sparse</code>	<i>Set the flag sparse of the LinOp object</i>
---------------------------------	--

Description

Set the flag sparse of the LinOp object

Usage

```
.LinOp__set_sparse(xp, sparseSEXP)
```

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>sparseSEXP</code>	an R boolean

`.LinOp__set_sparse_data`

Set the field named sparse_data of the LinOp object

Description

Set the field named sparse_data of the LinOp object

Usage

`.LinOp__set_sparse_data(xp, sparseMat)`

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>sparseMat</code>	a dgCMatrix-class object

`.LinOp__set_type`

Set the field named type for the LinOp object

Description

Set the field named type for the LinOp object

Usage

`.LinOp__set_type(xp, typeValue)`

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>typeValue</code>	an integer value

`.LinOp__size_push_back`

Perform a push back operation on the size field of LinOp

Description

Perform a push back operation on the size field of LinOp

Usage

`.LinOp__size_push_back(xp, intVal)`

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>intVal</code>	the integer value to push back

`.LinOp__slice_push_back`

Perform a push back operation on the slice field of LinOp

Description

Perform a push back operation on the slice field of LinOp

Usage

`.LinOp__slice_push_back(xp, intVec)`

Arguments

<code>xp</code>	the LinOp Object XPtr
<code>intVec</code>	an integer vector to push back

.ProblemData__get_const_to_row

Get the const_to_row field of the ProblemData Object

Description

Get the const_to_row field of the ProblemData Object

Usage

.ProblemData__get_const_to_row(xp)

Arguments

xp the ProblemData Object XPtr

Value

the const_to_row field as a named integer vector where the names are integers converted to characters

.ProblemData__get_const_vec

Get the const_vec field from the ProblemData Object

Description

Get the const_vec field from the ProblemData Object

Usage

.ProblemData__get_const_vec(xp)

Arguments

xp the ProblemData Object XPtr

Value

a numeric vector of the field const_vec from the ProblemData Object

.ProblemData__get_I Get the I field of the ProblemData Object

Description

Get the I field of the ProblemData Object

Usage

`.ProblemData__get_I(xp)`

Arguments

xp the ProblemData Object XPtr

Value

an integer vector of the field I from the ProblemData Object

.ProblemData__get_id_to_col
Get the id_to_col field of the ProblemData Object

Description

Get the id_to_col field of the ProblemData Object

Usage

`.ProblemData__get_id_to_col(xp)`

Arguments

xp the ProblemData Object XPtr

Value

the id_to_col field as a named integer vector where the names are integers converted to characters

.ProblemData__get_J *Get the J field of the ProblemData Object*

Description

Get the J field of the ProblemData Object

Usage

.ProblemData__get_J(xp)

Arguments

xp the ProblemData Object XPtr

Value

an integer vector of the field J from the ProblemData Object

.ProblemData__get_V *Get the V field of the ProblemData Object*

Description

Get the V field of the ProblemData Object

Usage

.ProblemData__get_V(xp)

Arguments

xp the ProblemData Object XPtr

Value

a numeric vector of doubles (the field V) from the ProblemData Object

<code>.ProblemData__new</code>	<i>Create a new ProblemData object.</i>
--------------------------------	---

Description

Create a new ProblemData object.

Usage

`.ProblemData__new()`

Value

an external ptr (Rcpp::XPtr) to a ProblemData object instance.

<code>.ProblemData__set_const_to_row</code>	<i>Set the const_to_row map of the ProblemData Object</i>
---	---

Description

Set the const_to_row map of the ProblemData Object

Usage

`.ProblemData__set_const_to_row(xp, iv)`

Arguments

- | | |
|-----------------|--|
| <code>xp</code> | the ProblemData Object XPtr |
| <code>iv</code> | a named integer vector with names being integers converted to characters |

.ProblemData__set_const_vec

Set the const_vec field in the ProblemData Object

Description

Set the const_vec field in the ProblemData Object

Usage

.ProblemData__set_const_vec(xp, cvp)

Arguments

xp	the ProblemData Object XPtr
cvp	a numeric vector of values for const_vec field of the ProblemData object

.ProblemData__set_I *Set the I field in the ProblemData Object*

Description

Set the I field in the ProblemData Object

Usage

.ProblemData__set_I(xp, ip)

Arguments

xp	the ProblemData Object XPtr
ip	an integer vector of values for field I of the ProblemData object

`.ProblemData__set_id_to_col`

Set the id_to_col field of the ProblemData Object

Description

Set the id_to_col field of the ProblemData Object

Usage

`.ProblemData__set_id_to_col(xp, iv)`

Arguments

<code>xp</code>	the ProblemData Object XPtr
<code>iv</code>	a named integer vector with names being integers converted to characters

`.ProblemData__set_J` *Set the J field in the ProblemData Object*

Description

Set the J field in the ProblemData Object

Usage

`.ProblemData__set_J(xp, jp)`

Arguments

<code>xp</code>	the ProblemData Object XPtr
<code>jp</code>	an integer vector of the values for field J of the ProblemData object

`.ProblemData__set_V` *Set the V field in the ProblemData Object*

Description

Set the V field in the ProblemData Object

Usage

`.ProblemData__set_V(xp, vp)`

Arguments

<code>xp</code>	the ProblemData Object XPtr
<code>vp</code>	a numeric vector of values for field V

`.p_norm` *Internal method for calculating the p-norm*

Description

Internal method for calculating the p-norm

Usage

`.p_norm(x, p)`

Arguments

<code>x</code>	A matrix
<code>p</code>	A number greater than or equal to 1, or equal to positive infinity

Value

Returns the specified norm of matrix x

/,Expression,Expression-method
The DivExpression class.

Description

This class represents one expression divided by another expression.

Usage

```
## S4 method for signature 'Expression,Expression'
e1 / e2

## S4 method for signature 'Expression,ConstVal'
e1 / e2

## S4 method for signature 'ConstVal,Expression'
e1 / e2

## S4 method for signature 'DivExpression'
to_numeric(object, values)

## S4 method for signature 'DivExpression'
is_quadratic(object)

## S4 method for signature 'DivExpression'
is_qpwa(object)

## S4 method for signature 'DivExpression'
dim_from_args(object)

## S4 method for signature 'DivExpression'
is_atom_convex(object)

## S4 method for signature 'DivExpression'
is_atom_concave(object)

## S4 method for signature 'DivExpression'
is_atom_log_log_convex(object)

## S4 method for signature 'DivExpression'
is_atom_log_log_concave(object)

## S4 method for signature 'DivExpression'
is_incr(object, idx)

## S4 method for signature 'DivExpression'
```



```

is_decr(object, idx)

## S4 method for signature 'DivExpression'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

e1, e2	The Expression objects or numeric constants to divide. The denominator, e2, must be a scalar constant.
object	A DivExpression object.
values	A list of arguments to the atom.
idx	An index into the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(DivExpression)`: Matrix division by a scalar.
- `is_quadratic(DivExpression)`: Is the left-hand expression quadratic and the right-hand expression constant?
- `is_qpwa(DivExpression)`: Is the expression quadratic of piecewise affine?
- `dim_from_args(DivExpression)`: The (row, col) dimensions of the left-hand expression.
- `is_atom_convex(DivExpression)`: Division is convex (affine) in its arguments only if the denominator is constant.
- `is_atom_concave(DivExpression)`: Division is concave (affine) in its arguments only if the denominator is constant.
- `is_atom_log_log_convex(DivExpression)`: Is the atom log-log convex?
- `is_atom_log_log_concave(DivExpression)`: Is the atom log-log concave?
- `is_incr(DivExpression)`: Is the right-hand expression positive?
- `is_decr(DivExpression)`: Is the right-hand expression negative?
- `graph_implementation(DivExpression)`: The graph implementation of the expression.

<=,Expression,Expression-method

The IneqConstraint class

Description

The IneqConstraint class

Usage

```
## S4 method for signature 'Expression,Expression'
e1 <= e2

## S4 method for signature 'Expression,ConstVal'
e1 <= e2

## S4 method for signature 'ConstVal,Expression'
e1 <= e2

## S4 method for signature 'Expression,Expression'
e1 < e2

## S4 method for signature 'Expression,ConstVal'
e1 < e2

## S4 method for signature 'ConstVal,Expression'
e1 < e2

## S4 method for signature 'Expression,Expression'
e1 >= e2

## S4 method for signature 'Expression,ConstVal'
e1 >= e2

## S4 method for signature 'ConstVal,Expression'
e1 >= e2

## S4 method for signature 'Expression,Expression'
e1 > e2

## S4 method for signature 'Expression,ConstVal'
e1 > e2

## S4 method for signature 'ConstVal,Expression'
e1 > e2

## S4 method for signature 'IneqConstraint'
name(x)

## S4 method for signature 'IneqConstraint'
dim(x)

## S4 method for signature 'IneqConstraint'
size(object)

## S4 method for signature 'IneqConstraint'
expr(object)
```

```
## S4 method for signature 'IneqConstraint'
is_dcp(object)

## S4 method for signature 'IneqConstraint'
is_dgp(object)

## S4 method for signature 'IneqConstraint'
residual(object)
```

Arguments

`e1, e2` The [Expression](#) objects or numeric constants to compare.
`x, object` A [IneqConstraint](#) object.

Methods (by generic)

- `name(IneqConstraint)`: The string representation of the constraint.
- `dim(IneqConstraint)`: The dimensions of the constrained expression.
- `size(IneqConstraint)`: The size of the constrained expression.
- `expr(IneqConstraint)`: The expression to constrain.
- `is_dcp(IneqConstraint)`: A non-positive constraint is DCP if its argument is convex.
- `is_dgp(IneqConstraint)`: Is the constraint DGP?
- `residual(IneqConstraint)`: The residual of the constraint.

`==,Expression,Expression-method`
The EqConstraint class

Description

The EqConstraint class

Usage

```
## S4 method for signature 'Expression,Expression'
e1 == e2

## S4 method for signature 'Expression,ConstVal'
e1 == e2

## S4 method for signature 'ConstVal,Expression'
e1 == e2

## S4 method for signature 'EqConstraint'
```

```

name(x)

## S4 method for signature 'EqConstraint'
dim(x)

## S4 method for signature 'EqConstraint'
size(object)

## S4 method for signature 'EqConstraint'
expr(object)

## S4 method for signature 'EqConstraint'
is_dcp(object)

## S4 method for signature 'EqConstraint'
is_dgp(object)

## S4 method for signature 'EqConstraint'
residual(object)

```

Arguments

e1, e2 The [Expression](#) objects or numeric constants to compare.
x, object A [EqConstraint](#) object.

Methods (by generic)

- name(EqConstraint): The string representation of the constraint.
- dim(EqConstraint): The dimensions of the constrained expression.
- size(EqConstraint): The size of the constrained expression.
- expr(EqConstraint): The expression to constrain.
- is_dcp(EqConstraint): Is the constraint DCP?
- is_dgp(EqConstraint): Is the constraint DGP?
- residual(EqConstraint): The residual of the constraint..

abs,Expression-method *Absolute Value*

Description

The elementwise absolute value.

Usage

```

## S4 method for signature 'Expression'
abs(x)

```

Arguments

x An [Expression](#).

Value

An [Expression](#) representing the absolute value of the input.

Examples

```
A <- Variable(2,2)
prob <- Problem(Minimize(sum(abs(A))), list(A <= -2))
result <- solve(prob)
result$value
result$getValue(A)
```

Abs-class

The Abs class.

Description

This class represents the elementwise absolute value.

Usage

```
Abs(x)

## S4 method for signature 'Abs'
to_numeric(object, values)

## S4 method for signature 'Abs'
allow_complex(object)

## S4 method for signature 'Abs'
sign_from_args(object)

## S4 method for signature 'Abs'
is_atom_convex(object)

## S4 method for signature 'Abs'
is_atom_concave(object)

## S4 method for signature 'Abs'
is_incr(object, idx)

## S4 method for signature 'Abs'
is_decr(object, idx)

## S4 method for signature 'Abs'
is_pwl(object)
```

Arguments

x	An Expression object.
object	An Abs object.
values	A list of arguments to the atom.
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Abs)`: The elementwise absolute value of the input.
- `allow_complex(Abs)`: Does the atom handle complex numbers?
- `sign_from_args(Abs)`: The atom is positive.
- `is_atom_convex(Abs)`: The atom is convex.
- `is_atom_concave(Abs)`: The atom is not concave.
- `is_incr(Abs)`: A logical value indicating whether the atom is weakly increasing.
- `is_decr(Abs)`: A logical value indicating whether the atom is weakly decreasing.
- `is_pwl(Abs)`: Is x piecewise linear?

Slots

x An [Expression](#) object.

accepts	<i>Reduction Acceptance</i>
---------	-----------------------------

Description

Determine whether the reduction accepts a problem.

Usage

```
accepts(object, problem)
```

Arguments

object	A Reduction object.
problem	A Problem to check.

Value

A logical value indicating whether the reduction can be applied.

AffAtom-class*The AffAtom class.*

Description

This virtual class represents an affine atomic expression.

Usage

```
## S4 method for signature 'AffAtom'
allow_complex(object)

## S4 method for signature 'AffAtom'
sign_from_args(object)

## S4 method for signature 'AffAtom'
is_imag(object)

## S4 method for signature 'AffAtom'
is_complex(object)

## S4 method for signature 'AffAtom'
is_atom_convex(object)

## S4 method for signature 'AffAtom'
is_atom_concave(object)

## S4 method for signature 'AffAtom'
is_incr(object, idx)

## S4 method for signature 'AffAtom'
is_decr(object, idx)

## S4 method for signature 'AffAtom'
is_quadratic(object)

## S4 method for signature 'AffAtom'
is_qpwa(object)

## S4 method for signature 'AffAtom'
is_pwl(object)

## S4 method for signature 'AffAtom'
is_psd(object)

## S4 method for signature 'AffAtom'
is_nsd(object)
```

```
## S4 method for signature 'AffAtom'
.grad(object, values)
```

Arguments

object	An AffAtom object.
idx	An index into the atom.
values	A list of numeric values for the arguments

Methods (by generic)

- `allow_complex(AffAtom)`: Does the atom handle complex numbers?
- `sign_from_args(AffAtom)`: The sign of the atom.
- `is_imag(AffAtom)`: Is the atom imaginary?
- `is_complex(AffAtom)`: Is the atom complex valued?
- `is_atom_convex(AffAtom)`: The atom is convex.
- `is_atom_concave(AffAtom)`: The atom is concave.
- `is_incr(AffAtom)`: The atom is weakly increasing in every argument.
- `is_decr(AffAtom)`: The atom is not weakly decreasing in any argument.
- `is_quadratic(AffAtom)`: Is every argument quadratic?
- `is_qpwa(AffAtom)`: Is every argument quadratic of piecewise affine?
- `is_pwl(AffAtom)`: Is every argument piecewise linear?
- `is_psd(AffAtom)`: Is the atom a positive semidefinite matrix?
- `is_nsd(AffAtom)`: Is the atom a negative semidefinite matrix?
- `.grad(AffAtom)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

<code>are_args_affine</code>	<i>Are the arguments affine?</i>
------------------------------	----------------------------------

Description

Are the arguments affine?

Usage

```
are_args_affine(constraints)
```

Arguments

constraints	A Constraint object.
-------------	--------------------------------------

Value

All the affine arguments in given constraints.

Atom-class

The Atom class.

Description

This virtual class represents atomic expressions in CVXR.

Usage

```
## S4 method for signature 'Atom'  
name(x)
```

```
## S4 method for signature 'Atom'  
validate_args(object)
```

```
## S4 method for signature 'Atom'  
dim(x)
```

```
## S4 method for signature 'Atom'  
nrow(x)
```

```
## S4 method for signature 'Atom'  
ncol(x)
```

```
## S4 method for signature 'Atom'  
allow_complex(object)
```

```
## S4 method for signature 'Atom'  
is_nonneg(object)
```

```
## S4 method for signature 'Atom'  
is_nonpos(object)
```

```
## S4 method for signature 'Atom'  
is_imag(object)
```

```
## S4 method for signature 'Atom'  
is_complex(object)
```

```
## S4 method for signature 'Atom'  
is_convex(object)
```

```
## S4 method for signature 'Atom'  
is_concave(object)
```

```
## S4 method for signature 'Atom'  
is_log_log_convex(object)
```

```

## S4 method for signature 'Atom'
is_log_log_concave(object)

## S4 method for signature 'Atom'
canonicalize(object)

## S4 method for signature 'Atom'
graph_implementation(object, arg_objs, dim, data = NA_real_)

## S4 method for signature 'Atom'
value_impl(object)

## S4 method for signature 'Atom'
value(object)

## S4 method for signature 'Atom'
grad(object)

## S4 method for signature 'Atom'
domain(object)

## S4 method for signature 'Atom'
atoms(object)

```

Arguments

x, object	An Atom object.
arg_objs	A list of linear expressions for each argument.
dim	A vector with two elements representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `name(Atom)`: Returns the string representation of the function call
- `validate_args(Atom)`: Raises an error if the arguments are invalid.
- `dim(Atom)`: The `c(row, col)` dimensions of the atom.
- `nrow(Atom)`: The number of rows in the atom.
- `ncol(Atom)`: The number of columns in the atom.
- `allow_complex(Atom)`: Does the atom handle complex numbers?
- `is_nonneg(Atom)`: A logical value indicating whether the atom is nonnegative.
- `is_nonpos(Atom)`: A logical value indicating whether the atom is nonpositive.
- `is_imag(Atom)`: A logical value indicating whether the atom is imaginary.
- `is_complex(Atom)`: A logical value indicating whether the atom is complex valued.

- `is_convex(Atom)`: A logical value indicating whether the atom is convex.
- `is_concave(Atom)`: A logical value indicating whether the atom is concave.
- `is_log_log_convex(Atom)`: A logical value indicating whether the atom is log-log convex.
- `is_log_log_concave(Atom)`: A logical value indicating whether the atom is log-log concave.
- `canonicalize(Atom)`: Represent the atom as an affine objective and conic constraints.
- `graph_implementation(Atom)`: The graph implementation of the atom.
- `value_impl(Atom)`: Returns the value of each of the componets in an Atom. Returns an empty matrix if it's an empty atom
- `value(Atom)`: Returns the value of the atom.
- `grad(Atom)`: The (sub/super)-gradient of the atom with respect to each variable.
- `domain(Atom)`: A list of constraints describing the closure of the region where the expression is finite.
- `atoms(Atom)`: Returns a list of the atom types present amongst this atom's arguments

AxisAtom-class

The AxisAtom class.

Description

This virtual class represents atomic expressions that can be applied along an axis in CVXR.

Usage

```
## S4 method for signature 'AxisAtom'
dim_from_args(object)

## S4 method for signature 'AxisAtom'
get_data(object)

## S4 method for signature 'AxisAtom'
validate_args(object)

## S4 method for signature 'AxisAtom'
.axis_grad(object, values)

## S4 method for signature 'AxisAtom'
.column_grad(object, value)
```

Arguments

object	An Atom object.
values	A list of numeric values for the arguments
value	A numeric value

Methods (by generic)

- `dim_from_args(AxisAtom)`: The dimensions of the atom determined from its arguments.
- `get_data(AxisAtom)`: A list containing `axis` and `keepdims`.
- `validate_args(AxisAtom)`: Check that the new dimensions have the same number of entries as the old.
- `.axis_grad(AxisAtom)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(AxisAtom)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable

Slots

`expr` A numeric element, data.frame, matrix, vector, or Expression.

`axis` (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.

`keepdims` (Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

BinaryOperator-class *The BinaryOperator class.*

Description

This base class represents expressions involving binary operators.

Usage

```
## S4 method for signature 'BinaryOperator'
name(x)
```

```
## S4 method for signature 'BinaryOperator'
to_numeric(object, values)
```

```
## S4 method for signature 'BinaryOperator'
sign_from_args(object)
```

```
## S4 method for signature 'BinaryOperator'
is_imag(object)
```

```
## S4 method for signature 'BinaryOperator'
is_complex(object)
```

Arguments

`x, object` A [BinaryOperator](#) object.

`values` A list of arguments to the atom.

Methods (by generic)

- `name(BinaryOperator)`: Returns the name of the BinaryOperator object.
- `to_numeric(BinaryOperator)`: Apply the binary operator to the values.
- `sign_from_args(BinaryOperator)`: Default to rule for multiplication.
- `is_imag(BinaryOperator)`: Is the expression imaginary?
- `is_complex(BinaryOperator)`: Is the expression complex valued?

Slots

`lh_exp` The [Expression](#) on the left-hand side of the operator.
`rh_exp` The [Expression](#) on the right-hand side of the operator.
`op_name` A character string indicating the binary operation.

bmat

*Block Matrix***Description**

Constructs a block matrix from a list of lists. Each internal list is stacked horizontally, and the internal lists are stacked vertically.

Usage

```
bmat(block_lists)
```

Arguments

`block_lists` A list of lists containing [Expression](#) objects, matrices, or vectors, which represent the blocks of the block matrix.

Value

An [Expression](#) representing the block matrix.

Examples

```
x <- Variable()
expr <- bmat(list(list(matrix(1, nrow = 3, ncol = 1), matrix(2, nrow = 3, ncol = 2)),
                  list(matrix(3, nrow = 1, ncol = 2), x)
                ))
prob <- Problem(Minimize(sum_entries(expr)), list(x >= 0))
result <- solve(prob)
result$value
```

CallbackParam-class *The CallbackParam class.*

Description

This class represents a parameter whose value is obtained by evaluating a function.

Usage

```
CallbackParam(callback, dim = NULL, ...)

## S4 method for signature 'CallbackParam'
value(object)
```

Arguments

callback	A callback function that generates the parameter value.
dim	The dimensions of the parameter.
...	Additional attribute arguments. See Leaf for details.
object	A CallbackParam object.

Slots

callback	A callback function that generates the parameter value.
dim	The dimensions of the parameter.

Examples

```
x <- Variable(2)
fun <- function() { value(x) }
y <- CallbackParam(fun, dim(x), nonneg = TRUE)
get_data(y)
```

Canonical-class *The Canonical class.*

Description

This virtual class represents a canonical expression.

Usage

```
## S4 method for signature 'Canonical'  
expr(object)
```

```
## S4 method for signature 'Canonical'  
id(object)
```

```
## S4 method for signature 'Canonical'  
canonical_form(object)
```

```
## S4 method for signature 'Canonical'  
variables(object)
```

```
## S4 method for signature 'Canonical'  
parameters(object)
```

```
## S4 method for signature 'Canonical'  
constants(object)
```

```
## S4 method for signature 'Canonical'  
atoms(object)
```

```
## S4 method for signature 'Canonical'  
get_data(object)
```

Arguments

object A [Canonical](#) object.

Methods (by generic)

- `expr(Canonical)`: The expression associated with the input.
- `id(Canonical)`: The unique ID of the canonical expression.
- `canonical_form(Canonical)`: The graph implementation of the input.
- `variables(Canonical)`: List of [Variable](#) objects in the expression.
- `parameters(Canonical)`: List of [Parameter](#) objects in the expression.
- `constants(Canonical)`: List of [Constant](#) objects in the expression.
- `atoms(Canonical)`: List of [Atom](#) objects in the expression.
- `get_data(Canonical)`: Information needed to reconstruct the expression aside from its arguments.

Canonicalization-class

The Canonicalization class.

Description

This class represents a canonicalization reduction.

Usage

```
## S4 method for signature 'Canonicalization,Problem'
perform(object, problem)

## S4 method for signature 'Canonicalization,Solution,InverseData'
invert(object, solution, inverse_data)

## S4 method for signature 'Canonicalization'
canonicalize_tree(object, expr)

## S4 method for signature 'Canonicalization'
canonicalize_expr(object, expr, args)
```

Arguments

object	A Canonicalization object.
problem	A Problem object.
solution	A Solution to a problem that generated the inverse data.
inverse_data	An InverseData object that contains the data encoding the original problem.
expr	An Expression object.
args	List of arguments to canonicalize the expression.

Methods (by generic)

- `perform(object = Canonicalization, problem = Problem)`: Recursively canonicalize the objective and every constraint.
- `invert( object = Canonicalization, solution = Solution, inverse_data = InverseData )`: Performs the reduction on a problem and returns an equivalent problem.
- `canonicalize_tree(Canonicalization)`: Recursively canonicalize an Expression.
- `canonicalize_expr(Canonicalization)`: Canonicalize an expression, w.r.t. canonicalized arguments.

canonicalize	<i>Canonicalize</i>
--------------	---------------------

Description

Computes the graph implementation of a canonical expression.

Usage

```
canonicalize(object)

canonical_form(object)
```

Arguments

object A [Canonical](#) object.

Value

A list of list(affine expression, list(constraints)).

CBC_CONIC-class	<i>An interface to the CBC solver</i>
-----------------	---------------------------------------

Description

An interface to the CBC solver

Usage

```
CBC_CONIC()

## S4 method for signature 'CBC_CONIC'
mip_capable(solver)

## S4 method for signature 'CBC_CONIC'
status_map(solver, status)

## S4 method for signature 'CBC_CONIC'
status_map_mip(solver, status)

## S4 method for signature 'CBC_CONIC'
status_map_lp(solver, status)

## S4 method for signature 'CBC_CONIC'
name(x)
```

```

## S4 method for signature 'CBC_CONIC'
import_solver(solver)

## S4 method for signature 'CBC_CONIC,Problem'
accepts(object, problem)

## S4 method for signature 'CBC_CONIC,Problem'
perform(object, problem)

## S4 method for signature 'CBC_CONIC,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'CBC_CONIC'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

<code>solver, object, x</code>	A CBC_CONIC object.
<code>status</code>	A status code returned by the solver.
<code>problem</code>	A Problem object.
<code>solution</code>	The raw solution returned by the solver.
<code>inverse_data</code>	A list containing data necessary for the inversion.
<code>data</code>	Data generated via an apply call.
<code>warm_start</code>	A boolean of whether to warm start the solver.
<code>verbose</code>	A boolean of whether to enable solver verbosity.
<code>feastol</code>	The feasible tolerance.
<code>reltol</code>	The relative tolerance.
<code>abstol</code>	The absolute tolerance.
<code>num_iter</code>	The maximum number of iterations.
<code>solver_opts</code>	A list of Solver specific options
<code>solver_cache</code>	Cache for the solver.

Methods (by generic)

- `mip_capable(CBC_CONIC)`: Can the solver handle mixed-integer programs?
- `status_map(CBC_CONIC)`: Converts status returned by the CBC solver to its respective CVXPY status.
- `status_map_mip(CBC_CONIC)`: Converts status returned by the CBC solver to its respective CVXPY status for mixed integer problems.
- `status_map_lp(CBC_CONIC)`: Converts status returned by the CBC solver to its respective CVXPY status for linear problems.
- `name(CBC_CONIC)`: Returns the name of the solver
- `import_solver(CBC_CONIC)`: Imports the solver
- `accepts(object = CBC_CONIC, problem = Problem)`: Can CBC_CONIC solve the problem?
- `perform(object = CBC_CONIC, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `invert(object = CBC_CONIC, solution = list, inverse_data = list)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(CBC_CONIC)`: Solve a problem represented by data returned from apply.

cdiac

*Global Monthly and Annual Temperature Anomalies (degrees C),
1850-2015 (Relative to the 1961-1990 Mean) (May 2016)*

Description

Global Monthly and Annual Temperature Anomalies (degrees C), 1850-2015 (Relative to the 1961-1990 Mean) (May 2016)

Usage

cdiac

Format

A data frame with 166 rows and 14 variables:

year Year

jan Anomaly for month of January

feb Anomaly for month of February

mar Anomaly for month of March

apr Anomaly for month of April

may Anomaly for month of May

jun Anomaly for month of June

jul Anomaly for month of July

aug Anomaly for month of August
sep Anomaly for month of September
oct Anomaly for month of October
nov Anomaly for month of November
dec Anomaly for month of December
annual Annual anomaly for the year

Source

<https://ess-dive.lbl.gov/>

References

<https://ess-dive.lbl.gov/>

Chain-class

The Chain class.

Description

This class represents a reduction that replaces symbolic parameters with their constraint values.

Usage

```
## S4 method for signature 'Chain'
as.character(x)

## S4 method for signature 'Chain,Problem'
accepts(object, problem)

## S4 method for signature 'Chain,Problem'
perform(object, problem)

## S4 method for signature 'Chain,SolutionORList,list'
invert(object, solution, inverse_data)
```

Arguments

<code>x, object</code>	A Chain object.
<code>problem</code>	A Problem object to check.
<code>solution</code>	A Solution or list.
<code>inverse_data</code>	A list that contains the data encoding the original problem.

Methods (by generic)

- `accepts(object = Chain, problem = Problem)`: A problem is accepted if the sequence of reductions is valid. In particular, the i -th reduction must accept the output of the i -1th reduction, with the first reduction (`self.reductions[0]`) in the sequence taking as input the supplied problem.
- `perform(object = Chain, problem = Problem)`: Applies the chain to a problem and returns an equivalent problem.
- `invert(object = Chain, solution = SolutionORList, inverse_data = list)`: Performs the reduction on a problem and returns an equivalent problem.

CLARABEL-class

An interface for the CLARABEL solver

Description

An interface for the CLARABEL solver

Usage

```
CLARABEL()

## S4 method for signature 'CLARABEL'
mip_capable(solver)

## S4 method for signature 'CLARABEL'
status_map(solver, status)

## S4 method for signature 'CLARABEL'
name(x)

## S4 method for signature 'CLARABEL'
import_solver(solver)

## S4 method for signature 'CLARABEL'
reduction_format_constr(object, problem, constr, exp_cone_order)

## S4 method for signature 'CLARABEL,Problem'
perform(object, problem)

## S4 method for signature 'CLARABEL,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'CLARABEL'
solve_via_data(
  object,
  data,
```

```

    warm_start,
    verbose,
    feastol,
    reltol,
    abstol,
    num_iter,
    solver_opts,
    solver_cache
)

```

Arguments

solver, object, x	A CLARABEL object.
status	A status code returned by the solver.
problem	A Problem object.
constr	A Constraint to format.
exp_cone_order	A list indicating how the exponential cone arguments are ordered.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance on the primal and dual residual.
reltol	The relative tolerance on the duality gap.
abstol	The absolute tolerance on the duality gap.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(CLARABEL)`: Can the solver handle mixed-integer programs?
- `status_map(CLARABEL)`: Converts status returned by CLARABEL solver to its respective CVXPY status.
- `name(CLARABEL)`: Returns the name of the solver
- `import_solver(CLARABEL)`: Imports the solver
- `reduction_format_constr(CLARABEL)`: Return a linear operator to multiply by PSD constraint coefficients.
- `perform(object = CLARABEL, problem = Problem)`: Returns a new problem and data for inverting the new solution
- `invert(object = CLARABEL, solution = list, inverse_data = list)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(CLARABEL)`: Solve a problem represented by data returned from apply.

```
CLARABEL.dims_to_solver_dict
```

Utility method for formatting a ConeDims instance into a dictionary that can be supplied to Clarabel

Description

Utility method for formatting a ConeDims instance into a dictionary that can be supplied to Clarabel

Usage

```
CLARABEL.dims_to_solver_dict(cone_dims)
```

Arguments

cone_dims A [ConeDims](#) instance.

Value

The dimensions of the cones.

```
CLARABEL.extract_dual_value
```

Extracts the dual value for constraint starting at offset.

Description

Special cases PSD constraints, as per the CLARABEL specification.

Usage

```
CLARABEL.extract_dual_value(result_vec, offset, constraint)
```

Arguments

result_vec The vector to extract dual values from.
 offset The starting point of the vector to extract from.
 constraint A [Constraint](#) object.

Value

The dual values for the corresponding PSD constraints

complex-atoms

Complex Numbers

Description

Basic atoms that support complex arithmetic.

Usage

```
## S4 method for signature 'Expression'  
Re(z)
```

```
## S4 method for signature 'Expression'  
Im(z)
```

```
## S4 method for signature 'Expression'  
Conj(z)
```

Arguments

`z` An [Expression](#) object.

Value

An [Expression](#) object that represents the real, imaginary, or complex conjugate.

complex-methods

Complex Properties

Description

Determine if an expression is real, imaginary, or complex.

Usage

```
is_real(object)
```

```
is_imag(object)
```

```
is_complex(object)
```

Arguments

`object` An [Expression](#) object.

Value

A logical value.

Complex2Real-class	<i>Lifts complex numbers to a real representation.</i>
--------------------	--

Description

This reduction takes in a complex problem and returns an equivalent real problem.

Usage

```
## S4 method for signature 'Complex2Real,Problem'
accepts(object, problem)

## S4 method for signature 'Complex2Real,Problem'
perform(object, problem)

## S4 method for signature 'Complex2Real,Solution,InverseData'
invert(object, solution, inverse_data)
```

Arguments

object	A Complex2Real object.
problem	A Problem object.
solution	A Solution object to invert.
inverse_data	A InverseData object containing data necessary for the inversion.

Methods (by generic)

- `accepts(object = Complex2Real, problem = Problem)`: Checks whether or not the problem involves any complex numbers.
- `perform(object = Complex2Real, problem = Problem)`: Converts a Complex problem into a Real one.
- `invert(object = Complex2Real, solution = Solution, inverse_data = InverseData)`: Returns a solution to the original problem given the inverse data.

Complex2Real.abs_canon

Complex canonicalizer for the absolute value atom

Description

Complex canonicalizer for the absolute value atom

Usage

```
Complex2Real.abs_canon(expr, real_args, imag_args, real2imag)
```

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of the absolute value atom of a complex expression, where the returned variables are its real and imaginary components parsed out.

Complex2Real.add	<i>Helper function to sum arguments.</i>
------------------	--

Description

Helper function to sum arguments.

Usage

```
Complex2Real.add(lh_arg, rh_arg, neg = FALSE)
```

Arguments

lh_arg	The arguments for the left-hand side
rh_arg	The arguments for the right-hand side
neg	Whether to negate the right hand side

Complex2Real.at_least_2D	<i>Upcast 0D and 1D to 2D.</i>
--------------------------	--------------------------------

Description

Upcast 0D and 1D to 2D.

Usage

```
Complex2Real.at_least_2D(expr)
```

Arguments

expr	An Expression object
------	--------------------------------------

Value

An expression of dimension at least 2.

Complex2Real.binary_canon
<i>Complex canonicalizer for the binary atom</i>

Description

Complex canonicalizer for the binary atom

Usage

Complex2Real.binary_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a binary atom, where the returned variables are the real component and the imaginary component.

Complex2Real.canonicalize_expr
<i>Canonicalizes a Complex Expression</i>

Description

Canonicalizes a Complex Expression

Usage

Complex2Real.canonicalize_expr(expr, real_args, imag_args, real2imag, leaf_map)

Arguments

expr	An Expression object.
real_args	A list of Constraint objects for the real part of the expression.
imag_args	A list of Constraint objects for the imaginary part of the expression.
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.
leaf_map	A map that consists of a tree representation of the overall expression

Value

A list of the parsed out real and imaginary components of the expression at hand.

Complex2Real.canonicalize_tree

Recursively Canonicalizes a Complex Expression.

Description

Recursively Canonicalizes a Complex Expression.

Usage

Complex2Real.canonicalize_tree(expr, real2imag, leaf_map)

Arguments

expr	An Expression object.
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.
leaf_map	A map that consists of a tree representation of the expression.

Value

A list of the parsed out real and imaginary components of the expression that was constructed by performing the canonicalization of each leaf in the tree.

Complex2Real.conj_canon

Complex canonicalizer for the conjugate atom

Description

Complex canonicalizer for the conjugate atom

Usage

Complex2Real.conj_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a conjugate atom, where the returned variables are the real components and negative of the imaginary component.

Complex2Real.constant_canon

Complex canonicalizer for the constant atom

Description

Complex canonicalizer for the constant atom

Usage

Complex2Real.constant_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a constant atom, where the returned variables are the real component and the imaginary component in the [Constant](#) atom.

Complex2Real.hermitian_canon
<i>Complex canonicalizer for the hermitian atom</i>

Description

Complex canonicalizer for the hermitian atom

Usage

Complex2Real.hermitian_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a hermitian matrix atom, where the returned variables are the real component and the imaginary component.

Complex2Real.imag_canon
<i>Complex canonicalizer for the imaginary atom</i>

Description

Complex canonicalizer for the imaginary atom

Usage

Complex2Real.imag_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of an imaginary atom, where the returned variables are the imaginary component and NULL for the real component.

Complex2Real.join	<i>Helper function to combine arguments.</i>
-------------------	--

Description

Helper function to combine arguments.

Usage

```
Complex2Real.join(expr, lh_arg, rh_arg)
```

Arguments

expr	An Expression object
lh_arg	The arguments for the left-hand side
rh_arg	The arguments for the right-hand side

Value

A joined expression of both left and right expressions

Complex2Real.lambda_sum_largest_canon
Complex canonicalizer for the largest sum atom

Description

Complex canonicalizer for the largest sum atom

Usage

Complex2Real.lambda_sum_largest_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of the largest sum atom, where the returned variables are the real component and the imaginary component.

Complex2Real.matrix_frac_canon
Complex canonicalizer for the matrix fraction atom

Description

Complex canonicalizer for the matrix fraction atom

Usage

Complex2Real.matrix_frac_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a matrix atom, where the returned variables are converted to real variables.

Complex2Real.nonpos_canon
<i>Complex canonicalizer for the non-positive atom</i>

Description

Complex canonicalizer for the non-positive atom

Usage

Complex2Real.nonpos_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a non positive atom, where the returned variables are the real component and the imaginary component.

Complex2Real.norm_nuc_canon
<i>Complex canonicalizer for the nuclear norm atom</i>

Description

Complex canonicalizer for the nuclear norm atom

Usage

Complex2Real.norm_nuc_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a nuclear norm matrix atom, where the returned variables are the real component and the imaginary component.

Complex2Real.param_canon
<i>Complex canonicalizer for the parameter matrix atom</i>

Description

Complex canonicalizer for the parameter matrix atom

Usage

Complex2Real.param_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a parameter matrix atom, where the returned variables are the real component and the imaginary component.

Complex2Real.pnorm_canon
<i>Complex canonicalizer for the p norm atom</i>

Description

Complex canonicalizer for the p norm atom

Usage

Complex2Real.pnorm_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a pnorm atom, where the returned variables are the real component and the NULL imaginary component.

Complex2Real.psd_canon
<i>Complex canonicalizer for the positive semidefinite atom</i>

Description

Complex canonicalizer for the positive semidefinite atom

Usage

Complex2Real.psd_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a positive semidefinite atom, where the returned variables are the real component and the NULL imaginary component.

Complex2Real.quad_canon
<i>Complex canonicalizer for the quadratic atom</i>

Description

Complex canonicalizer for the quadratic atom

Usage

Complex2Real.quad_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a quadratic atom, where the returned variables are the real component and the imaginary component as NULL.

Complex2Real.quad_over_lin_canon
<i>Complex canonicalizer for the quadratic over linear term atom</i>

Description

Complex canonicalizer for the quadratic over linear term atom

Usage

Complex2Real.quad_over_lin_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a quadratic over a linear term atom, where the returned variables are the real component and the imaginary component.

Complex2Real.real_canon
<i>Complex canonicalizer for the real atom</i>

Description

Complex canonicalizer for the real atom

Usage

Complex2Real.real_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a real atom, where the returned variables are the real component and NULL for the imaginary component.

Complex2Real.separable_canon

Complex canonicalizer for the separable atom

Description

Complex canonicalizer for the separable atom

Usage

Complex2Real.separable_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a separable atom, where the returned variables are its real and imaginary components parsed out.

Complex2Real.soc_canon

Complex canonicalizer for the SOC atom

Description

Complex canonicalizer for the SOC atom

Usage

Complex2Real.soc_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a SOC atom, where the returned variables are the real component and the NULL imaginary component.

Complex2Real.variable_canon
<i>Complex canonicalizer for the variable atom</i>

Description

Complex canonicalizer for the variable atom

Usage

Complex2Real.variable_canon(expr, real_args, imag_args, real2imag)

Arguments

- | | |
|-----------|---|
| expr | An Expression object |
| real_args | A list of Constraint objects for the real part of the expression |
| imag_args | A list of Constraint objects for the imaginary part of the expression |
| real2imag | A list mapping the ID of the real part of a complex expression to the ID of its imaginary part. |

Value

A canonicalization of a variable atom, where the returned variables are the real component and the NULL imaginary component.

Complex2Real.zero_canon
<i>Complex canonicalizer for the zero atom</i>

Description

Complex canonicalizer for the zero atom

Usage

Complex2Real.zero_canon(expr, real_args, imag_args, real2imag)

Arguments

expr	An Expression object
real_args	A list of Constraint objects for the real part of the expression
imag_args	A list of Constraint objects for the imaginary part of the expression
real2imag	A list mapping the ID of the real part of a complex expression to the ID of its imaginary part.

Value

A canonicalization of a zero atom, where the returned variables are the real component and the imaginary component.

cone-methods	<i>Second-Order Cone Methods</i>
--------------	----------------------------------

Description

The number of elementwise cones or a list of the sizes of the elementwise cones.

Usage

num_cones(object)

cone_sizes(object)

Arguments

object An [SOCAxis](#) object.

Value

The number of cones, or the size of a cone.

ConeDims-class	<i>Summary of cone dimensions present in constraints.</i>
----------------	---

Description

Constraints must be formatted as dictionary that maps from constraint type to a list of constraints of that type.

Details

Attributes ——— zero : int The dimension of the zero cone. nonpos : int The dimension of the non-positive cone. exp : int The dimension of the exponential cone. soc : list of int A list of the second-order cone dimensions. psd : list of int A list of the positive semidefinite cone dimensions, where the dimension of the PSD cone of k by k matrices is k.

ConeMatrixStuffing-class

Construct Matrices for Linear Cone Problems

Description

Linear cone problems are assumed to have a linear objective and cone constraints, which may have zero or more arguments, all of which must be affine.

Usage

```
## S4 method for signature 'ConeMatrixStuffing,Problem'
accepts(object, problem)

## S4 method for signature 'ConeMatrixStuffing,Problem,CoeffExtractor'
stuffed_objective(object, problem, extractor)
```

Arguments

object	A ConeMatrixStuffing object.
problem	A Problem object.
extractor	Used to extract the affine coefficients of the objective.

Details

minimize $c^T x$ subject to cone_constr1($A_1 x + b_1, \dots$) ... cone_constrK($A_K x + b_K, \dots$)

Methods (by generic)

- `accepts(object = ConeMatrixStuffing, problem = Problem)`: Is the solver accepted?
- `stuffed_objective(object = ConeMatrixStuffing, problem = Problem, extractor = CoeffExtractor)`: Returns a list of the stuffed matrices

ConicSolver-class

The ConicSolver class.

Description

Conic solver class with reduction semantics.

Usage

```

## S4 method for signature 'ConicSolver,Problem'
accepts(object, problem)

## S4 method for signature 'ConicSolver'
reduction_format_constr(object, problem, constr, exp_cone_order)

## S4 method for signature 'ConicSolver'
group_coeff_offset(object, problem, constraints, exp_cone_order)

## S4 method for signature 'ConicSolver,Solution,InverseData'
invert(object, solution, inverse_data)

```

Arguments

object	A ConicSolver object.
problem	A Problem object.
constr	A Constraint to format.
exp_cone_order	A list indicating how the exponential cone arguments are ordered.
constraints	A list of Constraint objects.
solution	A Solution object to invert.
inverse_data	A InverseData object containing data necessary for the inversion.

Methods (by generic)

- `accepts(object = ConicSolver, problem = Problem)`: Can the problem be solved with a conic solver?
- `reduction_format_constr(ConicSolver)`: Return a list representing a cone program whose problem data tensors will yield the coefficient "A" and offset "b" for the respective constraints: Linear Equations: $Ax = b$, Linear inequalities: $Ax \leq b$, Second order cone: $Ax \leq_{SOC} b$, Exponential cone: $Ax \leq_{EXP} b$, Semidefinite cone: $Ax \leq_{SOP} b$.
- `group_coeff_offset(ConicSolver)`: Combine the constraints into a single matrix, offset.
- `invert(object = ConicSolver, solution = Solution, inverse_data = InverseData)`: Returns the solution to the original problem given the `inverse_data`.

`ConicSolver.get_coeff_offset`

Return the coefficient and offset in $Ax + b$.

Description

Return the coefficient and offset in $Ax + b$.

Usage

```
ConicSolver.get_coeff_offset(expr)
```

Arguments

expr An [Expression](#) object.

Value

The coefficient and offset in $Ax + b$.

```
ConicSolver.get_spacing_matrix
```

Returns a sparse matrix that spaces out an expression.

Description

Returns a sparse matrix that spaces out an expression.

Usage

```
ConicSolver.get_spacing_matrix(dim, spacing, offset)
```

Arguments

dim A vector outlining the dimensions of the matrix.

spacing An int of the number of rows between the start of each non-zero block.

offset An int of the number of zeros at the beginning of the matrix.

Value

A sparse matrix that spaces out an expression

Conjugate-class	<i>The Conjugate class.</i>
-----------------	-----------------------------

Description

This class represents the complex conjugate of an expression.

Usage

```
Conjugate(expr)
```

```
## S4 method for signature 'Conjugate'
to_numeric(object, values)
```

```
## S4 method for signature 'Conjugate'
dim_from_args(object)
```

```
## S4 method for signature 'Conjugate'
is_incr(object, idx)
```

```
## S4 method for signature 'Conjugate'
is_decr(object, idx)
```

```
## S4 method for signature 'Conjugate'
is_symmetric(object)
```

```
## S4 method for signature 'Conjugate'
is_hermitian(object)
```

Arguments

expr	An Expression or R numeric data.
object	A Conjugate object.
values	A list of arguments to the atom.
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Conjugate)`: Elementwise complex conjugate of the constant.
- `dim_from_args(Conjugate)`: The (row, col) dimensions of the expression.
- `is_incr(Conjugate)`: Is the composition weakly increasing in argument idx?
- `is_decr(Conjugate)`: Is the composition weakly decreasing in argument idx?
- `is_symmetric(Conjugate)`: Is the expression symmetric?
- `is_hermitian(Conjugate)`: Is the expression hermitian?

Slots

expr An [Expression](#) or R numeric data.

Constant-class

The Constant class.

Description

This class represents a constant.

Coerce an R object or expression into the [Constant](#) class.

Usage

```
Constant(value)
```

```
## S4 method for signature 'Constant'  
show(object)
```

```
## S4 method for signature 'Constant'  
name(x)
```

```
## S4 method for signature 'Constant'  
constants(object)
```

```
## S4 method for signature 'Constant'  
value(object)
```

```
## S4 method for signature 'Constant'  
is_pos(object)
```

```
## S4 method for signature 'Constant'  
grad(object)
```

```
## S4 method for signature 'Constant'  
dim(x)
```

```
## S4 method for signature 'Constant'  
canonicalize(object)
```

```
## S4 method for signature 'Constant'  
is_nonneg(object)
```

```
## S4 method for signature 'Constant'  
is_nonpos(object)
```

```
## S4 method for signature 'Constant'
```

```

is_imag(object)

## S4 method for signature 'Constant'
is_complex(object)

## S4 method for signature 'Constant'
is_symmetric(object)

## S4 method for signature 'Constant'
is_hermitian(object)

## S4 method for signature 'Constant'
is_psd(object)

## S4 method for signature 'Constant'
is_nsd(object)

as.Constant(expr)

```

Arguments

value	A numeric element, vector, matrix, or data.frame. Vectors are automatically cast into a matrix column.
x, object	A Constant object.
expr	An Expression , numeric element, vector, matrix, or data.frame.

Value

A [Constant](#) representing the input as a constant.

Methods (by generic)

- `name(Constant)`: The name of the constant.
- `constants(Constant)`: Returns itself as a constant.
- `value(Constant)`: The value of the constant.
- `is_pos(Constant)`: A logical value indicating whether all elements of the constant are positive.
- `grad(Constant)`: An empty list since the gradient of a constant is zero.
- `dim(Constant)`: The `c(row, col)` dimensions of the constant.
- `canonicalize(Constant)`: The canonical form of the constant.
- `is_nonneg(Constant)`: A logical value indicating whether all elements of the constant are non-negative.
- `is_nonpos(Constant)`: A logical value indicating whether all elements of the constant are non-positive.
- `is_imag(Constant)`: A logical value indicating whether the constant is imaginary.
- `is_complex(Constant)`: A logical value indicating whether the constant is complex-valued.

- `is_symmetric(Constant)`: A logical value indicating whether the constant is symmetric.
- `is_hermitian(Constant)`: A logical value indicating whether the constant is a Hermitian matrix.
- `is_psd(Constant)`: A logical value indicating whether the constant is a positive semidefinite matrix.
- `is_nsd(Constant)`: A logical value indicating whether the constant is a negative semidefinite matrix.

Slots

`value` A numeric element, vector, matrix, or data.frame. Vectors are automatically cast into a matrix column.

`sparse` (Internal) A logical value indicating whether the value is a sparse matrix.

`is_pos` (Internal) A logical value indicating whether all elements are non-negative.

`is_neg` (Internal) A logical value indicating whether all elements are non-positive.

Examples

```
x <- Constant(5)
y <- Constant(diag(3))
get_data(y)
value(y)
is_nonneg(y)
size(y)
as.Constant(y)
```

ConstantSolver-class *The ConstantSolver class.*

Description

The ConstantSolver class.

Usage

```
## S4 method for signature 'ConstantSolver'
mip_capable(solver)

## S4 method for signature 'ConstantSolver,Problem'
accepts(object, problem)

## S4 method for signature 'ConstantSolver,Problem'
perform(object, problem)

## S4 method for signature 'ConstantSolver,Solution,list'
invert(object, solution, inverse_data)
```

```

## S4 method for signature 'ConstantSolver'
name(x)

## S4 method for signature 'ConstantSolver'
import_solver(solver)

## S4 method for signature 'ConstantSolver'
is_installed(solver)

## S4 method for signature 'ConstantSolver'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

## S4 method for signature 'ConstantSolver,ANY'
reduction_solve(object, problem, warm_start, verbose, solver_opts)

```

Arguments

solver, object, x	A ConstantSolver object.
problem	A Problem object.
solution	A Solution object to invert.
inverse_data	A list containing data necessary for the inversion.
data	Data for the solver.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(ConstantSolver)`: Can the solver handle mixed-integer programs?
- `accepts(object = ConstantSolver, problem = Problem)`: Is the solver capable of solving the problem?
- `perform(object = ConstantSolver, problem = Problem)`: Returns a list of the Constant-Solver, Problem, and an empty list.
- `invert(object = ConstantSolver, solution = Solution, inverse_data = list)`: Returns the solution.
- `name(ConstantSolver)`: Returns the name of the solver.
- `import_solver(ConstantSolver)`: Imports the solver.
- `is_installed(ConstantSolver)`: Is the solver installed?
- `solve_via_data(ConstantSolver)`: Solve a problem represented by data returned from `apply`.
- `reduction_solve(object = ConstantSolver, problem = ANY)`: Solve the problem and return a [Solution](#) object.

 Constraint-class

The Constraint class.

Description

This virtual class represents a mathematical constraint.

Usage

```
## S4 method for signature 'Constraint'
as.character(x)

## S4 method for signature 'Constraint'
dim(x)

## S4 method for signature 'Constraint'
size(object)

## S4 method for signature 'Constraint'
is_real(object)

## S4 method for signature 'Constraint'
is_imag(object)

## S4 method for signature 'Constraint'
is_complex(object)

## S4 method for signature 'Constraint'
```

```

is_dcp(object)

## S4 method for signature 'Constraint'
is_dgp(object)

## S4 method for signature 'Constraint'
residual(object)

## S4 method for signature 'Constraint'
violation(object)

## S4 method for signature 'Constraint'
constr_value(object, tolerance = 1e-08)

## S4 method for signature 'Constraint'
get_data(object)

## S4 method for signature 'Constraint'
dual_value(object)

## S4 replacement method for signature 'Constraint'
dual_value(object) <- value

## S4 method for signature 'ZeroConstraint'
size(object)

```

Arguments

x, object	A Constraint object.
tolerance	The tolerance for checking if the constraint is violated.
value	A numeric scalar, vector, or matrix.

Methods (by generic)

- `dim(Constraint)`: The dimensions of the constrained expression.
- `size(Constraint)`: The size of the constrained expression.
- `is_real(Constraint)`: Is the constraint real?
- `is_imag(Constraint)`: Is the constraint imaginary?
- `is_complex(Constraint)`: Is the constraint complex?
- `is_dcp(Constraint)`: Is the constraint DCP?
- `is_dgp(Constraint)`: Is the constraint DGP?
- `residual(Constraint)`: The residual of a constraint
- `violation(Constraint)`: The violation of a constraint.
- `constr_value(Constraint)`: The value of a constraint.
- `get_data(Constraint)`: Information needed to reconstruct the object aside from the args.

- `dual_value(Constraint)`: The dual values of a constraint.
- `dual_value(Constraint) <- value`: Replaces the dual values of a constraint..
- `size(ZeroConstraint)`: The size of the constrained expression.

`construct_intermediate_chain, Problem, list-method`

Builds a chain that rewrites a problem into an intermediate representation suitable for numeric reductions.

Description

Builds a chain that rewrites a problem into an intermediate representation suitable for numeric reductions.

Usage

```
## S4 method for signature 'Problem,list'
construct_intermediate_chain(problem, candidates, gp = FALSE)
```

Arguments

<code>problem</code>	The problem for which to build a chain.
<code>candidates</code>	A list of candidate solvers.
<code>gp</code>	A logical value indicating whether the problem is a geometric program.

Value

A [Chain](#) object that can be used to convert the problem to an intermediate form.

`construct_solving_chain`

Build a reduction chain from a problem to an installed solver.

Description

Build a reduction chain from a problem to an installed solver.

Usage

```
construct_solving_chain(problem, candidates)
```

Arguments

<code>problem</code>	The problem for which to build a chain.
<code>candidates</code>	A list of candidate solvers.

Value

A [SolvingChain](#) that can be used to solve the problem.

constr_value	<i>Is Constraint Violated?</i>
--------------	--------------------------------

Description

Checks whether the constraint violation is less than a tolerance.

Usage

```
constr_value(object, tolerance = 1e-08)
```

Arguments

object	A Constraint object.
tolerance	A numeric scalar representing the absolute tolerance to impose on the violation.

Value

A logical value indicating whether the violation is less than the tolerance. Raises an error if the residual is NA.

conv	<i>Discrete Convolution</i>
------	-----------------------------

Description

The 1-D discrete convolution of two vectors.

Usage

```
conv(lh_exp, rh_exp)
```

Arguments

lh_exp	An Expression or vector representing the left-hand value.
rh_exp	An Expression or vector representing the right-hand value.

Value

An [Expression](#) representing the convolution of the input.

Examples

```

set.seed(129)
x <- Variable(5)
h <- matrix(stats::rnorm(2), nrow = 2, ncol = 1)
prob <- Problem(Minimize(sum(conv(h, x))))
result <- solve(prob)
result$value
result$getValue(x)

```

Conv-class

*The Conv class.***Description**

This class represents the 1-D discrete convolution of two vectors.

Usage

```
Conv(lh_exp, rh_exp)
```

```
## S4 method for signature 'Conv'
to_numeric(object, values)
```

```
## S4 method for signature 'Conv'
validate_args(object)
```

```
## S4 method for signature 'Conv'
dim_from_args(object)
```

```
## S4 method for signature 'Conv'
sign_from_args(object)
```

```
## S4 method for signature 'Conv'
is_incr(object, idx)
```

```
## S4 method for signature 'Conv'
is_decr(object, idx)
```

```
## S4 method for signature 'Conv'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

lh_exp	An Expression or R numeric data representing the left-hand vector.
rh_exp	An Expression or R numeric data representing the right-hand vector.
object	A Conv object.
values	A list of arguments to the atom.

idx	An index into the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(Conv)`: The convolution of the two values.
- `validate_args(Conv)`: Check both arguments are vectors and the first is a constant.
- `dim_from_args(Conv)`: The dimensions of the atom.
- `sign_from_args(Conv)`: The sign of the atom.
- `is_incr(Conv)`: Is the left-hand expression positive?
- `is_decr(Conv)`: Is the left-hand expression negative?
- `graph_implementation(Conv)`: The graph implementation of the atom.

Slots

lh_exp An [Expression](#) or R numeric data representing the left-hand vector.
rh_exp An [Expression](#) or R numeric data representing the right-hand vector.

CPLEX_CONIC-class	<i>An interface for the CPLEX solver</i>
-------------------	--

Description

An interface for the CPLEX solver

Usage

```
CPLEX_CONIC()

CPLEX_CONIC()

## S4 method for signature 'CPLEX_CONIC'
mip_capable(solver)

## S4 method for signature 'CPLEX_CONIC'
name(x)

## S4 method for signature 'CPLEX_CONIC'
import_solver(solver)

## S4 method for signature 'CPLEX_CONIC,Problem'
accepts(object, problem)
```

```

## S4 method for signature 'CPLEX_CONIC'
status_map(solver, status)

## S4 method for signature 'CPLEX_CONIC,Problem'
perform(object, problem)

## S4 method for signature 'CPLEX_CONIC,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'CPLEX_CONIC'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A CPLEX_CONIC object.
problem	A Problem object.
status	A status code returned by the solver.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance on the primal and dual residual.
reltol	The relative tolerance on the duality gap.
abstol	The absolute tolerance on the duality gap.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(CPLEX_CONIC)`: Can the solver handle mixed-integer programs?

- `name(CPLEX_CONIC)`: Returns the name of the solver.
- `import_solver(CPLEX_CONIC)`: Imports the solver.
- `accepts(object = CPLEX_CONIC, problem = Problem)`: Can CPLEX solve the problem?
- `status_map(CPLEX_CONIC)`: Converts status returned by the CPLEX solver to its respective CVXPY status.
- `perform(object = CPLEX_CONIC, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `invert(object = CPLEX_CONIC, solution = list, inverse_data = list)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(CPLEX_CONIC)`: Solve a problem represented by data returned from apply.

CPLEX_QP-class

An interface for the CPLEX solver.

Description

An interface for the CPLEX solver.

Usage

```
CPLEX_QP()

## S4 method for signature 'CPLEX_QP'
mip_capable(solver)

## S4 method for signature 'CPLEX_QP'
status_map(solver, status)

## S4 method for signature 'CPLEX_QP'
name(x)

## S4 method for signature 'CPLEX_QP'
import_solver(solver)

## S4 method for signature 'CPLEX_QP,list,InverseData'
invert(object, solution, inverse_data)

## S4 method for signature 'CPLEX_QP'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
```



```

    abstol,
    num_iter,
    solver_opts,
    solver_cache
)

```

Arguments

status	A status code returned by the solver.
x, object, solver	A CPLEX_QP object.
solution	The raw solution returned by the solver.
inverse_data	A InverseData object containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance on the primal and dual residual.
reltol	The relative tolerance on the duality gap.
abstol	The absolute tolerance on the duality gap.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(CPLEX_QP)`: Can the solver handle mixed-integer programs?
- `status_map(CPLEX_QP)`: Converts status returned by the CPLEX solver to its respective CVXPY status.
- `name(CPLEX_QP)`: Returns the name of the solver.
- `import_solver(CPLEX_QP)`: Imports the solver.
- `invert(object = CPLEX_QP, solution = list, inverse_data = InverseData)`: Returns the solution to the original problem given the `inverse_data`.
- `solve_via_data(CPLEX_QP)`: Solve a problem represented by data returned from `apply`.

CumMax-class

*The CumMax class.***Description**

This class represents the cumulative maximum of an expression.

Usage

```
CumMax(expr, axis = 2)

## S4 method for signature 'CumMax'
to_numeric(object, values)

## S4 method for signature 'CumMax'
.grad(object, values)

## S4 method for signature 'CumMax'
.column_grad(object, value)

## S4 method for signature 'CumMax'
dim_from_args(object)

## S4 method for signature 'CumMax'
sign_from_args(object)

## S4 method for signature 'CumMax'
get_data(object)

## S4 method for signature 'CumMax'
is_atom_convex(object)

## S4 method for signature 'CumMax'
is_atom_concave(object)

## S4 method for signature 'CumMax'
is_incr(object, idx)

## S4 method for signature 'CumMax'
is_decr(object, idx)
```

Arguments

expr	An Expression .
axis	A numeric vector indicating the axes along which to apply the function. For a 2D matrix, 1 indicates rows, 2 indicates columns, and c(1,2) indicates rows and columns.

object	A CumMax object.
values	A list of numeric values for the arguments
value	A numeric value.
idx	An index into the atom.

Methods (by generic)

- `to_numeric(CumMax)`: The cumulative maximum along the axis.
- `.grad(CumMax)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(CumMax)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable
- `dim_from_args(CumMax)`: The dimensions of the atom determined from its arguments.
- `sign_from_args(CumMax)`: The (is positive, is negative) sign of the atom.
- `get_data(CumMax)`: Returns the axis along which the cumulative max is taken.
- `is_atom_convex(CumMax)`: Is the atom convex?
- `is_atom_concave(CumMax)`: Is the atom concave?
- `is_incr(CumMax)`: Is the atom weakly increasing in the index?
- `is_decr(CumMax)`: Is the atom weakly decreasing in the index?

Slots

`expr` An [Expression](#).

`axis` A numeric vector indicating the axes along which to apply the function. For a 2D matrix, 1 indicates rows, 2 indicates columns, and `c(1, 2)` indicates rows and columns.

<code>cummax_axis</code>	<i>Cumulative Maximum</i>
--------------------------	---------------------------

Description

The cumulative maximum, $\max_{i=1,\dots,k} x_i$ for $k = 1, \dots, n$. When calling `cummax`, matrices are automatically flattened into column-major order before the max is taken.

Usage

```
cummax_axis(expr, axis = 2)
```

```
## S4 method for signature 'Expression'
cummax(x)
```

Arguments

`axis` (Optional) The dimension across which to apply the function: 1 indicates rows, and 2 indicates columns. The default is 2.

`x, expr` An [Expression](#), vector, or matrix.

Examples

```

val <- cbind(c(1,2), c(3,4))
value(cummax(Constant(val)))
value(cummax_axis(Constant(val)))

x <- Variable(2,2)
prob <- Problem(Minimize(cummax(x)[4]), list(x == val))
result <- solve(prob)
result$value
result$getValue(cummax(x))

```

CumSum-class

*The CumSum class.***Description**

This class represents the cumulative sum.

Usage

```

CumSum(expr, axis = 2)

## S4 method for signature 'CumSum'
to_numeric(object, values)

## S4 method for signature 'CumSum'
dim_from_args(object)

## S4 method for signature 'CumSum'
get_data(object)

## S4 method for signature 'CumSum'
.grad(object, values)

## S4 method for signature 'CumSum'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

expr	An Expression to be summed.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, and 2 indicates columns. The default is 2.
object	A CumSum object.
values	A list of numeric values for the arguments
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(CumSum)`: The cumulative sum of the values along the specified axis.
- `dim_from_args(CumSum)`: The dimensions of the atom.
- `get_data(CumSum)`: Returns the axis along which the cumulative sum is taken.
- `.grad(CumSum)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `graph_implementation(CumSum)`: The graph implementation of the atom.

Slots

`expr` An [Expression](#) to be summed.

`axis` (Optional) The dimension across which to apply the function: 1 indicates rows, and 2 indicates columns. The default is 2.

<code>cumsum_axis</code>	<i>Cumulative Sum</i>
--------------------------	-----------------------

Description

The cumulative sum, $\sum_{i=1}^k x_i$ for $k = 1, \dots, n$. When calling `cumsum`, matrices are automatically flattened into column-major order before the sum is taken.

Usage

```
cumsum_axis(expr, axis = 2)

## S4 method for signature 'Expression'
cumsum(x)
```

Arguments

`axis` (Optional) The dimension across which to apply the function: 1 indicates rows, and 2 indicates columns. The default is 2.

`x, expr` An [Expression](#), vector, or matrix.

Examples

```
val <- cbind(c(1,2), c(3,4))
value(cumsum(Constant(val)))
value(cumsum_axis(Constant(val)))

x <- Variable(2,2)
prob <- Problem(Minimize(cumsum(x)[4]), list(x == val))
result <- solve(prob)
result$value
result$getValue(cumsum(x))
```

curvature	<i>Curvature of Expression</i>
-----------	--------------------------------

Description

The curvature of an expression.
The curvature of an expression.

Usage

```
curvature(object)  
  
## S4 method for signature 'Expression'  
curvature(object)
```

Arguments

object An [Expression](#) object.

Value

A string indicating the curvature of the expression, either "CONSTANT", "AFFINE", "CONVEX", "CONCAVE", or "UNKNOWN".
A string indicating the curvature of the expression, either "CONSTANT", "AFFINE", "CONVEX", "CONCAVE", or "UNKNOWN".

Examples

```
x <- Variable()  
c <- Constant(5)  
  
curvature(c)  
curvature(x)  
curvature(x^2)  
curvature(sqrt(x))  
curvature(log(x^3) + sqrt(x))
```

curvature-atom	<i>Curvature of an Atom</i>
----------------	-----------------------------

Description

Determine if an atom is convex, concave, or affine.

Usage

```
is_atom_convex(object)

is_atom_concave(object)

is_atom_affine(object)

## S4 method for signature 'Atom'
is_atom_convex(object)

## S4 method for signature 'Atom'
is_atom_concave(object)

## S4 method for signature 'Atom'
is_atom_affine(object)

## S4 method for signature 'Atom'
is_atom_log_log_convex(object)

## S4 method for signature 'Atom'
is_atom_log_log_concave(object)

## S4 method for signature 'Atom'
is_atom_log_log_affine(object)
```

Arguments

object A [Atom](#) object.

Value

A logical value.

Examples

```
x <- Variable()

is_atom_convex(x^2)
is_atom_convex(sqrt(x))
is_atom_convex(log(x))

is_atom_concave(-abs(x))
is_atom_concave(x^2)
is_atom_concave(sqrt(x))

is_atom_affine(2*x)
is_atom_affine(x^2)
```

curvature-comp

Curvature of Composition

Description

Determine whether a composition is non-decreasing or non-increasing in an index.

Usage

```
is_incr(object, idx)
```

```
is_decr(object, idx)
```

```
## S4 method for signature 'Atom'
is_incr(object, idx)
```

```
## S4 method for signature 'Atom'
is_decr(object, idx)
```

Arguments

object A [Atom](#) object.

idx An index into the atom.

Value

A logical value.

Examples

```
x <- Variable()
is_incr(log(x), 1)
is_incr(x^2, 1)
is_decr(min(x), 1)
is_decr(abs(x), 1)
```

curvature-methods

Curvature Properties

Description

Determine if an expression is constant, affine, convex, concave, quadratic, piecewise linear (pwl), or quadratic/piecewise affine (qpwa).

Usage

```
is_constant(object)

is_affine(object)

is_convex(object)

is_concave(object)

is_quadratic(object)

is_pwl(object)

is_qpwa(object)
```

Arguments

object An [Expression](#) object.

Value

A logical value.

Examples

```
x <- Variable()
c <- Constant(5)

is_constant(c)
is_constant(x)

is_affine(c)
is_affine(x)
is_affine(x^2)

is_convex(c)
is_convex(x)
is_convex(x^2)
is_convex(sqrt(x))

is_concave(c)
is_concave(x)
is_concave(x^2)
is_concave(sqrt(x))

is_quadratic(x^2)
is_quadratic(sqrt(x))

is_pwl(c)
is_pwl(x)
is_pwl(x^2)
```

CvxAttr2Constr-class *The CvxAttr2Constr class.*

Description

This class represents a reduction that expands convex variable attributes into constraints.

Usage

```
## S4 method for signature 'CvxAttr2Constr,Problem'
perform(object, problem)

## S4 method for signature 'CvxAttr2Constr,Solution,list'
invert(object, solution, inverse_data)
```

Arguments

object	A CvxAttr2Constr object.
problem	A Problem object.
solution	A Solution to a problem that generated the inverse data.
inverse_data	The inverse data returned by an invocation to apply.

Methods (by generic)

- `perform(object = CvxAttr2Constr, problem = Problem)`: Expand convex variable attributes to constraints.
- `invert(object = CvxAttr2Constr, solution = Solution, inverse_data = list)`: Performs the reduction on a problem and returns an equivalent problem.

CVXOPT-class *An interface for the CVXOPT solver.*

Description

An interface for the CVXOPT solver.

Usage

```
## S4 method for signature 'CVXOPT'
mip_capable(solver)

## S4 method for signature 'CVXOPT'
status_map(solver, status)
```

```

## S4 method for signature 'CVXOPT'
name(x)

## S4 method for signature 'CVXOPT'
import_solver(solver)

## S4 method for signature 'CVXOPT,Problem'
accepts(object, problem)

## S4 method for signature 'CVXOPT,Problem'
perform(object, problem)

## S4 method for signature 'CVXOPT,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'CVXOPT'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A CVXOPT object.
status	A status code returned by the solver.
problem	A Problem object.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance on the primal and dual residual.
reltol	The relative tolerance on the duality gap.
abstol	The absolute tolerance on the duality gap.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(CVXOPT)`: Can the solver handle mixed-integer programs?
- `status_map(CVXOPT)`: Converts status returned by the CVXOPT solver to its respective CVXPY status.
- `name(CVXOPT)`: Returns the name of the solver.
- `import_solver(CVXOPT)`: Imports the solver.
- `accepts(object = CVXOPT, problem = Problem)`: Can CVXOPT solve the problem?
- `perform(object = CVXOPT, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `invert(object = CVXOPT, solution = list, inverse_data = list)`: Returns the solution to the original problem given the `inverse_data`.
- `solve_via_data(CVXOPT)`: Solve a problem represented by data returned from `apply`.

cvxr_norm	<i>Matrix Norm (Alternative)</i>
-----------	----------------------------------

Description

A wrapper on the different norm atoms. This is different from the standard "norm" method in the R base package. If `p = 2`, `axis = NA`, and `x` is a matrix, this returns the maximum singular value.

Usage

```
cvxr_norm(x, p = 2, axis = NA_real_, keepdims = FALSE)
```

Arguments

<code>x</code>	An Expression or numeric constant representing a vector or matrix.
<code>p</code>	The type of norm. May be a number (p-norm), "inf" (infinity-norm), "nuc" (nuclear norm), or "fro" (Frobenius norm). The default is <code>p = 2</code> .
<code>axis</code>	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
<code>keepdims</code>	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Value

An [Expression](#) representing the norm.

See Also

[norm](#)

Dcp2Cone-class	<i>Reduce DCP Problem to Conic Form</i>
----------------	---

Description

This reduction takes as input (minimization) DCP problems and converts them into problems with affine objectives and conic constraints whose arguments are affine.

Usage

```
## S4 method for signature 'Dcp2Cone,Problem'
accepts(object, problem)
```

```
## S4 method for signature 'Dcp2Cone,Problem'
perform(object, problem)
```

Arguments

object	A Dcp2Cone object.
problem	A Problem object.

Methods (by generic)

- `accepts(object = Dcp2Cone, problem = Problem)`: A problem is accepted if it is a minimization and is DCP.
- `perform(object = Dcp2Cone, problem = Problem)`: Converts a DCP problem to a conic form.

Dcp2Cone.entr_canon	<i>Dcp2Cone canonicalizer for the entropy atom</i>
---------------------	--

Description

Dcp2Cone canonicalizer for the entropy atom

Usage

```
Dcp2Cone.entr_canon(expr, args)
```

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from an entropy atom where the objective function is just the variable t with an ExpCone constraint.

<code>Dcp2Cone.exp_canon</code>	<i>Dcp2Cone canonicalizer for the exponential atom</i>
---------------------------------	--

Description

Dcp2Cone canonicalizer for the exponential atom

Usage

`Dcp2Cone.exp_canon(expr, args)`

Arguments

- | | |
|-------------------|--|
| <code>expr</code> | An Expression object |
| <code>args</code> | A list of Constraint objects |

Value

A cone program constructed from an exponential atom where the objective function is the variable t with an ExpCone constraint.

<code>Dcp2Cone.geo_mean_canon</code>	<i>Dcp2Cone canonicalizer for the geometric mean atom</i>
--------------------------------------	---

Description

Dcp2Cone canonicalizer for the geometric mean atom

Usage

`Dcp2Cone.geo_mean_canon(expr, args)`

Arguments

- | | |
|-------------------|--|
| <code>expr</code> | An Expression object |
| <code>args</code> | A list of Constraint objects |

Value

A cone program constructed from a geometric mean atom where the objective function is the variable t with geometric mean constraints

Dcp2Cone.huber_canon *Dcp2Cone canonicalizer for the huber atom*

Description

Dcp2Cone canonicalizer for the huber atom

Usage

Dcp2Cone.huber_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a huber atom where the objective function is the variable t with square and absolute constraints

Dcp2Cone.indicator_canon
 Dcp2Cone canonicalizer for the indicator atom

Description

Dcp2Cone canonicalizer for the indicator atom

Usage

Dcp2Cone.indicator_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from an indicator atom and where 0 is the objective function with the given constraints in the function.

Dcp2Cone.kl_div_canon *Dcp2Cone canonicalizer for the KL Divergence atom*

Description

Dcp2Cone canonicalizer for the KL Divergence atom

Usage

Dcp2Cone.kl_div_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a KL divergence atom where t is the objective function with the ExpCone constraints.

Dcp2Cone.lambda_max_canon
 Dcp2Cone canonicalizer for the lambda maximization atom

Description

Dcp2Cone canonicalizer for the lambda maximization atom

Usage

Dcp2Cone.lambda_max_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a lambda maximization atom where t is the objective function and a PSD constraint and a constraint requiring I*t to be symmetric.

Dcp2Cone.lambda_sum_largest_canon

Dcp2Cone canonicalizer for the largest lambda sum atom

Description

Dcp2Cone canonicalizer for the largest lambda sum atom

Usage

Dcp2Cone.lambda_sum_largest_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a lambda sum of the k largest elements atom where $k \cdot t + \text{trace}(Z)$ is the objective function. t denotes the variable subject to constraints and Z is a PSD matrix variable whose dimensions consist of the length of the vector at hand. The constraints require the the diagonal matrix of the vector to be symmetric and PSD.

Dcp2Cone.log1p_canon *Dcp2Cone canonicalizer for the log 1p atom*

Description

Dcp2Cone canonicalizer for the log 1p atom

Usage

Dcp2Cone.log1p_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a log 1p atom where t is the objective function and the constraints consist of ExpCone constraints + 1.

Dcp2Cone.logistic_canon	<i>Dcp2Cone canonicalizer for the logistic function atom</i>
-------------------------	--

Description

Dcp2Cone canonicalizer for the logistic function atom

Usage

Dcp2Cone.logistic_canon(expr, args)

Arguments

- | | |
|------|--|
| expr | An Expression object |
| args | A list of Constraint objects |

Value

A cone program constructed from the logistic atom where the objective function is given by t0 and the constraints consist of the ExpCone constraints.

Dcp2Cone.log_canon	<i>Dcp2Cone canonicalizer for the log atom</i>
--------------------	--

Description

Dcp2Cone canonicalizer for the log atom

Usage

Dcp2Cone.log_canon(expr, args)

Arguments

- | | |
|------|--|
| expr | An Expression object |
| args | A list of Constraint objects |

Value

A cone program constructed from a log atom where t is the objective function and the constraints consist of ExpCone constraints

Dcp2Cone.log_det_canon

Dcp2Cone canonicalizer for the log determinant atom

Description

Dcp2Cone canonicalizer for the log determinant atom

Usage

Dcp2Cone.log_det_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a log determinant atom where the objective function is the sum of the log of the vector D and the constraints consist of requiring the matrix Z to be diagonal and the diagonal Z to equal D, Z to be upper triangular and $DZ; t(Z)A$ to be positive semidefinite, where A is a n by n matrix.

Dcp2Cone.log_sum_exp_canon

Dcp2Cone canonicalizer for the log sum of the exp atom

Description

Dcp2Cone canonicalizer for the log sum of the exp atom

Usage

Dcp2Cone.log_sum_exp_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from the log sum of the exp atom where the objective is the t variable and the constraints consist of the ExpCone constraints and requiring t to be less than a matrix of ones of the same size.

Dcp2Cone.matrix_frac_canon

Dcp2Cone canonicalizer for the matrix fraction atom

Description

Dcp2Cone canonicalizer for the matrix fraction atom

Usage

Dcp2Cone.matrix_frac_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from the matrix fraction atom, where the objective function is the trace of Tvar, a m by m matrix where the constraints consist of the matrix of the Schur complement of Tvar to consist of P, an n by n, given matrix, X, an n by m given matrix, and Tvar.

Dcp2Cone.normNuc_canon

Dcp2Cone canonicalizer for the nuclear norm atom

Description

Dcp2Cone canonicalizer for the nuclear norm atom

Usage

Dcp2Cone.normNuc_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a nuclear norm atom, where the objective function consists of .5 times the trace of a matrix X of size m+n by m+n where the constraint consist of the top right corner of the matrix being the original matrix.

Dcp2Cone.pnorm_canon *Dcp2Cone canonicalizer for the p norm atom*

Description

Dcp2Cone canonicalizer for the p norm atom

Usage

Dcp2Cone.pnorm_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a pnorm atom, where the objective is a variable t of dimension of the original vector in the problem and the constraints consist of geometric mean constraints.

Dcp2Cone.power_canon *Dcp2Cone canonicalizer for the power atom*

Description

Dcp2Cone canonicalizer for the power atom

Usage

Dcp2Cone.power_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a power atom, where the objective function consists of the variable t which is of the dimension of the original vector from the power atom and the constraints consists of geometric mean constraints.

Dcp2Cone.quad_form_canon

Dcp2Cone canonicalizer for the quadratic form atom

Description

Dcp2Cone canonicalizer for the quadratic form atom

Usage

Dcp2Cone.quad_form_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a quadratic form atom, where the objective function consists of the scaled objective function from the quadratic over linear canonicalization and same with the constraints.

Dcp2Cone.quad_over_lin_canon

Dcp2Cone canonicalizer for the quadratic over linear term atom

Description

Dcp2Cone canonicalizer for the quadratic over linear term atom

Usage

Dcp2Cone.quad_over_lin_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a quadratic over linear term atom where the objective function consists of a one dimensional variable t with SOC constraints.

Dcp2Cone.sigma_max_canon

Dcp2Cone canonicalizer for the sigma max atom

Description

Dcp2Cone canonicalizer for the sigma max atom

Usage

Dcp2Cone.sigma_max_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A cone program constructed from a sigma max atom where the objective function consists of the variable t that is of the same dimension as the original expression with specified constraints in the function.

Dgp2Dcp-class

Reduce DGP problems to DCP problems.

Description

This reduction takes as input a DGP problem and returns an equivalent DCP problem. Because every (generalized) geometric program is a DGP problem, this reduction can be used to convert geometric programs into convex form.

Usage

```
## S4 method for signature 'Dgp2Dcp,Problem'
accepts(object, problem)
```

```
## S4 method for signature 'Dgp2Dcp,Problem'
perform(object, problem)
```

```
## S4 method for signature 'Dgp2Dcp'
canonicalize_expr(object, expr, args)
```

```
## S4 method for signature 'Dgp2Dcp,Solution,InverseData'
invert(object, solution, inverse_data)
```

Arguments

object	A Dgp2Dcp object.
problem	A Problem object.
expr	An Expression object corresponding to the DGP problem.
args	A list of values corresponding to the DGP expression
solution	A Solution object to invert.
inverse_data	A InverseData object containing data necessary for the inversion.

Methods (by generic)

- `accepts(object = Dgp2Dcp, problem = Problem)`: Is the problem DGP?
- `perform(object = Dgp2Dcp, problem = Problem)`: Converts the DGP problem to a DCP problem.
- `canonicalize_expr(Dgp2Dcp)`: Canonicalizes each atom within an Dgp2Dcp expression.
- `invert(object = Dgp2Dcp, solution = Solution, inverse_data = InverseData)`: Returns the solution to the original problem given the inverse_data.

Dgp2Dcp.add_canon	<i>Dgp2Dcp canonicalizer for the addition atom</i>
-------------------	--

Description

Dgp2Dcp canonicalizer for the addition atom

Usage

```
Dgp2Dcp.add_canon(expr, args)
```

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the addition atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.constant_canon	<i>Dgp2Dcp canonicalizer for the constant atom</i>
------------------------	--

Description

Dgp2Dcp canonicalizer for the constant atom

Usage

Dgp2Dcp.constant_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the constant atom of a DGP expression, where the returned expression is the DCP equivalent resulting from the log of the expression.

Dgp2Dcp.div_canon	<i>Dgp2Dcp canonicalizer for the division atom</i>
-------------------	--

Description

Dgp2Dcp canonicalizer for the division atom

Usage

Dgp2Dcp.div_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the division atom of a DGP expression, where the returned expression is the log transformed DCP equivalent.

Dgp2Dcp.exp_canon	<i>Dgp2Dcp canonicalizer for the exp atom</i>
-------------------	---

Description

Dgp2Dcp canonicalizer for the exp atom

Usage

Dgp2Dcp.exp_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the exp atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.eye_minus_inv_canon	<i>Dgp2Dcp canonicalizer for the $(I - X)^{-1}$ atom</i>
-----------------------------	---

Description

Dgp2Dcp canonicalizer for the $(I - X)^{-1}$ atom

Usage

Dgp2Dcp.eye_minus_inv_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the $(I - X)^{-1}$ atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

`Dgp2Dcp.geo_mean_canon`*Dgp2Dcp canonicalizer for the geometric mean atom*

Description

Dgp2Dcp canonicalizer for the geometric mean atom

Usage

`Dgp2Dcp.geo_mean_canon(expr, args)`

Arguments

<code>expr</code>	An Expression object
<code>args</code>	A list of values for the <code>expr</code> variable

Value

A canonicalization of the geometric mean atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

`Dgp2Dcp.log_canon`*Dgp2Dcp canonicalizer for the log atom*

Description

Dgp2Dcp canonicalizer for the log atom

Usage

`Dgp2Dcp.log_canon(expr, args)`

Arguments

<code>expr</code>	An Expression object
<code>args</code>	A list of values for the <code>expr</code> variable

Value

A canonicalization of the log atom of a DGP expression, where the returned expression is the log of the original expression..

Dgp2Dcp.mulexpression_canon	<i>Dgp2Dcp canonicalizer for the multiplication expression atom</i>
-----------------------------	---

Description

Dgp2Dcp canonicalizer for the multiplication expression atom

Usage

Dgp2Dcp.mulexpression_canon(expr, args)

Arguments

- | | |
|------|--|
| expr | An Expression object |
| args | A list of values for the expr variable |

Value

A canonicalization of the multiplication expression atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.mul_canon	<i>Dgp2Dcp canonicalizer for the multiplication atom</i>
-------------------	--

Description

Dgp2Dcp canonicalizer for the multiplication atom

Usage

Dgp2Dcp.mul_canon(expr, args)

Arguments

- | | |
|------|--|
| expr | An Expression object |
| args | A list of values for the expr variable |

Value

A canonicalization of the multiplication atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.nonpos_constr_canon

Dgp2Dcp canonicalizer for the non-positive constraint atom

Description

Dgp2Dcp canonicalizer for the non-positive constraint atom

Usage

Dgp2Dcp.nonpos_constr_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the non-positive constraint atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.norm1_canon *Dgp2Dcp canonicalizer for the 1 norm atom*

Description

Dgp2Dcp canonicalizer for the 1 norm atom

Usage

Dgp2Dcp.norm1_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the norm1 atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.norm_inf_canon

Dgp2Dcp canonicalizer for the infinite norm atom

Description

Dgp2Dcp canonicalizer for the infinite norm atom

Usage

Dgp2Dcp.norm_inf_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the infinity norm atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.one_minus_pos_canon

Dgp2Dcp canonicalizer for the 1-x atom

Description

Dgp2Dcp canonicalizer for the 1-x atom

Usage

Dgp2Dcp.one_minus_pos_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the 1-x with $0 < x < 1$ atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.parameter_canon

Dgp2Dcp canonicalizer for the parameter atom

Description

Dgp2Dcp canonicalizer for the parameter atom

Usage

Dgp2Dcp.parameter_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the parameter atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.pf_eigenvalue_canon

Dgp2Dcp canonicalizer for the spectral radius atom

Description

Dgp2Dcp canonicalizer for the spectral radius atom

Usage

Dgp2Dcp.pf_eigenvalue_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the spectral radius atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.pnorm_canon	<i>Dgp2Dcp canonicalizer for the p norm atom</i>
---------------------	--

Description

Dgp2Dcp canonicalizer for the p norm atom

Usage

Dgp2Dcp.pnorm_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the pnorm atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.power_canon	<i>Dgp2Dcp canonicalizer for the power atom</i>
---------------------	---

Description

Dgp2Dcp canonicalizer for the power atom

Usage

Dgp2Dcp.power_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the power atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.prod_canon	<i>Dgp2Dcp canonicalizer for the product atom</i>
--------------------	---

Description

Dgp2Dcp canonicalizer for the product atom

Usage

Dgp2Dcp.prod_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the product atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.quad_form_canon	<i>Dgp2Dcp canonicalizer for the quadratic form atom</i>
-------------------------	--

Description

Dgp2Dcp canonicalizer for the quadratic form atom

Usage

Dgp2Dcp.quad_form_canon(expr, args)

Arguments

expr	An Expression object
args	A list of values for the expr variable

Value

A canonicalization of the quadratic form atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.quad_over_lin_canon	<i>Dgp2Dcp canonicalizer for the quadratic over linear term atom</i>
-----------------------------	--

Description

Dgp2Dcp canonicalizer for the quadratic over linear term atom

Usage

Dgp2Dcp.quad_over_lin_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the quadratic over linear atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.sum_canon	<i>Dgp2Dcp canonicalizer for the sum atom</i>
-------------------	---

Description

Dgp2Dcp canonicalizer for the sum atom

Usage

Dgp2Dcp.sum_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the sum atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.trace_canon	<i>Dgp2Dcp canonicalizer for the trace atom</i>
---------------------	---

Description

Dgp2Dcp canonicalizer for the trace atom

Usage

Dgp2Dcp.trace_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the trace atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

Dgp2Dcp.zero_constr_canon	<i>Dgp2Dcp canonicalizer for the zero constraint atom</i>
---------------------------	---

Description

Dgp2Dcp canonicalizer for the zero constraint atom

Usage

Dgp2Dcp.zero_constr_canon(expr, args)

Arguments

- expr An [Expression](#) object
- args A list of values for the expr variable

Value

A canonicalization of the zero constraint atom of a DGP expression, where the returned expression is the transformed DCP equivalent.

DgpCanonMethods-class *DGP canonical methods class.*

Description

Canonicalization of DGPs is a stateful procedure, hence the need for a class.

Usage

```
## S4 method for signature 'DgpCanonMethods'
names(x)

## S4 method for signature 'DgpCanonMethods'
x$name
```

Arguments

x	A DgpCanonMethods object.
name	The name of the atom or expression to canonicalize.

Methods (by generic)

- names(DgpCanonMethods): Returns the name of all the canonicalization methods
- \$: Returns either a canonicalized variable or a corresponding Dgp2Dcp canonicalization method

Diag	<i>Turns an expression into a DiagVec object</i>
------	--

Description

Turns an expression into a DiagVec object

Usage

```
Diag(expr)
```

Arguments

expr	An Expression that represents a vector or square matrix.
------	--

Value

An [Expression](#) representing the diagonal vector/matrix.

diag,Expression-method

Matrix Diagonal

Description

Extracts the diagonal from a matrix or makes a vector into a diagonal matrix.

Usage

```
## S4 method for signature 'Expression'
diag(x = 1, nrow, ncol)
```

Arguments

x An [Expression](#), vector, or square matrix.

nrow, ncol (Optional) Dimensions for the result when x is not a matrix.

Value

An [Expression](#) representing the diagonal vector or matrix.

Examples

```
C <- Variable(3,3)
obj <- Maximize(C[1,3])
constraints <- list(diag(C) == 1, C[1,2] == 0.6, C[2,3] == -0.3, C == Variable(3,3, PSD = TRUE))
prob <- Problem(obj, constraints)
result <- solve(prob)
result$value
result$getValue(C)
```

DiagMat-class

The DiagMat class.

Description

This class represents the extraction of the diagonal from a square matrix.

Usage

```

DiagMat(expr)

## S4 method for signature 'DiagMat'
to_numeric(object, values)

## S4 method for signature 'DiagMat'
dim_from_args(object)

## S4 method for signature 'DiagMat'
is_atom_log_log_convex(object)

## S4 method for signature 'DiagMat'
is_atom_log_log_concave(object)

## S4 method for signature 'DiagMat'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

expr	An Expression representing the matrix whose diagonal we are interested in.
object	A DiagMat object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(DiagMat)`: Extract the diagonal from a square matrix constant.
- `dim_from_args(DiagMat)`: The size of the atom.
- `is_atom_log_log_convex(DiagMat)`: Is the atom log-log convex?
- `is_atom_log_log_concave(DiagMat)`: Is the atom log-log concave?
- `graph_implementation(DiagMat)`: The graph implementation of the atom.

Slots

expr An [Expression](#) representing the matrix whose diagonal we are interested in.

DiagVec-class

*The DiagVec class.***Description**

This class represents the conversion of a vector into a diagonal matrix.

Usage

```
DiagVec(expr)

## S4 method for signature 'DiagVec'
to_numeric(object, values)

## S4 method for signature 'DiagVec'
dim_from_args(object)

## S4 method for signature 'DiagVec'
is_atom_log_log_convex(object)

## S4 method for signature 'DiagVec'
is_atom_log_log_concave(object)

## S4 method for signature 'DiagVec'
is_symmetric(object)

## S4 method for signature 'DiagVec'
is_hermitian(object)

## S4 method for signature 'DiagVec'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

expr	An Expression representing the vector to convert.
object	A DiagVec object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(DiagVec)`: Convert the vector constant into a diagonal matrix.
- `dim_from_args(DiagVec)`: The dimensions of the atom.

- `is_atom_log_log_convex(DiagVec)`: Is the atom log-log convex?
- `is_atom_log_log_concave(DiagVec)`: Is the atom log-log concave?
- `is_symmetric(DiagVec)`: Is the expression symmetric?
- `is_hermitian(DiagVec)`: Is the expression hermitian?
- `graph_implementation(DiagVec)`: The graph implementation of the atom.

Slots

`expr` An [Expression](#) representing the vector to convert.

Diff	<i>Takes the k-th order differences</i>
------	---

Description

Takes the k-th order differences

Usage

`Diff(x, lag = 1, k = 1, axis = 2)`

Arguments

<code>x</code>	An Expression that represents a vector
<code>lag</code>	The degree of lag between differences
<code>k</code>	The integer value of the order of differences
<code>axis</code>	The axis along which to apply the function. For a 2D matrix, 1 indicates rows and 2 indicates columns.

Value

Takes in a vector of length n and returns a vector of length n-k of the kth order differences

diff, Expression-method

Lagged and Iterated Differences

Description

The lagged and iterated differences of a vector. If x is length n , this function returns a length $n - k$ vector of the k th order difference between the lagged terms. `diff(x)` returns the vector of differences between adjacent elements in the vector, i.e. $[x[2] - x[1], x[3] - x[2], \dots]$. `diff(x, 1, 2)` is the second-order differences vector, equivalently `diff(diff(x))`. `diff(x, 1, 0)` returns the vector x unchanged. `diff(x, 2)` returns the vector of differences $[x[3] - x[1], x[4] - x[2], \dots]$, equivalent to $x[(1+\text{lag}):n] - x[1:(n-\text{lag})]$.

Usage

```
## S4 method for signature 'Expression'
diff(x, lag = 1, differences = 1, ...)
```

Arguments

<code>x</code>	An Expression .
<code>lag</code>	An integer indicating which lag to use.
<code>differences</code>	An integer indicating the order of the difference.
<code>...</code>	(Optional) Addition axis argument, specifying the dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is <code>axis = 1</code> .

Value

An [Expression](#) representing the k th order difference.

Examples

```
## Problem data
m <- 101
L <- 2
h <- L/(m-1)

## Form objective and constraints
x <- Variable(m)
y <- Variable(m)
obj <- sum(y)
constr <- list(x[1] == 0, y[1] == 1, x[m] == 1, y[m] == 1, diff(x)^2 + diff(y)^2 <= h^2)

## Solve the catenary problem
prob <- Problem(Minimize(obj), constr)
result <- solve(prob)
```

```
## Plot and compare with ideal catenary
xs <- result$getValue(x)
ys <- result$getValue(y)
plot(c(0, 1), c(0, 1), type = 'n', xlab = "x", ylab = "y")
lines(xs, ys, col = "blue", lwd = 2)
grid()
```

DiffPos	<i>The DiffPos atom.</i>
---------	--------------------------

Description

The difference between expressions, $x - y$, where $x > y > 0$.

Usage

```
DiffPos(x, y)
```

Arguments

- x An [Expression](#)
- y An [Expression](#)

Value

The difference $x - y$ with domain $x, y : x > y > 0$.

dim_from_args	<i>Atom Dimensions</i>
---------------	------------------------

Description

Determine the dimensions of an atom based on its arguments.

Usage

```
dim_from_args(object)

## S4 method for signature 'Atom'
dim_from_args(object)
```

Arguments

- object A [Atom](#) object.

Value

A numeric vector c(row, col) indicating the dimensions of the atom.

domain	<i>Domain</i>
--------	---------------

Description

A list of constraints describing the closure of the region where the expression is finite.

Usage

```
domain(object)
```

Arguments

object An [Expression](#) object.

Value

A list of [Constraint](#) objects.

Examples

```
a <- Variable(name = "a")
dom <- domain(p_norm(a, -0.5))
prob <- Problem(Minimize(a), dom)
result <- solve(prob)
result$value

b <- Variable()
dom <- domain(kl_div(a, b))
result <- solve(Problem(Minimize(a + b), dom))
result$getValue(a)
result$getValue(b)

A <- Variable(2, 2, name = "A")
dom <- domain(lambda_max(A))
A0 <- rbind(c(1,2), c(3,4))
result <- solve(Problem(Minimize(norm2(A - A0)), dom))
result$getValue(A)

dom <- domain(log_det(A + diag(rep(1,2))))
prob <- Problem(Minimize(sum(diag(A))), dom)
result <- solve(prob, solver = "SCS")
result$value
```

`dspop`*Direct Standardization: Population*

Description

Randomly generated data for direct standardization example. Sex was drawn from a Bernoulli distribution, and age was drawn from a uniform distribution on 10, . . . , 60. The response was drawn from a normal distribution with a mean that depends on sex and age, and a variance of 1.

Usage`dspop`**Format**

A data frame with 1000 rows and 3 variables:

y Response variable

sex Sex of individual, coded male (0) and female (1)

age Age of individual

See Also

[dssamp](#)

`dssamp`*Direct Standardization: Sample*

Description

A sample of [dspop](#) for direct standardization example. The sample is skewed such that young males are overrepresented in comparison to the population.

Usage`dssamp`**Format**

A data frame with 100 rows and 3 variables:

y Response variable

sex Sex of individual, coded male (0) and female (1)

age Age of individual

See Also

[dspop](#)

dual_value-methods	<i>Get and Set Dual Value</i>
--------------------	-------------------------------

Description

Get and set the value of the dual variable in a constraint.

Usage

```
dual_value(object)

dual_value(object) <- value
```

Arguments

object	A Constraint object.
value	A numeric scalar, vector, or matrix to assign to the object.

ECOS-class	<i>An interface for the ECOS solver</i>
------------	---

Description

An interface for the ECOS solver

Usage

```
ECOS()

## S4 method for signature 'ECOS'
mip_capable(solver)

## S4 method for signature 'ECOS'
status_map(solver, status)

## S4 method for signature 'ECOS'
import_solver(solver)

## S4 method for signature 'ECOS'
name(x)

## S4 method for signature 'ECOS,Problem'
perform(object, problem)

## S4 method for signature 'ECOS,list,list'
invert(object, solution, inverse_data)
```

Arguments

solver, object, x	A ECOS object.
status	A status code returned by the solver.
problem	A Problem object.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.

Methods (by generic)

- `mip_capable(ECOS)`: Can the solver handle mixed-integer programs?
- `status_map(ECOS)`: Converts status returned by the ECOS solver to its respective CVXPY status.
- `import_solver(ECOS)`: Imports the solver
- `name(ECOS)`: Returns the name of the solver
- `perform(object = ECOS, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `invert(object = ECOS, solution = list, inverse_data = list)`: Returns the solution to the original problem given the `inverse_data`.

ECOS.dims_to_solver_dict

Utility method for formatting a ConeDims instance into a dictionary that can be supplied to ECOS.

Description

Utility method for formatting a ConeDims instance into a dictionary that can be supplied to ECOS.

Usage

```
ECOS.dims_to_solver_dict(cone_dims)
```

Arguments

cone_dims	A ConeDims instance.
-----------	--------------------------------------

Value

A dictionary of cone dimensions

ECOS_BB-class	<i>An interface for the ECOS BB solver.</i>
---------------	---

Description

An interface for the ECOS BB solver.

Usage

```
ECOS_BB()

## S4 method for signature 'ECOS_BB'
mip_capable(solver)

## S4 method for signature 'ECOS_BB'
name(x)

## S4 method for signature 'ECOS_BB,Problem'
perform(object, problem)

## S4 method for signature 'ECOS_BB'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)
```

Arguments

solver, object, x	A ECOS_BB object.
problem	A Problem object.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.

num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(ECOS_BB)`: Can the solver handle mixed-integer programs?
- `name(ECOS_BB)`: Returns the name of the solver.
- `perform(object = ECOS_BB, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `solve_via_data(ECOS_BB)`: Solve a problem represented by data returned from `apply`.

Elementwise-class	<i>The Elementwise class.</i>
-------------------	-------------------------------

Description

This virtual class represents an elementwise atom.

Usage

```
## S4 method for signature 'Elementwise'
dim_from_args(object)

## S4 method for signature 'Elementwise'
validate_args(object)

## S4 method for signature 'Elementwise'
is_symmetric(object)
```

Arguments

`object` An [Elementwise](#) object.

Methods (by generic)

- `dim_from_args(Elementwise)`: Dimensions is the same as the sum of the arguments' dimensions.
- `validate_args(Elementwise)`: Verify that all the dimensions are the same or can be promoted.
- `is_symmetric(Elementwise)`: Is the expression symmetric?

EliminatePwl-class	<i>The EliminatePwl class.</i>
--------------------	--------------------------------

Description

This class eliminates piecewise linear atoms.

Usage

```
## S4 method for signature 'EliminatePwl,Problem'
accepts(object, problem)
```

Arguments

object	An EliminatePwl object.
problem	A Problem object.

Methods (by generic)

- `accepts(object = EliminatePwl, problem = Problem)`: Does this problem contain piecewise linear atoms?

EliminatePwl.abs_canon

EliminatePwl canonicalizer for the absolute atom

Description

EliminatePwl canonicalizer for the absolute atom

Usage

```
EliminatePwl.abs_canon(expr, args)
```

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed from an absolute atom where the objective function consists of the variable that is of the same dimension as the original expression and the constraints consist of splitting the absolute value into two inequalities.

EliminatePwl.cummax_canon

EliminatePwl canonicalizer for the cumulative max atom

Description

EliminatePwl canonicalizer for the cumulative max atom

Usage

EliminatePwl.cummax_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed from a cumulative max atom where the objective function consists of the variable Y which is of the same dimension as the original expression and the constraints consist of row/column constraints depending on the axis

EliminatePwl.cumsum_canon

EliminatePwl canonicalizer for the cumulative sum atom

Description

EliminatePwl canonicalizer for the cumulative sum atom

Usage

EliminatePwl.cumsum_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed from a cumulative sum atom where the objective is Y that is of the same dimension as the matrix of the expression and the constraints consist of various row constraints

EliminatePwl.max_elemwise_canon

EliminatePwl canonicalizer for the elementwise maximum atom

Description

EliminatePwl canonicalizer for the elementwise maximum atom

Usage

EliminatePwl.max_elemwise_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed by a elementwise maximum atom where the objective function is the variable t of the same dimension as the expression and the constraints consist of a simple inequality.

EliminatePwl.max_entries_canon

EliminatePwl canonicalizer for the max entries atom

Description

EliminatePwl canonicalizer for the max entries atom

Usage

EliminatePwl.max_entries_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed from the max entries atom where the objective function consists of the variable t of the same size as the original expression and the constraints consist of a vector multiplied by a vector of 1's.

EliminatePwl.min_elemwise_canon

EliminatePwl canonicalizer for the elementwise minimum atom

Description

EliminatePwl canonicalizer for the elementwise minimum atom

Usage

EliminatePwl.min_elemwise_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed by a minimum elementwise atom where the objective function is the negative of variable t produced by max_elemwise_canon of the same dimension as the expression and the constraints consist of a simple inequality.

EliminatePwl.min_entries_canon

EliminatePwl canonicalizer for the minimum entries atom

Description

EliminatePwl canonicalizer for the minimum entries atom

Usage

EliminatePwl.min_entries_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed by a minimum entries atom where the objective function is the negative of variable t produced by max_elemwise_canon of the same dimension as the expression and the constraints consist of a simple inequality.

EliminatePwl.norm1_canon

EliminatePwl canonicalizer for the 1 norm atom

Description

EliminatePwl canonicalizer for the 1 norm atom

Usage

EliminatePwl.norm1_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed by the norm1 atom where the objective function consists of the sum of the variables created by the abs_canon function and the constraints consist of constraints generated by abs_canon.

EliminatePwl.norm_inf_canon

EliminatePwl canonicalizer for the infinite norm atom

Description

EliminatePwl canonicalizer for the infinite norm atom

Usage

EliminatePwl.norm_inf_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed by the infinite norm atom where the objective function consists variable t of the same dimension as the expression and the constraints consist of a vector constructed by multiplying t to a vector of 1's

EliminatePwl.sum_largest_canon

EliminatePwl canonicalizer for the largest sum atom

Description

EliminatePwl canonicalizer for the largest sum atom

Usage

EliminatePwl.sum_largest_canon(expr, args)

Arguments

expr	An Expression object
args	A list of Constraint objects

Value

A canonicalization of the piecewise-linear atom constructed by the k largest sums atom where the objective function consists of the sum of variables t that is of the same dimension as the expression plus k

entr

Entropy Function

Description

The elementwise entropy function, $-x \log(x)$.

Usage

entr(x)

Arguments

x	An Expression , vector, or matrix.
---	--

Value

An [Expression](#) representing the entropy of the input.

Examples

```
x <- Variable(5)
obj <- Maximize(sum(entr(x)))
prob <- Problem(obj, list(sum(x) == 1))
result <- solve(prob)
result$getValue(x)
```

Entr-class

*The Entr class.***Description**

This class represents the elementwise operation $-x \log(x)$.

Usage

```
Entr(x)

## S4 method for signature 'Entr'
to_numeric(object, values)

## S4 method for signature 'Entr'
sign_from_args(object)

## S4 method for signature 'Entr'
is_atom_convex(object)

## S4 method for signature 'Entr'
is_atom_concave(object)

## S4 method for signature 'Entr'
is_incr(object, idx)

## S4 method for signature 'Entr'
is_decr(object, idx)

## S4 method for signature 'Entr'
.grad(object, values)

## S4 method for signature 'Entr'
.domain(object)
```

Arguments

x	An Expression or numeric constant.
object	An Entr object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Entr)`: The elementwise entropy function evaluated at the value.
- `sign_from_args(Entr)`: The sign of the atom is unknown.
- `is_atom_convex(Entr)`: The atom is not convex.
- `is_atom_concave(Entr)`: The atom is concave.
- `is_incr(Entr)`: The atom is weakly increasing.
- `is_decr(Entr)`: The atom is weakly decreasing.
- `.grad(Entr)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.domain(Entr)`: Returns constraints describing the domain of the node

Slots

- x An [Expression](#) or numeric constant.

 EvalParams-class

The EvalParams class.

Description

This class represents a reduction that replaces symbolic parameters with their constant values.

Usage

```
## S4 method for signature 'EvalParams,Problem'
perform(object, problem)

## S4 method for signature 'EvalParams,Solution,list'
invert(object, solution, inverse_data)
```

Arguments

<code>object</code>	A EvalParams object.
<code>problem</code>	A Problem object.
<code>solution</code>	A Solution to a problem that generated the inverse data.
<code>inverse_data</code>	The inverse data returned by an invocation to <code>apply</code> .

Methods (by generic)

- `perform(object = EvalParams, problem = Problem)`: Replace parameters with constant values.
- `invert(object = EvalParams, solution = Solution, inverse_data = list)`: Returns a solution to the original problem given the `inverse_data`.

exp, Expression-method *Natural Exponential*

Description

The elementwise natural exponential.

Usage

```
## S4 method for signature 'Expression'
exp(x)
```

Arguments

x An [Expression](#).

Value

An [Expression](#) representing the natural exponential of the input.

Examples

```
x <- Variable(5)
obj <- Minimize(sum(exp(x)))
prob <- Problem(obj, list(sum(x) == 1))
result <- solve(prob)
result$getValue(x)
```

Exp-class *The Exp class.*

Description

This class represents the elementwise natural exponential e^x .

Usage

```
Exp(x)

## S4 method for signature 'Exp'
to_numeric(object, values)

## S4 method for signature 'Exp'
sign_from_args(object)

## S4 method for signature 'Exp'
```

```

is_atom_convex(object)

## S4 method for signature 'Exp'
is_atom_concave(object)

## S4 method for signature 'Exp'
is_atom_log_log_convex(object)

## S4 method for signature 'Exp'
is_atom_log_log_concave(object)

## S4 method for signature 'Exp'
is_incr(object, idx)

## S4 method for signature 'Exp'
is_decr(object, idx)

## S4 method for signature 'Exp'
.grad(object, values)

```

Arguments

x	An Expression object.
object	An Exp object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Exp)`: The matrix with each element exponentiated.
- `sign_from_args(Exp)`: The atom is positive.
- `is_atom_convex(Exp)`: The atom is convex.
- `is_atom_concave(Exp)`: The atom is not concave.
- `is_atom_log_log_convex(Exp)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Exp)`: Is the atom log-log concave?
- `is_incr(Exp)`: The atom is weakly increasing.
- `is_decr(Exp)`: The atom is not weakly decreasing.
- `.grad(Exp)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x An [Expression](#) object.

ExpCone-class	<i>The ExpCone class.</i>
---------------	---------------------------

Description

This class represents a reformulated exponential cone constraint operating elementwise on a, b, c .

Usage

```
ExpCone(x, y, z, id = NA_integer_)

## S4 method for signature 'ExpCone'
as.character(x)

## S4 method for signature 'ExpCone'
residual(object)

## S4 method for signature 'ExpCone'
size(object)

## S4 method for signature 'ExpCone'
num_cones(object)

## S4 method for signature 'ExpCone'
cone_sizes(object)

## S4 method for signature 'ExpCone'
is_dcp(object)

## S4 method for signature 'ExpCone'
is_dgp(object)

## S4 method for signature 'ExpCone'
canonicalize(object)
```

Arguments

x	The variable x in the exponential cone.
y	The variable y in the exponential cone.
z	The variable z in the exponential cone.
id	(Optional) A numeric value representing the constraint ID.
<code>object</code>	A ExpCone object.

Details

Original cone:

$$K = \{(x, y, z) | y > 0, ye^{x/y} \leq z\} \cup \{(x, y, z) | x \leq 0, y = 0, z \geq 0\}$$

Reformulated cone:

$$K = \{(x, y, z) | y, z > 0, y \log(y) + x \leq y \log(z)\} \cup \{(x, y, z) | x \leq 0, y = 0, z \geq 0\}$$

Methods (by generic)

- `residual(ExpCone)`: The size of the x argument.
- `size(ExpCone)`: The number of entries in the combined cones.
- `num_cones(ExpCone)`: The number of elementwise cones.
- `cone_sizes(ExpCone)`: The dimensions of the exponential cones.
- `is_dcp(ExpCone)`: An exponential constraint is DCP if each argument is affine.
- `is_dgp(ExpCone)`: Is the constraint DGP?
- `canonicalize(ExpCone)`: Canonicalizes by converting expressions to LinOps.

Slots

- x The variable x in the exponential cone.
- y The variable y in the exponential cone.
- z The variable z in the exponential cone.

Expression-class	<i>The Expression class.</i>
------------------	------------------------------

Description

This class represents a mathematical expression.

Usage

```
## S4 method for signature 'Expression'
value(object)

## S4 method for signature 'Expression'
grad(object)

## S4 method for signature 'Expression'
domain(object)

## S4 method for signature 'Expression'
as.character(x)
```

```
## S4 method for signature 'Expression'
name(x)

## S4 method for signature 'Expression'
expr(object)

## S4 method for signature 'Expression'
is_constant(object)

## S4 method for signature 'Expression'
is_affine(object)

## S4 method for signature 'Expression'
is_convex(object)

## S4 method for signature 'Expression'
is_concave(object)

## S4 method for signature 'Expression'
is_dcp(object)

## S4 method for signature 'Expression'
is_log_log_constant(object)

## S4 method for signature 'Expression'
is_log_log_affine(object)

## S4 method for signature 'Expression'
is_log_log_convex(object)

## S4 method for signature 'Expression'
is_log_log_concave(object)

## S4 method for signature 'Expression'
is_dgp(object)

## S4 method for signature 'Expression'
is_hermitian(object)

## S4 method for signature 'Expression'
is_psd(object)

## S4 method for signature 'Expression'
is_nsd(object)

## S4 method for signature 'Expression'
is_quadratic(object)
```

```
## S4 method for signature 'Expression'
is_symmetric(object)

## S4 method for signature 'Expression'
is_pwl(object)

## S4 method for signature 'Expression'
is_qpwa(object)

## S4 method for signature 'Expression'
is_zero(object)

## S4 method for signature 'Expression'
is_nonneg(object)

## S4 method for signature 'Expression'
is_nonpos(object)

## S4 method for signature 'Expression'
dim(x)

## S4 method for signature 'Expression'
is_real(object)

## S4 method for signature 'Expression'
is_imag(object)

## S4 method for signature 'Expression'
is_complex(object)

## S4 method for signature 'Expression'
size(object)

## S4 method for signature 'Expression'
ndim(object)

## S4 method for signature 'Expression'
flatten(object)

## S4 method for signature 'Expression'
is_scalar(object)

## S4 method for signature 'Expression'
is_vector(object)

## S4 method for signature 'Expression'
is_matrix(object)
```

```
## S4 method for signature 'Expression'
nrow(x)
```

```
## S4 method for signature 'Expression'
ncol(x)
```

Arguments

x, object An [Expression](#) object.

Methods (by generic)

- `value(Expression)`: The value of the expression.
- `grad(Expression)`: The (sub/super)-gradient of the expression with respect to each variable.
- `domain(Expression)`: A list of constraints describing the closure of the region where the expression is finite.
- `as.character(Expression)`: The string representation of the expression.
- `name(Expression)`: The name of the expression.
- `expr(Expression)`: The expression itself.
- `is_constant(Expression)`: The expression is constant if it contains no variables or is identically zero.
- `is_affine(Expression)`: The expression is affine if it is constant or both convex and concave.
- `is_convex(Expression)`: A logical value indicating whether the expression is convex.
- `is_concave(Expression)`: A logical value indicating whether the expression is concave.
- `is_dcp(Expression)`: The expression is DCP if it is convex or concave.
- `is_log_log_constant(Expression)`: Is the expression log-log constant, i.e., elementwise positive?
- `is_log_log_affine(Expression)`: Is the expression log-log affine?
- `is_log_log_convex(Expression)`: Is the expression log-log convex?
- `is_log_log_concave(Expression)`: Is the expression log-log concave?
- `is_dgp(Expression)`: The expression is DGP if it is log-log DCP.
- `is_hermitian(Expression)`: A logical value indicating whether the expression is a Hermitian matrix.
- `is_psd(Expression)`: A logical value indicating whether the expression is a positive semidefinite matrix.
- `is_nsd(Expression)`: A logical value indicating whether the expression is a negative semidefinite matrix.
- `is_quadratic(Expression)`: A logical value indicating whether the expression is quadratic.
- `is_symmetric(Expression)`: A logical value indicating whether the expression is symmetric.

- `is_pwl(Expression)`: A logical value indicating whether the expression is piecewise linear.
- `is_qpwa(Expression)`: A logical value indicating whether the expression is quadratic of piecewise affine.
- `is_zero(Expression)`: The expression is zero if it is both nonnegative and nonpositive.
- `is_nonneg(Expression)`: A logical value indicating whether the expression is nonnegative.
- `is_nonpos(Expression)`: A logical value indicating whether the expression is nonpositive.
- `dim(Expression)`: The `c(row, col)` dimensions of the expression.
- `is_real(Expression)`: A logical value indicating whether the expression is real.
- `is_imag(Expression)`: A logical value indicating whether the expression is imaginary.
- `is_complex(Expression)`: A logical value indicating whether the expression is complex.
- `size(Expression)`: The number of entries in the expression.
- `ndim(Expression)`: The number of dimensions of the expression.
- `flatten(Expression)`: Vectorizes the expression.
- `is_scalar(Expression)`: A logical value indicating whether the expression is a scalar.
- `is_vector(Expression)`: A logical value indicating whether the expression is a row or column vector.
- `is_matrix(Expression)`: A logical value indicating whether the expression is a matrix.
- `nrow(Expression)`: Number of rows in the expression.
- `ncol(Expression)`: Number of columns in the expression.

 expression-parts

Parts of an Expression Leaf

Description

List the variables, parameters, constants, or atoms in a canonical expression.

Usage

`variables(object)`

`parameters(object)`

`constants(object)`

`atoms(object)`

Arguments

`object` A [Leaf](#) object.

Value

A list of [Variable](#), [Parameter](#), [Constant](#), or [Atom](#) objects.

Examples

```
set.seed(67)
m <- 50
n <- 10
beta <- Variable(n)
y <- matrix(rnorm(m), nrow = m)
X <- matrix(rnorm(m*n), nrow = m, ncol = n)
lambda <- Parameter()

expr <- sum_squares(y - X %*% beta) + lambda*p_norm(beta, 1)
variables(expr)
parameters(expr)
constants(expr)
lapply(constants(expr), function(c) { value(c) })
```

extract_dual_value	<i>Gets a specified value of a dual variable.</i>
--------------------	---

Description

Gets a specified value of a dual variable.

Usage

```
extract_dual_value(result_vec, offset, constraint)
```

Arguments

result_vec	A vector containing the dual variable values.
offset	An offset to get correct index of dual values.
constraint	A list of the constraints in the problem.

Value

A list of a dual variable value and its offset.

extract_mip_idx	<i>Coalesces bool, int indices for variables.</i>
-----------------	---

Description

Coalesces bool, int indices for variables.

Usage

```
extract_mip_idx(variables)
```

Arguments

variables A list of [Variable](#) objects.

Value

Coalesces bool, int indices for variables. The indexing scheme assumes that the variables will be coalesced into a single one-dimensional variable, with each variable being reshaped in Fortran order.

EyeMinusInv-class	<i>The EyeMinusInv class.</i>
-------------------	-------------------------------

Description

This class represents the unity resolvent of an elementwise positive matrix X , i.e., $(I - X)^{-1}$, and it enforces the constraint that the spectral radius of X is at most 1. This atom is log-log convex.

Usage

```
EyeMinusInv(X)

## S4 method for signature 'EyeMinusInv'
to_numeric(object, values)

## S4 method for signature 'EyeMinusInv'
name(x)

## S4 method for signature 'EyeMinusInv'
dim_from_args(object)

## S4 method for signature 'EyeMinusInv'
sign_from_args(object)

## S4 method for signature 'EyeMinusInv'
```

```

is_atom_convex(object)

## S4 method for signature 'EyeMinusInv'
is_atom_concave(object)

## S4 method for signature 'EyeMinusInv'
is_atom_log_log_convex(object)

## S4 method for signature 'EyeMinusInv'
is_atom_log_log_concave(object)

## S4 method for signature 'EyeMinusInv'
is_incr(object, idx)

## S4 method for signature 'EyeMinusInv'
is_decr(object, idx)

## S4 method for signature 'EyeMinusInv'
.grad(object, values)

```

Arguments

X	An Expression or numeric matrix.
object, x	An EyeMinusInv object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- to_numeric(EyeMinusInv): The unity resolvent of the matrix.
- name(EyeMinusInv): The name and arguments of the atom.
- dim_from_args(EyeMinusInv): The dimensions of the atom determined from its arguments.
- sign_from_args(EyeMinusInv): The (is positive, is negative) sign of the atom.
- is_atom_convex(EyeMinusInv): Is the atom convex?
- is_atom_concave(EyeMinusInv): Is the atom concave?
- is_atom_log_log_convex(EyeMinusInv): Is the atom log-log convex?
- is_atom_log_log_concave(EyeMinusInv): Is the atom log-log concave?
- is_incr(EyeMinusInv): Is the atom weakly increasing in the index?
- is_decr(EyeMinusInv): Is the atom weakly decreasing in the index?
- .grad(EyeMinusInv): Gives EyeMinusInv the (sub/super)gradient of the atom w.r.t. each variable

Slots

X An [Expression](#) or numeric matrix.

eye_minus_inv	<i>Unity Resolvent</i>
---------------	------------------------

Description

The unity resolvent of a positive matrix. For an elementwise positive matrix X , this atom represents $(I - X)^{-1}$, and it enforces the constraint that the spectral radius of X is at most 1.

Usage

```
eye_minus_inv(X)
```

Arguments

X An [Expression](#) or positive square matrix.

Details

This atom is log-log convex.

Value

An [Expression](#) representing the unity resolvent of the input.

Examples

```
A <- Variable(2,2, pos = TRUE)
prob <- Problem(Minimize(matrix_trace(A)), list(eye_minus_inv(A) <=1))
result <- solve(prob, gp = TRUE)
result$value
result$getValue(A)
```

FlipObjective-class	<i>The FlipObjective class.</i>
---------------------	---------------------------------

Description

This class represents a reduction that flips a minimization objective to a maximization and vice versa.

Usage

```
## S4 method for signature 'FlipObjective,Problem'
perform(object, problem)

## S4 method for signature 'FlipObjective,Solution,list'
invert(object, solution, inverse_data)
```

Arguments

object	A FlipObjective object.
problem	A Problem object.
solution	A Solution to a problem that generated the inverse data.
inverse_data	The inverse data returned by an invocation to apply.

Methods (by generic)

- `perform(object = FlipObjective, problem = Problem)`: Flip a minimization objective to a maximization and vice versa.
- `invert(object = FlipObjective, solution = Solution, inverse_data = list)`: Map the solution of the flipped problem to that of the original.

format_constr	<i>Format Constraints</i>
---------------	---------------------------

Description

Format constraints for the solver.

Usage

```
format_constr(object, eq_constr, leq_constr, dims, solver)
```

Arguments

object	A Constraint object.
eq_constr	A list of the equality constraints in the canonical problem.
leq_constr	A list of the inequality constraints in the canonical problem.
dims	A list with the dimensions of the conic constraints.
solver	A string representing the solver to be called.

Value

A list containing equality constraints, inequality constraints, and dimensions.

GeoMean-class

The GeoMean class.

Description

This class represents the (weighted) geometric mean of vector x with optional powers given by p .

Usage

```
GeoMean(x, p = NA_real_, max_denom = 1024)
```

```
## S4 method for signature 'GeoMean'
to_numeric(object, values)
```

```
## S4 method for signature 'GeoMean'
.domain(object)
```

```
## S4 method for signature 'GeoMean'
.grad(object, values)
```

```
## S4 method for signature 'GeoMean'
.name(x)
```

```
## S4 method for signature 'GeoMean'
.dim_from_args(object)
```

```
## S4 method for signature 'GeoMean'
.sign_from_args(object)
```

```
## S4 method for signature 'GeoMean'
.is_atom_convex(object)
```

```
## S4 method for signature 'GeoMean'
.is_atom_concave(object)
```

```
## S4 method for signature 'GeoMean'
.is_atom_log_log_convex(object)
```

```
## S4 method for signature 'GeoMean'
.is_atom_log_log_concave(object)
```

```
## S4 method for signature 'GeoMean'
.is_incr(object, idx)
```

```
## S4 method for signature 'GeoMean'
.is_decr(object, idx)
```

```

## S4 method for signature 'GeoMean'
get_data(object)

## S4 method for signature 'GeoMean'
copy(object, args = NULL, id_objects = list())

```

Arguments

x	An Expression or numeric vector.
p	(Optional) A vector of weights for the weighted geometric mean. The default is a vector of ones, giving the unweighted geometric mean $x_1^{1/n} \cdots x_n^{1/n}$.
max_denom	(Optional) The maximum denominator to use in approximating $p/\text{sum}(p)$ with w . If w is not an exact representation, increasing <code>max_denom</code> may offer a more accurate representation, at the cost of requiring more convex inequalities to represent the geometric mean. Defaults to 1024.
object	A GeoMean object.
values	A list of numeric values for the arguments
idx	An index into the atom.
args	An optional list that contains the arguments to reconstruct the atom. Default is to use current arguments of the atom.
id_objects	Currently unused.

Details

$$(x_1^{p_1} \cdots x_n^{p_n})^{\frac{1}{1^T p}}$$

The geometric mean includes an implicit constraint that $x_i \geq 0$ whenever $p_i > 0$. If $p_i = 0$, x_i will be unconstrained. The only exception to this rule occurs when p has exactly one nonzero element, say p_i , in which case $\text{GeoMean}(x, p)$ is equivalent to x_i (without the nonnegativity constraint). A specific case of this is when $x \in \mathbf{R}^1$.

Methods (by generic)

- `to_numeric(GeoMean)`: The (weighted) geometric mean of the elements of x .
- `.domain(GeoMean)`: Returns constraints describing the domain of the node
- `.grad(GeoMean)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `name(GeoMean)`: The name and arguments of the atom.
- `dim_from_args(GeoMean)`: The atom is a scalar.
- `sign_from_args(GeoMean)`: The atom is non-negative.
- `is_atom_convex(GeoMean)`: The atom is not convex.
- `is_atom_concave(GeoMean)`: The atom is concave.
- `is_atom_log_log_convex(GeoMean)`: Is the atom log-log convex?
- `is_atom_log_log_concave(GeoMean)`: Is the atom log-log concave?

- `is_incr(GeoMean)`: The atom is weakly increasing in every argument.
- `is_decr(GeoMean)`: The atom is not weakly decreasing in any argument.
- `get_data(GeoMean)`: Returns `list(w, dyadic completion, tree of dyads)`.
- `copy(GeoMean)`: Returns a shallow copy of the `GeoMean` atom

Slots

- `x` An [Expression](#) or numeric vector.
- `p` (Optional) A vector of weights for the weighted geometric mean. The default is a vector of ones, giving the **unweighted** geometric mean $x_1^{1/n} \cdots x_n^{1/n}$.
- `max_denom` (Optional) The maximum denominator to use in approximating $p/\text{sum}(p)$ with `w`. If `w` is not an exact representation, increasing `max_denom` may offer a more accurate representation, at the cost of requiring more convex inequalities to represent the geometric mean. Defaults to 1024.
- `w` (Internal) A list of bigq objects that represent a rational approximation of $p/\text{sum}(p)$.
- `approx_error` (Internal) The error in approximating $p/\text{sum}(p)$ with `w`, given by $\|p/\mathbf{1}^T p - w\|_\infty$.

geo_mean	<i>Geometric Mean</i>
----------	-----------------------

Description

The (weighted) geometric mean of vector x with optional powers given by p .

Usage

```
geo_mean(x, p = NA_real_, max_denom = 1024)
```

Arguments

- `x` An [Expression](#) or vector.
- `p` (Optional) A vector of weights for the weighted geometric mean. Defaults to a vector of ones, giving the **unweighted** geometric mean $x_1^{1/n} \cdots x_n^{1/n}$.
- `max_denom` (Optional) The maximum denominator to use in approximating $p/\text{sum}(p)$ with `w`. If `w` is not an exact representation, increasing `max_denom` may offer a more accurate representation, at the cost of requiring more convex inequalities to represent the geometric mean. Defaults to 1024.

Details

$$(x_1^{p_1} \cdots x_n^{p_n})^{\frac{1}{\mathbf{1}^T p}}$$

The geometric mean includes an implicit constraint that $x_i \geq 0$ whenever $p_i > 0$. If $p_i = 0$, x_i will be unconstrained. The only exception to this rule occurs when p has exactly one nonzero element, say p_i , in which case `geo_mean(x, p)` is equivalent to x_i (without the nonnegativity constraint). A specific case of this is when $x \in \mathbf{R}^1$.

Value

An [Expression](#) representing the geometric mean of the input.

Examples

```
x <- Variable(2)
cost <- geo_mean(x)
prob <- Problem(Maximize(cost), list(sum(x) <= 1))
result <- solve(prob)
result$value
result$getValue(x)

## Not run:
x <- Variable(5)
p <- c(0.07, 0.12, 0.23, 0.19, 0.39)
prob <- Problem(Maximize(geo_mean(x,p)), list(p_norm(x) <= 1))
result <- solve(prob)
result$value
result$getValue(x)

## End(Not run)
```

get_data

Get Expression Data

Description

Get information needed to reconstruct the expression aside from its arguments.

Usage

```
get_data(object)
```

Arguments

object A [Expression](#) object.

Value

A list containing data.

<code>get_dual_values</code>	<i>Gets the values of the dual variables.</i>
------------------------------	---

Description

Gets the values of the dual variables.

Usage

```
get_dual_values(result_vec, parse_func, constraints)
```

Arguments

- `result_vec` A vector containing the dual variable values.
- `parse_func` Function handle for the parser.
- `constraints` A list of the constraints in the problem.

Value

A map of constraint ID to dual variable value.

<code>get_id</code>	<i>Get ID</i>
---------------------	---------------

Description

Get the next identifier value.

Usage

```
get_id()
```

Value

A new unique integer identifier.

Examples

```
## Not run:  
  get_id()  
  
## End(Not run)
```

get_np	<i>Get numpy handle</i>
--------	-------------------------

Description

Get the numpy handle or fail if not available

Usage

```
get_np()
```

Value

the numpy handle

Examples

```
## Not run:
  get_np

## End(Not run)
```

get_problem_data	<i>Get Problem Data</i>
------------------	-------------------------

Description

Get the problem data used in the call to the solver.

Usage

```
get_problem_data(object, solver, gp)
```

Arguments

object	A Problem object.
solver	A string indicating the solver that the problem data is for. Call <code>installed_solvers()</code> to see all available.
gp	(Optional) A logical value indicating whether the problem is a geometric program.

Value

A list containing the data for the solver, the solving chain for the problem, and the inverse data needed to invert the solution.

Examples

```
a <- Variable(name = "a")
data <- get_problem_data(Problem(Minimize(exp(a) + 2)), "SCS")[[1]]
data[["dims"]]
data[["c"]]
data[["A"]]

x <- Variable(2, name = "x")
data <- get_problem_data(Problem(Minimize(p_norm(x) + 3)), "ECOS")[[1]]
data[["dims"]]
data[["c"]]
data[["A"]]
data[["G"]]
```

get_sp	<i>Get scipy handle</i>
--------	-------------------------

Description

Get the scipy handle or fail if not available

Usage

```
get_sp()
```

Value

the scipy handle

Examples

```
## Not run:
  get_sp

## End(Not run)
```

GLPK-class	<i>An interface for the GLPK solver.</i>
------------	--

Description

An interface for the GLPK solver.

Usage

```

GLPK()

## S4 method for signature 'GLPK'
mip_capable(solver)

## S4 method for signature 'GLPK'
status_map(solver, status)

## S4 method for signature 'GLPK'
name(x)

## S4 method for signature 'GLPK'
import_solver(solver)

## S4 method for signature 'GLPK,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'GLPK'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A GLPK object.
status	A status code returned by the solver.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.

num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(GLPK)`: Can the solver handle mixed-integer programs?
- `status_map(GLPK)`: Converts status returned by the GLPK solver to its respective CVXPY status.
- `name(GLPK)`: Returns the name of the solver.
- `import_solver(GLPK)`: Imports the solver.
- `invert(object = GLPK, solution = list, inverse_data = list)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(GLPK)`: Solve a problem represented by data returned from apply.

GLPK_MI-class	<i>An interface for the GLPK MI solver.</i>
---------------	---

Description

An interface for the GLPK MI solver.

Usage

```
GLPK_MI()

## S4 method for signature 'GLPK_MI'
mip_capable(solver)

## S4 method for signature 'GLPK_MI'
status_map(solver, status)

## S4 method for signature 'GLPK_MI'
name(x)

## S4 method for signature 'GLPK_MI'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
```

```

    solver_opts,
    solver_cache
)

```

Arguments

solver, object, x	A GLPK_MI object.
status	A status code returned by the solver.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(GLPK_MI)`: Can the solver handle mixed-integer programs?
- `status_map(GLPK_MI)`: Converts status returned by the `GLPK_MI` solver to its respective CVXPY status.
- `name(GLPK_MI)`: Returns the name of the solver.
- `solve_via_data(GLPK_MI)`: Solve a problem represented by data returned from apply.

grad

Sub/Super-Gradient

Description

The (sub/super)-gradient of the expression with respect to each variable. Matrix expressions are vectorized, so the gradient is a matrix. NA indicates variable values are unknown or outside the domain.

Usage

```
grad(object)
```

Arguments

object	An Expression object.
--------	---------------------------------------

Value

A list mapping each variable to a sparse matrix.

Examples

```
x <- Variable(2, name = "x")
A <- Variable(2, 2, name = "A")

value(x) <- c(-3,4)
expr <- p_norm(x, 2)
grad(expr)

value(A) <- rbind(c(3,-4), c(4,3))
expr <- p_norm(A, 0.5)
grad(expr)

value(A) <- cbind(c(1,2), c(-1,0))
expr <- abs(A)
grad(expr)
```

graph_implementation *Graph Implementation*

Description

Reduces the atom to an affine expression and list of constraints.

Usage

```
graph_implementation(object, arg_objs, dim, data)
```

Arguments

object	An Expression object.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Value

A list of list(LinOp for objective, list of constraints), where LinOp is a list representing the linear operator.

group_constraints	<i>Organize the constraints into a dictionary keyed by constraint names.</i>
-------------------	--

Description

Organize the constraints into a dictionary keyed by constraint names.

Usage

```
group_constraints(constraints)
```

Arguments

constraints a list of constraints.

Value

A list of constraint types where `constr_map[[cone_type]]` maps to a list.

GUROBI_CONIC-class	<i>An interface for the GUROBI conic solver.</i>
--------------------	--

Description

An interface for the GUROBI conic solver.

Usage

```
GUROBI_CONIC()

## S4 method for signature 'GUROBI_CONIC'
mip_capable(solver)

## S4 method for signature 'GUROBI_CONIC'
name(x)

## S4 method for signature 'GUROBI_CONIC'
import_solver(solver)

## S4 method for signature 'GUROBI_CONIC'
status_map(solver, status)

## S4 method for signature 'GUROBI_CONIC,Problem'
accepts(object, problem)

## S4 method for signature 'GUROBI_CONIC,Problem'
```

```

perform(object, problem)

## S4 method for signature 'GUROBI_CONIC,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'GUROBI_CONIC'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A GUROBI_CONIC object.
status	A status code returned by the solver.
problem	A Problem object.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(GUROBI_CONIC)`: Can the solver handle mixed-integer programs?
- `name(GUROBI_CONIC)`: Returns the name of the solver.
- `import_solver(GUROBI_CONIC)`: Imports the solver.
- `status_map(GUROBI_CONIC)`: Converts status returned by the GUROBI solver to its respective CVXPY status.

- `accepts(object = GUROBI_CONIC, problem = Problem)`: Can GUROBI_CONIC solve the problem?
- `perform(object = GUROBI_CONIC, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `invert(object = GUROBI_CONIC, solution = list, inverse_data = list)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(GUROBI_CONIC)`: Solve a problem represented by data returned from apply.

GUROBI_QP-class

An interface for the GUROBI_QP solver.

Description

An interface for the GUROBI_QP solver.

Usage

```
GUROBI_QP()

## S4 method for signature 'GUROBI_QP'
mip_capable(solver)

## S4 method for signature 'GUROBI_QP'
status_map(solver, status)

## S4 method for signature 'GUROBI_QP'
name(x)

## S4 method for signature 'GUROBI_QP'
import_solver(solver)

## S4 method for signature 'GUROBI_QP'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

## S4 method for signature 'GUROBI_QP,list,InverseData'
invert(object, solution, inverse_data)
```

Arguments

solver, object, x	A GUROBI_QP object.
status	A status code returned by the solver.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.
solution	The raw solution returned by the solver.
inverse_data	A InverseData object containing data necessary for the inversion.

Methods (by generic)

- `mip_capable(GUROBI_QP)`: Can the solver handle mixed-integer programs?
- `status_map(GUROBI_QP)`: Converts status returned by the GUROBI solver to its respective CVXPY status.
- `name(GUROBI_QP)`: Returns the name of the solver.
- `import_solver(GUROBI_QP)`: Imports the solver.
- `solve_via_data(GUROBI_QP)`: Solve a problem represented by data returned from apply.
- `invert(object = GUROBI_QP, solution = list, inverse_data = InverseData)`: Returns the solution to the original problem given the inverse_data.

HarmonicMean

The HarmonicMean atom.

Description

The harmonic mean of x , $\frac{1}{n} \sum_{i=1}^n x_i^{-1}$, where n is the length of x .

Usage

HarmonicMean(x)

Arguments

x	An expression or number whose harmonic mean is to be computed. Must have positive entries.
---	--

Value

The harmonic mean of x .

harmonic_mean	<i>Harmonic Mean</i>
---------------	----------------------

Description

The harmonic mean, $(\frac{1}{n} \sum_{i=1}^n x_i^{-1})^{-1}$. For a matrix, the function is applied over all entries.

Usage

```
harmonic_mean(x)
```

Arguments

x An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the harmonic mean of the input.

Examples

```
x <- Variable()
prob <- Problem(Maximize(harmonic_mean(x)), list(x >= 0, x <= 5))
result <- solve(prob)
result$value
result$getValue(x)
```

hstack	<i>Horizontal Concatenation</i>
--------	---------------------------------

Description

The horizontal concatenation of expressions. This is equivalent to cbind when applied to objects with the same number of rows.

Usage

```
hstack(...)
```

Arguments

... [Expression](#) objects, vectors, or matrices. All arguments must have the same number of rows.

Value

An [Expression](#) representing the concatenated inputs.

Examples

```

x <- Variable(2)
y <- Variable(3)
c <- matrix(1, nrow = 1, ncol = 5)
prob <- Problem(Minimize(c %*% t(hstack(t(x), t(y)))), list(x == c(1,2), y == c(3,4,5)))
result <- solve(prob)
result$value

c <- matrix(1, nrow = 1, ncol = 4)
prob <- Problem(Minimize(c %*% t(hstack(t(x), t(x)))), list(x == c(1,2)))
result <- solve(prob)
result$value

A <- Variable(2,2)
C <- Variable(3,2)
c <- matrix(1, nrow = 2, ncol = 2)
prob <- Problem(Minimize(sum_entries(hstack(t(A), t(C)))), list(A >= 2*c, C == -2))
result <- solve(prob)
result$value
result$getValue(A)

D <- Variable(3,3)
expr <- hstack(C, D)
obj <- expr[1,2] + sum(hstack(expr, expr))
constr <- list(C >= 0, D >= 0, D[1,1] == 2, C[1,2] == 3)
prob <- Problem(Minimize(obj), constr)
result <- solve(prob)
result$value
result$getValue(C)
result$getValue(D)

```

HStack-class

The HStack class.

Description

Horizontal concatenation of values.

Usage

```

HStack(...)

## S4 method for signature 'HStack'
to_numeric(object, values)

## S4 method for signature 'HStack'
dim_from_args(object)

## S4 method for signature 'HStack'

```

```

is_atom_log_log_convex(object)

## S4 method for signature 'HStack'
is_atom_log_log_concave(object)

## S4 method for signature 'HStack'
validate_args(object)

## S4 method for signature 'HStack'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

...	Expression objects or matrices. All arguments must have the same dimensions except for axis 2 (columns).
object	A HStack object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(HStack)`: Horizontally concatenate the values using `cbind`.
- `dim_from_args(HStack)`: The dimensions of the atom.
- `is_atom_log_log_convex(HStack)`: Is the atom log-log convex?
- `is_atom_log_log_concave(HStack)`: Is the atom log-log concave?
- `validate_args(HStack)`: Check all arguments have the same height.
- `graph_implementation(HStack)`: The graph implementation of the atom.

Slots

... [Expression](#) objects or matrices. All arguments must have the same dimensions except for axis 2 (columns).

huber

Huber Function

Description

The elementwise Huber function, $Huber(x, M) = 1$

$2M|x| - M^2$ for $|x| \geq |M|$

$|x|^2$ for $|x| \leq |M|$.

Usage

```
huber(x, M = 1)
```

Arguments

x An [Expression](#), vector, or matrix.

M (Optional) A positive scalar value representing the threshold. Defaults to 1.

Value

An [Expression](#) representing the Huber function evaluated at the input.

Examples

```
set.seed(11)
n <- 10
m <- 450
p <- 0.1      # Fraction of responses with sign flipped

# Generate problem data
beta_true <- 5*matrix(stats::rnorm(n), nrow = n)
X <- matrix(stats::rnorm(m*n), nrow = m, ncol = n)
y_true <- X %%% beta_true
eps <- matrix(stats::rnorm(m), nrow = m)

# Randomly flip sign of some responses
factor <- 2*rbinom(m, size = 1, prob = 1-p) - 1
y <- factor * y_true + eps

# Huber regression
beta <- Variable(n)
obj <- sum(huber(y - X %%% beta, 1))
prob <- Problem(Minimize(obj))
result <- solve(prob)
result$getValue(beta)
```

Huber-class

The Huber class.

Description

This class represents the elementwise Huber function, $Huber(x, M = 1)$

$2M|x| - M^2$ for $|x| \geq |M|$

$|x|^2$ for $|x| \leq |M|$.

Usage

```

Huber(x, M = 1)

## S4 method for signature 'Huber'
to_numeric(object, values)

## S4 method for signature 'Huber'
sign_from_args(object)

## S4 method for signature 'Huber'
is_atom_convex(object)

## S4 method for signature 'Huber'
is_atom_concave(object)

## S4 method for signature 'Huber'
is_incr(object, idx)

## S4 method for signature 'Huber'
is_decr(object, idx)

## S4 method for signature 'Huber'
is_quadratic(object)

## S4 method for signature 'Huber'
get_data(object)

## S4 method for signature 'Huber'
validate_args(object)

## S4 method for signature 'Huber'
.grad(object, values)

```

Arguments

x	An Expression object.
M	A positive scalar value representing the threshold. Defaults to 1.
object	A Huber object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Huber)`: The Huber function evaluated elementwise on the input value.
- `sign_from_args(Huber)`: The atom is positive.
- `is_atom_convex(Huber)`: The atom is convex.

- `is_atom_concave(Huber)`: The atom is not concave.
- `is_incr(Huber)`: A logical value indicating whether the atom is weakly increasing.
- `is_decr(Huber)`: A logical value indicating whether the atom is weakly decreasing.
- `is_quadratic(Huber)`: The atom is quadratic if x is affine.
- `get_data(Huber)`: A list containing the parameter M .
- `validate_args(Huber)`: Check that M is a non-negative constant.
- `.grad(Huber)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x An [Expression](#) or numeric constant.

M A positive scalar value representing the threshold. Defaults to 1.

id	<i>Identification Number</i>
----	------------------------------

Description

A unique identification number used internally to keep track of variables and constraints. Should not be modified by the user.

Usage

```
id(object)
```

Arguments

object A [Variable](#) or [Constraint](#) object.

Value

A non-negative integer identifier.

See Also

[get_id](#) [setIdCounter](#)

Examples

```
x <- Variable()
constr <- (x >= 5)
id(x)
id(constr)
```

Imag-class*The Imag class.*

Description

This class represents the imaginary part of an expression.

Usage

```
Imag(expr)

## S4 method for signature 'Imag'
to_numeric(object, values)

## S4 method for signature 'Imag'
dim_from_args(object)

## S4 method for signature 'Imag'
is_imag(object)

## S4 method for signature 'Imag'
is_complex(object)

## S4 method for signature 'Imag'
is_symmetric(object)
```

Arguments

expr	An Expression representing a vector or matrix.
object	An Imag object.
values	A list of arguments to the atom.

Methods (by generic)

- `to_numeric(Imag)`: The imaginary part of the given value.
- `dim_from_args(Imag)`: The dimensions of the atom.
- `is_imag(Imag)`: Is the atom imaginary?
- `is_complex(Imag)`: Is the atom complex valued?
- `is_symmetric(Imag)`: Is the atom symmetric?

Slots

expr An [Expression](#) representing a vector or matrix.

import_solver	<i>Import Solver</i>
---------------	----------------------

Description

Import the R library that interfaces with the specified solver.

Usage

```
import_solver(solver)
```

Arguments

solver A [ReductionSolver](#) object.

Examples

```
import_solver(ECOS())
import_solver(SCS())
```

installed_solvers	<i>List installed solvers</i>
-------------------	-------------------------------

Description

List available solvers, taking currently blacklisted solvers into account.

Usage

```
installed_solvers()

add_to_solver_blacklist(solvers)

remove_from_solver_blacklist(solvers)

set_solver_blacklist(solvers)
```

Arguments

solvers a character vector of solver names, default character(0)

Value

The names of all the installed solvers as a character vector.

The current blacklist (character vector), invisibly.

Functions

- `add_to_solver_blacklist()`: Add to solver blacklist, useful for temporarily disabling a solver
- `remove_from_solver_blacklist()`: Remove solvers from blacklist
- `set_solver_blacklist()`: Set solver blacklist to a value

InverseData-class	<i>The InverseData class.</i>
-------------------	-------------------------------

Description

This class represents the data encoding an optimization problem.

<code>invert</code>	<i>Return Original Solution</i>
---------------------	---------------------------------

Description

Returns a solution to the original problem given the inverse data.

Usage

```
invert(object, solution, inverse_data)
```

Arguments

<code>object</code>	A Reduction object.
<code>solution</code>	A Solution to a problem that generated <code>inverse_data</code> .
<code>inverse_data</code>	A InverseData object encoding the original problem.

Value

A [Solution](#) to the original problem.

inv_pos

Reciprocal Function

Description

The elementwise reciprocal function, $\frac{1}{x}$

Usage

```
inv_pos(x)
```

Arguments

x An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the reciprocal of the input.

Examples

```
A <- Variable(2,2)
val <- cbind(c(1,2), c(3,4))
prob <- Problem(Minimize(inv_pos(A)[1,2]), list(A == val))
result <- solve(prob)
result$value
```

is_dcp

DCP Compliance

Description

Determine if a problem or expression complies with the disciplined convex programming rules.

Usage

```
is_dcp(object)
```

Arguments

object A [Problem](#) or [Expression](#) object.

Value

A logical value indicating whether the problem or expression is DCP compliant, i.e. no unknown curvatures.

Examples

```
x <- Variable()
prob <- Problem(Minimize(x^2), list(x >= 5))
is_dcp(prob)
solve(prob)
```

is_dgp

*DGP Compliance***Description**

Determine if a problem or expression complies with the disciplined geometric programming rules.

Usage

```
is_dgp(object)
```

Arguments

object A [Problem](#) or [Expression](#) object.

Value

A logical value indicating whether the problem or expression is DCP compliant, i.e. no unknown curvatures.

Examples

```
x <- Variable(pos = TRUE)
y <- Variable(pos = TRUE)
prob <- Problem(Minimize(x*y), list(x >= 5, y >= 5))
is_dgp(prob)
solve(prob, gp = TRUE)
```

is_mixed_integer

*Is Problem Mixed Integer?***Description**

Determine if a problem is a mixed-integer program.

Usage

```
is_mixed_integer(object)
```

Arguments

object A [Problem](#) object.

Value

A logical value indicating whether the problem is a mixed-integer program

is_qp	<i>Is Problem a QP?</i>
-------	-------------------------

Description

Determine if a problem is a quadratic program.

Usage

is_qp(object)

Arguments

object A [Problem](#) object.

Value

A logical value indicating whether the problem is a quadratic program.

is_stuffed_cone_constraint	<i>Is the constraint a stuffed cone constraint?</i>
----------------------------	---

Description

Is the constraint a stuffed cone constraint?

Usage

is_stuffed_cone_constraint(constraint)

Arguments

constraint A [Constraint](#) object.

Value

Is the constraint a stuffed-cone constraint?

`is_stuffed_cone_objective`*Is the objective a stuffed cone objective?*

Description

Is the objective a stuffed cone objective?

Usage

```
is_stuffed_cone_objective(objective)
```

Arguments

`objective` An [Objective](#) object.

Value

Is the objective a stuffed-cone objective?

`is_stuffed_qp_objective`*Is the QP objective stuffed?*

Description

Is the QP objective stuffed?

Usage

```
is_stuffed_qp_objective(objective)
```

Arguments

`objective` A [Minimize](#) or [Maximize](#) object representing the optimization objective.

Value

Is the objective a stuffed QP?

KLDiv-class

The KLDiv class.

Description

The elementwise KL-divergence $x \log(x/y) - x + y$.

Usage

```
KLDiv(x, y)

## S4 method for signature 'KLDiv'
to_numeric(object, values)

## S4 method for signature 'KLDiv'
sign_from_args(object)

## S4 method for signature 'KLDiv'
is_atom_convex(object)

## S4 method for signature 'KLDiv'
is_atom_concave(object)

## S4 method for signature 'KLDiv'
is_incr(object, idx)

## S4 method for signature 'KLDiv'
is_decr(object, idx)

## S4 method for signature 'KLDiv'
.grad(object, values)

## S4 method for signature 'KLDiv'
.domain(object)
```

Arguments

x	An Expression or numeric constant.
y	An Expression or numeric constant.
object	A KLDiv object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(KLDiv)`: The KL-divergence evaluated elementwise on the input value.
- `sign_from_args(KLDiv)`: The atom is positive.
- `is_atom_convex(KLDiv)`: The atom is convex.
- `is_atom_concave(KLDiv)`: The atom is not concave.
- `is_incr(KLDiv)`: The atom is not monotonic in any argument.
- `is_decr(KLDiv)`: The atom is not monotonic in any argument.
- `.grad(KLDiv)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.domain(KLDiv)`: Returns constraints describing the domain of the node

Slots

- x An [Expression](#) or numeric constant.
- y An [Expression](#) or numeric constant.

kl_div

*Kullback-Leibler Divergence***Description**

The elementwise Kullback-Leibler divergence, $x \log(x/y) - x + y$.

Usage

```
kl_div(x, y)
```

Arguments

- x An [Expression](#), vector, or matrix.
- y An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the KL-divergence of the input.

Examples

```
n <- 5
alpha <- seq(10, n-1+10)/n
beta <- seq(10, n-1+10)/n
P_tot <- 0.5
W_tot <- 1.0

P <- Variable(n)
W <- Variable(n)
```

```

R <- kl_div(alpha*W, alpha*(W + beta*P)) - alpha*beta*P
obj <- sum(R)
constr <- list(P >= 0, W >= 0, sum(P) == P_tot, sum(W) == W_tot)
prob <- Problem(Minimize(obj), constr)
result <- solve(prob)

result$value
result$getValue(P)
result$getValue(W)

```

Kron-class

The Kron class.

Description

This class represents the kronecker product.

Usage

```

Kron(lh_exp, rh_exp)

## S4 method for signature 'Kron'
to_numeric(object, values)

## S4 method for signature 'Kron'
validate_args(object)

## S4 method for signature 'Kron'
dim_from_args(object)

## S4 method for signature 'Kron'
sign_from_args(object)

## S4 method for signature 'Kron'
is_incr(object, idx)

## S4 method for signature 'Kron'
is_decr(object, idx)

## S4 method for signature 'Kron'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

lh_exp	An Expression or numeric constant representing the left-hand matrix.
rh_exp	An Expression or numeric constant representing the right-hand matrix.
object	A Kron object.

values	A list of arguments to the atom.
idx	An index into the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector with two elements representing the size of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(Kron)`: The kronecker product of the two values.
- `validate_args(Kron)`: Check both arguments are vectors and the first is a constant.
- `dim_from_args(Kron)`: The dimensions of the atom.
- `sign_from_args(Kron)`: The sign of the atom.
- `is_incr(Kron)`: Is the left-hand expression positive?
- `is_decr(Kron)`: Is the right-hand expression negative?
- `graph_implementation(Kron)`: The graph implementation of the atom.

Slots

lh_exp An [Expression](#) or numeric constant representing the left-hand matrix.
rh_exp An [Expression](#) or numeric constant representing the right-hand matrix.

kronecker, Expression, ANY-method
Kronecker Product

Description

The generalized kronecker product of two matrices.

Usage

```
## S4 method for signature 'Expression,ANY'
kronecker(X, Y, FUN = "*", make.dimnames = FALSE, ...)

## S4 method for signature 'ANY,Expression'
kronecker(X, Y, FUN = "*", make.dimnames = FALSE, ...)
```

Arguments

X	An Expression or matrix.
Y	An Expression or matrix.
FUN	Hardwired to "*" for the kronecker product.
make.dimnames	(Unimplemented) Dimension names are not supported in Expression objects.
...	(Unimplemented) Optional arguments.

Value

An [Expression](#) that represents the kronecker product.

Examples

```
X <- cbind(c(1,2), c(3,4))
Y <- Variable(2,2)
val <- cbind(c(5,6), c(7,8))

obj <- X %x% Y
prob <- Problem(Minimize(kronecker(X,Y)[1,1]), list(Y == val))
result <- solve(prob)
result$value
result$getValue(kronecker(X,Y))
```

LambdaMax-class

The LambdaMax class.

Description

The maximum eigenvalue of a matrix, $\lambda_{\max}(A)$.

Usage

```
LambdaMax(A)

## S4 method for signature 'LambdaMax'
to_numeric(object, values)

## S4 method for signature 'LambdaMax'
.domain(object)

## S4 method for signature 'LambdaMax'
.grad(object, values)

## S4 method for signature 'LambdaMax'
.validate_args(object)

## S4 method for signature 'LambdaMax'
.dim_from_args(object)

## S4 method for signature 'LambdaMax'
.sign_from_args(object)

## S4 method for signature 'LambdaMax'
.is_atom_convex(object)

## S4 method for signature 'LambdaMax'
```

```
is_atom_concave(object)

## S4 method for signature 'LambdaMax'
is_incr(object, idx)

## S4 method for signature 'LambdaMax'
is_decr(object, idx)
```

Arguments

A	An Expression or numeric matrix.
object	A LambdaMax object.
values	A list of arguments to the atom.
idx	An index into the atom.

Methods (by generic)

- `to_numeric(LambdaMax)`: The largest eigenvalue of A. Requires that A be symmetric.
- `.domain(LambdaMax)`: Returns the constraints describing the domain of the atom.
- `.grad(LambdaMax)`: Gives the (sub/super)gradient of the atom with respect to each argument. Matrix expressions are vectorized, so the gradient is a matrix.
- `validate_args(LambdaMax)`: Check that A is square.
- `dim_from_args(LambdaMax)`: The atom is a scalar.
- `sign_from_args(LambdaMax)`: The sign of the atom is unknown.
- `is_atom_convex(LambdaMax)`: The atom is convex.
- `is_atom_concave(LambdaMax)`: The atom is not concave.
- `is_incr(LambdaMax)`: The atom is not monotonic in any argument.
- `is_decr(LambdaMax)`: The atom is not monotonic in any argument.

Slots

A An [Expression](#) or numeric matrix.

LambdaMin	<i>The LambdaMin atom.</i>
-----------	----------------------------

Description

The minimum eigenvalue of a matrix, $\lambda_{\min}(A)$.

Usage

```
LambdaMin(A)
```

Arguments

A An [Expression](#) or numeric matrix.

Value

Returns the minimum eigenvalue of a matrix.

LambdaSumLargest-class

The LambdaSumLargest class.

Description

This class represents the sum of the k largest eigenvalues of a matrix.

Usage

```
LambdaSumLargest(A, k)

## S4 method for signature 'LambdaSumLargest'
allow_complex(object)

## S4 method for signature 'LambdaSumLargest'
to_numeric(object, values)

## S4 method for signature 'LambdaSumLargest'
validate_args(object)

## S4 method for signature 'LambdaSumLargest'
get_data(object)

## S4 method for signature 'LambdaSumLargest'
.grad(object, values)
```

Arguments

A An [Expression](#) or numeric matrix.

k A positive integer.

object A [LambdaSumLargest](#) object.

values A list of numeric values for the arguments

Methods (by generic)

- `allow_complex(LambdaSumLargest)`: Does the atom handle complex numbers?
- `to_numeric(LambdaSumLargest)`: Returns the largest eigenvalue of A, which must be symmetric.
- `validate_args(LambdaSumLargest)`: Verify that the argument A is square.
- `get_data(LambdaSumLargest)`: Returns the parameter k.
- `.grad(LambdaSumLargest)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

k A positive integer.

LambdaSumSmallest	<i>The LambdaSumSmallest atom.</i>
-------------------	------------------------------------

Description

This class represents the sum of the k smallest eigenvalues of a matrix.

Usage

`LambdaSumSmallest(A, k)`

Arguments

A	An Expression or numeric matrix.
k	A positive integer.

Value

Returns the sum of the k smallest eigenvalues of a matrix.

lambda_max	<i>Maximum Eigenvalue</i>
------------	---------------------------

Description

The maximum eigenvalue of a matrix, $\lambda_{\max}(A)$.

Usage

`lambda_max(A)`

Arguments

A An [Expression](#) or matrix.

Value

An [Expression](#) representing the maximum eigenvalue of the input.

Examples

```
A <- Variable(2,2)
prob <- Problem(Minimize(lambda_max(A)), list(A >= 2))
result <- solve(prob)
result$value
result$getValue(A)

obj <- Maximize(A[2,1] - A[1,2])
prob <- Problem(obj, list(lambda_max(A) <= 100, A[1,1] == 2, A[2,2] == 2, A[2,1] == 2))
result <- solve(prob)
result$value
result$getValue(A)
```

lambda_min	<i>Minimum Eigenvalue</i>
------------	---------------------------

Description

The minimum eigenvalue of a matrix, $\lambda_{\min}(A)$.

Usage

```
lambda_min(A)
```

Arguments

A An [Expression](#) or matrix.

Value

An [Expression](#) representing the minimum eigenvalue of the input.

Examples

```
A <- Variable(2,2)
val <- cbind(c(5,7), c(7,-3))
prob <- Problem(Maximize(lambda_min(A)), list(A == val))
result <- solve(prob)
result$value
result$getValue(A)
```

lambda_sum_largest	<i>Sum of Largest Eigenvalues</i>
--------------------	-----------------------------------

Description

The sum of the largest k eigenvalues of a matrix.

Usage

```
lambda_sum_largest(A, k)
```

Arguments

A	An Expression or matrix.
k	The number of eigenvalues to sum over.

Value

An [Expression](#) representing the sum of the largest k eigenvalues of the input.

Examples

```
C <- Variable(3,3)
val <- cbind(c(1,2,3), c(2,4,5), c(3,5,6))
prob <- Problem(Minimize(lambda_sum_largest(C,2)), list(C == val))
result <- solve(prob)
result$value
result$getValue(C)
```

lambda_sum_smallest	<i>Sum of Smallest Eigenvalues</i>
---------------------	------------------------------------

Description

The sum of the smallest k eigenvalues of a matrix.

Usage

```
lambda_sum_smallest(A, k)
```

Arguments

A	An Expression or matrix.
k	The number of eigenvalues to sum over.

Value

An [Expression](#) representing the sum of the smallest k eigenvalues of the input.

Examples

```
C <- Variable(3,3)
val <- cbind(c(1,2,3), c(2,4,5), c(3,5,6))
prob <- Problem(Maximize(lambda_sum_smallest(C,2)), list(C == val))
result <- solve(prob)
result$value
result$getValue(C)
```

leaf-attr	<i>Attributes of an Expression Leaf</i>
-----------	---

Description

Determine if an expression is positive or negative.

Usage

```
is_pos(object)
is_neg(object)
```

Arguments

object A [Leaf](#) object.

Value

A logical value.

Leaf-class	<i>The Leaf class.</i>
------------	------------------------

Description

This class represents a leaf node, i.e. a Variable, Constant, or Parameter.

Usage

```
## S4 method for signature 'Leaf'
get_data(object)

## S4 method for signature 'Leaf'
dim(x)

## S4 method for signature 'Leaf'
variables(object)

## S4 method for signature 'Leaf'
parameters(object)

## S4 method for signature 'Leaf'
constants(object)

## S4 method for signature 'Leaf'
atoms(object)

## S4 method for signature 'Leaf'
is_convex(object)

## S4 method for signature 'Leaf'
is_concave(object)

## S4 method for signature 'Leaf'
is_log_log_convex(object)

## S4 method for signature 'Leaf'
is_log_log_concave(object)

## S4 method for signature 'Leaf'
is_nonneg(object)

## S4 method for signature 'Leaf'
is_nonpos(object)

## S4 method for signature 'Leaf'
is_pos(object)

## S4 method for signature 'Leaf'
is_neg(object)

## S4 method for signature 'Leaf'
is_hermitian(object)

## S4 method for signature 'Leaf'
is_symmetric(object)
```

```
## S4 method for signature 'Leaf'
is_imag(object)

## S4 method for signature 'Leaf'
is_complex(object)

## S4 method for signature 'Leaf'
domain(object)

## S4 method for signature 'Leaf'
project(object, value)

## S4 method for signature 'Leaf'
project_and_assign(object, value)

## S4 method for signature 'Leaf'
value(object)

## S4 replacement method for signature 'Leaf'
value(object) <- value

## S4 method for signature 'Leaf'
validate_val(object, val)

## S4 method for signature 'Leaf'
is_psd(object)

## S4 method for signature 'Leaf'
is_nsd(object)

## S4 method for signature 'Leaf'
is_quadratic(object)

## S4 method for signature 'Leaf'
is_pwl(object)
```

Arguments

object, x	A Leaf object.
value	A numeric scalar, vector, or matrix.
val	The assigned value.

Methods (by generic)

- `get_data(Leaf)`: Leaves are not copied.
- `dim(Leaf)`: The dimensions of the leaf node.
- `variables(Leaf)`: List of [Variable](#) objects in the leaf node.

- `parameters(Leaf)`: List of [Parameter](#) objects in the leaf node.
- `constants(Leaf)`: List of [Constant](#) objects in the leaf node.
- `atoms(Leaf)`: List of [Atom](#) objects in the leaf node.
- `is_convex(Leaf)`: A logical value indicating whether the leaf node is convex.
- `is_concave(Leaf)`: A logical value indicating whether the leaf node is concave.
- `is_log_log_convex(Leaf)`: Is the expression log-log convex?
- `is_log_log_concave(Leaf)`: Is the expression log-log concave?
- `is_nonneg(Leaf)`: A logical value indicating whether the leaf node is nonnegative.
- `is_nonpos(Leaf)`: A logical value indicating whether the leaf node is nonpositive.
- `is_pos(Leaf)`: Is the expression positive?
- `is_neg(Leaf)`: Is the expression negative?
- `is_hermitian(Leaf)`: A logical value indicating whether the leaf node is hermitian.
- `is_symmetric(Leaf)`: A logical value indicating whether the leaf node is symmetric.
- `is_imag(Leaf)`: A logical value indicating whether the leaf node is imaginary.
- `is_complex(Leaf)`: A logical value indicating whether the leaf node is complex.
- `domain(Leaf)`: A list of constraints describing the closure of the region where the leaf node is finite. Default is the full domain.
- `project(Leaf)`: Project value onto the attribute set of the leaf.
- `project_and_assign(Leaf)`: Project and assign a value to the leaf.
- `value(Leaf)`: Get the value of the leaf.
- `value(Leaf) <- value`: Set the value of the leaf.
- `validate_val(Leaf)`: Check that `val` satisfies symbolic attributes of leaf.
- `is_psd(Leaf)`: A logical value indicating whether the leaf node is a positive semidefinite matrix.
- `is_nsd(Leaf)`: A logical value indicating whether the leaf node is a negative semidefinite matrix.
- `is_quadratic(Leaf)`: Leaf nodes are always quadratic.
- `is_pwl(Leaf)`: Leaf nodes are always piecewise linear.

Slots

`id` (Internal) A unique integer identification number used internally.

`dim` The dimensions of the leaf.

`value` The numeric value of the leaf.

`nonneg` Is the leaf nonnegative?

`nonpos` Is the leaf nonpositive?

`complex` Is the leaf a complex number?

`imag` Is the leaf imaginary?

`symmetric` Is the leaf a symmetric matrix?

diag Is the leaf a diagonal matrix?

PSD Is the leaf positive semidefinite?

NSD Is the leaf negative semidefinite?

hermitian Is the leaf hermitian?

boolean Is the leaf boolean? Is the variable boolean? May be TRUE = entire leaf is boolean, FALSE = entire leaf is not boolean, or a vector of indices which should be constrained as boolean, where each index is a vector of length exactly equal to the length of dim.

integer Is the leaf integer? The semantics are the same as the boolean argument.

sparsity A matrix representing the fixed sparsity pattern of the leaf.

pos Is the leaf strictly positive?

neg Is the leaf strictly negative?

linearize

Affine Approximation to an Expression

Description

Gives an elementwise lower (upper) bound for convex (concave) expressions that is tight at the current variable/parameter values. No guarantees for non-DCP expressions.

Usage

```
linearize(expr)
```

Arguments

expr An [Expression](#) to linearize.

Details

If f and g are convex, the objective $f-g$ can be (heuristically) minimized using the implementation below of the convex-concave method:

```
for(iters in 1:N) solve(Problem(Minimize(f - linearize(g))))
```

Value

An affine expression or NA if cannot be linearized.

ListORConstr-class *A Class Union of List and Constraint*

Description

A Class Union of List and Constraint

Usage

```
## S4 method for signature 'ListORConstr'
id(object)
```

Arguments

object A list or [Constraint](#) object.

Methods (by generic)

- `id(ListORConstr)`: Returns the ID associated with the list or constraint.

log, Expression-method *Logarithms*

Description

The elementwise logarithm. `log` computes the logarithm, by default the natural logarithm, `log10` computes the common (i.e., base 10) logarithm, and `log2` computes the binary (i.e., base 2) logarithms. The general form `log(x, base)` computes logarithms with base `base`. `log1p` computes elementwise the function $\log(1 + x)$.

Usage

```
## S4 method for signature 'Expression'
log(x, base = base::exp(1))

## S4 method for signature 'Expression'
log10(x)

## S4 method for signature 'Expression'
log2(x)

## S4 method for signature 'Expression'
log1p(x)
```

Arguments

x	An Expression .
base	(Optional) A positive number that is the base with respect to which the logarithm is computed. Defaults to e .

Value

An [Expression](#) representing the exponentiated input.

Examples

```
# Log in objective
x <- Variable(2)
obj <- Maximize(sum(log(x)))
constr <- list(x <= matrix(c(1, exp(1))))
prob <- Problem(obj, constr)
result <- solve(prob)
result$value
result$getValue(x)

# Log in constraint
obj <- Minimize(sum(x))
constr <- list(log2(x) >= 0, x <= matrix(c(1,1)))
prob <- Problem(obj, constr)
result <- solve(prob)
result$value
result$getValue(x)

# Index into log
obj <- Maximize(log10(x)[2])
constr <- list(x <= matrix(c(1, exp(1))))
prob <- Problem(obj, constr)
result <- solve(prob)
result$value

# Scalar log
obj <- Maximize(log1p(x[2]))
constr <- list(x <= matrix(c(1, exp(1))))
prob <- Problem(obj, constr)
result <- solve(prob)
result$value
```

Log-class

The Log class.

Description

This class represents the elementwise natural logarithm $\log(x)$.

Usage

```

Log(x)

## S4 method for signature 'Log'
to_numeric(object, values)

## S4 method for signature 'Log'
sign_from_args(object)

## S4 method for signature 'Log'
is_atom_convex(object)

## S4 method for signature 'Log'
is_atom_concave(object)

## S4 method for signature 'Log'
is_atom_log_log_convex(object)

## S4 method for signature 'Log'
is_atom_log_log_concave(object)

## S4 method for signature 'Log'
is_incr(object, idx)

## S4 method for signature 'Log'
is_decr(object, idx)

## S4 method for signature 'Log'
.grad(object, values)

## S4 method for signature 'Log'
.domain(object)

```

Arguments

x	An Expression or numeric constant.
object	A Log object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Log)`: The elementwise natural logarithm of the input value.
- `sign_from_args(Log)`: The sign of the atom is unknown.
- `is_atom_convex(Log)`: The atom is not convex.
- `is_atom_concave(Log)`: The atom is concave.

- `is_atom_log_log_convex(Log)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Log)`: Is the atom log-log concave?
- `is_incr(Log)`: The atom is weakly increasing.
- `is_decr(Log)`: The atom is not weakly decreasing.
- `.grad(Log)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.domain(Log)`: Returns constraints describing the domain of the node

Slots

- x An [Expression](#) or numeric constant.

Log1p-class

The Log1p class.

Description

This class represents the elementwise operation $\log(1 + x)$.

Usage

`Log1p(x)`

```
## S4 method for signature 'Log1p'
to_numeric(object, values)
```

```
## S4 method for signature 'Log1p'
sign_from_args(object)
```

```
## S4 method for signature 'Log1p'
.grad(object, values)
```

```
## S4 method for signature 'Log1p'
.domain(object)
```

Arguments

- x An [Expression](#) or numeric constant.
- object A [Log1p](#) object.
- values A list of numeric values for the arguments

Methods (by generic)

- `to_numeric(Log1p)`: The elementwise natural logarithm of one plus the input value.
- `sign_from_args(Log1p)`: The sign of the atom.
- `.grad(Log1p)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.domain(Log1p)`: Returns constraints describing the domain of the node

Slots

x An [Expression](#) or numeric constant.

LogDet-class

The LogDet class.

Description

The natural logarithm of the determinant of a matrix, $\log \det(A)$.

Usage

```
LogDet(A)
```

```
## S4 method for signature 'LogDet'
to_numeric(object, values)
```

```
## S4 method for signature 'LogDet'
validate_args(object)
```

```
## S4 method for signature 'LogDet'
dim_from_args(object)
```

```
## S4 method for signature 'LogDet'
sign_from_args(object)
```

```
## S4 method for signature 'LogDet'
is_atom_convex(object)
```

```
## S4 method for signature 'LogDet'
is_atom_concave(object)
```

```
## S4 method for signature 'LogDet'
is_incr(object, idx)
```

```
## S4 method for signature 'LogDet'
is_decr(object, idx)
```

```
## S4 method for signature 'LogDet'
.grad(object, values)
```

```
## S4 method for signature 'LogDet'
.domain(object)
```

Arguments

A	An Expression or numeric matrix.
object	A LogDet object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(LogDet)`: The log-determinant of SDP matrix A. This is the sum of logs of the eigenvalues and is equivalent to the nuclear norm of the matrix logarithm of A.
- `validate_args(LogDet)`: Check that A is square.
- `dim_from_args(LogDet)`: The atom is a scalar.
- `sign_from_args(LogDet)`: The atom is non-negative.
- `is_atom_convex(LogDet)`: The atom is not convex.
- `is_atom_concave(LogDet)`: The atom is concave.
- `is_incr(LogDet)`: The atom is not monotonic in any argument.
- `is_decr(LogDet)`: The atom is not monotonic in any argument.
- `.grad(LogDet)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.domain(LogDet)`: Returns constraints describing the domain of the node

Slots

A An [Expression](#) or numeric matrix.

logistic

Logistic Function

Description

The elementwise logistic function, $\log(1+e^x)$. This is a special case of $\log(\text{sum}(\exp))$ that evaluates to a vector rather than to a scalar, which is useful for logistic regression.

Usage

```
logistic(x)
```

Arguments

x An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the logistic function evaluated at the input.

Examples

```

set.seed(92)
n <- 20
m <- 1000
sigma <- 45

beta_true <- stats::rnorm(n)
idxs <- sample(n, size = 0.8*n, replace = FALSE)
beta_true[idxs] <- 0
X <- matrix(stats::rnorm(m*n, 0, 5), nrow = m, ncol = n)
y <- sign(X %*% beta_true + stats::rnorm(m, 0, sigma))

beta <- Variable(n)
X_sign <- apply(X, 2, function(x) { ifelse(y <= 0, -1, 1) * x })
obj <- -sum(logistic(-X[y <= 0,] %*% beta)) - sum(logistic(X[y == 1,] %*% beta))
prob <- Problem(Maximize(obj))
result <- solve(prob)

log_odds <- result$getValue(X %*% beta)
beta_res <- result$getValue(beta)
y_probs <- 1/(1 + exp(-X %*% beta_res))
log(y_probs/(1 - y_probs))

```

Logistic-class

The Logistic class.

Description

This class represents the elementwise operation $\log(1 + e^x)$. This is a special case of $\log(\text{sum}(\exp))$ that evaluates to a vector rather than to a scalar, which is useful for logistic regression.

Usage

```

Logistic(x)

## S4 method for signature 'Logistic'
to_numeric(object, values)

## S4 method for signature 'Logistic'
sign_from_args(object)

## S4 method for signature 'Logistic'
is_atom_convex(object)

## S4 method for signature 'Logistic'
is_atom_concave(object)

## S4 method for signature 'Logistic'

```

```

is_incr(object, idx)

## S4 method for signature 'Logistic'
is_decr(object, idx)

## S4 method for signature 'Logistic'
.grad(object, values)

```

Arguments

x	An Expression or numeric constant.
object	A Logistic object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(Logistic)`: Evaluates e^x elementwise, adds one, and takes the natural logarithm.
- `sign_from_args(Logistic)`: The atom is positive.
- `is_atom_convex(Logistic)`: The atom is convex.
- `is_atom_concave(Logistic)`: The atom is not concave.
- `is_incr(Logistic)`: The atom is weakly increasing.
- `is_decr(Logistic)`: The atom is not weakly decreasing.
- `.grad(Logistic)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x An [Expression](#) or numeric constant.

LogSumExp-class	<i>The LogSumExp class.</i>
-----------------	-----------------------------

Description

The natural logarithm of the sum of the elementwise exponential, $\log \sum_{i=1}^n e^{x_i}$.

Usage

```

LogSumExp(x, axis = NA_real_, keepdims = FALSE)

## S4 method for signature 'LogSumExp'
to_numeric(object, values)

## S4 method for signature 'LogSumExp'

```



```

.grad(object, values)

## S4 method for signature 'LogSumExp'
.column_grad(object, value)

## S4 method for signature 'LogSumExp'
.sign_from_args(object)

## S4 method for signature 'LogSumExp'
.is_atom_convex(object)

## S4 method for signature 'LogSumExp'
.is_atom_concave(object)

## S4 method for signature 'LogSumExp'
.is_incr(object, idx)

## S4 method for signature 'LogSumExp'
.is_decr(object, idx)

```

Arguments

x	An Expression representing a vector or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.
object	A LogSumExp object.
values	A list of numeric values.
value	A numeric value.
idx	An index into the atom.

Methods (by generic)

- `to_numeric(LogSumExp)`: Evaluates e^x elementwise, sums, and takes the natural log.
- `.grad(LogSumExp)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(LogSumExp)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable.
- `sign_from_args(LogSumExp)`: Returns sign (is positive, is negative) of the atom.
- `is_atom_convex(LogSumExp)`: The atom is convex.
- `is_atom_concave(LogSumExp)`: The atom is not concave.
- `is_incr(LogSumExp)`: The atom is weakly increasing in the index.
- `is_decr(LogSumExp)`: The atom is not weakly decreasing in the index.

Slots

- x An [Expression](#) representing a vector or matrix.
- axis (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
- keepdims (Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

log_det	<i>Log-Determinant</i>
---------	------------------------

Description

The natural logarithm of the determinant of a matrix, $\log \det(A)$.

Usage

```
log_det(A)
```

Arguments

A An [Expression](#) or matrix.

Value

An [Expression](#) representing the log-determinant of the input.

Examples

```
x <- t(data.frame(c(0.55, 0.25, -0.2, -0.25, -0.0, 0.4),
                  c(0.0, 0.35, 0.2, -0.1, -0.3, -0.2)))
n <- nrow(x)
m <- ncol(x)

A <- Variable(n,n)
b <- Variable(n)
obj <- Maximize(log_det(A))
constr <- lapply(1:m, function(i) { p_norm(A %*% as.matrix(x[,i]) + b) <= 1 })
prob <- Problem(obj, constr)
result <- solve(prob)
result$value
```

log_log_curvature	<i>Log-Log Curvature of Expression</i>
-------------------	--

Description

The log-log curvature of an expression.

The log-log curvature of an expression.

Usage

```
log_log_curvature(object)
```

```
## S4 method for signature 'Expression'
```

```
log_log_curvature(object)
```

Arguments

object An [Expression](#) object.

Value

A string indicating the log-log curvature of the expression, either "LOG_LOG_CONSTANT", "LOG_LOG_AFFINE", "LOG_LOG_CONVEX", "LOG_LOG_CONCAVE", or "UNKNOWN".

A string indicating the log-log curvature of the expression, either "LOG_LOG_CONSTANT", "LOG_LOG_AFFINE", "LOG_LOG_CONVEX", "LOG_LOG_CONCAVE", or "UNKNOWN".

log_log_curvature-atom	<i>Log-Log Curvature of an Atom</i>
------------------------	-------------------------------------

Description

Determine if an atom is log-log convex, concave, or affine.

Usage

```
is_atom_log_log_convex(object)
```

```
is_atom_log_log_concave(object)
```

```
is_atom_log_log_affine(object)
```

Arguments

object A [Atom](#) object.

Value

A logical value.

log_log_curvature-methods
<i>Log-Log Curvature Properties</i>

Description

Determine if an expression is log-log constant, log-log affine, log-log convex, or log-log concave.

Usage

```
is_log_log_constant(object)
is_log_log_affine(object)
is_log_log_convex(object)
is_log_log_concave(object)
```

Arguments

object An [Expression](#) object.

Value

A logical value.

log_sum_exp	<i>Log-Sum-Exponential</i>
-------------	----------------------------

Description

The natural logarithm of the sum of the elementwise exponential, $\log \sum_{i=1}^n e^{x_i}$.

Usage

```
log_sum_exp(x, axis = NA_real_, keepdims = FALSE)
```

Arguments

x	An Expression , vector, or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Value

An [Expression](#) representing the log-sum-exponential of the input.

Examples

```
A <- Variable(2,2)
val <- cbind(c(5,7), c(0,-3))
prob <- Problem(Minimize(log_sum_exp(A)), list(A == val))
result <- solve(prob)
result$getValue(A)
```

```
make_sparse_diagonal_matrix
      Make a CSC sparse diagonal matrix
```

Description

Make a CSC sparse diagonal matrix

Usage

```
make_sparse_diagonal_matrix(size, diagonal = NULL)
```

Arguments

size	number of rows or columns
diagonal	if specified, the diagonal values, in which case size is ignored

Value

a compressed sparse column diagonal matrix

MatrixFrac-class	<i>The MatrixFrac class.</i>
------------------	------------------------------

Description

The matrix fraction function $\text{tr}(X^T P^{-1} X)$.

Usage

```
MatrixFrac(X, P)

## S4 method for signature 'MatrixFrac'
allow_complex(object)

## S4 method for signature 'MatrixFrac'
to_numeric(object, values)

## S4 method for signature 'MatrixFrac'
validate_args(object)

## S4 method for signature 'MatrixFrac'
dim_from_args(object)

## S4 method for signature 'MatrixFrac'
sign_from_args(object)

## S4 method for signature 'MatrixFrac'
is_atom_convex(object)

## S4 method for signature 'MatrixFrac'
is_atom_concave(object)

## S4 method for signature 'MatrixFrac'
is_incr(object, idx)

## S4 method for signature 'MatrixFrac'
is_decr(object, idx)

## S4 method for signature 'MatrixFrac'
is_quadratic(object)

## S4 method for signature 'MatrixFrac'
is_qpwa(object)

## S4 method for signature 'MatrixFrac'
.domain(object)
```

```
## S4 method for signature 'MatrixFrac'
.grad(object, values)
```

Arguments

X	An Expression or numeric matrix.
P	An Expression or numeric matrix.
object	A MatrixFrac object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `allow_complex(MatrixFrac)`: Does the atom handle complex numbers?
- `to_numeric(MatrixFrac)`: The trace of $X^T P^{-1} X$.
- `validate_args(MatrixFrac)`: Check that the dimensions of x and P match.
- `dim_from_args(MatrixFrac)`: The atom is a scalar.
- `sign_from_args(MatrixFrac)`: The atom is positive.
- `is_atom_convex(MatrixFrac)`: The atom is convex.
- `is_atom_concave(MatrixFrac)`: The atom is not concave.
- `is_incr(MatrixFrac)`: The atom is not monotonic in any argument.
- `is_decr(MatrixFrac)`: The atom is not monotonic in any argument.
- `is_quadratic(MatrixFrac)`: True if x is affine and P is constant.
- `is_qpwa(MatrixFrac)`: True if x is piecewise linear and P is constant.
- `.domain(MatrixFrac)`: Returns constraints describing the domain of the node
- `.grad(MatrixFrac)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

X An [Expression](#) or numeric matrix.
P An [Expression](#) or numeric matrix.

MatrixStuffing-class *The MatrixStuffing class.*

Description

The MatrixStuffing class.

Usage

```
## S4 method for signature 'MatrixStuffing,Problem'
perform(object, problem)

## S4 method for signature 'MatrixStuffing,Solution,InverseData'
invert(object, solution, inverse_data)
```

Arguments

object	A MatrixStuffing object.
problem	A Problem object to stuff; the arguments of every constraint must be affine.
solution	A Solution to a problem that generated the inverse data.
inverse_data	The data encoding the original problem.

Methods (by generic)

- `perform(object = MatrixStuffing, problem = Problem)`: Returns a stuffed problem. The returned problem is a minimization problem in which every constraint in the problem has affine arguments that are expressed in the form A
- `invert(object = MatrixStuffing, solution = Solution, inverse_data = InverseData)`: Returns the solution to the original problem given the `inverse_data`.

matrix_frac

Matrix Fraction

Description

$$\text{tr}(X^T P^{-1} X).$$

Usage

```
matrix_frac(X, P)
```

Arguments

X	An Expression or matrix. Must have the same number of rows as P.
P	An Expression or matrix. Must be an invertible square matrix.

Value

An [Expression](#) representing the matrix fraction evaluated at the input.

Examples

```
## Not run:
set.seed(192)
m <- 100
n <- 80
r <- 70

A <- matrix(stats::rnorm(m*n), nrow = m, ncol = n)
b <- matrix(stats::rnorm(m), nrow = m, ncol = 1)
G <- matrix(stats::rnorm(r*n), nrow = r, ncol = n)
h <- matrix(stats::rnorm(r), nrow = r, ncol = 1)

# ||Ax-b||^2 = x^T (A^T A) x - 2(A^T b)^T x + ||b||^2
P <- t(A) %*% A
q <- -2 * t(A) %*% b
r <- t(b) %*% b
Pinv <- base::solve(P)

x <- Variable(n)
obj <- matrix_frac(x, Pinv) + t(q) %*% x + r
constr <- list(G %*% x == h)
prob <- Problem(Minimize(obj), constr)
result <- solve(prob)
result$value

## End(Not run)
```

matrix_prop-methods *Matrix Properties*

Description

Determine if an expression is positive semidefinite, negative semidefinite, hermitian, and/or symmetric.

Usage

```
is_psd(object)

is_nsd(object)

is_hermitian(object)

is_symmetric(object)
```

Arguments

object An [Expression](#) object.

Value

A logical value.

matrix_trace	<i>Matrix Trace</i>
--------------	---------------------

Description

The sum of the diagonal entries in a matrix.

Usage

```
matrix_trace(expr)
```

Arguments

expr An [Expression](#) or matrix.

Value

An [Expression](#) representing the trace of the input.

Examples

```
C <- Variable(3,3)
val <- cbind(3:5, 6:8, 9:11)
prob <- Problem(Maximize(matrix_trace(C)), list(C == val))
result <- solve(prob)
result$value
```

MaxElemwise-class	<i>The MaxElemwise class.</i>
-------------------	-------------------------------

Description

This class represents the elementwise maximum.

Usage

```

MaxElemwise(arg1, arg2, ...)

## S4 method for signature 'MaxElemwise'
to_numeric(object, values)

## S4 method for signature 'MaxElemwise'
sign_from_args(object)

## S4 method for signature 'MaxElemwise'
is_atom_convex(object)

## S4 method for signature 'MaxElemwise'
is_atom_concave(object)

## S4 method for signature 'MaxElemwise'
is_atom_log_log_convex(object)

## S4 method for signature 'MaxElemwise'
is_atom_log_log_concave(object)

## S4 method for signature 'MaxElemwise'
is_incr(object, idx)

## S4 method for signature 'MaxElemwise'
is_decr(object, idx)

## S4 method for signature 'MaxElemwise'
is_pwl(object)

## S4 method for signature 'MaxElemwise'
.grad(object, values)

```

Arguments

arg1	The first Expression in the maximum operation.
arg2	The second Expression in the maximum operation.
...	Additional Expression objects in the maximum operation.
object	A MaxElemwise object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(MaxElemwise)`: The elementwise maximum.
- `sign_from_args(MaxElemwise)`: The sign of the atom.

- `is_atom_convex(MaxElemwise)`: The atom is convex.
- `is_atom_concave(MaxElemwise)`: The atom is not concave.
- `is_atom_log_log_convex(MaxElemwise)`: Is the atom log-log convex?
- `is_atom_log_log_concave(MaxElemwise)`: Is the atom log-log concave?
- `is_incr(MaxElemwise)`: The atom is weakly increasing.
- `is_decr(MaxElemwise)`: The atom is not weakly decreasing.
- `is_pwl(MaxElemwise)`: Are all the arguments piecewise linear?
- `.grad(MaxElemwise)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

- `arg1` The first [Expression](#) in the maximum operation.
- `arg2` The second [Expression](#) in the maximum operation.
- ... Additional [Expression](#) objects in the maximum operation.

MaxEntries-class	<i>The MaxEntries class.</i>
------------------	------------------------------

Description

The maximum of an expression.

Usage

```
MaxEntries(x, axis = NA_real_, keepdims = FALSE)
```

```
## S4 method for signature 'MaxEntries'
to_numeric(object, values)
```

```
## S4 method for signature 'MaxEntries'
sign_from_args(object)
```

```
## S4 method for signature 'MaxEntries'
is_atom_convex(object)
```

```
## S4 method for signature 'MaxEntries'
is_atom_concave(object)
```

```
## S4 method for signature 'MaxEntries'
is_atom_log_log_convex(object)
```

```
## S4 method for signature 'MaxEntries'
is_atom_log_log_concave(object)
```

```

## S4 method for signature 'MaxEntries'
is_incr(object, idx)

## S4 method for signature 'MaxEntries'
is_decr(object, idx)

## S4 method for signature 'MaxEntries'
is_pwl(object)

## S4 method for signature 'MaxEntries'
.grad(object, values)

## S4 method for signature 'MaxEntries'
.column_grad(object, value)

```

Arguments

x	An Expression representing a vector or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.
object	A MaxEntries object.
values	A list of numeric values for the arguments
idx	An index into the atom.
value	A numeric value

Methods (by generic)

- `to_numeric(MaxEntries)`: The largest entry in x.
- `sign_from_args(MaxEntries)`: The sign of the atom.
- `is_atom_convex(MaxEntries)`: The atom is convex.
- `is_atom_concave(MaxEntries)`: The atom is not concave.
- `is_atom_log_log_convex(MaxEntries)`: Is the atom log-log convex.
- `is_atom_log_log_concave(MaxEntries)`: Is the atom log-log concave.
- `is_incr(MaxEntries)`: The atom is weakly increasing in every argument.
- `is_decr(MaxEntries)`: The atom is not weakly decreasing in any argument.
- `is_pwl(MaxEntries)`: Is x piecewise linear?
- `.grad(MaxEntries)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(MaxEntries)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable

Slots

- x An [Expression](#) representing a vector or matrix.
- axis (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
- keepdims (Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Maximize-class

The Maximize class.

Description

This class represents an optimization objective for maximization.

Usage

```
Maximize(expr)

## S4 method for signature 'Maximize'
canonicalize(object)

## S4 method for signature 'Maximize'
is_dcp(object)

## S4 method for signature 'Maximize'
is_dgp(object)
```

Arguments

- expr A scalar [Expression](#) to maximize.
- object A [Maximize](#) object.

Methods (by generic)

- canonicalize(Maximize): Negates the target expression's objective.
- is_dcp(Maximize): A logical value indicating whether the objective is concave.
- is_dgp(Maximize): A logical value indicating whether the objective is log-log concave.

Slots

- expr A scalar [Expression](#) to maximize.

Examples

```
x <- Variable(3)
alpha <- c(0.8,1.0,1.2)
obj <- sum(log(alpha + x))
constr <- list(x >= 0, sum(x) == 1)
prob <- Problem(Maximize(obj), constr)
result <- solve(prob)
result$value
result$getValue(x)
```

max_elemwise	<i>Elementwise Maximum</i>
--------------	----------------------------

Description

The elementwise maximum.

Usage

```
max_elemwise(arg1, arg2, ...)
```

Arguments

- arg1 An [Expression](#), vector, or matrix.
- arg2 An [Expression](#), vector, or matrix.
- ... Additional [Expression](#) objects, vectors, or matrices.

Value

An [Expression](#) representing the elementwise maximum of the inputs.

Examples

```
c <- matrix(c(1,-1))
prob <- Problem(Minimize(max_elemwise(t(c), 2, 2 + t(c))[2]))
result <- solve(prob)
result$value
```

max_entries

*Maximum***Description**

The maximum of an expression.

Usage

```
max_entries(x, axis = NA_real_, keepdims = FALSE)
```

```
## S3 method for class 'Expression'
max(..., na.rm = FALSE)
```

Arguments

x	An Expression , vector, or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.
...	Numeric scalar, vector, matrix, or Expression objects.
na.rm	(Unimplemented) A logical value indicating whether missing values should be removed.

Value

An [Expression](#) representing the maximum of the input.

Examples

```
x <- Variable(2)
val <- matrix(c(-5,-10))
prob <- Problem(Minimize(max_entries(x)), list(x == val))
result <- solve(prob)
result$value

A <- Variable(2,2)
val <- rbind(c(-5,2), c(-3,1))
prob <- Problem(Minimize(max_entries(A, axis = 1)[2,1]), list(A == val))
result <- solve(prob)
result$value

x <- Variable(2)
val <- matrix(c(-5,-10))
prob <- Problem(Minimize(max_entries(x)), list(x == val))
result <- solve(prob)
```



```

result$value

A <- Variable(2,2)
val <- rbind(c(-5,2), c(-3,1))
prob <- Problem(Minimize(max_entries(A, axis = 1)[2,1]), list(A == val))
result <- solve(prob)
result$value

```

mean.Expression	<i>Arithmetic Mean</i>
-----------------	------------------------

Description

The arithmetic mean of an expression.

Usage

```

## S3 method for class 'Expression'
mean(x, trim = 0, na.rm = FALSE, ...)

```

Arguments

x	An Expression object.
trim	(Unimplemented) The fraction (0 to 0.5) of observations to be trimmed from each end of x before the mean is computed.
na.rm	(Unimplemented) A logical value indicating whether missing values should be removed.
...	(Unimplemented) Optional arguments.

Value

An [Expression](#) representing the mean of the input.

Examples

```

A <- Variable(2,2)
val <- cbind(c(-5,2), c(-3,1))
prob <- Problem(Minimize(mean(A)), list(A == val))
result <- solve(prob)
result$value

```

MinElemwise-class	<i>The MinElemwise class.</i>
-------------------	-------------------------------

Description

This class represents the elementwise minimum.

Usage

```
MinElemwise(arg1, arg2, ...)

## S4 method for signature 'MinElemwise'
to_numeric(object, values)

## S4 method for signature 'MinElemwise'
sign_from_args(object)

## S4 method for signature 'MinElemwise'
is_atom_convex(object)

## S4 method for signature 'MinElemwise'
is_atom_concave(object)

## S4 method for signature 'MinElemwise'
is_atom_log_log_convex(object)

## S4 method for signature 'MinElemwise'
is_atom_log_log_concave(object)

## S4 method for signature 'MinElemwise'
is_incr(object, idx)

## S4 method for signature 'MinElemwise'
is_decr(object, idx)

## S4 method for signature 'MinElemwise'
is_pwl(object)

## S4 method for signature 'MinElemwise'
.grad(object, values)
```

Arguments

arg1	The first Expression in the minimum operation.
arg2	The second Expression in the minimum operation.
...	Additional Expression objects in the minimum operation.

object	A MinElemwise object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(MinElemwise)`: The elementwise minimum.
- `sign_from_args(MinElemwise)`: The sign of the atom.
- `is_atom_convex(MinElemwise)`: The atom is not convex.
- `is_atom_concave(MinElemwise)`: The atom is not concave.
- `is_atom_log_log_convex(MinElemwise)`: Is the atom log-log convex?
- `is_atom_log_log_concave(MinElemwise)`: Is the atom log-log concave?
- `is_incr(MinElemwise)`: The atom is weakly increasing.
- `is_decr(MinElemwise)`: The atom is not weakly decreasing.
- `is_pwl(MinElemwise)`: Are all the arguments piecewise linear?
- `.grad(MinElemwise)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

- arg1 The first [Expression](#) in the minimum operation.
- arg2 The second [Expression](#) in the minimum operation.
- ... Additional [Expression](#) objects in the minimum operation.

MinEntries-class	<i>The MinEntries class.</i>
------------------	------------------------------

Description

The minimum of an expression.

Usage

```
MinEntries(x, axis = NA_real_, keepdims = FALSE)

## S4 method for signature 'MinEntries'
to_numeric(object, values)

## S4 method for signature 'MinEntries'
sign_from_args(object)

## S4 method for signature 'MinEntries'
is_atom_convex(object)

## S4 method for signature 'MinEntries'
```

```

is_atom_concave(object)

## S4 method for signature 'MinEntries'
is_atom_log_log_convex(object)

## S4 method for signature 'MinEntries'
is_atom_log_log_concave(object)

## S4 method for signature 'MinEntries'
is_incr(object, idx)

## S4 method for signature 'MinEntries'
is_decr(object, idx)

## S4 method for signature 'MinEntries'
is_pwl(object)

## S4 method for signature 'MinEntries'
.grad(object, values)

## S4 method for signature 'MinEntries'
.column_grad(object, value)

```

Arguments

x	An Expression representing a vector or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.
object	A MinEntries object.
values	A list of numeric values for the arguments
idx	An index into the atom.
value	A numeric value

Methods (by generic)

- `to_numeric(MinEntries)`: The largest entry in x.
- `sign_from_args(MinEntries)`: The sign of the atom.
- `is_atom_convex(MinEntries)`: The atom is not convex.
- `is_atom_concave(MinEntries)`: The atom is concave.
- `is_atom_log_log_convex(MinEntries)`: Is the atom log-log convex?
- `is_atom_log_log_concave(MinEntries)`: Is the atom log-log concave?
- `is_incr(MinEntries)`: The atom is weakly increasing in every argument.

- `is_decr(MinEntries)`: The atom is not weakly decreasing in any argument.
- `is_pwl(MinEntries)`: Is x piecewise linear?
- `.grad(MinEntries)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(MinEntries)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable

Slots

- x An [Expression](#) representing a vector or matrix.
- `axis` (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
- `keepdims` (Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.

Minimize-class

The Minimize class.

Description

This class represents an optimization objective for minimization.

Usage

```
Minimize(expr)

## S4 method for signature 'Minimize'
canonicalize(object)

## S4 method for signature 'Minimize'
is_dcp(object)

## S4 method for signature 'Minimize'
is_dgp(object)
```

Arguments

`expr` A scalar [Expression](#) to minimize.

`object` A [Minimize](#) object.

Methods (by generic)

- `canonicalize(Minimize)`: Pass on the target expression's objective and constraints.
- `is_dcp(Minimize)`: A logical value indicating whether the objective is convex.
- `is_dgp(Minimize)`: A logical value indicating whether the objective is log-log convex.

Slots

`expr` A scalar [Expression](#) to minimize.

<code>min_elemwise</code>	<i>Elementwise Minimum</i>
---------------------------	----------------------------

Description

The elementwise minimum.

Usage

```
min_elemwise(arg1, arg2, ...)
```

Arguments

- `arg1` An [Expression](#), vector, or matrix.
- `arg2` An [Expression](#), vector, or matrix.
- `...` Additional [Expression](#) objects, vectors, or matrices.

Value

An [Expression](#) representing the elementwise minimum of the inputs.

Examples

```
a <- cbind(c(-5,2), c(-3,-1))
b <- cbind(c(5,4), c(-1,2))
prob <- Problem(Minimize(min_elemwise(a, 0, b)[1,2]))
result <- solve(prob)
result$value
```

<code>min_entries</code>	<i>Minimum</i>
--------------------------	----------------

Description

The minimum of an expression.

Usage

```
min_entries(x, axis = NA_real_, keepdims = FALSE)

## S3 method for class 'Expression'
min(..., na.rm = FALSE)
```

Arguments

x	An Expression , vector, or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.
...	Numeric scalar, vector, matrix, or Expression objects.
na.rm	(Unimplemented) A logical value indicating whether missing values should be removed.

Value

An [Expression](#) representing the minimum of the input.

Examples

```
A <- Variable(2,2)
val <- cbind(c(-5,2), c(-3,1))
prob <- Problem(Maximize(min_entries(A)), list(A == val))
result <- solve(prob)
result$value

A <- Variable(2,2)
val <- cbind(c(-5,2), c(-3,1))
prob <- Problem(Maximize(min_entries(A)), list(A == val))
result <- solve(prob)
result$value
```

mip_capable	<i>Solver Capabilities</i>
-------------	----------------------------

Description

Determine if a solver is capable of solving a mixed-integer program (MIP).

Usage

```
mip_capable(solver)
```

Arguments

solver	A ReductionSolver object.
--------	---

Value

A logical value.

Examples

```
mip_capable(ECOS())
```

MixedNorm	<i>The MixedNorm atom.</i>
-----------	----------------------------

Description

The $l_{p,q}$ norm of X, $(\sum_k (\sum_l ||X_{k,l}||^p)^{q/p})^{1/q}$.

Usage

```
MixedNorm(X, p = 2, q = 1)
```

Arguments

- | | |
|---|--|
| X | The matrix to take the $l_{p,q}$ norm of |
| p | The type of inner norm |
| q | The type of outer norm |

Value

Returns the mixed norm of X with specified parameters p and q

<i>mixed_norm</i>	<i>Mixed Norm</i>
-------------------	-------------------

Description

$$l_{p,q}(x) = \left(\sum_{i=1}^n (\sum_{j=1}^m |x_{i,j}|)^{q/p} \right)^{1/q}.$$

Usage

```
mixed_norm(X, p = 2, q = 1)
```

Arguments

- | | |
|---|--|
| X | An Expression , vector, or matrix. |
| p | The type of inner norm. |
| q | The type of outer norm. |

Value

An [Expression](#) representing the $l_{p,q}$ norm of the input.

Examples

```

A <- Variable(2,2)
val <- cbind(c(3,3), c(4,4))
prob <- Problem(Minimize(mixed_norm(A,2,1)), list(A == val))
result <- solve(prob)
result$value
result$getValue(A)

val <- cbind(c(1,4), c(5,6))
prob <- Problem(Minimize(mixed_norm(A,1,Inf)), list(A == val))
result <- solve(prob)
result$value
result$getValue(A)

```

MOSEK-class

An interface for the MOSEK solver.

Description

An interface for the MOSEK solver.

Usage

```

MOSEK()

## S4 method for signature 'MOSEK'
mip_capable(solver)

## S4 method for signature 'MOSEK'
import_solver(solver)

## S4 method for signature 'MOSEK'
name(x)

## S4 method for signature 'MOSEK,Problem'
accepts(object, problem)

## S4 method for signature 'MOSEK'
block_format(object, problem, constraints, exp_cone_order = NA)

## S4 method for signature 'MOSEK,Problem'
perform(object, problem)

## S4 method for signature 'MOSEK'
solve_via_data(
  object,
  data,

```

```

        warm_start,
        verbose,
        feastol,
        reltol,
        abstol,
        num_iter,
        solver_opts,
        solver_cache
    )

    ## S4 method for signature 'MOSEK,ANY,ANY'
    invert(object, solution, inverse_data)

```

Arguments

solver, object, x	A MOSEK object.
problem	A Problem object.
constraints	A list of Constraint objects for which coefficient and offset data ("G", "h" respectively) is needed
exp_cone_order	A parameter that is only used when a Constraint object describes membership in the exponential cone.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.
solution	The raw solution returned by the solver.
inverse_data	A list containing data necessary for the inversion.

Methods (by generic)

- `mip_capable(MOSEK)`: Can the solver handle mixed-integer programs?
- `import_solver(MOSEK)`: Imports the solver.
- `name(MOSEK)`: Returns the name of the solver.
- `accepts(object = MOSEK, problem = Problem)`: Can MOSEK solve the problem?
- `block_format(MOSEK)`: Returns a large matrix "coeff" and a vector of constants "offset" such that every [Constraint](#) in "constraints" holds at z in $\mathbb{R}^n$ iff "coeff" * $z \leq_K$ offset", where K is a product of cones supported by MOSEK and CVXR (zero cone, nonnegative orthant, second order cone, exponential cone). The nature of K is inferred later by accessing the data in "lengths" and "ids".

- `perform(object = MOSEK, problem = Problem)`: Returns a new problem and data for inverting the new solution.
- `solve_via_data(MOSEK)`: Solve a problem represented by data returned from `apply`.
- `invert(object = MOSEK, solution = ANY, inverse_data = ANY)`: Returns the solution to the original problem given the `inverse_data`.

`MOSEK.parse_dual_vars` *Parses MOSEK dual variables into corresponding CVXR constraints and dual values*

Description

Parses MOSEK dual variables into corresponding CVXR constraints and dual values

Usage

```
MOSEK.parse_dual_vars(dual_var, constr_id_to_constr_dim)
```

Arguments

`dual_var` List of the dual variables returned by the MOSEK solution.

`constr_id_to_constr_dim` A list that contains the mapping of entry "id" that is the index of the CVXR [Constraint](#) object to which the next "dim" entries of the dual variable belong.

Value

A list with the mapping of the CVXR [Constraint](#) object indices with the corresponding dual values.

`MOSEK.recover_dual_variables`
Recovers MOSEK solutions dual variables

Description

Recovers MOSEK solutions dual variables

Usage

```
MOSEK.recover_dual_variables(sol, inverse_data)
```

Arguments

`sol` List of the solutions returned by the MOSEK solver.

`inverse_data` A list of the data returned by the `perform` function.

Value

A list containing the mapping of CVXR’s [Constraint](#) object’s id to its corresponding dual variables in the current solution.

multiply	<i>Elementwise Multiplication</i>
----------	-----------------------------------

Description

The elementwise product of two expressions. The first expression must be constant.

Usage

```
multiply(lh_exp, rh_exp)
```

Arguments

- lh_exp An [Expression](#), vector, or matrix representing the left-hand value.
- rh_exp An [Expression](#), vector, or matrix representing the right-hand value.

Value

An [Expression](#) representing the elementwise product of the inputs.

Examples

```
A <- Variable(2,2)
c <- cbind(c(1,-1), c(2,-2))
expr <- multiply(c, A)
obj <- Minimize(norm_inf(expr))
prob <- Problem(obj, list(A == 5))
result <- solve(prob)
result$value
result$getValue(expr)
```

Multiply-class	<i>The Multiply class.</i>
----------------	----------------------------

Description

This class represents the elementwise product of two expressions.

Usage

```

Multiply(lh_exp, rh_exp)

## S4 method for signature 'Multiply'
to_numeric(object, values)

## S4 method for signature 'Multiply'
dim_from_args(object)

## S4 method for signature 'Multiply'
is_atom_log_log_convex(object)

## S4 method for signature 'Multiply'
is_atom_log_log_concave(object)

## S4 method for signature 'Multiply'
is_psd(object)

## S4 method for signature 'Multiply'
is_nsd(object)

## S4 method for signature 'Multiply'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

lh_exp	An Expression or R numeric data.
rh_exp	An Expression or R numeric data.
object	A Multiply object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(Multiply)`: Multiplies the values elementwise.
- `dim_from_args(Multiply)`: The sum of the argument dimensions - 1.
- `is_atom_log_log_convex(Multiply)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Multiply)`: Is the atom log-log concave?
- `is_psd(Multiply)`: Is the expression a positive semidefinite matrix?
- `is_nsd(Multiply)`: Is the expression a negative semidefinite matrix?
- `graph_implementation(Multiply)`: The graph implementation of the expression.

name	<i>Variable, Parameter, or Expression Name</i>
------	--

Description

The string representation of a variable, parameter, or expression.

Usage

name(x)

Arguments

x A [Variable](#), [Parameter](#), or [Expression](#) object.

Value

For [Variable](#) or [Parameter](#) objects, the value in the name slot. For [Expression](#) objects, a string indicating the nested atoms and their respective arguments.

Examples

```
x <- Variable()
y <- Variable(3, name = "yVar")

name(x)
name(y)
```

Neg	<i>An alias for -MinElemwise(x, 0)</i>
-----	--

Description

An alias for -MinElemwise(x, 0)

Usage

Neg(x)

Arguments

x An R numeric value or [Expression](#).

Value

An alias for -MinElemwise(x, 0)

neg	<i>Elementwise Negative</i>
-----	-----------------------------

Description

The elementwise absolute negative portion of an expression, $-\min(x_i, 0)$. This is equivalent to `-min_elemwise(x, 0)`.

Usage

```
neg(x)
```

Arguments

`x` An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the negative portion of the input.

Examples

```
x <- Variable(2)
val <- matrix(c(-3,3))
prob <- Problem(Minimize(neg(x)[1]), list(x == val))
result <- solve(prob)
result$value
```

`NonlinearConstraint-class`

The NonlinearConstraint class.

Description

This class represents a nonlinear inequality constraint, $f(x) \leq 0$ where f is twice-differentiable.

Usage

```
NonlinearConstraint(f, vars_, id = NA_integer_)
```

Arguments

`f` A nonlinear function.

`vars_` A list of variables involved in the function.

`id` (Optional) An integer representing the unique ID of the constraint.

Slots

f A nonlinear function.

vars_ A list of variables involved in the function.

.x_dim (Internal) The dimensions of a column vector with number of elements equal to the total elements in all the variables.

NonPosConstraint-class

The NonPosConstraint class

Description

The NonPosConstraint class

Usage

```
## S4 method for signature 'NonPosConstraint'
name(x)
```

```
## S4 method for signature 'NonPosConstraint'
is_dcp(object)
```

```
## S4 method for signature 'NonPosConstraint'
is_dgp(object)
```

```
## S4 method for signature 'NonPosConstraint'
canonicalize(object)
```

```
## S4 method for signature 'NonPosConstraint'
residual(object)
```

Arguments

x, object A [NonPosConstraint](#) object.

Methods (by generic)

- name(NonPosConstraint): The string representation of the constraint.
- is_dcp(NonPosConstraint): Is the constraint DCP?
- is_dgp(NonPosConstraint): Is the constraint DGP?
- canonicalize(NonPosConstraint): The graph implementation of the object.
- residual(NonPosConstraint): The residual of the constraint.

Norm	<i>The Norm atom.</i>
------	-----------------------

Description

Wrapper around the different norm atoms.

Usage

```
Norm(x, p = 2, axis = NA_real_, keepdims = FALSE)
```

Arguments

x	The matrix to take the norm of
p	The type of norm. Valid options include any positive integer, 'fro' (for frobenius), 'nuc' (sum of singular values), np.inf or 'inf' (infinity norm).
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Value

Returns the specified norm of x.

norm, Expression, character-method
<i>Matrix Norm</i>

Description

The matrix norm, which can be the 1-norm ("1"), infinity-norm ("I"), Frobenius norm ("F"), maximum modulus of all the entries ("M"), or the spectral norm ("2"), as determined by the value of type.

Usage

```
## S4 method for signature 'Expression,character'
norm(x, type)
```

Arguments

x	An Expression .
type	A character indicating the type of norm desired. • "O", "o" or "1" specifies the 1-norm (maximum absolute column sum). • "I" or "i" specifies the infinity-norm (maximum absolute row sum). • "F" or "f" specifies the Frobenius norm (Euclidean norm of the vectorized x). • "M" or "m" specifies the maximum modulus of all the elements in x. • "2" specifies the spectral norm, which is the largest singular value of x.

Value

An [Expression](#) representing the norm of the input.

See Also

The [p_norm](#) function calculates the vector p-norm.

Examples

```
C <- Variable(3,2)
val <- Constant(rbind(c(1,2), c(3,4), c(5,6)))
prob <- Problem(Minimize(norm(C, "F")), list(C == val))
result <- solve(prob, solver = "SCS")
result$value
```

norm1	<i>1-Norm</i>
-------	---------------

Description

$$\|x\|_1 = \sum_{i=1}^n |x_i|.$$

Usage

```
norm1(x, axis = NA_real_, keepdims = FALSE)
```

Arguments

x	An Expression , vector, or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Value

An [Expression](#) representing the 1-norm of the input.

Examples

```
a <- Variable()
prob <- Problem(Minimize(norm1(a)), list(a <= -2))
result <- solve(prob)
result$value
result$getValue(a)

prob <- Problem(Maximize(-norm1(a)), list(a <= -2))
result <- solve(prob)
result$value
result$getValue(a)

x <- Variable(2)
z <- Variable(2)
prob <- Problem(Minimize(norm1(x - z) + 5), list(x >= c(2,3), z <= c(-1,-4)))
result <- solve(prob)
result$value
result$getValue(x[1] - z[1])
```

Norm1-class

The Norm1 class.

Description

This class represents the 1-norm of an expression.

Usage

```
Norm1(x, axis = NA_real_, keepdims = FALSE)

## S4 method for signature 'Norm1'
name(x)

## S4 method for signature 'Norm1'
to_numeric(object, values)

## S4 method for signature 'Norm1'
allow_complex(object)

## S4 method for signature 'Norm1'
sign_from_args(object)

## S4 method for signature 'Norm1'
is_atom_convex(object)
```

```

## S4 method for signature 'Norm1'
is_atom_concave(object)

## S4 method for signature 'Norm1'
is_incr(object, idx)

## S4 method for signature 'Norm1'
is_decr(object, idx)

## S4 method for signature 'Norm1'
is_pwl(object)

## S4 method for signature 'Norm1'
get_data(object)

## S4 method for signature 'Norm1'
.domain(object)

## S4 method for signature 'Norm1'
.grad(object, values)

## S4 method for signature 'Norm1'
.column_grad(object, value)

```

Arguments

x	An Expression object.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.
object	A Norm1 object.
values	A list of numeric values for the arguments
idx	An index into the atom.
value	A numeric value

Methods (by generic)

- `name(Norm1)`: The name and arguments of the atom.
- `to_numeric(Norm1)`: Returns the 1-norm of x along the given axis.
- `allow_complex(Norm1)`: Does the atom handle complex numbers?
- `sign_from_args(Norm1)`: The atom is always positive.
- `is_atom_convex(Norm1)`: The atom is convex.
- `is_atom_concave(Norm1)`: The atom is not concave.

- `is_incr(Norm1)`: Is the composition weakly increasing in argument `idx`?
- `is_decr(Norm1)`: Is the composition weakly decreasing in argument `idx`?
- `is_pwl(Norm1)`: Is the atom piecewise linear?
- `get_data(Norm1)`: Returns the axis.
- `.domain(Norm1)`: Returns constraints describing the domain of the node
- `.grad(Norm1)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(Norm1)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable

Slots

x An [Expression](#) object.

Norm2	<i>The Norm2 atom.</i>
-------	------------------------

Description

The 2-norm of an expression.

Usage

`Norm2(x, axis = NA_real_, keepdims = FALSE)`

Arguments

x	An Expression object.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Value

Returns the 2-norm of x.

norm2

*Euclidean Norm***Description**

$$\|x\|_2 = \left(\sum_{i=1}^n x_i^2\right)^{1/2}.$$

Usage

```
norm2(x, axis = NA_real_, keepdims = FALSE)
```

Arguments

x	An Expression , vector, or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

Value

An [Expression](#) representing the Euclidean norm of the input.

Examples

```
a <- Variable()
prob <- Problem(Minimize(norm2(a)), list(a <= -2))
result <- solve(prob)
result$value
result$getValue(a)

prob <- Problem(Maximize(-norm2(a)), list(a <= -2))
result <- solve(prob)
result$value
result$getValue(a)

x <- Variable(2)
z <- Variable(2)
prob <- Problem(Minimize(norm2(x - z) + 5), list(x >= c(2,3), z <= c(-1,-4)))
result <- solve(prob)
result$value
result$getValue(x)
result$getValue(z)

prob <- Problem(Minimize(norm2(t(x - z)) + 5), list(x >= c(2,3), z <= c(-1,-4)))
result <- solve(prob)
result$value
result$getValue(x)
```

```
result$getValue(z)
```

NormInf-class	<i>The NormInf class.</i>
---------------	---------------------------

Description

This class represents the infinity-norm.

Usage

```
## S4 method for signature 'NormInf'
name(x)

## S4 method for signature 'NormInf'
to_numeric(object, values)

## S4 method for signature 'NormInf'
allow_complex(object)

## S4 method for signature 'NormInf'
sign_from_args(object)

## S4 method for signature 'NormInf'
is_atom_convex(object)

## S4 method for signature 'NormInf'
is_atom_concave(object)

## S4 method for signature 'NormInf'
is_atom_log_log_convex(object)

## S4 method for signature 'NormInf'
is_atom_log_log_concave(object)

## S4 method for signature 'NormInf'
is_incr(object, idx)

## S4 method for signature 'NormInf'
is_decr(object, idx)

## S4 method for signature 'NormInf'
is_pwl(object)

## S4 method for signature 'NormInf'
get_data(object)
```

```

## S4 method for signature 'NormInf'
.domain(object)

## S4 method for signature 'NormInf'
.grad(object, values)

## S4 method for signature 'NormInf'
.column_grad(object, value)

```

Arguments

x, object	A NormInf object.
values	A list of numeric values for the arguments
idx	An index into the atom.
value	A numeric value

Methods (by generic)

- `name(NormInf)`: The name and arguments of the atom.
- `to_numeric(NormInf)`: Returns the infinity norm of x.
- `allow_complex(NormInf)`: Does the atom handle complex numbers?
- `sign_from_args(NormInf)`: The atom is always positive.
- `is_atom_convex(NormInf)`: The atom is convex.
- `is_atom_concave(NormInf)`: The atom is not concave.
- `is_atom_log_log_convex(NormInf)`: Is the atom log-log convex?
- `is_atom_log_log_concave(NormInf)`: Is the atom log-log concave?
- `is_incr(NormInf)`: Is the composition weakly increasing in argument idx?
- `is_decr(NormInf)`: Is the composition weakly decreasing in argument idx?
- `is_pwl(NormInf)`: Is the atom piecewise linear?
- `get_data(NormInf)`: Returns the axis.
- `.domain(NormInf)`: Returns constraints describing the domain of the node
- `.grad(NormInf)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(NormInf)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable

NormNuc-class

The NormNuc class.

Description

The nuclear norm, i.e. sum of the singular values of a matrix.

Usage

```
NormNuc(A)
```

```
## S4 method for signature 'NormNuc'
to_numeric(object, values)
```

```
## S4 method for signature 'NormNuc'
allow_complex(object)
```

```
## S4 method for signature 'NormNuc'
dim_from_args(object)
```

```
## S4 method for signature 'NormNuc'
sign_from_args(object)
```

```
## S4 method for signature 'NormNuc'
is_atom_convex(object)
```

```
## S4 method for signature 'NormNuc'
is_atom_concave(object)
```

```
## S4 method for signature 'NormNuc'
is_incr(object, idx)
```

```
## S4 method for signature 'NormNuc'
is_decr(object, idx)
```

```
## S4 method for signature 'NormNuc'
.grad(object, values)
```

Arguments

A	An Expression or numeric matrix.
object	A NormNuc object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(NormNuc)`: The nuclear norm (i.e., the sum of the singular values) of A.
- `allow_complex(NormNuc)`: Does the atom handle complex numbers?
- `dim_from_args(NormNuc)`: The atom is a scalar.
- `sign_from_args(NormNuc)`: The atom is positive.
- `is_atom_convex(NormNuc)`: The atom is convex.
- `is_atom_concave(NormNuc)`: The atom is not concave.
- `is_incr(NormNuc)`: The atom is not monotonic in any argument.
- `is_decr(NormNuc)`: The atom is not monotonic in any argument.
- `.grad(NormNuc)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

A An [Expression](#) or numeric matrix.

<code>norm_inf</code>	<i>Infinity-Norm</i>
-----------------------	----------------------

Description

$$\|x\|_\infty = \max_{i=1,\dots,n} |x_i|.$$

Usage

```
norm_inf(x, axis = NA_real_, keepdims = FALSE)
```

Arguments

<code>x</code>	An Expression , vector, or matrix.
<code>axis</code>	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
<code>keepdims</code>	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.

Value

An [Expression](#) representing the infinity-norm of the input.

Examples

```

a <- Variable()
b <- Variable()
c <- Variable()

prob <- Problem(Minimize(norm_inf(a)), list(a >= 2))
result <- solve(prob)
result$value
result$getValue(a)

prob <- Problem(Minimize(3*norm_inf(a + 2*b) + c), list(a >= 2, b <= -1, c == 3))
result <- solve(prob)
result$value
result$getValue(a + 2*b)
result$getValue(c)

prob <- Problem(Maximize(-norm_inf(a)), list(a <= -2))
result <- solve(prob)
result$value
result$getValue(a)

x <- Variable(2)
z <- Variable(2)
prob <- Problem(Minimize(norm_inf(x - z) + 5), list(x >= c(2,3), z <= c(-1,-4)))
result <- solve(prob)
result$value
result$getValue(x[1] - z[1])

```

norm_nuc

*Nuclear Norm***Description**

The nuclear norm, i.e. sum of the singular values of a matrix.

Usage

```
norm_nuc(A)
```

Arguments

A An [Expression](#) or matrix.

Value

An [Expression](#) representing the nuclear norm of the input.

Examples

```

C <- Variable(3,3)
val <- cbind(3:5, 6:8, 9:11)
prob <- Problem(Minimize(norm_nuc(C)), list(C == val))
result <- solve(prob)
result$value

```

Objective-arith

*Arithmetic Operations on Objectives***Description**

Add, subtract, multiply, or divide optimization objectives.

Usage

```

## S4 method for signature 'Objective,numeric'
e1 + e2

## S4 method for signature 'numeric,Objective'
e1 + e2

## S4 method for signature 'Minimize,missing'
e1 - e2

## S4 method for signature 'Minimize,Minimize'
e1 + e2

## S4 method for signature 'Minimize,Maximize'
e1 + e2

## S4 method for signature 'Objective,Minimize'
e1 - e2

## S4 method for signature 'Objective,Maximize'
e1 - e2

## S4 method for signature 'Minimize,Objective'
e1 - e2

## S4 method for signature 'Maximize,Objective'
e1 - e2

## S4 method for signature 'Objective,numeric'
e1 - e2

## S4 method for signature 'numeric,Objective'

```

```

e1 - e2

## S4 method for signature 'Minimize,numeric'
e1 * e2

## S4 method for signature 'Maximize,numeric'
e1 * e2

## S4 method for signature 'numeric,Minimize'
e1 * e2

## S4 method for signature 'numeric,Maximize'
e1 * e2

## S4 method for signature 'Objective,numeric'
e1 / e2

## S4 method for signature 'Maximize,missing'
e1 - e2

## S4 method for signature 'Maximize,Maximize'
e1 + e2

## S4 method for signature 'Maximize,Minimize'
e1 + e2

```

Arguments

e1 The left-hand [Minimize](#), [Maximize](#), or numeric value.

e2 The right-hand [Minimize](#), [Maximize](#), or numeric value.

Value

A [Minimize](#) or [Maximize](#) object.

Objective-class	<i>The Objective class.</i>
-----------------	-----------------------------

Description

This class represents an optimization objective.

Usage

```

Objective(expr)

## S4 method for signature 'Objective'

```

```

value(object)

## S4 method for signature 'Objective'
is_quadratic(object)

## S4 method for signature 'Objective'
is_qpwa(object)

```

Arguments

expr A scalar [Expression](#) to optimize.
 object An [Objective](#) object.

Methods (by generic)

- value(Objective): The value of the objective expression.
- is_quadratic(Objective): Is the objective a quadratic function?
- is_qpwa(Objective): Is the objective a quadratic of piecewise affine function?

Slots

expr A scalar [Expression](#) to optimize.

OneMinusPos-class	<i>The OneMinusPos class.</i>
-------------------	-------------------------------

Description

This class represents the difference $1 - x$ with domain $\{x : 0 < x < 1\}$

Usage

```

OneMinusPos(x)

## S4 method for signature 'OneMinusPos'
name(x)

## S4 method for signature 'OneMinusPos'
to_numeric(object, values)

## S4 method for signature 'OneMinusPos'
dim_from_args(object)

## S4 method for signature 'OneMinusPos'
sign_from_args(object)

## S4 method for signature 'OneMinusPos'

```

```

is_atom_convex(object)

## S4 method for signature 'OneMinusPos'
is_atom_concave(object)

## S4 method for signature 'OneMinusPos'
is_atom_log_log_convex(object)

## S4 method for signature 'OneMinusPos'
is_atom_log_log_concave(object)

## S4 method for signature 'OneMinusPos'
is_incr(object, idx)

## S4 method for signature 'OneMinusPos'
is_decr(object, idx)

## S4 method for signature 'OneMinusPos'
.grad(object, values)

```

Arguments

x	An Expression or numeric matrix.
object	A OneMinusPos object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `name(OneMinusPos)`: The name and arguments of the atom.
- `to_numeric(OneMinusPos)`: Returns one minus the value.
- `dim_from_args(OneMinusPos)`: The dimensions of the atom.
- `sign_from_args(OneMinusPos)`: Returns the sign (is positive, is negative) of the atom.
- `is_atom_convex(OneMinusPos)`: Is the atom convex?
- `is_atom_concave(OneMinusPos)`: Is the atom concave?
- `is_atom_log_log_convex(OneMinusPos)`: Is the atom log-log convex?
- `is_atom_log_log_concave(OneMinusPos)`: Is the atom log-log concave?
- `is_incr(OneMinusPos)`: Is the atom weakly increasing in the argument `idx`?
- `is_decr(OneMinusPos)`: Is the atom weakly decreasing in the argument `idx`?
- `.grad(OneMinusPos)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x An [Expression](#) or numeric matrix.

one_minus_pos

Difference on Restricted Domain

Description

The difference $1 - x$ with domain $\{x : 0 < x < 1\}$.

Usage

```
one_minus_pos(x)
```

Arguments

`x` An [Expression](#), vector, or matrix.

Details

This atom is log-log concave.

Value

An [Expression](#) representing one minus the input restricted to $(0, 1)$.

Examples

```
x <- Variable(pos = TRUE)
y <- Variable(pos = TRUE)
prob <- Problem(Maximize(one_minus_pos(x*y)), list(x <= 2 * y^2, y >= .2))
result <- solve(prob, gp = TRUE)
result$value
result$getValue(x)
result$getValue(y)
```

OSQP-class

An interface for the OSQP solver.

Description

An interface for the OSQP solver.

Usage

```

OSQP()

## S4 method for signature 'OSQP'
status_map(solver, status)

## S4 method for signature 'OSQP'
name(x)

## S4 method for signature 'OSQP'
import_solver(solver)

## S4 method for signature 'OSQP,list,InverseData'
invert(object, solution, inverse_data)

## S4 method for signature 'OSQP'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A OSQP object.
status	A status code returned by the solver.
solution	The raw solution returned by the solver.
inverse_data	A InverseData object containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `status_map(OSQP)`: Converts status returned by the OSQP solver to its respective CVXPY status.
- `name(OSQP)`: Returns the name of the solver.
- `import_solver(OSQP)`: Imports the solver.
- `invert(object = OSQP, solution = list, inverse_data = InverseData)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(OSQP)`: Solve a problem represented by data returned from apply.

Parameter-class

The Parameter class.

Description

This class represents a parameter, either scalar or a matrix.

Usage

```

Parameter(
  rows = NULL,
  cols = NULL,
  name = NA_character_,
  value = NA_real_,
  ...
)

## S4 method for signature 'Parameter'
get_data(object)

## S4 method for signature 'Parameter'
name(x)

## S4 method for signature 'Parameter'
value(object)

## S4 replacement method for signature 'Parameter'
value(object) <- value

## S4 method for signature 'Parameter'
grad(object)

## S4 method for signature 'Parameter'
parameters(object)

## S4 method for signature 'Parameter'
canonicalize(object)

```

Arguments

rows	The number of rows in the parameter.
cols	The number of columns in the parameter.
name	(Optional) A character string representing the name of the parameter.
value	(Optional) A numeric element, vector, matrix, or data.frame. Defaults to NA and may be changed with <code>value<-</code> later.
...	Additional attribute arguments. See Leaf for details.
object, x	A Parameter object.

Methods (by generic)

- `get_data(Parameter)`: Returns `list(dim, name, value, attributes)`.
- `name(Parameter)`: The name of the parameter.
- `value(Parameter)`: The value of the parameter.
- `value(Parameter) <- value`: Set the value of the parameter.
- `grad(Parameter)`: An empty list since the gradient of a parameter is zero.
- `parameters(Parameter)`: Returns itself as a parameter.
- `canonicalize(Parameter)`: The canonical form of the parameter.

Slots

rows	The number of rows in the parameter.
cols	The number of columns in the parameter.
name	(Optional) A character string representing the name of the parameter.
value	(Optional) A numeric element, vector, matrix, or data.frame. Defaults to NA and may be changed with <code>value<-</code> later.

Examples

```
x <- Parameter(3, name = "x0", nonpos = TRUE) ## 3-vec negative
is_nonneg(x)
is_nonpos(x)
size(x)
```

perform	<i>Perform Reduction</i>
---------	--------------------------

Description

Performs the reduction on a problem and returns an equivalent problem.

Usage

```
perform(object, problem)
```

Arguments

object	A Reduction object.
problem	A Problem on which the reduction will be performed.

Value

A list containing

"problem" A [Problem](#) or list representing the equivalent problem.

"inverse_data" A [InverseData](#) or list containing the data needed to invert this particular reduction.

PfEigenvalue-class	<i>The PfEigenvalue class.</i>
--------------------	--------------------------------

Description

This class represents the Perron-Frobenius eigenvalue of a positive matrix.

Usage

```
PfEigenvalue(X)

## S4 method for signature 'PfEigenvalue'
name(x)

## S4 method for signature 'PfEigenvalue'
to_numeric(object, values)

## S4 method for signature 'PfEigenvalue'
dim_from_args(object)

## S4 method for signature 'PfEigenvalue'
sign_from_args(object)
```

```

## S4 method for signature 'PfEigenvalue'
is_atom_convex(object)

## S4 method for signature 'PfEigenvalue'
is_atom_concave(object)

## S4 method for signature 'PfEigenvalue'
is_atom_log_log_convex(object)

## S4 method for signature 'PfEigenvalue'
is_atom_log_log_concave(object)

## S4 method for signature 'PfEigenvalue'
is_incr(object, idx)

## S4 method for signature 'PfEigenvalue'
is_decr(object, idx)

## S4 method for signature 'PfEigenvalue'
.grad(object, values)

```

Arguments

X	An Expression or numeric matrix.
x, object	A PfEigenvalue object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `name(PfEigenvalue)`: The name and arguments of the atom.
- `to_numeric(PfEigenvalue)`: Returns the Perron-Frobenius eigenvalue of X.
- `dim_from_args(PfEigenvalue)`: The dimensions of the atom.
- `sign_from_args(PfEigenvalue)`: Returns the sign (is positive, is negative) of the atom.
- `is_atom_convex(PfEigenvalue)`: Is the atom convex?
- `is_atom_concave(PfEigenvalue)`: Is the atom concave?
- `is_atom_log_log_convex(PfEigenvalue)`: Is the atom log-log convex?
- `is_atom_log_log_concave(PfEigenvalue)`: Is the atom log-log concave?
- `is_incr(PfEigenvalue)`: Is the atom weakly increasing in the argument idx?
- `is_decr(PfEigenvalue)`: Is the atom weakly decreasing in the argument idx?
- `.grad(PfEigenvalue)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

X An [Expression](#) or numeric matrix.

pf_eigenvalue

*Perron-Frobenius Eigenvalue***Description**

The Perron-Frobenius eigenvalue of a positive matrix.

Usage

```
pf_eigenvalue(X)
```

Arguments

X An [Expression](#) or positive square matrix.

Details

For an elementwise positive matrix X , this atom represents its spectral radius, i.e., the magnitude of its largest eigenvalue. Because X is positive, the spectral radius equals its largest eigenvalue, which is guaranteed to be positive.

This atom is log-log convex.

Value

An [Expression](#) representing the largest eigenvalue of the input.

Examples

```
n <- 3
X <- Variable(n, n, pos=TRUE)
objective_fn <- pf_eigenvalue(X)
constraints <- list( X[1,1]== 1.0,
                    X[1,3] == 1.9,
                    X[2,2] == .8,
                    X[3,1] == 3.2,
                    X[3,2] == 5.9,
                    X[1, 2] * X[2, 1] * X[2,3] * X[3,3] == 1)
problem <- Problem(Minimize(objective_fn), constraints)
result <- solve(problem, gp=TRUE)
result$value
result$getValue(X)
```

Pnorm-class

*The Pnorm class.***Description**

This class represents the vector p-norm.

Usage

```
Pnorm(x, p = 2, axis = NA_real_, keepdims = FALSE, max_denom = 1024)
```

```
## S4 method for signature 'Pnorm'
allow_complex(object)
```

```
## S4 method for signature 'Pnorm'
to_numeric(object, values)
```

```
## S4 method for signature 'Pnorm'
validate_args(object)
```

```
## S4 method for signature 'Pnorm'
sign_from_args(object)
```

```
## S4 method for signature 'Pnorm'
is_atom_convex(object)
```

```
## S4 method for signature 'Pnorm'
is_atom_concave(object)
```

```
## S4 method for signature 'Pnorm'
is_atom_log_log_convex(object)
```

```
## S4 method for signature 'Pnorm'
is_atom_log_log_concave(object)
```

```
## S4 method for signature 'Pnorm'
is_incr(object, idx)
```

```
## S4 method for signature 'Pnorm'
is_decr(object, idx)
```

```
## S4 method for signature 'Pnorm'
is_pwl(object)
```

```
## S4 method for signature 'Pnorm'
get_data(object)
```

```

## S4 method for signature 'Pnorm'
name(x)

## S4 method for signature 'Pnorm'
.domain(object)

## S4 method for signature 'Pnorm'
.grad(object, values)

## S4 method for signature 'Pnorm'
.column_grad(object, value)

```

Arguments

x	An Expression representing a vector or matrix.
p	A number greater than or equal to 1, or equal to positive infinity.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.
max_denom	(Optional) The maximum denominator considered in forming a rational approximation for p . The default is 1024.
object	A Pnorm object.
values	A list of numeric values for the arguments
idx	An index into the atom.
value	A numeric value

Details

If given a matrix variable, Pnorm will treat it as a vector and compute the p-norm of the concatenated columns.

For $p \geq 1$, the p-norm is given by

$$\|x\|_p = \left(\sum_{i=1}^n |x_i|^p \right)^{1/p}$$

with domain $x \in \mathbf{R}^n$. For $p < 1, p \neq 0$, the p-norm is given by

$$\|x\|_p = \left(\sum_{i=1}^n x_i^p \right)^{1/p}$$

with domain $x \in \mathbf{R}_+^n$.

- Note that the "p-norm" is actually a **norm** only when $p \geq 1$ or $p = +\infty$. For these cases, it is convex.
- The expression is undefined when $p = 0$.
- Otherwise, when $p < 1$, the expression is concave, but not a true norm.

Methods (by generic)

- `allow_complex(Pnorm)`: Does the atom handle complex numbers?
- `to_numeric(Pnorm)`: The p-norm of x .
- `validate_args(Pnorm)`: Check that the arguments are valid.
- `sign_from_args(Pnorm)`: The atom is positive.
- `is_atom_convex(Pnorm)`: The atom is convex if $p \geq 1$.
- `is_atom_concave(Pnorm)`: The atom is concave if $p < 1$.
- `is_atom_log_log_convex(Pnorm)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Pnorm)`: Is the atom log-log concave?
- `is_incr(Pnorm)`: The atom is weakly increasing if $p < 1$ or $p > 1$ and x is positive.
- `is_decr(Pnorm)`: The atom is weakly decreasing if $p > 1$ and x is negative.
- `is_pwl(Pnorm)`: The atom is not piecewise linear unless $p = 1$ or $p = \infty$.
- `get_data(Pnorm)`: Returns `list(p, axis)`.
- `name(Pnorm)`: The name and arguments of the atom.
- `.domain(Pnorm)`: Returns constraints describing the domain of the node
- `.grad(Pnorm)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.column_grad(Pnorm)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable

Slots

- x An [Expression](#) representing a vector or matrix.
- p A number greater than or equal to 1, or equal to positive infinity.
- `max_denom` The maximum denominator considered in forming a rational approximation for p .
- `axis` (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
- `keepdims` (Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.
- `.approx_error` (Internal) The absolute difference between p and its rational approximation.
- `.original_p` (Internal) The original input p .

Pos

*An alias for `MaxElemwise(x, 0)`***Description**An alias for `MaxElemwise(x, 0)`**Usage**`Pos(x)`

Arguments

x An R numeric value or [Expression](#).

Value

An alias for `MaxElemwise(x, 0)`

pos	<i>Elementwise Positive</i>
-----	-----------------------------

Description

The elementwise positive portion of an expression, $\max(x_i, 0)$. This is equivalent to `max_elemwise(x, 0)`.

Usage

`pos(x)`

Arguments

x An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the positive portion of the input.

Examples

```
x <- Variable(2)
val <- matrix(c(-3,2))
prob <- Problem(Minimize(pos(x)[1]), list(x == val))
result <- solve(prob)
result$value
```

Power-class	<i>The Power class.</i>
-------------	-------------------------

Description

This class represents the elementwise power function $f(x) = x^p$. If `expr` is a CVXR expression, then `expr^p` is equivalent to `Power(expr, p)`.

Usage

```
Power(x, p, max_denom = 1024)

## S4 method for signature 'Power'
to_numeric(object, values)

## S4 method for signature 'Power'
sign_from_args(object)

## S4 method for signature 'Power'
is_atom_convex(object)

## S4 method for signature 'Power'
is_atom_concave(object)

## S4 method for signature 'Power'
is_atom_log_log_convex(object)

## S4 method for signature 'Power'
is_atom_log_log_concave(object)

## S4 method for signature 'Power'
is_constant(object)

## S4 method for signature 'Power'
is_incr(object, idx)

## S4 method for signature 'Power'
is_decr(object, idx)

## S4 method for signature 'Power'
is_quadratic(object)

## S4 method for signature 'Power'
is_qpwa(object)

## S4 method for signature 'Power'
.grad(object, values)

## S4 method for signature 'Power'
.domain(object)

## S4 method for signature 'Power'
.get_data(object)

## S4 method for signature 'Power'
.copy(object, args = NULL, id_objects = list())
```

```
## S4 method for signature 'Power'
name(x)
```

Arguments

x	The Expression to be raised to a power.
p	A numeric value indicating the scalar power.
max_denom	The maximum denominator considered in forming a rational approximation of p.
object	A Power object.
values	A list of numeric values for the arguments
idx	An index into the atom.
args	A list of arguments to reconstruct the atom. If args=NULL, use the current args of the atom
id_objects	Currently unused.

Details

For $p = 0$, $f(x) = 1$, constant, positive.

For $p = 1$, $f(x) = x$, affine, increasing, same sign as x .

For $p = 2, 4, 8, \dots$, $f(x) = |x|^p$, convex, signed monotonicity, positive.

For $p < 0$ and $f(x) =$

x^p for $x > 0$

$+\infty$ $x \leq 0$

, this function is convex, decreasing, and positive.

For $0 < p < 1$ and $f(x) =$

x^p for $x \geq 0$

$-\infty$ $x < 0$

, this function is concave, increasing, and positive.

For $p > 1$, $p \neq 2, 4, 8, \dots$ and $f(x) =$

x^p for $x \geq 0$

$+\infty$ $x < 0$

, this function is convex, increasing, and positive.

Methods (by generic)

- `to_numeric(Power)`: Throw an error if the power is negative and cannot be handled.
- `sign_from_args(Power)`: The sign of the atom.
- `is_atom_convex(Power)`: Is $p \leq 0$ or $p \geq 1$?
- `is_atom_concave(Power)`: Is $p \geq 0$ or $p \leq 1$?
- `is_atom_log_log_convex(Power)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Power)`: Is the atom log-log concave?
- `is_constant(Power)`: A logical value indicating whether the atom is constant.
- `is_incr(Power)`: A logical value indicating whether the atom is weakly increasing.
- `is_decr(Power)`: A logical value indicating whether the atom is weakly decreasing.
- `is_quadratic(Power)`: A logical value indicating whether the atom is quadratic.
- `is_qpwa(Power)`: A logical value indicating whether the atom is quadratic or piecewise affine.
- `.grad(Power)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `.domain(Power)`: Returns constraints describing the domain of the node
- `get_data(Power)`: A list containing the output of `pow_low`, `pow_mid`, or `pow_high` depending on the input power.
- `copy(Power)`: Returns a shallow copy of the power atom
- `name(Power)`: Returns the expression in string form.

Slots

- x The [Expression](#) to be raised to a power.
- p A numeric value indicating the scalar power.
- max_denom The maximum denominator considered in forming a rational approximation of p.

 Problem-arith

Arithmetic Operations on Problems

Description

Add, subtract, multiply, or divide DCP optimization problems.

Usage

```
## S4 method for signature 'Problem,missing'
e1 + e2

## S4 method for signature 'Problem,missing'
e1 - e2

## S4 method for signature 'Problem,numeric'
```

```

e1 + e2

## S4 method for signature 'numeric,Problem'
e1 + e2

## S4 method for signature 'Problem,Problem'
e1 + e2

## S4 method for signature 'Problem,numeric'
e1 - e2

## S4 method for signature 'numeric,Problem'
e1 - e2

## S4 method for signature 'Problem,Problem'
e1 - e2

## S4 method for signature 'Problem,numeric'
e1 * e2

## S4 method for signature 'numeric,Problem'
e1 * e2

## S4 method for signature 'Problem,numeric'
e1 / e2

```

Arguments

e1 The left-hand [Problem](#) object.
e2 The right-hand [Problem](#) object.

Value

A [Problem](#) object.

Problem-class	<i>The Problem class.</i>
---------------	---------------------------

Description

This class represents a convex optimization problem.

Usage

```

Problem(objective, constraints = list())

## S4 method for signature 'Problem'

```

```
objective(object)

## S4 replacement method for signature 'Problem'
objective(object) <- value

## S4 method for signature 'Problem'
constraints(object)

## S4 replacement method for signature 'Problem'
constraints(object) <- value

## S4 method for signature 'Problem'
value(object)

## S4 replacement method for signature 'Problem'
value(object) <- value

## S4 method for signature 'Problem'
status(object)

## S4 method for signature 'Problem'
is_dcp(object)

## S4 method for signature 'Problem'
is_dgp(object)

## S4 method for signature 'Problem'
is_qp(object)

## S4 method for signature 'Problem'
canonicalize(object)

## S4 method for signature 'Problem'
is_mixed_integer(object)

## S4 method for signature 'Problem'
variables(object)

## S4 method for signature 'Problem'
parameters(object)

## S4 method for signature 'Problem'
constants(object)

## S4 method for signature 'Problem'
atoms(object)

## S4 method for signature 'Problem'
```

```

size_metrics(object)

## S4 method for signature 'Problem'
solver_stats(object)

## S4 replacement method for signature 'Problem'
solver_stats(object) <- value

## S4 method for signature 'Problem,character,logical'
get_problem_data(object, solver, gp)

## S4 method for signature 'Problem,character,missing'
get_problem_data(object, solver, gp)

## S4 method for signature 'Problem'
unpack_results(object, solution, chain, inverse_data)

```

Arguments

objective	A Minimize or Maximize object representing the optimization objective.
constraints	(Optional) A list of Constraint objects representing constraints on the optimization variables.
object	A Problem class.
value	A Minimize or Maximize object (objective), list of Constraint objects (constraints), or numeric scalar (value).
solver	A string indicating the solver that the problem data is for. Call <code>installed_solvers()</code> to see all available.
gp	Is the problem a geometric problem?
solution	A Solution object.
chain	The corresponding solving Chain .
inverse_data	A InverseData object or list containing data necessary for the inversion.

Methods (by generic)

- `objective(Problem)`: The objective of the problem.
- `objective(Problem) <- value`: Set the value of the problem objective.
- `constraints(Problem)`: A list of the constraints of the problem.
- `constraints(Problem) <- value`: Set the value of the problem constraints.
- `value(Problem)`: The value from the last time the problem was solved (or NA if not solved).
- `value(Problem) <- value`: Set the value of the optimal objective.
- `status(Problem)`: The status from the last time the problem was solved.
- `is_dcp(Problem)`: A logical value indicating whether the problem satisfies DCP rules.
- `is_dgp(Problem)`: A logical value indicating whether the problem satisfies DGP rules.
- `is_qp(Problem)`: A logical value indicating whether the problem is a quadratic program.

- `canonicalize(Problem)`: The graph implementation of the problem.
- `is_mixed_integer(Problem)`: logical value indicating whether the problem is a mixed integer program.
- `variables(Problem)`: List of [Variable](#) objects in the problem.
- `parameters(Problem)`: List of [Parameter](#) objects in the problem.
- `constants(Problem)`: List of [Constant](#) objects in the problem.
- `atoms(Problem)`: List of [Atom](#) objects in the problem.
- `size_metrics(Problem)`: Information about the size of the problem.
- `solver_stats(Problem)`: Additional information returned by the solver.
- `solver_stats(Problem) <- value`: Set the additional information returned by the solver in the problem.
- `get_problem_data(object = Problem, solver = character, gp = logical)`: Get the problem data passed to the specified solver.
- `get_problem_data(object = Problem, solver = character, gp = missing)`: Get the problem data passed to the specified solver.
- `unpack_results(Problem)`: Parses the output from a solver and updates the problem state, including the status, objective value, and values of the primal and dual variables. Assumes the results are from the given solver.

Slots

`objective` A [Minimize](#) or [Maximize](#) object representing the optimization objective.

`constraints` (Optional) A list of constraints on the optimization variables.

`value` (Internal) Used internally to hold the value of the optimization objective at the solution.

`status` (Internal) Used internally to hold the status of the problem solution.

`.cached_data` (Internal) Used internally to hold cached matrix data.

`.separable_problems` (Internal) Used internally to hold separable problem data.

`.size_metrics` (Internal) Used internally to hold size metrics.

`.solver_stats` (Internal) Used internally to hold solver statistics.

Examples

```
x <- Variable(2)
p <- Problem(Minimize(p_norm(x, 2)), list(x >= 0))
is_dcp(p)
x <- Variable(2)
A <- matrix(c(1,-1,-1, 1), nrow = 2)
p <- Problem(Minimize(quad_form(x, A)), list(x >= 0))
is_qp(p)
```

problem-parts	<i>Parts of a Problem</i>
---------------	---------------------------

Description

Get and set the objective, constraints, or size metrics (get only) of a problem.

Usage

```
objective(object)

objective(object) <- value

constraints(object)

constraints(object) <- value

size_metrics(object)
```

Arguments

object	A Problem object.
value	The value to assign to the slot.

Value

For getter functions, the requested slot of the object. `x <- Variable()` `prob <- Problem(Minimize(x^2), list(x >= 5))` `objective(prob)` `constraints(prob)` `size_metrics(prob)`
`objective(prob) <- Maximize(sqrt(x))` `constraints(prob) <- list(x <= 10)` `objective(prob)` `constraints(prob)`

ProdEntries-class	<i>The ProdEntries class.</i>
-------------------	-------------------------------

Description

The product of the entries in an expression.

Usage

```
ProdEntries(..., axis = NA_real_, keepdims = FALSE)

## S4 method for signature 'ProdEntries'
to_numeric(object, values)

## S4 method for signature 'ProdEntries'
```

```

sign_from_args(object)

## S4 method for signature 'ProdEntries'
is_atom_convex(object)

## S4 method for signature 'ProdEntries'
is_atom_concave(object)

## S4 method for signature 'ProdEntries'
is_atom_log_log_convex(object)

## S4 method for signature 'ProdEntries'
is_atom_log_log_concave(object)

## S4 method for signature 'ProdEntries'
is_incr(object, idx)

## S4 method for signature 'ProdEntries'
is_decr(object, idx)

## S4 method for signature 'ProdEntries'
.column_grad(object, value)

## S4 method for signature 'ProdEntries'
.grad(object, values)

```

Arguments

...	Expression objects, vectors, or matrices.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $n \times 1$ column vector. The default is FALSE.
object	A ProdEntries object.
values	A list of numeric values for the arguments
idx	An index into the atom.
value	A numeric value.

Methods (by generic)

- `to_numeric(ProdEntries)`: The product of all the entries.
- `sign_from_args(ProdEntries)`: Returns the sign (is positive, is negative) of the atom.
- `is_atom_convex(ProdEntries)`: Is the atom convex?
- `is_atom_concave(ProdEntries)`: Is the atom concave?
- `is_atom_log_log_convex(ProdEntries)`: Is the atom log-log convex?

- `is_atom_log_log_concave(ProdEntries)`: is the atom log-log concave?
- `is_incr(ProdEntries)`: Is the atom weakly increasing in the argument `idx`?
- `is_decr(ProdEntries)`: Is the atom weakly decreasing in the argument `idx`?
- `.column_grad(ProdEntries)`: Gives the (sub/super)gradient of the atom w.r.t. each column variable
- `.grad(ProdEntries)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

`expr` An [Expression](#) representing a vector or matrix.

`axis` (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.

prod_entries

Product of Entries

Description

The product of entries in a vector or matrix.

Usage

```
prod_entries(..., axis = NA_real_, keepdims = FALSE)
```

```
## S3 method for class 'Expression'
prod(..., na.rm = FALSE)
```

Arguments

- | | |
|-----------------------|--|
| <code>...</code> | Numeric scalar, vector, matrix, or Expression objects. |
| <code>axis</code> | (Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA. |
| <code>keepdims</code> | (Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE. |
| <code>na.rm</code> | (Unimplemented) A logical value indicating whether missing values should be removed. |

Details

This atom is log-log affine, but it is neither convex nor concave.

Value

An [Expression](#) representing the product of the entries of the input.

Examples

```

n <- 2
X <- Variable(n, n, pos=TRUE)
obj <- sum(X)
constraints <- list(prod_entries(X) == 4)
prob <- Problem(Minimize(obj), constraints)
result <- solve(prob, gp=TRUE)
result$value
result$getValue(X)

n <- 2
X <- Variable(n, n, pos=TRUE)
obj <- sum(X)
constraints <- list(prod(X) == 4)
prob <- Problem(Minimize(obj), constraints)
result <- solve(prob, gp=TRUE)
result$value

```

project-methods

Project Value

Description

Project a value onto the attribute set of a [Leaf](#). A sensible idiom is `value(leaf) = project(leaf, val)`.

Usage

```

project(object, value)

project_and_assign(object, value)

```

Arguments

object	A Leaf object.
value	The assigned value.

Value

The value rounded to the attribute type.

Promote-class

The Promote class.

Description

This class represents the promotion of a scalar expression into a vector/matrix.

Usage

```
Promote(expr, promoted_dim)

## S4 method for signature 'Promote'
to_numeric(object, values)

## S4 method for signature 'Promote'
is_symmetric(object)

## S4 method for signature 'Promote'
dim_from_args(object)

## S4 method for signature 'Promote'
is_atom_log_log_convex(object)

## S4 method for signature 'Promote'
is_atom_log_log_concave(object)

## S4 method for signature 'Promote'
get_data(object)

## S4 method for signature 'Promote'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

expr	An Expression or numeric constant.
promoted_dim	The desired dimensions.
object	A Promote object.
values	A list containing the value to promote.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(Promote)`: Promotes the value to the new dimensions.
- `is_symmetric(Promote)`: Is the expression symmetric?
- `dim_from_args(Promote)`: Returns the (row, col) dimensions of the expression.
- `is_atom_log_log_convex(Promote)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Promote)`: Is the atom log-log concave?
- `get_data(Promote)`: Returns information needed to reconstruct the expression besides the args.
- `graph_implementation(Promote)`: The graph implementation of the atom.

Slots

`expr` An [Expression](#) or numeric constant.

`promoted_dim` The desired dimensions.

PSDWrap-class

The PSDWrap class.

Description

A no-op wrapper to assert the input argument is positive semidefinite.

Usage

```
PSDWrap(arg)
```

```
## S4 method for signature 'PSDWrap'
is_psd(object)
```

Arguments

`arg` A [Expression](#) object or matrix.

`object` A [PSDWrap](#) object.

Methods (by generic)

- `is_psd(PSDWrap)`: Is the atom positive semidefinite?

psd_coeff_offset	<i>Given a problem returns a PSD constraint</i>
------------------	---

Description

Given a problem returns a PSD constraint

Usage

```
psd_coeff_offset(problem, c)
```

Arguments

problem	A Problem object.
c	A vector of coefficients.

Value

Returns an array G and vector h such that the given constraint is equivalent to $G * z \leq_{PSD} h$.

psolve	<i>Solve a DCP Problem</i>
--------	----------------------------

Description

Solve a DCP compliant optimization problem.

Usage

```
psolve(
  object,
  solver = NA,
  ignore_dcp = FALSE,
  warm_start = FALSE,
  verbose = FALSE,
  parallel = FALSE,
  gp = FALSE,
  feastol = NULL,
  reltol = NULL,
  abstol = NULL,
  num_iter = NULL,
  ...
)

## S4 method for signature 'Problem'
```



```

psolve(
  object,
  solver = NA,
  ignore_dcp = FALSE,
  warm_start = FALSE,
  verbose = FALSE,
  parallel = FALSE,
  gp = FALSE,
  feastol = NULL,
  reltol = NULL,
  abstol = NULL,
  num_iter = NULL,
  ...
)

## S4 method for signature 'Problem,ANY'
solve(a, b = NA, ...)

```

Arguments

<code>object, a</code>	A Problem object.
<code>solver, b</code>	(Optional) A string indicating the solver to use. Defaults to "ECOS".
<code>ignore_dcp</code>	(Optional) A logical value indicating whether to override the DCP check for a problem.
<code>warm_start</code>	(Optional) A logical value indicating whether the previous solver result should be used to warm start.
<code>verbose</code>	(Optional) A logical value indicating whether to print additional solver output.
<code>parallel</code>	(Optional) A logical value indicating whether to solve in parallel if the problem is separable.
<code>gp</code>	(Optional) A logical value indicating whether the problem is a geometric program. Defaults to FALSE.
<code>feastol</code>	The feasible tolerance on the primal and dual residual.
<code>reltol</code>	The relative tolerance on the duality gap.
<code>abstol</code>	The absolute tolerance on the duality gap.
<code>num_iter</code>	The maximum number of iterations.
<code>...</code>	Additional options that will be passed to the specific solver. In general, these options will override any default settings imposed by CVXR.

Value

A list containing the solution to the problem:

`status` The status of the solution. Can be "optimal", "optimal_inaccurate", "infeasible", "infeasible_inaccurate", "unbounded", "unbounded_inaccurate", or "solver_error".

`value` The optimal value of the objective function.

`solver` The name of the solver.

`solve_time` The time (in seconds) it took for the solver to solve the problem.

`setup_time` The time (in seconds) it took for the solver to set up the problem.

`num_iters` The number of iterations the solver had to go through to find a solution.

`getValue` A function that takes a [Variable](#) object and retrieves its primal value.

`getDualValue` A function that takes a [Constraint](#) object and retrieves its dual value(s).

Examples

```
a <- Variable(name = "a")
prob <- Problem(Minimize(norm_inf(a)), list(a >= 2))
result <- psolve(prob, solver = "ECOS", verbose = TRUE)
result$status
result$value
result$getValue(a)
result$getDualValue(constraints(prob)[[1]])
```

<code>p_norm</code>	<i>P-Norm</i>
---------------------	---------------

Description

The vector p-norm. If given a matrix variable, `p_norm` will treat it as a vector and compute the p-norm of the concatenated columns.

Usage

```
p_norm(x, p = 2, axis = NA_real_, keepdims = FALSE, max_denom = 1024)
```

Arguments

<code>x</code>	An Expression , vector, or matrix.
<code>p</code>	A number greater than or equal to 1, or equal to positive infinity.
<code>axis</code>	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
<code>keepdims</code>	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an <i>nx1</i> column vector. The default is FALSE.
<code>max_denom</code>	(Optional) The maximum denominator considered in forming a rational approximation for <i>p</i> . The default is 1024.

Details

For $p \geq 1$, the p-norm is given by

$$\|x\|_p = \left(\sum_{i=1}^n |x_i|^p \right)^{1/p}$$

with domain $x \in \mathbf{R}^n$. For $p < 1, p \neq 0$, the p-norm is given by

$$\|x\|_p = \left(\sum_{i=1}^n x_i^p \right)^{1/p}$$

with domain $x \in \mathbf{R}_+^n$.

- Note that the "p-norm" is actually a **norm** only when $p \geq 1$ or $p = +\infty$. For these cases, it is convex.
- The expression is undefined when $p = 0$.
- Otherwise, when $p < 1$, the expression is concave, but not a true norm.

Value

An [Expression](#) representing the p-norm of the input.

Examples

```
x <- Variable(3)
prob <- Problem(Minimize(p_norm(x,2)))
result <- solve(prob)
result$value
result$getValue(x)

prob <- Problem(Minimize(p_norm(x,Inf)))
result <- solve(prob)
result$value
result$getValue(x)

## Not run:
a <- c(1.0, 2, 3)
prob <- Problem(Minimize(p_norm(x,1.6)), list(t(x) %*% a >= 1))
result <- solve(prob)
result$value
result$getValue(x)

prob <- Problem(Minimize(sum(abs(x - a))), list(p_norm(x,-1) >= 0))
result <- solve(prob)
result$value
result$getValue(x)

## End(Not run)
```

Qp2SymbolicQp-class	<i>The Qp2SymbolicQp class.</i>
---------------------	---------------------------------

Description

This class reduces a quadratic problem to a problem that consists of affine expressions and symbolic quadratic forms.

QpMatrixStuffing-class	<i>The QpMatrixStuffing class.</i>
------------------------	------------------------------------

Description

This class fills in numeric values for the problem instance and outputs a DCP-compliant minimization problem with an objective of the form

Details

QuadForm(x, p) + t(q)
and Zero/NonPos constraints, both of which exclusively carry affine arguments

QpSolver-class	<i>A QP solver interface.</i>
----------------	-------------------------------

Description

A QP solver interface.

Usage

```
## S4 method for signature 'QpSolver,Problem'  
accepts(object, problem)  
  
## S4 method for signature 'QpSolver,Problem'  
perform(object, problem)
```

Arguments

object	A QpSolver object.
problem	A Problem object.

Methods (by generic)

- `accepts(object = QpSolver, problem = Problem)`: Is this a QP problem?
- `perform(object = QpSolver, problem = Problem)`: Constructs a QP problem data stored in a list

QuadForm-class	<i>The QuadForm class.</i>
----------------	----------------------------

Description

This class represents the quadratic form $x^T P x$

Usage

```

QuadForm(x, P)

## S4 method for signature 'QuadForm'
name(x)

## S4 method for signature 'QuadForm'
allow_complex(object)

## S4 method for signature 'QuadForm'
to_numeric(object, values)

## S4 method for signature 'QuadForm'
validate_args(object)

## S4 method for signature 'QuadForm'
sign_from_args(object)

## S4 method for signature 'QuadForm'
dim_from_args(object)

## S4 method for signature 'QuadForm'
is_atom_convex(object)

## S4 method for signature 'QuadForm'
is_atom_concave(object)

## S4 method for signature 'QuadForm'
is_atom_log_log_convex(object)

## S4 method for signature 'QuadForm'
is_atom_log_log_concave(object)

```

```

## S4 method for signature 'QuadForm'
is_incr(object, idx)

## S4 method for signature 'QuadForm'
is_decr(object, idx)

## S4 method for signature 'QuadForm'
is_quadratic(object)

## S4 method for signature 'QuadForm'
is_pwl(object)

## S4 method for signature 'QuadForm'
.grad(object, values)

```

Arguments

x	An Expression or numeric vector.
P	An Expression , numeric matrix, or vector.
object	A QuadForm object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `name(QuadForm)`: The name and arguments of the atom.
- `allow_complex(QuadForm)`: Does the atom handle complex numbers?
- `to_numeric(QuadForm)`: Returns the quadratic form.
- `validate_args(QuadForm)`: Checks the dimensions of the arguments.
- `sign_from_args(QuadForm)`: Returns the sign (is positive, is negative) of the atom.
- `dim_from_args(QuadForm)`: The dimensions of the atom.
- `is_atom_convex(QuadForm)`: Is the atom convex?
- `is_atom_concave(QuadForm)`: Is the atom concave?
- `is_atom_log_log_convex(QuadForm)`: Is the atom log-log convex?
- `is_atom_log_log_concave(QuadForm)`: Is the atom log-log concave?
- `is_incr(QuadForm)`: Is the atom weakly increasing in the argument `idx`?
- `is_decr(QuadForm)`: Is the atom weakly decreasing in the argument `idx`?
- `is_quadratic(QuadForm)`: Is the atom quadratic?
- `is_pwl(QuadForm)`: Is the atom piecewise linear?
- `.grad(QuadForm)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x	An Expression or numeric vector.
P	An Expression , numeric matrix, or vector.

QuadOverLin-class *The QuadOverLin class.*

Description

This class represents the sum of squared entries in X divided by a scalar y, $\sum_{i,j} X_{i,j}^2 / y$.

Usage

```

QuadOverLin(x, y)

## S4 method for signature 'QuadOverLin'
allow_complex(object)

## S4 method for signature 'QuadOverLin'
to_numeric(object, values)

## S4 method for signature 'QuadOverLin'
validate_args(object)

## S4 method for signature 'QuadOverLin'
dim_from_args(object)

## S4 method for signature 'QuadOverLin'
sign_from_args(object)

## S4 method for signature 'QuadOverLin'
is_atom_convex(object)

## S4 method for signature 'QuadOverLin'
is_atom_concave(object)

## S4 method for signature 'QuadOverLin'
is_atom_log_log_convex(object)

## S4 method for signature 'QuadOverLin'
is_atom_log_log_concave(object)

## S4 method for signature 'QuadOverLin'
is_incr(object, idx)

## S4 method for signature 'QuadOverLin'
is_decr(object, idx)

## S4 method for signature 'QuadOverLin'
is_quadratic(object)

```

```

## S4 method for signature 'QuadOverLin'
is_qpwa(object)

## S4 method for signature 'QuadOverLin'
.domain(object)

## S4 method for signature 'QuadOverLin'
.grad(object, values)

```

Arguments

x	An Expression or numeric matrix.
y	A scalar Expression or numeric constant.
object	A QuadOverLin object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `allow_complex(QuadOverLin)`: Does the atom handle complex numbers?
- `to_numeric(QuadOverLin)`: The sum of the entries of x squared over y.
- `validate_args(QuadOverLin)`: Check the dimensions of the arguments.
- `dim_from_args(QuadOverLin)`: The atom is a scalar.
- `sign_from_args(QuadOverLin)`: The atom is positive.
- `is_atom_convex(QuadOverLin)`: The atom is convex.
- `is_atom_concave(QuadOverLin)`: The atom is not concave.
- `is_atom_log_log_convex(QuadOverLin)`: Is the atom log-log convex?
- `is_atom_log_log_concave(QuadOverLin)`: Is the atom log-log concave?
- `is_incr(QuadOverLin)`: A logical value indicating whether the atom is weakly increasing in argument idx.
- `is_decr(QuadOverLin)`: A logical value indicating whether the atom is weakly decreasing in argument idx.
- `is_quadratic(QuadOverLin)`: Quadratic if x is affine and y is constant.
- `is_qpwa(QuadOverLin)`: Quadratic of piecewise affine if x is piecewise linear and y is constant.
- `.domain(QuadOverLin)`: Returns constraints describing the domain of the node
- `.grad(QuadOverLin)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x	An Expression or numeric matrix.
y	A scalar Expression or numeric constant.

quad_form

*Quadratic Form***Description**

The quadratic form, $x^T P x$.

Usage

```
quad_form(x, P)
```

Arguments

x An [Expression](#) or vector.
P An [Expression](#) or matrix.

Value

An [Expression](#) representing the quadratic form evaluated at the input.

Examples

```
x <- Variable(2)
P <- rbind(c(4,0), c(0,9))
prob <- Problem(Minimize(quad_form(x,P)), list(x >= 1))
result <- solve(prob)
result$value
result$getValue(x)

A <- Variable(2,2)
c <- c(1,2)
prob <- Problem(Minimize(quad_form(c,A)), list(A >= 1))
result <- solve(prob)
result$value
result$getValue(A)
```

quad_over_lin

*Quadratic over Linear***Description**

$$\sum_{i,j} X_{i,j}^2 / y.$$
Usage

```
quad_over_lin(x, y)
```

Arguments

- `x` An [Expression](#), vector, or matrix.
- `y` A scalar [Expression](#) or numeric constant.

Value

An [Expression](#) representing the quadratic over linear function value evaluated at the input.

Examples

```
x <- Variable(3,2)
y <- Variable()
val <- cbind(c(-1,2,-2), c(-1,2,-2))
prob <- Problem(Minimize(quad_over_lin(x,y)), list(x == val, y <= 2))
result <- solve(prob)
result$value
result$getValue(x)
result$getValue(y)
```

Rdict-class

The Rdict class.

Description

A simple, internal dictionary composed of a list of keys and a list of values. These keys/values can be any type, including nested lists, S4 objects, etc. Incredibly inefficient hack, but necessary for the geometric mean atom, since it requires mixed numeric/gmp objects.

Usage

```
Rdict(keys = list(), values = list())

## S4 method for signature 'Rdict'
x$name

## S4 method for signature 'Rdict'
length(x)

## S4 method for signature 'ANY,Rdict'
is.element(el, set)

## S4 method for signature 'Rdict,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'Rdict,ANY,ANY,ANY'
x[i, j, ...] <- value
```

Arguments

keys	A list of keys.
values	A list of values corresponding to the keys.
x, set	A Rdict object.
name	Either "keys" for a list of keys, "values" for a list of values, or "items" for a list of lists where each nested list is a (key, value) pair.
el	The element to search the dictionary of values for.
i	A key into the dictionary.
j, drop, ...	Unused arguments.
value	The value to assign to key i.

Slots

keys	A list of keys.
values	A list of values corresponding to the keys.

Rdictdefault-class	<i>The Rdictdefault class.</i>
--------------------	--------------------------------

Description

This is a subclass of [Rdict](#) that contains an additional slot for a default function, which assigns a value to an input key. Only partially implemented, but working well enough for the geometric mean. Will be combined with [Rdict](#) later.

Usage

```
Rdictdefault(keys = list(), values = list(), default)

## S4 method for signature 'Rdictdefault,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]
```

Arguments

keys	A list of keys.
values	A list of values corresponding to the keys.
default	A function that takes as input a key and outputs a value to assign to that key.
x	A Rdictdefault object.
i	A key into the dictionary.
j, drop, ...	Unused arguments.

Slots

keys A list of keys.

values A list of values corresponding to the keys.

default A function that takes as input a key and outputs a value to assign to that key.

See Also

[Rdict](#)

Real-class

The Real class.

Description

This class represents the real part of an expression.

Usage

```
Real(expr)
```

```
## S4 method for signature 'Real'
to_numeric(object, values)
```

```
## S4 method for signature 'Real'
dim_from_args(object)
```

```
## S4 method for signature 'Real'
is_imag(object)
```

```
## S4 method for signature 'Real'
is_complex(object)
```

```
## S4 method for signature 'Real'
is_symmetric(object)
```

Arguments

expr An [Expression](#) representing a vector or matrix.

object An [Real](#) object.

values A list of arguments to the atom.

Methods (by generic)

- `to_numeric(Real)`: The imaginary part of the given value.
- `dim_from_args(Real)`: The dimensions of the atom.
- `is_imag(Real)`: Is the atom imaginary?
- `is_complex(Real)`: Is the atom complex valued?
- `is_symmetric(Real)`: Is the atom symmetric?

Slots

`expr` An [Expression](#) representing a vector or matrix.

reduce	<i>Reduce a Problem</i>
--------	-------------------------

Description

Reduces the owned problem to an equivalent problem.

Usage

`reduce(object)`

Arguments

`object` A [Reduction](#) object.

Value

An equivalent problem, encoded either as a [Problem](#) object or a list.

Reduction-class	<i>The Reduction class.</i>
-----------------	-----------------------------

Description

This virtual class represents a reduction, an actor that transforms a problem into an equivalent problem. By equivalent, we mean that there exists a mapping between solutions of either problem: if we reduce a problem *A* to another problem *B* and then proceed to find a solution to *B*, we can convert it to a solution of *A* with at most a moderate amount of effort.

Usage

```
## S4 method for signature 'Reduction,Problem'
accepts(object, problem)

## S4 method for signature 'Reduction'
reduce(object)

## S4 method for signature 'Reduction,Solution'
retrieve(object, solution)

## S4 method for signature 'Reduction,Problem'
perform(object, problem)

## S4 method for signature 'Reduction,Solution,list'
invert(object, solution, inverse_data)
```

Arguments

object	A Reduction object.
problem	A Problem object.
solution	A Solution to a problem that generated the inverse data.
inverse_data	The data encoding the original problem.

Details

Every reduction supports three methods: `accepts`, `perform`, and `invert`. The `accepts` method of a particular reduction codifies the types of problems that it is applicable to, the `perform` method takes a problem and reduces it to a (new) equivalent form, and the `invert` method maps solutions from reduced-to problems to their problems of provenance.

Methods (by generic)

- `accepts(object = Reduction, problem = Problem)`: States whether the reduction accepts a problem.
- `reduce(Reduction)`: Reduces the owned problem to an equivalent problem.
- `retrieve(object = Reduction, solution = Solution)`: Retrieves a solution to the owned problem.
- `perform(object = Reduction, problem = Problem)`: Performs the reduction on a problem and returns an equivalent problem.
- `invert(object = Reduction, solution = Solution, inverse_data = list)`: Returns a solution to the original problem given the inverse data.

ReductionSolver-class *The ReductionSolver class.*

Description

The ReductionSolver class.

Usage

```
## S4 method for signature 'ReductionSolver'
mip_capable(solver)

## S4 method for signature 'ReductionSolver'
name(x)

## S4 method for signature 'ReductionSolver'
import_solver(solver)

## S4 method for signature 'ReductionSolver'
is_installed(solver)

## S4 method for signature 'ReductionSolver'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

## S4 method for signature 'ReductionSolver,ANY'
reduction_solve(
  object,
  problem,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts
)
```

```

## S4 method for signature 'ECOS'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A ReductionSolver object.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	An integer number indicating level of solver verbosity.
feastol	The feasible tolerance on the primal and dual residual.
reltol	The relative tolerance on the duality gap.
abstol	The absolute tolerance on the duality gap.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.
problem	A Problem object.

Methods (by generic)

- `mip_capable(ReductionSolver)`: Can the solver handle mixed-integer programs?
- `name(ReductionSolver)`: Returns the name of the solver
- `import_solver(ReductionSolver)`: Imports the solver
- `is_installed(ReductionSolver)`: Is the solver installed?
- `solve_via_data(ReductionSolver)`: Solve a problem represented by data returned from `apply`.
- `reduction_solve(object = ReductionSolver, problem = ANY)`: Solve a problem represented by data returned from `apply`.
- `solve_via_data(ECOS)`: Solve a problem represented by data returned from `apply`.

resetOptions	<i>Reset Options</i>
--------------	----------------------

Description

Reset the global package variable `.CVXR.options`.

Usage

```
resetOptions()
```

Value

The default value of CVXR package global `.CVXR.options`.

Examples

```
## Not run:
  resetOptions()

## End(Not run)
```

Reshape-class	<i>The Reshape class.</i>
---------------	---------------------------

Description

This class represents the reshaping of an expression. The operator vectorizes the expression, then unvectorizes it into the new dimensions. Entries are stored in column-major order.

Usage

```
Reshape(expr, new_dim)

## S4 method for signature 'Reshape'
to_numeric(object, values)

## S4 method for signature 'Reshape'
validate_args(object)

## S4 method for signature 'Reshape'
dim_from_args(object)

## S4 method for signature 'Reshape'
is_atom_log_log_convex(object)
```

```
## S4 method for signature 'Reshape'
is_atom_log_log_concave(object)

## S4 method for signature 'Reshape'
get_data(object)

## S4 method for signature 'Reshape'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

expr	An Expression or numeric matrix.
new_dim	The new dimensions.
object	A Reshape object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- to_numeric(Reshape): Reshape the value into the specified dimensions.
- validate_args(Reshape): Check the new shape has the same number of entries as the old.
- dim_from_args(Reshape): The c(rows, cols) dimensions of the new expression.
- is_atom_log_log_convex(Reshape): Is the atom log-log convex?
- is_atom_log_log_concave(Reshape): Is the atom log-log concave?
- get_data(Reshape): Returns a list containing the new shape.
- graph_implementation(Reshape): The graph implementation of the atom.

Slots

expr	An Expression or numeric matrix.
new_dim	The new dimensions.

 reshape_expr

Reshape an Expression

Description

This function vectorizes an expression, then unvectorizes it into a new shape. Entries are stored in column-major order.

Usage

```
reshape_expr(expr, new_dim)
```

Arguments

`expr` An [Expression](#), vector, or matrix.

`new_dim` The new dimensions.

Value

An [Expression](#) representing the reshaped input.

Examples

```
x <- Variable(4)
mat <- cbind(c(1,-1), c(2,-2))
vec <- matrix(1:4)
expr <- reshape_expr(x,c(2,2))
obj <- Minimize(sum(mat %*% expr))
prob <- Problem(obj, list(x == vec))
result <- solve(prob)
result$value

A <- Variable(2,2)
c <- 1:4
expr <- reshape_expr(A,c(4,1))
obj <- Minimize(t(expr) %*% c)
constraints <- list(A == cbind(c(-1,-2), c(3,4)))
prob <- Problem(obj, constraints)
result <- solve(prob)
result$value
result$getValue(expr)
result$getValue(reshape_expr(expr,c(2,2)))

C <- Variable(3,2)
expr <- reshape_expr(C,c(2,3))
mat <- rbind(c(1,-1), c(2,-2))
C_mat <- rbind(c(1,4), c(2,5), c(3,6))
obj <- Minimize(sum(mat %*% expr))
prob <- Problem(obj, list(C == C_mat))
result <- solve(prob)
result$value
result$getValue(expr)

a <- Variable()
c <- cbind(c(1,-1), c(2,-2))
expr <- reshape_expr(c * a,c(1,4))
obj <- Minimize(expr %*% (1:4))
prob <- Problem(obj, list(a == 2))
result <- solve(prob)
result$value
```

```
result$getValue(expr)

expr <- reshape_expr(c * a,c(4,1))
obj <- Minimize(t(expr) %*% (1:4))
prob <- Problem(obj, list(a == 2))
result <- solve(prob)
result$value
result$getValue(expr)
```

residual-methods	<i>Constraint Residual</i>
------------------	----------------------------

Description

The residual expression of a constraint, i.e. the amount by which it is violated, and the value of that violation. For instance, if our constraint is $g(x) \leq 0$, the residual is $\max(g(x), 0)$ applied elementwise.

Usage

```
residual(object)

violation(object)
```

Arguments

object A [Constraint](#) object.

Value

A [Expression](#) representing the residual, or the value of this expression.

retrieve	<i>Retrieve Solution</i>
----------	--------------------------

Description

Retrieves a solution to the owned problem.

Usage

```
retrieve(object, solution)
```

Arguments

object A [Reduction](#) object.
solution A [Solution](#) object.

Value

A [Solution](#) to the problem emitted by [reduce](#).

scaled_lower_tri	<i>Utility methods for special handling of semidefinite constraints.</i>
------------------	--

Description

Utility methods for special handling of semidefinite constraints.

Usage

```
scaled_lower_tri(matrix)
```

Arguments

matrix The matrix to get the lower triangular matrix for

Value

The lower triangular part of the matrix, stacked in column-major order

scaled_upper_tri	<i>Utility methods for special handling of semidefinite constraints.</i>
------------------	--

Description

Utility methods for special handling of semidefinite constraints.

Usage

```
scaled_upper_tri(matrix)
```

Arguments

matrix The matrix to get the upper triangular matrix for

Value

The upper triangular part of the matrix, stacked in column-major order

scalene	<i>Scalene Function</i>
---------	-------------------------

Description

The elementwise weighted sum of the positive and negative portions of an expression, $\alpha \max(x_i, 0) - \beta \min(x_i, 0)$. This is equivalent to `alpha*pos(x) + beta*neg(x)`.

Usage

`scalene(x, alpha, beta)`

Arguments

- `x` An [Expression](#), vector, or matrix.
- `alpha` The weight on the positive portion of `x`.
- `beta` The weight on othe negative portion of `x`.

Value

An [Expression](#) representing the scalene function evaluated at the input.

Examples

```
## Not run:
A <- Variable(2,2)
val <- cbind(c(-5,2), c(-3,1))
prob <- Problem(Minimize(scalene(A,2,3)[1,1]), list(A == val))
result <- solve(prob)
result$value
result$getValue(scalene(A, 0.7, 0.3))

## End(Not run)
```

SCS-class	<i>An interface for the SCS solver</i>
-----------	--

Description

An interface for the SCS solver

Usage

```

SCS()

## S4 method for signature 'SCS'
mip_capable(solver)

## S4 method for signature 'SCS'
status_map(solver, status)

## S4 method for signature 'SCS'
name(x)

## S4 method for signature 'SCS'
import_solver(solver)

## S4 method for signature 'SCS'
reduction_format_constr(object, problem, constr, exp_cone_order)

## S4 method for signature 'SCS,Problem'
perform(object, problem)

## S4 method for signature 'SCS,list,list'
invert(object, solution, inverse_data)

## S4 method for signature 'SCS'
solve_via_data(
  object,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts,
  solver_cache
)

```

Arguments

solver, object, x	A SCS object.
status	A status code returned by the solver.
problem	A Problem object.
constr	A Constraint to format.
exp_cone_order	A list indicating how the exponential cone arguments are ordered.
solution	The raw solution returned by the solver.

inverse_data	A list containing data necessary for the inversion.
data	Data generated via an apply call.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance on the primal and dual residual.
reltol	The relative tolerance on the duality gap.
abstol	The absolute tolerance on the duality gap.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
solver_cache	Cache for the solver.

Methods (by generic)

- `mip_capable(SCS)`: Can the solver handle mixed-integer programs?
- `status_map(SCS)`: Converts status returned by SCS solver to its respective CVXPY status.
- `name(SCS)`: Returns the name of the solver
- `import_solver(SCS)`: Imports the solver
- `reduction_format_constr(SCS)`: Return a linear operator to multiply by PSD constraint coefficients.
- `perform(object = SCS, problem = Problem)`: Returns a new problem and data for inverting the new solution
- `invert(object = SCS, solution = list, inverse_data = list)`: Returns the solution to the original problem given the inverse_data.
- `solve_via_data(SCS)`: Solve a problem represented by data returned from apply.

SCS.dims_to_solver_dict

Utility method for formatting a ConeDims instance into a dictionary that can be supplied to SCS.

Description

Utility method for formatting a ConeDims instance into a dictionary that can be supplied to SCS.

Usage

```
SCS.dims_to_solver_dict(cone_dims)
```

Arguments

cone_dims A [ConeDims](#) instance.

Value

The dimensions of the cones.

SCS.extract_dual_value
<i>Extracts the dual value for constraint starting at offset.</i>

Description

Special cases PSD constraints, as per the SCS specification.

Usage

SCS.extract_dual_value(result_vec, offset, constraint)

Arguments

- result_vec The vector to extract dual values from.
- offset The starting point of the vector to extract from.
- constraint A [Constraint](#) object.

Value

The dual values for the corresponding PSD constraints

setIdCounter	<i>Set ID Counter</i>
--------------	-----------------------

Description

Set the CVXR variable/constraint identification number counter.

Usage

setIdCounter(value = 0L)

Arguments

- value The value to assign as ID.

Value

the changed value of the package global `.CVXR.options`.

Examples

```
## Not run:
  setIdCounter(value = 0L)

## End(Not run)
```

SigmaMax-class	<i>The SigmaMax class.</i>
----------------	----------------------------

Description

The maximum singular value of a matrix.

Usage

```
SigmaMax(A = A)

## S4 method for signature 'SigmaMax'
to_numeric(object, values)

## S4 method for signature 'SigmaMax'
allow_complex(object)

## S4 method for signature 'SigmaMax'
dim_from_args(object)

## S4 method for signature 'SigmaMax'
sign_from_args(object)

## S4 method for signature 'SigmaMax'
is_atom_convex(object)

## S4 method for signature 'SigmaMax'
is_atom_concave(object)

## S4 method for signature 'SigmaMax'
is_incr(object, idx)

## S4 method for signature 'SigmaMax'
is_decr(object, idx)

## S4 method for signature 'SigmaMax'
.grad(object, values)
```

Arguments

A	An Expression or matrix.
object	A SigmaMax object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(SigmaMax)`: The largest singular value of A.
- `allow_complex(SigmaMax)`: Does the atom handle complex numbers?
- `dim_from_args(SigmaMax)`: The atom is a scalar.
- `sign_from_args(SigmaMax)`: The atom is positive.
- `is_atom_convex(SigmaMax)`: The atom is convex.
- `is_atom_concave(SigmaMax)`: The atom is concave.
- `is_incr(SigmaMax)`: The atom is not monotonic in any argument.
- `is_decr(SigmaMax)`: The atom is not monotonic in any argument.
- `.grad(SigmaMax)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

A An [Expression](#) or numeric matrix.

sigma_max

*Maximum Singular Value***Description**

The maximum singular value of a matrix.

Usage

```
sigma_max(A = A)
```

Arguments

A An [Expression](#) or matrix.

Value

An [Expression](#) representing the maximum singular value.

Examples

```
C <- Variable(3,2)
val <- rbind(c(1,2), c(3,4), c(5,6))
obj <- sigma_max(C)
constr <- list(C == val)
prob <- Problem(Minimize(obj), constr)
result <- solve(prob, solver = "SCS")
result$value
result$getValue(C)
```

sign, Expression-method
<i>Sign of Expression</i>

Description

The sign of an expression.

Usage

```
## S4 method for signature 'Expression'
sign(x)
```

Arguments

x An [Expression](#) object.

Value

A string indicating the sign of the expression, either "ZERO", "NONNEGATIVE", "NONPOSITIVE", or "UNKNOWN".

sign-methods	<i>Sign Properties</i>
--------------	------------------------

Description

Determine if an expression is positive, negative, or zero.

Usage

```
is_zero(object)
is_nonneg(object)
is_nonpos(object)
```

Arguments

object An [Expression](#) object.

Value

A logical value.

Examples

```
pos <- Constant(1)
neg <- Constant(-1)
zero <- Constant(0)
unknown <- Variable()
```

```
is_zero(pos)
is_zero(-zero)
is_zero(unknown)
is_zero(pos + neg)
```

```
is_nonneg(pos + zero)
is_nonneg(pos * neg)
is_nonneg(pos - neg)
is_nonneg(unknown)
```

```
is_nonpos(-pos)
is_nonpos(pos + neg)
is_nonpos(neg * zero)
is_nonpos(neg - pos)
```

sign_from_args

Atom Sign

Description

Determine the sign of an atom based on its arguments.

Usage

```
sign_from_args(object)
```

```
## S4 method for signature 'Atom'
sign_from_args(object)
```

Arguments

object An [Atom](#) object.

Value

A logical vector c(is positive, is negative) indicating the sign of the atom.

size	Size of Expression
Description	
The size of an expression.	
Usage	
size(object)	
## S4 method for signature 'ListORExpr'	
size(object)	
Arguments	
object	An Expression object.
Value	
A vector with two elements c(row, col) representing the dimensions of the expression.	
Examples	
<pre>x <- Variable() y <- Variable(3) z <- Variable(3,2) size(x) size(y) size(z) size(x + y) size(z - x)</pre>	
size-methods	Size Properties

Description

Determine if an expression is a scalar, vector, or matrix.

Usage

```
is_scalar(object)

is_vector(object)

is_matrix(object)
```

Arguments

object An [Expression](#) object.

Value

A logical value.

Examples

```
x <- Variable()
y <- Variable(3)
z <- Variable(3,2)

is_scalar(x)
is_scalar(y)
is_scalar(x + y)

is_vector(x)
is_vector(y)
is_vector(2*z)

is_matrix(x)
is_matrix(y)
is_matrix(z)
is_matrix(z - x)
```

SizeMetrics-class	<i>The SizeMetrics class.</i>
-------------------	-------------------------------

Description

This class contains various metrics regarding the problem size.

Usage

```
SizeMetrics(problem)
```

Arguments

problem A [Problem](#) object.

Slots

num_scalar_variables The number of scalar variables in the problem.

num_scalar_data The number of constants used across all matrices and vectors in the problem. Some constants are not apparent when the problem is constructed. For example, the sum_squares expression is a wrapper for a quad_over_lin expression with a constant 1 in the denominator.

`num_scalar_eq_constr` The number of scalar equality constraints in the problem.
`num_scalar_leq_constr` The number of scalar inequality constraints in the problem.
`max_data_dimension` The longest dimension of any data block constraint or parameter.
`max_big_small_squared` The maximum value of $(\text{big})(\text{small})^2$ over all data blocks of the problem, where (big) is the larger dimension and (small) is the smaller dimension for each data block.

 SOC-class

The SOC class.

Description

This class represents a second-order cone constraint, i.e. $\|x\|_2 \leq t$.

Usage

```

SOC(t, X, axis = 2, id = NA_integer_)

## S4 method for signature 'SOC'
as.character(x)

## S4 method for signature 'SOC'
residual(object)

## S4 method for signature 'SOC'
get_data(object)

## S4 method for signature 'SOC'
format_constr(object, eq_constr, leq_constr, dims, solver)

## S4 method for signature 'SOC'
num_cones(object)

## S4 method for signature 'SOC'
size(object)

## S4 method for signature 'SOC'
cone_sizes(object)

## S4 method for signature 'SOC'
is_dcp(object)

## S4 method for signature 'SOC'
is_dgp(object)

## S4 method for signature 'SOC'
canonicalize(object)
  
```


Arguments

<code>t</code>	The scalar part of the second-order constraint.
<code>X</code>	A matrix whose rows/columns are each a cone.
<code>axis</code>	The dimension along which to slice: 1 indicates rows, and 2 indicates columns. The default is 2.
<code>id</code>	(Optional) A numeric value representing the constraint ID.
<code>x, object</code>	A SOC object.
<code>eq_constr</code>	A list of the equality constraints in the canonical problem.
<code>leq_constr</code>	A list of the inequality constraints in the canonical problem.
<code>dims</code>	A list with the dimensions of the conic constraints.
<code>solver</code>	A string representing the solver to be called.

Methods (by generic)

- `residual(SOC)`: The residual of the second-order constraint.
- `get_data(SOC)`: Information needed to reconstruct the object aside from the args.
- `format_constr(SOC)`: Format SOC constraints as inequalities for the solver.
- `num_cones(SOC)`: The number of elementwise cones.
- `size(SOC)`: The number of entries in the combined cones.
- `cone_sizes(SOC)`: The dimensions of the second-order cones.
- `is_dcp(SOC)`: An SOC constraint is DCP if each of its arguments is affine.
- `is_dgp(SOC)`: Is the constraint DGP?
- `canonicalize(SOC)`: The canonicalization of the constraint.

Slots

<code>t</code>	The scalar part of the second-order constraint.
<code>X</code>	A matrix whose rows/columns are each a cone.
<code>axis</code>	The dimension along which to slice: 1 indicates rows, and 2 indicates columns. The default is 2.

SOCAxis-class

The SOCAxis class.

Description

This class represents a second-order cone constraint for each row/column. It Assumes t is a vector the same length as X 's rows (columns) for `axis == 1 (2)`.

Usage

```

SOCAxis(t, X, axis, id = NA_integer_)

## S4 method for signature 'SOCAxis'
as.character(x)

## S4 method for signature 'SOCAxis'
format_constr(object, eq_constr, leq_constr, dims, solver)

## S4 method for signature 'SOCAxis'
num_cones(object)

## S4 method for signature 'SOCAxis'
cone_sizes(object)

## S4 method for signature 'SOCAxis'
size(object)

```

Arguments

t	The scalar part of the second-order constraint.
X	A matrix whose rows/columns are each a cone.
axis	The dimension across which to take the slice: 1 indicates rows, and 2 indicates columns.
id	(Optional) A numeric value representing the constraint ID.
x, object	A SOCAxis object.
eq_constr	A list of the equality constraints in the canonical problem.
leq_constr	A list of the inequality constraints in the canonical problem.
dims	A list with the dimensions of the conic constraints.
solver	A string representing the solver to be called.

Methods (by generic)

- `format_constr(SOCAxis)`: Format SOC constraints as inequalities for the solver.
- `num_cones(SOCAxis)`: The number of elementwise cones.
- `cone_sizes(SOCAxis)`: The dimensions of a single cone.
- `size(SOCAxis)`: The dimensions of the (elementwise) second-order cones.

Slots

t The scalar part of the second-order constraint.

x_elems A list containing X, a matrix whose rows/columns are each a cone.

axis The dimension across which to take the slice: 1 indicates rows, and 2 indicates columns.

Solution-class	<i>The Solution class.</i>
----------------	----------------------------

Description

This class represents a solution to an optimization problem.

Usage

```
## S4 method for signature 'Solution'
as.character(x)
```

Arguments

x A [Solution](#) object.

SolverStats-class	<i>The SolverStats class.</i>
-------------------	-------------------------------

Description

This class contains the miscellaneous information that is returned by a solver after solving, but that is not captured directly by the [Problem](#) object.

Usage

```
SolverStats(results_dict = list(), solver_name = NA_character_)
```

Arguments

results_dict A list containing the results returned by the solver.
solver_name The name of the solver.

Value

A list containing

solver_name The name of the solver.

solve_time The time (in seconds) it took for the solver to solve the problem.

setup_time The time (in seconds) it took for the solver to set up the problem.

num_iters The number of iterations the solver had to go through to find a solution.

Slots

solver_name The name of the solver.
 solve_time The time (in seconds) it took for the solver to solve the problem.
 setup_time The time (in seconds) it took for the solver to set up the problem.
 num_iters The number of iterations the solver had to go through to find a solution.

SolvingChain-class *The SolvingChain class.*

Description

This class represents a reduction chain that ends with a solver.

Usage

```

## S4 method for signature 'SolvingChain,Chain'
prepend(object, chain)

## S4 method for signature 'SolvingChain,Problem'
reduction_solve(
  object,
  problem,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts
)

## S4 method for signature 'SolvingChain'
reduction_solve_via_data(
  object,
  problem,
  data,
  warm_start,
  verbose,
  feastol,
  reltol,
  abstol,
  num_iter,
  solver_opts
)

```

Arguments

object	A SolvingChain object.
chain	A Chain to prepend.
problem	The problem to solve.
warm_start	A boolean of whether to warm start the solver.
verbose	A boolean of whether to enable solver verbosity.
feastol	The feasible tolerance.
reltol	The relative tolerance.
abstol	The absolute tolerance.
num_iter	The maximum number of iterations.
solver_opts	A list of Solver specific options
data	Data for the solver.

Methods (by generic)

- `prepend(object = SolvingChain, chain = Chain)`: Create and return a new `SolvingChain` by concatenating `chain` with this instance.
- `reduction_solve(object = SolvingChain, problem = Problem)`: Applies each reduction in the chain to the problem, solves it, and then inverts the chain to return a solution of the supplied problem.
- `reduction_solve_via_data(SolvingChain)`: Solves the problem using the data output by the an apply invocation.

sqrt,Expression-method

Square Root

Description

The elementwise square root.

Usage

```
## S4 method for signature 'Expression'
sqrt(x)
```

Arguments

x An [Expression](#).

Value

An [Expression](#) representing the square root of the input. `A <- Variable(2,2) val <- cbind(c(2,4), c(16,1)) prob <- Problem(Maximize(sqrt(A)[1,2]), list(A == val)) result <- solve(prob) result$value`

square, Expression-method
Square

Description

The elementwise square.

Usage

```
## S4 method for signature 'Expression'
square(x)
```

Arguments

x An [Expression](#).

Value

An [Expression](#) representing the square of the input. `A <- Variable(2,2) val <- cbind(c(2,4), c(16,1))`
`prob <- Problem(Minimize(square(A)[1,2]), list(A == val)) result <- solve(prob) result$value`

SumEntries-class *The SumEntries class.*

Description

This class represents the sum of all entries in a vector or matrix.

Usage

```
SumEntries(expr, axis = NA_real_, keepdims = FALSE)

## S4 method for signature 'SumEntries'
to_numeric(object, values)

## S4 method for signature 'SumEntries'
is_atom_log_log_convex(object)

## S4 method for signature 'SumEntries'
is_atom_log_log_concave(object)

## S4 method for signature 'SumEntries'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

expr	An Expression representing a vector or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.
object	A SumEntries object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- to_numeric(SumEntries): Sum the entries along the specified axis.
- is_atom_log_log_convex(SumEntries): Is the atom log-log convex?
- is_atom_log_log_concave(SumEntries): Is the atom log-log concave?
- graph_implementation(SumEntries): The graph implementation of the atom.

Slots

expr	An Expression representing a vector or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.

SumLargest-class	<i>The SumLargest class.</i>
------------------	------------------------------

Description

The sum of the largest k values of a matrix.

Usage

```
SumLargest(x, k)

## S4 method for signature 'SumLargest'
to_numeric(object, values)

## S4 method for signature 'SumLargest'
```

```

validate_args(object)

## S4 method for signature 'SumLargest'
dim_from_args(object)

## S4 method for signature 'SumLargest'
sign_from_args(object)

## S4 method for signature 'SumLargest'
is_atom_convex(object)

## S4 method for signature 'SumLargest'
is_atom_concave(object)

## S4 method for signature 'SumLargest'
is_incr(object, idx)

## S4 method for signature 'SumLargest'
is_decr(object, idx)

## S4 method for signature 'SumLargest'
get_data(object)

## S4 method for signature 'SumLargest'
.grad(object, values)

```

Arguments

x	An Expression or numeric matrix.
k	The number of largest values to sum over.
object	A SumLargest object.
values	A list of numeric values for the arguments
idx	An index into the atom.

Methods (by generic)

- `to_numeric(SumLargest)`: The sum of the k largest entries of the vector or matrix.
- `validate_args(SumLargest)`: Check that k is a positive integer.
- `dim_from_args(SumLargest)`: The atom is a scalar.
- `sign_from_args(SumLargest)`: The sign of the atom.
- `is_atom_convex(SumLargest)`: The atom is convex.
- `is_atom_concave(SumLargest)`: The atom is not concave.
- `is_incr(SumLargest)`: The atom is weakly increasing in every argument.
- `is_decr(SumLargest)`: The atom is not weakly decreasing in any argument.
- `get_data(SumLargest)`: A list containing k.
- `.grad(SumLargest)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

- x An [Expression](#) or numeric matrix.
- k The number of largest values to sum over.

SumSmallest	<i>The SumSmallest atom.</i>
-------------	------------------------------

Description

The sum of the smallest k values of a matrix.

Usage

SumSmallest(x, k)

Arguments

- x An [Expression](#) or numeric matrix.
- k The number of smallest values to sum over.

Value

Sum of the smlalest k values

SumSquares	<i>The SumSquares atom.</i>
------------	-----------------------------

Description

The sum of the squares of the entries.

Usage

SumSquares(expr)

Arguments

- expr An [Expression](#) or numeric matrix.

Value

Sum of the squares of the entries in the expression.

sum_entries

*Sum of Entries***Description**

The sum of entries in a vector or matrix.

Usage

```
sum_entries(expr, axis = NA_real_, keepdims = FALSE)
```

```
## S3 method for class 'Expression'
sum(..., na.rm = FALSE)
```

Arguments

expr	An Expression , vector, or matrix.
axis	(Optional) The dimension across which to apply the function: 1 indicates rows, 2 indicates columns, and NA indicates rows and columns. The default is NA.
keepdims	(Optional) Should dimensions be maintained when applying the atom along an axis? If FALSE, result will be collapsed into an $nx1$ column vector. The default is FALSE.
...	Numeric scalar, vector, matrix, or Expression objects.
na.rm	(Unimplemented) A logical value indicating whether missing values should be removed.

Value

An [Expression](#) representing the sum of the entries of the input.

Examples

```
x <- Variable(2)
prob <- Problem(Minimize(sum_entries(x)), list(t(x) >= matrix(c(1,2), nrow = 1, ncol = 2)))
result <- solve(prob)
result$value
result$getValue(x)

C <- Variable(3,2)
prob <- Problem(Maximize(sum_entries(C)), list(C[2:3,] <= 2, C[1,] == 1))
result <- solve(prob)
result$value
result$getValue(C)

x <- Variable(2)
prob <- Problem(Minimize(sum_entries(x)), list(t(x) >= matrix(c(1,2), nrow = 1, ncol = 2)))
result <- solve(prob)
result$value
```

```

result$getValue(x)

C <- Variable(3,2)
prob <- Problem(Maximize(sum_entries(C)), list(C[2:3,] <= 2, C[1,] == 1))
result <- solve(prob)
result$value
result$getValue(C)

```

sum_largest	<i>Sum of Largest Values</i>
-------------	------------------------------

Description

The sum of the largest k values of a vector or matrix.

Usage

```
sum_largest(x, k)
```

Arguments

x	An Expression , vector, or matrix.
k	The number of largest values to sum over.

Value

An [Expression](#) representing the sum of the largest k values of the input.

Examples

```

set.seed(122)
m <- 300
n <- 9
X <- matrix(stats::rnorm(m*n), nrow = m, ncol = n)
X <- cbind(rep(1,m), X)
b <- c(0, 0.8, 0, 1, 0.2, 0, 0.4, 1, 0, 0.7)
y <- X %*% b + stats::rnorm(m)

beta <- Variable(n+1)
obj <- sum_largest((y - X %*% beta)^2, 100)
prob <- Problem(Minimize(obj))
result <- solve(prob)
result$getValue(beta)

```

sum_smallest	<i>Sum of Smallest Values</i>
--------------	-------------------------------

Description

The sum of the smallest k values of a vector or matrix.

Usage

sum_smallest(x, k)

Arguments

- x An [Expression](#), vector, or matrix.
- k The number of smallest values to sum over.

Value

An [Expression](#) representing the sum of the smallest k values of the input.

Examples

```
set.seed(1323)
m <- 300
n <- 9
X <- matrix(stats::rnorm(m*n), nrow = m, ncol = n)
X <- cbind(rep(1,m), X)
b <- c(0, 0.8, 0, 1, 0.2, 0, 0.4, 1, 0, 0.7)
factor <- 2*rbinom(m, size = 1, prob = 0.8) - 1
y <- factor * (X %*% b) + stats::rnorm(m)

beta <- Variable(n+1)
obj <- sum_smallest(y - X %*% beta, 200)
prob <- Problem(Maximize(obj), list(0 <= beta, beta <= 1))
result <- solve(prob)
result$getValue(beta)
```

sum_squares	<i>Sum of Squares</i>
-------------	-----------------------

Description

The sum of the squared entries in a vector or matrix.

Usage

sum_squares(expr)

Arguments

expr An [Expression](#), vector, or matrix.

Value

An [Expression](#) representing the sum of squares of the input.

Examples

```
set.seed(212)
m <- 30
n <- 20
A <- matrix(stats::rnorm(m*n), nrow = m, ncol = n)
b <- matrix(stats::rnorm(m), nrow = m, ncol = 1)

x <- Variable(n)
obj <- Minimize(sum_squares(A %*% x - b))
constr <- list(0 <= x, x <= 1)
prob <- Problem(obj, constr)
result <- solve(prob)

result$value
result$getValue(x)
result$getDualValue(constr[[1]])
```

SymbolicQuadForm-class

The SymbolicQuadForm class.

Description

The SymbolicQuadForm class.

Usage

```
SymbolicQuadForm(x, P, expr)

## S4 method for signature 'SymbolicQuadForm'
dim_from_args(object)

## S4 method for signature 'SymbolicQuadForm'
sign_from_args(object)

## S4 method for signature 'SymbolicQuadForm'
get_data(object)

## S4 method for signature 'SymbolicQuadForm'
is_atom_convex(object)
```

```

## S4 method for signature 'SymbolicQuadForm'
is_atom_concave(object)

## S4 method for signature 'SymbolicQuadForm'
is_incr(object, idx)

## S4 method for signature 'SymbolicQuadForm'
is_decr(object, idx)

## S4 method for signature 'SymbolicQuadForm'
is_quadratic(object)

## S4 method for signature 'SymbolicQuadForm'
.grad(object, values)

```

Arguments

x	An Expression or numeric vector.
P	An Expression , numeric matrix, or vector.
expr	The original Expression .
object	A SymbolicQuadForm object.
idx	An index into the atom.
values	A list of numeric values for the arguments

Methods (by generic)

- `dim_from_args(SymbolicQuadForm)`: The dimensions of the atom.
- `sign_from_args(SymbolicQuadForm)`: The sign (is positive, is negative) of the atom.
- `get_data(SymbolicQuadForm)`: The original expression.
- `is_atom_convex(SymbolicQuadForm)`: Is the original expression convex?
- `is_atom_concave(SymbolicQuadForm)`: Is the original expression concave?
- `is_incr(SymbolicQuadForm)`: Is the original expression weakly increasing in argument `idx`?
- `is_decr(SymbolicQuadForm)`: Is the original expression weakly decreasing in argument `idx`?
- `is_quadratic(SymbolicQuadForm)`: The atom is quadratic.
- `.grad(SymbolicQuadForm)`: Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

x An [Expression](#) or numeric vector.
P An [Expression](#), numeric matrix, or vector.
original_expression The original [Expression](#).

t.Expression	<i>Matrix Transpose</i>
--------------	-------------------------

Description

The transpose of a matrix.

Usage

```
## S3 method for class 'Expression'
t(x)

## S4 method for signature 'Expression'
t(x)
```

Arguments

x An [Expression](#) representing a matrix.

Value

An [Expression](#) representing the transposed matrix.

Examples

```
x <- Variable(3, 4)
t(x)
```

TotalVariation	<i>The TotalVariation atom.</i>
----------------	---------------------------------

Description

The total variation of a vector, matrix, or list of matrices. Uses L1 norm of discrete gradients for vectors and L2 norm of discrete gradients for matrices.

Usage

```
TotalVariation(value, ...)
```

Arguments

value An [Expression](#) representing the value to take the total variation of.
... Additional matrices extending the third dimension of value.

Value

An expression representing the total variation.

to_numeric	<i>Numeric Value of Atom</i>
------------	------------------------------

Description

Returns the numeric value of the atom evaluated on the specified arguments.

Usage

```
to_numeric(object, values)
```

Arguments

- object An [Atom](#) object.
- values A list of arguments to the atom.

Value

A numeric scalar, vector, or matrix.

Trace-class	<i>The Trace class.</i>
-------------	-------------------------

Description

This class represents the sum of the diagonal entries in a matrix.

Usage

```
Trace(expr)

## S4 method for signature 'Trace'
to_numeric(object, values)

## S4 method for signature 'Trace'
validate_args(object)

## S4 method for signature 'Trace'
dim_from_args(object)

## S4 method for signature 'Trace'
is_atom_log_log_convex(object)

## S4 method for signature 'Trace'
is_atom_log_log_concave(object)

## S4 method for signature 'Trace'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```


Arguments

expr	An Expression representing a matrix.
object	A Trace object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- to_numeric(Trace): Sum the diagonal entries.
- validate_args(Trace): Check the argument is a square matrix.
- dim_from_args(Trace): The atom is a scalar.
- is_atom_log_log_convex(Trace): Is the atom log-log convex?
- is_atom_log_log_concave(Trace): Is the atom log-log concave?
- graph_implementation(Trace): The graph implementation of the atom.

Slots

expr An [Expression](#) representing a matrix.

Transpose-class	<i>The Transpose class.</i>
-----------------	-----------------------------

Description

This class represents the matrix transpose.

Usage

```
## S4 method for signature 'Transpose'
to_numeric(object, values)

## S4 method for signature 'Transpose'
is_symmetric(object)

## S4 method for signature 'Transpose'
is_hermitian(object)

## S4 method for signature 'Transpose'
dim_from_args(object)

## S4 method for signature 'Transpose'
is_atom_log_log_convex(object)
```

```
## S4 method for signature 'Transpose'
is_atom_log_log_concave(object)

## S4 method for signature 'Transpose'
get_data(object)

## S4 method for signature 'Transpose'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

object	A Transpose object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- to_numeric(Transpose): The transpose of the given value.
- is_symmetric(Transpose): Is the expression symmetric?
- is_hermitian(Transpose): Is the expression hermitian?
- dim_from_args(Transpose): The dimensions of the atom.
- is_atom_log_log_convex(Transpose): Is the atom log-log convex?
- is_atom_log_log_concave(Transpose): Is the atom log-log concave?
- get_data(Transpose): Returns the axes for transposition.
- graph_implementation(Transpose): The graph implementation of the atom.

triu_to_full	<i>Expands upper triangular to full matrix.</i>
--------------	---

Description

Expands upper triangular to full matrix.

Usage

```
triu_to_full(upper_tri, n)
```

Arguments

upper_tri	A matrix representing the uppertriangular part of the matrix, stacked in column-major order
n	The number of rows (columns) in the full square matrix.

Value

A matrix that is the scaled expansion of the upper triangular matrix.

tri_to_full	<i>Expands lower triangular to full matrix.</i>
-------------	---

Description

Expands lower triangular to full matrix.

Usage

```
tri_to_full(lower_tri, n)
```

Arguments

- | | |
|-----------|--|
| lower_tri | A matrix representing the lower triangular part of the matrix, stacked in column-major order |
| n | The number of rows (columns) in the full square matrix. |

Value

A matrix that is the scaled expansion of the lower triangular matrix.

tv	<i>Total Variation</i>
----	------------------------

Description

The total variation of a vector, matrix, or list of matrices. Uses L1 norm of discrete gradients for vectors and L2 norm of discrete gradients for matrices.

Usage

```
tv(value, ...)
```

Arguments

- | | |
|-------|--|
| value | An Expression , vector, or matrix. |
| ... | (Optional) Expression objects or numeric constants that extend the third dimension of value. |

Value

An [Expression](#) representing the total variation of the input.

Examples

```

rows <- 10
cols <- 10
Uorig <- matrix(sample(0:255, size = rows * cols, replace = TRUE), nrow = rows, ncol = cols)

# Known is 1 if the pixel is known, 0 if the pixel was corrupted
Known <- matrix(0, nrow = rows, ncol = cols)
for(i in 1:rows) {
  for(j in 1:cols) {
    if(stats::runif(1) > 0.7)
      Known[i,j] <- 1
  }
}
Ucorr <- Known %**% Uorig

# Recover the original image using total variation in-painting
U <- Variable(rows, cols)
obj <- Minimize(tv(U))
constraints <- list(Known * U == Known * Ucorr)
prob <- Problem(obj, constraints)
result <- solve(prob, solver = "SCS")
result$getValue(U)

```

UnaryOperator-class *The UnaryOperator class.*

Description

This base class represents expressions involving unary operators.

Usage

```

## S4 method for signature 'UnaryOperator'
name(x)

## S4 method for signature 'UnaryOperator'
to_numeric(object, values)

```

Arguments

x, object	A UnaryOperator object.
values	A list of arguments to the atom.

Methods (by generic)

- `name(UnaryOperator)`: Returns the expression in string form.
- `to_numeric(UnaryOperator)`: Applies the unary operator to the value.

Slots

- expr The [Expression](#) that is being operated upon.
- op_name A character string indicating the unary operation.

unpack_results	<i>Parse output from a solver and updates problem state</i>
----------------	---

Description

Updates problem status, problem value, and primal and dual variable values

Usage

unpack_results(object, solution, chain, inverse_data)

Arguments

- object A [Problem](#) object.
- solution A [Solution](#) object.
- chain The corresponding solving [Chain](#).
- inverse_data A [InverseData](#) object or list containing data necessary for the inversion.

Value

A list containing the solution to the problem:

- status The status of the solution. Can be "optimal", "optimal_inaccurate", "infeasible", "infeasible_inaccurate", "unbounded", "unbounded_inaccurate", or "solver_error".
- value The optimal value of the objective function.
- solver The name of the solver.
- solve_time The time (in seconds) it took for the solver to solve the problem.
- setup_time The time (in seconds) it took for the solver to set up the problem.
- num_iters The number of iterations the solver had to go through to find a solution.
- getValue A function that takes a [Variable](#) object and retrieves its primal value.
- getDualValue A function that takes a [Constraint](#) object and retrieves its dual value(s).

Examples

```
## Not run:
x <- Variable(2)
obj <- Minimize(x[1] + cvxr_norm(x, 1))
constraints <- list(x >= 2)
prob1 <- Problem(obj, constraints)
# Solve with ECOS.
ecos_data <- get_problem_data(prob1, "ECOS")
# Call ECOS solver interface directly
ecos_output <- ECOSolver::ECOS_solve(
  c = ecos_data[["c"]],
  G = ecos_data[["G"]],
  h = ecos_data[["h"]],
  dims = ecos_data[["dims"]],
  A = ecos_data[["A"]],
  b = ecos_data[["b"]]
)
# Unpack raw solver output.
res1 <- unpack_results(prob1, "ECOS", ecos_output)
# Without DCP validation (so be sure of your math), above is equivalent to:
# res1 <- solve(prob1, solver = "ECOS")
X <- Variable(2,2, PSD = TRUE)
Fmat <- rbind(c(1,0), c(0,-1))
obj <- Minimize(sum_squares(X - Fmat))
prob2 <- Problem(obj)
scs_data <- get_problem_data(prob2, "SCS")
scs_output <- scs::scs(
  A = scs_data[["A"]],
  b = scs_data[["b"]],
  obj = scs_data[["c"]],
  cone = scs_data[["dims"]]
)
res2 <- unpack_results(prob2, "SCS", scs_output)
# Without DCP validation (so be sure of your math), above is equivalent to:
# res2 <- solve(prob2, solver = "SCS")

## End(Not run)
```

updated_scaled_lower_tri

Utility methods for special handling of semidefinite constraints.

Description

Utility methods for special handling of semidefinite constraints.

Usage

```
updated_scaled_lower_tri(matrix)
```

Arguments

matrix The matrix to get the lower triangular matrix for

Value

The lower triangular part of the matrix, stacked in column-major order

UpperTri-class	<i>The UpperTri class.</i>
----------------	----------------------------

Description

The vectorized strictly upper triangular entries of a matrix.

Usage

```
UpperTri(expr)

## S4 method for signature 'UpperTri'
to_numeric(object, values)

## S4 method for signature 'UpperTri'
validate_args(object)

## S4 method for signature 'UpperTri'
dim_from_args(object)

## S4 method for signature 'UpperTri'
is_atom_log_log_convex(object)

## S4 method for signature 'UpperTri'
is_atom_log_log_concave(object)

## S4 method for signature 'UpperTri'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

expr An [Expression](#) or numeric matrix.

object An [UpperTri](#) object.

values A list of arguments to the atom.

arg_objs A list of linear expressions for each argument.

dim A vector representing the dimensions of the resulting expression.

data A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(UpperTri)`: Vectorize the upper triangular entries.
- `validate_args(UpperTri)`: Check the argument is a square matrix.
- `dim_from_args(UpperTri)`: The dimensions of the atom.
- `is_atom_log_log_convex(UpperTri)`: Is the atom log-log convex?
- `is_atom_log_log_concave(UpperTri)`: Is the atom log-log concave?
- `graph_implementation(UpperTri)`: The graph implementation of the atom.

Slots

`expr` An [Expression](#) or numeric matrix.

<code>upper_tri</code>	<i>Upper Triangle of a Matrix</i>
------------------------	-----------------------------------

Description

The vectorized strictly upper triangular entries of a matrix.

Usage

`upper_tri(expr)`

Arguments

`expr` An [Expression](#) or matrix.

Value

An [Expression](#) representing the upper triangle of the input.

Examples

```
C <- Variable(3,3)
val <- cbind(3:5, 6:8, 9:11)
prob <- Problem(Maximize(upper_tri(C)[3,1]), list(C == val))
result <- solve(prob)
result$value
result$getValue(upper_tri(C))
```

validate_args	<i>Validate Arguments</i>
---------------	---------------------------

Description

Validate an atom's arguments, returning an error if any are invalid.

Usage

```
validate_args(object)
```

Arguments

object	An Atom object.
--------	---------------------------------

validate_val	<i>Validate Value</i>
--------------	-----------------------

Description

Check that the value satisfies a [Leaf](#)'s symbolic attributes.

Usage

```
validate_val(object, val)
```

Arguments

object	A Leaf object.
val	The assigned value.

Value

The value converted to proper matrix type.

value-methods	<i>Get or Set Value</i>
---------------	-------------------------

Description

Get or set the value of a variable, parameter, expression, or problem.

Usage

```
value(object)

value(object) <- value
```

Arguments

- object A [Variable](#), [Parameter](#), [Expression](#), or [Problem](#) object.
- value A numeric scalar, vector, or matrix to assign to the object.

Value

The numeric value of the variable, parameter, or expression. If any part of the mathematical object is unknown, return NA.

Examples

```
lambda <- Parameter()
value(lambda)

value(lambda) <- 5
value(lambda)
```

Variable-class	<i>The Variable class.</i>
----------------	----------------------------

Description

This class represents an optimization variable.

Usage

```
Variable(rows = NULL, cols = NULL, name = NA_character_, ...)

## S4 method for signature 'Variable'
as.character(x)

## S4 method for signature 'Variable'
```

```

name(x)

## S4 method for signature 'Variable'
value(object)

## S4 method for signature 'Variable'
grad(object)

## S4 method for signature 'Variable'
variables(object)

## S4 method for signature 'Variable'
canonicalize(object)

```

Arguments

rows	The number of rows in the variable.
cols	The number of columns in the variable.
name	(Optional) A character string representing the name of the variable.
...	(Optional) Additional attribute arguments. See Leaf for details.
x, object	A Variable object.

Methods (by generic)

- `name(Variable)`: The name of the variable.
- `value(Variable)`: Get the value of the variable.
- `grad(Variable)`: The sub/super-gradient of the variable represented as a sparse matrix.
- `variables(Variable)`: Returns itself as a variable.
- `canonicalize(Variable)`: The canonical form of the variable.

Slots

`dim` The dimensions of the variable.

`name` (Optional) A character string representing the name of the variable.

Examples

```

x <- Variable(3, name = "x0") ## 3-int variable
y <- Variable(3, 3, name = "y0") # Matrix variable
as.character(y)
id(y)
is_nonneg(x)
is_nonpos(x)
size(y)
name(y)
value(y) <- matrix(1:9, nrow = 3)
value(y)

```

```
grad(y)
variables(y)
canonicalize(y)
```

vec	<i>Vectorization of a Matrix</i>
-----	----------------------------------

Description

Flattens a matrix into a vector in column-major order.

Usage

```
vec(X)
```

Arguments

X An [Expression](#) or matrix.

Value

An [Expression](#) representing the vectorized matrix.

Examples

```
A <- Variable(2,2)
c <- 1:4
expr <- vec(A)
obj <- Minimize(t(expr) %**% c)
constraints <- list(A == cbind(c(-1,-2), c(3,4)))
prob <- Problem(obj, constraints)
result <- solve(prob)
result$value
result$getValue(expr)
```

vectorized_lower_tri_to_mat	<i>Turns symmetric 2D array into a lower triangular matrix</i>
-----------------------------	--

Description

Turns symmetric 2D array into a lower triangular matrix

Usage

```
vectorized_lower_tri_to_mat(v, dim)
```

Arguments

- v** A list of length $(\text{dim} * (\text{dim} + 1) / 2)$.
- dim** The number of rows (equivalently, columns) in the output array.

Value

Return the symmetric 2D array defined by taking "v" to specify its lower triangular matrix.

vstack	<i>Vertical Concatenation</i>
--------	-------------------------------

Description

The vertical concatenation of expressions. This is equivalent to `rbind` when applied to objects with the same number of columns.

Usage

```
vstack(...)
```

Arguments

- ...** [Expression](#) objects, vectors, or matrices. All arguments must have the same number of columns.

Value

An [Expression](#) representing the concatenated inputs.

Examples

```
x <- Variable(2)
y <- Variable(3)
c <- matrix(1, nrow = 1, ncol = 5)
prob <- Problem(Minimize(c %*% vstack(x, y)), list(x == c(1,2), y == c(3,4,5)))
result <- solve(prob)
result$value

c <- matrix(1, nrow = 1, ncol = 4)
prob <- Problem(Minimize(c %*% vstack(x, x)), list(x == c(1,2)))
result <- solve(prob)
result$value

A <- Variable(2,2)
C <- Variable(3,2)
c <- matrix(1, nrow = 2, ncol = 2)
prob <- Problem(Minimize(sum(vstack(A, C))), list(A >= 2*c, C == -2))
result <- solve(prob)
result$value
```

```

B <- Variable(2,2)
c <- matrix(1, nrow = 1, ncol = 2)
prob <- Problem(Minimize(sum(vstack(c %%% A, c %%% B))), list(A >= 2, B == -2))
result <- solve(prob)
result$value

```

VStack-class

The VStack class.

Description

Vertical concatenation of values.

Usage

```

VStack(...)

## S4 method for signature 'VStack'
to_numeric(object, values)

## S4 method for signature 'VStack'
validate_args(object)

## S4 method for signature 'VStack'
dim_from_args(object)

## S4 method for signature 'VStack'
is_atom_log_log_convex(object)

## S4 method for signature 'VStack'
is_atom_log_log_concave(object)

## S4 method for signature 'VStack'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

...	Expression objects or matrices. All arguments must have the same number of columns.
object	A VStack object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(VStack)`: Vertically concatenate the values using `rbind`.
- `validate_args(VStack)`: Check all arguments have the same width.
- `dim_from_args(VStack)`: The dimensions of the atom.
- `is_atom_log_log_convex(VStack)`: Is the atom log-log convex?
- `is_atom_log_log_concave(VStack)`: Is the atom log-log concave?
- `graph_implementation(VStack)`: The graph implementation of the atom.

Slots

... [Expression](#) objects or matrices. All arguments must have the same number of columns.

 Wrap-class

The Wrap class.

Description

This virtual class represents a no-op wrapper to assert properties.

Usage

```
## S4 method for signature 'Wrap'
to_numeric(object, values)

## S4 method for signature 'Wrap'
dim_from_args(object)

## S4 method for signature 'Wrap'
is_atom_log_log_convex(object)

## S4 method for signature 'Wrap'
is_atom_log_log_concave(object)

## S4 method for signature 'Wrap'
graph_implementation(object, arg_objs, dim, data = NA_real_)
```

Arguments

<code>object</code>	A Wrap object.
<code>values</code>	A list of arguments to the atom.
<code>arg_objs</code>	A list of linear expressions for each argument.
<code>dim</code>	A vector representing the dimensions of the resulting expression.
<code>data</code>	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(Wrap)`: Returns the input value.
- `dim_from_args(Wrap)`: The dimensions of the atom.
- `is_atom_log_log_convex(Wrap)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Wrap)`: Is the atom log-log concave?
- `graph_implementation(Wrap)`: The graph implementation of the atom.

ZeroConstraint-class *The ZeroConstraint class*

Description

The ZeroConstraint class

Usage

```
## S4 method for signature 'ZeroConstraint'
name(x)

## S4 method for signature 'ZeroConstraint'
dim(x)

## S4 method for signature 'ZeroConstraint'
is_dcp(object)

## S4 method for signature 'ZeroConstraint'
is_dgp(object)

## S4 method for signature 'ZeroConstraint'
residual(object)

## S4 method for signature 'ZeroConstraint'
canonicalize(object)
```

Arguments

`x, object` A [ZeroConstraint](#) object.

Methods (by generic)

- `name(ZeroConstraint)`: The string representation of the constraint.
- `dim(ZeroConstraint)`: The dimensions of the constrained expression.
- `is_dcp(ZeroConstraint)`: Is the constraint DCP?
- `is_dgp(ZeroConstraint)`: Is the constraint DGP?
- `residual(ZeroConstraint)`: The residual of a constraint
- `canonicalize(ZeroConstraint)`: The graph implementation of the object.

[,Expression,index,missing,ANY-method
The SpecialIndex class.

Description

This class represents indexing using logical indexing or a list of indices into a matrix.

Usage

```
## S4 method for signature 'Expression,index,missing,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,missing,index,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,index,index,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,matrix,index,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,index,matrix,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,matrix,matrix,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,matrix,missing,ANY'
x[i, j, ..., drop = TRUE]

SpecialIndex(expr, key)

## S4 method for signature 'SpecialIndex'
name(x)

## S4 method for signature 'SpecialIndex'
is_atom_log_log_convex(object)

## S4 method for signature 'SpecialIndex'
is_atom_log_log_concave(object)

## S4 method for signature 'SpecialIndex'
get_data(object)

## S4 method for signature 'SpecialIndex'
.grad(object)
```

Arguments

x, object	An Index object.
i, j	The row and column indices of the slice.
...	(Unimplemented) Optional arguments.
drop	(Unimplemented) A logical value indicating whether the result should be coerced to the lowest possible dimension.
expr	An Expression representing a vector or matrix.
key	A list containing the start index, end index, and step size of the slice.

Methods (by generic)

- name(SpecialIndex): Returns the index in string form.
- is_atom_log_log_convex(SpecialIndex): Is the atom log-log convex?
- is_atom_log_log_concave(SpecialIndex): Is the atom log-log concave?
- get_data(SpecialIndex): A list containing key.
- .grad(SpecialIndex): Gives the (sub/super)gradient of the atom w.r.t. each variable

Slots

expr An [Expression](#) representing a vector or matrix.
key A list containing the start index, end index, and step size of the slice.

[,Expression,missing,missing,ANY-method
The Index class.

Description

This class represents indexing or slicing into a matrix.

Usage

```
## S4 method for signature 'Expression,missing,missing,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,numeric,missing,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,missing,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'Expression,numeric,numeric,ANY'
x[i, j, ..., drop = TRUE]
```

```

Index(expr, key)

## S4 method for signature 'Index'
to_numeric(object, values)

## S4 method for signature 'Index'
dim_from_args(object)

## S4 method for signature 'Index'
is_atom_log_log_convex(object)

## S4 method for signature 'Index'
is_atom_log_log_concave(object)

## S4 method for signature 'Index'
get_data(object)

## S4 method for signature 'Index'
graph_implementation(object, arg_objs, dim, data = NA_real_)

## S4 method for signature 'SpecialIndex'
to_numeric(object, values)

## S4 method for signature 'SpecialIndex'
dim_from_args(object)

```

Arguments

x	A Expression object.
i, j	The row and column indices of the slice.
...	(Unimplemented) Optional arguments.
drop	(Unimplemented) A logical value indicating whether the result should be coerced to the lowest possible dimension.
expr	An Expression representing a vector or matrix.
key	A list containing the start index, end index, and step size of the slice.
object	An Index object.
values	A list of arguments to the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(Index)`: The index/slice into the given value.
- `dim_from_args(Index)`: The dimensions of the atom.

- `is_atom_log_log_convex(Index)`: Is the atom log-log convex?
- `is_atom_log_log_concave(Index)`: Is the atom log-log concave?
- `get_data(Index)`: A list containing key.
- `graph_implementation(Index)`: The graph implementation of the atom.
- `to_numeric(SpecialIndex)`: The index/slice into the given value.
- `dim_from_args(SpecialIndex)`: The dimensions of the atom.

Slots

`expr` An [Expression](#) representing a vector or matrix.

`key` A list containing the start index, end index, and step size of the slice.

%*%,Expression,Expression-method

The MulExpression class.

Description

This class represents the matrix product of two linear expressions. See [Multiply](#) for the elementwise product.

Usage

```
## S4 method for signature 'Expression,Expression'
x %*% y
```

```
## S4 method for signature 'Expression,ConstVal'
x %*% y
```

```
## S4 method for signature 'ConstVal,Expression'
x %*% y
```

```
## S4 method for signature 'MulExpression'
to_numeric(object, values)
```

```
## S4 method for signature 'MulExpression'
dim_from_args(object)
```

```
## S4 method for signature 'MulExpression'
is_atom_convex(object)
```

```
## S4 method for signature 'MulExpression'
is_atom_concave(object)
```

```
## S4 method for signature 'MulExpression'
```

```

is_atom_log_log_convex(object)

## S4 method for signature 'MulExpression'
is_atom_log_log_concave(object)

## S4 method for signature 'MulExpression'
is_incr(object, idx)

## S4 method for signature 'MulExpression'
is_decr(object, idx)

## S4 method for signature 'MulExpression'
.grad(object, values)

## S4 method for signature 'MulExpression'
graph_implementation(object, arg_objs, dim, data = NA_real_)

```

Arguments

x, y	The Expression objects or numeric constants to multiply.
object	A MulExpression object.
values	A list of numeric values for the arguments
idx	An index into the atom.
arg_objs	A list of linear expressions for each argument.
dim	A vector representing the dimensions of the resulting expression.
data	A list of additional data required by the atom.

Methods (by generic)

- `to_numeric(MulExpression)`: Matrix multiplication.
- `dim_from_args(MulExpression)`: The (row, col) dimensions of the expression.
- `is_atom_convex(MulExpression)`: Multiplication is convex (affine) in its arguments only if one of the arguments is constant.
- `is_atom_concave(MulExpression)`: If the multiplication atom is convex, then it is affine.
- `is_atom_log_log_convex(MulExpression)`: Is the atom log-log convex?
- `is_atom_log_log_concave(MulExpression)`: Is the atom log-log concave?
- `is_incr(MulExpression)`: Is the left-hand expression positive?
- `is_decr(MulExpression)`: Is the left-hand expression negative?
- `.grad(MulExpression)`: Gives the (sub/super)gradient of the atom w.r.t. each variable
- `graph_implementation(MulExpression)`: The graph implementation of the expression.

See Also

[Multiply](#)

%>>%*The PSDConstraint class.*

Description

This class represents the positive semidefinite constraint, $\frac{1}{2}(X + X^T) \succeq 0$, i.e. $z^T(X + X^T)z \geq 0$ for all z .

Usage

```
e1 %>>% e2
```

```
e1 %<<% e2
```

```
## S4 method for signature 'Expression,Expression'
e1 %>>% e2
```

```
## S4 method for signature 'Expression,ConstVal'
e1 %>>% e2
```

```
## S4 method for signature 'ConstVal,Expression'
e1 %>>% e2
```

```
## S4 method for signature 'Expression,Expression'
e1 %<<% e2
```

```
## S4 method for signature 'Expression,ConstVal'
e1 %<<% e2
```

```
## S4 method for signature 'ConstVal,Expression'
e1 %<<% e2
```

```
PSDConstraint(expr, id = NA_integer_)
```

```
## S4 method for signature 'PSDConstraint'
name(x)
```

```
## S4 method for signature 'PSDConstraint'
is_dcp(object)
```

```
## S4 method for signature 'PSDConstraint'
is_dgp(object)
```

```
## S4 method for signature 'PSDConstraint'
residual(object)
```

```
## S4 method for signature 'PSDConstraint'
```

canonicalize(object)

Arguments

e1, e2	The Expression objects or numeric constants to compare.
expr	An Expression , numeric element, vector, or matrix representing X .
id	(Optional) A numeric value representing the constraint ID.
x, object	A PSDConstraint object.

Methods (by generic)

- name(PSDConstraint): The string representation of the constraint.
- is_dcp(PSDConstraint): The constraint is DCP if the left-hand and right-hand expressions are affine.
- is_dgp(PSDConstraint): Is the constraint DGP?
- residual(PSDConstraint): A [Expression](#) representing the residual of the constraint.
- canonicalize(PSDConstraint): The graph implementation of the object. Marks the top level constraint as the dual_holder so the dual value will be saved to the [PSDConstraint](#).

Slots

expr An [Expression](#), numeric element, vector, or matrix representing X .

$\wedge$, Expression, numeric-method
Elementwise Power

Description

Raises each element of the input to the power p . If expr is a CVXR expression, then expr^p is equivalent to `power(expr, p)`.

Usage

```
## S4 method for signature 'Expression,numeric'
e1 ^ e2
```

```
power(x, p, max_denom = 1024)
```

Arguments

e1	An Expression object to exponentiate.
e2	The power of the exponential. Must be a numeric scalar.
x	An Expression , vector, or matrix.
p	A scalar value indicating the exponential power.
max_denom	The maximum denominator considered in forming a rational approximation of p .

Details

For $p = 0$ and $f(x) = 1$, this function is constant and positive. For $p = 1$ and $f(x) = x$, this function is affine, increasing, and the same sign as x . For $p = 2, 4, 8, \dots$ and $f(x) = |x|^p$, this function is convex, positive, with signed monotonicity. For $p < 0$ and $f(x) =$

x^p for $x > 0$

$+\infty$ $x \leq 0$

, this function is convex, decreasing, and positive. For $0 < p < 1$ and $f(x) =$

x^p for $x \geq 0$

$-\infty$ $x < 0$

, this function is concave, increasing, and positive. For $p > 1, p \neq 2, 4, 8, \dots$ and $f(x) =$

x^p for $x \geq 0$

$+\infty$ $x < 0$

, this function is convex, increasing, and positive.

Examples

```
## Not run:
x <- Variable()
prob <- Problem(Minimize(power(x,1.7) + power(x,-2.3) - power(x,0.45)))
result <- solve(prob)
result$value
result$getValue(x)

## End(Not run)
```


Index

- * **data**
 - cdiac, [51](#)
 - dspop, [132](#)
 - dssamp, [132](#)
- *(multiply), [236](#)
- *, ConstVal, Expression-method
 - (*, Expression, Expression-method), [11](#)
- *, Expression, ConstVal-method
 - (*, Expression, Expression-method), [11](#)
- *, Expression, Expression-method, [11](#)
- *, Maximize, numeric-method
 - (Objective-arith), [252](#)
- *, Minimize, numeric-method
 - (Objective-arith), [252](#)
- *, Problem, numeric-method
 - (Problem-arith), [269](#)
- *, numeric, Maximize-method
 - (Objective-arith), [252](#)
- *, numeric, Minimize-method
 - (Objective-arith), [252](#)
- *, numeric, Problem-method
 - (Problem-arith), [269](#)
- +, ConstVal, Expression-method
 - (+, Expression, missing-method), [11](#)
- +, Expression, ConstVal-method
 - (+, Expression, missing-method), [11](#)
- +, Expression, Expression-method
 - (+, Expression, missing-method), [11](#)
- +, Expression, missing-method, [11](#)
- +, Maximize, Maximize-method
 - (Objective-arith), [252](#)
- +, Maximize, Minimize-method
 - (Objective-arith), [252](#)
- +, Minimize, Maximize-method
 - (Objective-arith), [252](#)
- +, Minimize, Minimize-method
 - (Objective-arith), [252](#)
- +, Objective, numeric-method
 - (Objective-arith), [252](#)
- +, Problem, Problem-method
 - (Problem-arith), [269](#)
- +, Problem, missing-method
 - (Problem-arith), [269](#)
- +, Problem, numeric-method
 - (Problem-arith), [269](#)
- +, numeric, Objective-method
 - (Objective-arith), [252](#)
- +, numeric, Problem-method
 - (Problem-arith), [269](#)
- , ConstVal, Expression-method
 - (-, Expression, missing-method), [13](#)
- , Expression, ConstVal-method
 - (-, Expression, missing-method), [13](#)
- , Expression, Expression-method
 - (-, Expression, missing-method), [13](#)
- , Expression, missing-method, [13](#)
- , Maximize, Objective-method
 - (Objective-arith), [252](#)
- , Maximize, missing-method
 - (Objective-arith), [252](#)
- , Minimize, Objective-method
 - (Objective-arith), [252](#)
- , Minimize, missing-method
 - (Objective-arith), [252](#)
- , Objective, Maximize-method
 - (Objective-arith), [252](#)
- , Objective, Minimize-method
 - (Objective-arith), [252](#)
- , Objective, numeric-method
 - (Objective-arith), [252](#)

- , Problem, Problem-method
(Problem-arith), 269
- , Problem, missing-method
(Problem-arith), 269
- , Problem, numeric-method
(Problem-arith), 269
- , numeric, Objective-method
(Objective-arith), 252
- , numeric, Problem-method
(Problem-arith), 269
- .Abs (Abs-class), 37
- .AddExpression
(+, Expression, missing-method),
11
- .CallbackParam (CallbackParam-class), 46
- .Canonicalization
(Canonicalization-class), 48
- .Chain (Chain-class), 52
- .ConeDims (ConeDims-class), 72
- .Conjugate (Conjugate-class), 76
- .Constant (Constant-class), 77
- .Conv (Conv-class), 85
- .CumMax (CumMax-class), 90
- .CumSum (CumSum-class), 92
- .Dcp2Cone (Dcp2Cone-class), 101
- .DgpCanonMethods
(DgpCanonMethods-class), 124
- .DiagMat (DiagMat-class), 125
- .DiagVec (DiagVec-class), 127
- .DivExpression
(/, Expression, Expression-method),
32
- .EliminatePwl (EliminatePwl-class), 137
- .Entr (Entr-class), 143
- .EqConstraint
(==, Expression, Expression-method),
35
- .Exp (Exp-class), 145
- .ExpCone (ExpCone-class), 147
- .EyeMinusInv (EyeMinusInv-class), 154
- .GeoMean (GeoMean-class), 158
- .HStack (HStack-class), 174
- .Huber (Huber-class), 176
- .Imag (Imag-class), 179
- .Index
([, Expression, missing, missing, ANY-method),
346
- .IneqConstraint
(<=, Expression, Expression-method),
33
- .InverseData (InverseData-class), 181
- .KLDiv (KLDiv-class), 186
- .Kron (Kron-class), 188
- .LambdaMax (LambdaMax-class), 190
- .LambdaSumLargest
(LambdaSumLargest-class), 192
- .LinOpVector__new, 16
- .LinOpVector__push_back, 16
- .LinOp__args_push_back, 17
- .LinOp__get_dense_data, 17
- .LinOp__get_id, 18
- .LinOp__get_size, 18
- .LinOp__get_slice, 19
- .LinOp__get_sparse, 19
- .LinOp__get_sparse_data, 20
- .LinOp__get_type, 20
- .LinOp__new, 21
- .LinOp__set_dense_data, 21
- .LinOp__set_size, 21
- .LinOp__set_slice, 22
- .LinOp__set_sparse, 22
- .LinOp__set_sparse_data, 23
- .LinOp__set_type, 23
- .LinOp__size_push_back, 24
- .LinOp__slice_push_back, 24
- .LinOp_at_index, 16
- .Log (Log-class), 202
- .Log1p (Log1p-class), 204
- .LogDet (LogDet-class), 205
- .LogSumExp (LogSumExp-class), 208
- .Logistic (Logistic-class), 207
- .MatrixFrac (MatrixFrac-class), 214
- .MaxElemwise (MaxElemwise-class), 218
- .MaxEntries (MaxEntries-class), 220
- .Maximize (Maximize-class), 222
- .MinElemwise (MinElemwise-class), 226
- .MinEntries (MinEntries-class), 227
- .Minimize (Minimize-class), 229
- .MulExpression
(%*, Expression, Expression-method),
348
- .Multiply (Multiply-class), 236
- .NegExpression
(-, Expression, missing-method),
13
- .NonPosConstraint

- (NonPosConstraint-class), 240
- .NonlinearConstraint
 - (NonlinearConstraint-class), 239
- .Norm1 (Norm1-class), 243
- .NormInf (NormInf-class), 247
- .NormNuc (NormNuc-class), 249
- .Objective (Objective-class), 253
- .OneMinusPos (OneMinusPos-class), 254
- .PSDConstraint (%>>%), 350
- .PSDWrap (PSDWrap-class), 279
- .Parameter (Parameter-class), 258
- .PfEigenvalue (PfEigenvalue-class), 260
- .Pnorm (Pnorm-class), 263
- .Power (Power-class), 266
- .Problem (Problem-class), 270
- .ProblemData__get_I, 26
- .ProblemData__get_J, 27
- .ProblemData__get_V, 27
- .ProblemData__get_const_to_row, 25
- .ProblemData__get_const_vec, 25
- .ProblemData__get_id_to_col, 26
- .ProblemData__new, 28
- .ProblemData__set_I, 29
- .ProblemData__set_J, 30
- .ProblemData__set_V, 31
- .ProblemData__set_const_to_row, 28
- .ProblemData__set_const_vec, 29
- .ProblemData__set_id_to_col, 30
- .ProdEntries (ProdEntries-class), 274
- .Promote (Promote-class), 278
- .Qp2SymbolicQp (Qp2SymbolicQp-class), 284
- .QuadForm (QuadForm-class), 285
- .QuadOverLin (QuadOverLin-class), 287
- .Real (Real-class), 292
- .Reshape (Reshape-class), 297
- .SOC (SOC-class), 312
- .SOCAxis (SOCAxis-class), 313
- .SigmaMax (SigmaMax-class), 306
- .SizeMetrics (SizeMetrics-class), 311
- .Solution (Solution-class), 315
- .SolverStats (SolverStats-class), 315
- .SolvingChain (SolvingChain-class), 316
- .SpecialIndex
 - ([, Expression, index, missing, ANY-method), 345
- .SumEntries (SumEntries-class), 318
- .SumLargest (SumLargest-class), 319
- .SymbolicQuadForm
 - (SymbolicQuadForm-class), 325
- .Trace (Trace-class), 328
- .Transpose (Transpose-class), 329
- .UpperTri (UpperTri-class), 335
- .VStack (VStack-class), 342
- .Variable (Variable-class), 338
- .ZeroConstraint (ZeroConstraint-class), 344
- .axis_grad, AxisAtom-method
 - (AxisAtom-class), 43
- .build_matrix_0, 14
- .build_matrix_1, 15
- .column_grad, AxisAtom-method
 - (AxisAtom-class), 43
- .column_grad, CumMax-method
 - (CumMax-class), 90
- .column_grad, LogSumExp-method
 - (LogSumExp-class), 208
- .column_grad, MaxEntries-method
 - (MaxEntries-class), 220
- .column_grad, MinEntries-method
 - (MinEntries-class), 227
- .column_grad, Norm1-method
 - (Norm1-class), 243
- .column_grad, NormInf-method
 - (NormInf-class), 247
- .column_grad, Pnorm-method
 - (Pnorm-class), 263
- .column_grad, ProdEntries-method
 - (ProdEntries-class), 274
- .decomp_quad, 15
- .domain, Entr-method (Entr-class), 143
- .domain, GeoMean-method (GeoMean-class), 158
- .domain, KLDiv-method (KLDiv-class), 186
- .domain, LambdaMax-method
 - (LambdaMax-class), 190
- .domain, Log-method (Log-class), 202
- .domain, Log1p-method (Log1p-class), 204
- .domain, LogDet-method (LogDet-class), 205
- .domain, MatrixFrac-method
 - (MatrixFrac-class), 214
- .domain, Norm1-method (Norm1-class), 243
- .domain, NormInf-method (NormInf-class), 247

- .domain, Pnorm-method (Pnorm-class), 263
- .domain, Power-method (Power-class), 266
- .domain, QuadOverLin-method
(QuadOverLin-class), 287
- .grad, AffAtom-method (AffAtom-class), 39
- .grad, CumMax-method (CumMax-class), 90
- .grad, CumSum-method (CumSum-class), 92
- .grad, Entr-method (Entr-class), 143
- .grad, Exp-method (Exp-class), 145
- .grad, EyeMinusInv-method
(EyeMinusInv-class), 154
- .grad, GeoMean-method (GeoMean-class),
158
- .grad, Huber-method (Huber-class), 176
- .grad, KLDiv-method (KLDiv-class), 186
- .grad, LambdaMax-method
(LambdaMax-class), 190
- .grad, LambdaSumLargest-method
(LambdaSumLargest-class), 192
- .grad, Log-method (Log-class), 202
- .grad, Log1p-method (Log1p-class), 204
- .grad, LogDet-method (LogDet-class), 205
- .grad, LogSumExp-method
(LogSumExp-class), 208
- .grad, Logistic-method (Logistic-class),
207
- .grad, MatrixFrac-method
(MatrixFrac-class), 214
- .grad, MaxElemwise-method
(MaxElemwise-class), 218
- .grad, MaxEntries-method
(MaxEntries-class), 220
- .grad, MinElemwise-method
(MinElemwise-class), 226
- .grad, MinEntries-method
(MinEntries-class), 227
- .grad, MulExpression-method
(%*, Expression, Expression-method),
348
- .grad, Norm1-method (Norm1-class), 243
- .grad, NormInf-method (NormInf-class),
247
- .grad, NormNuc-method (NormNuc-class),
249
- .grad, OneMinusPos-method
(OneMinusPos-class), 254
- .grad, PfEigenvalue-method
(PfEigenvalue-class), 260
- .grad, Pnorm-method (Pnorm-class), 263
- .grad, Power-method (Power-class), 266
- .grad, ProdEntries-method
(ProdEntries-class), 274
- .grad, QuadForm-method (QuadForm-class),
285
- .grad, QuadOverLin-method
(QuadOverLin-class), 287
- .grad, SigmaMax-method (SigmaMax-class),
306
- .grad, SpecialIndex-method
([, Expression, index, missing, ANY-method),
345
- .grad, SumLargest-method
(SumLargest-class), 319
- .grad, SymbolicQuadForm-method
(SymbolicQuadForm-class), 325
- .p_norm, 31
- /, ConstVal, Expression-method
(/, Expression, Expression-method),
32
- /, Expression, ConstVal-method
(/, Expression, Expression-method),
32
- /, Expression, Expression-method, 32
- /, Objective, numeric-method
(Objective-arith), 252
- /, Problem, numeric-method
(Problem-arith), 269
- <, ConstVal, Expression-method
(<=, Expression, Expression-method),
33
- <, Expression, ConstVal-method
(<=, Expression, Expression-method),
33
- <, Expression, Expression-method
(<=, Expression, Expression-method),
33
- <=, ConstVal, Expression-method
(<=, Expression, Expression-method),
33
- <=, Expression, ConstVal-method
(<=, Expression, Expression-method),
33
- <=, Expression, Expression-method, 33
- ==, ConstVal, Expression-method
(==, Expression, Expression-method),
35

- ==, Expression, ConstVal-method
(==, Expression, Expression-method),
35
- ==, Expression, Expression-method, 35
- >, ConstVal, Expression-method
(<=, Expression, Expression-method),
33
- >, Expression, ConstVal-method
(<=, Expression, Expression-method),
33
- >, Expression, Expression-method
(<=, Expression, Expression-method),
33
- >=, ConstVal, Expression-method
(<=, Expression, Expression-method),
33
- >=, Expression, ConstVal-method
(<=, Expression, Expression-method),
33
- >=, Expression, Expression-method
(<=, Expression, Expression-method),
33
- [, Expression, index, index, ANY-method
([, Expression, index, missing, ANY-method),
345
- [, Expression, index, matrix, ANY-method
([, Expression, index, missing, ANY-method),
345
- [, Expression, index, missing, ANY-method,
345
- [, Expression, matrix, index, ANY-method
([, Expression, index, missing, ANY-method),
345
- [, Expression, matrix, matrix, ANY-method
([, Expression, index, missing, ANY-method),
345
- [, Expression, matrix, missing, ANY-method
([, Expression, index, missing, ANY-method),
345
- [, Expression, missing, index, ANY-method
([, Expression, index, missing, ANY-method),
345
- [, Expression, missing, missing, ANY-method,
346
- [, Expression, missing, numeric, ANY-method
([, Expression, missing, missing, ANY-method),
346
- [, Expression, numeric, missing, ANY-method
([, Expression, missing, missing, ANY-method),
346
- [, Expression, numeric, numeric, ANY-method
([, Expression, missing, missing, ANY-method),
346
- [, Rdict, ANY, ANY, ANY-method
(Rdict-class), 290
- [, Rdictdefault, ANY, ANY, ANY-method
(Rdictdefault-class), 291
- [<-, Rdict, ANY, ANY, ANY-method
(Rdict-class), 290
- \$, DgpCanonMethods-method
(DgpCanonMethods-class), 124
- \$, Rdict-method (Rdict-class), 290
- %*, ConstVal, Expression-method
(%*, Expression, Expression-method),
348
- %*, Expression, ConstVal-method
(%*, Expression, Expression-method),
348
- %*% (>%), 350
- %*%, ConstVal, Expression-method (>%),
350
- %*%, Expression, ConstVal-method (>%),
350
- %*%, Expression, Expression-method
(%*%, Expression, Expression-method),
350
- %*%, ConstVal, Expression-method (>%),
350
- %*%, Expression, ConstVal-method (>%),
350
- %*%, Expression, Expression-method
(%*%, Expression, Expression-method),
350
- %x% (kronecker, Expression, ANY-method),
189
- %*%, Expression, Expression-method, 348
- %>>%, 350
- ^(^, Expression, numeric-method), 351
- ^, Expression, numeric-method, 351
- abs, 38
- Abs (Abs-class), 37
- abs (abs, Expression-method), 36
- abs, Expression-method, 36
- Abs-class, 37
- accepts, 38
- accepts, CBC_CONIC, Problem-method
(CBC_CONIC-class), 49

- accepts, Chain, Problem-method
(Chain-class), [52](#)
- accepts, Complex2Real, Problem-method
(Complex2Real-class), [57](#)
- accepts, ConeMatrixStuffing, Problem-method
(ConeMatrixStuffing-class), [73](#)
- accepts, ConicSolver, Problem-method
(ConicSolver-class), [73](#)
- accepts, ConstantSolver, Problem-method
(ConstantSolver-class), [79](#)
- accepts, CPLEX_CONIC, Problem-method
(CPLEX_CONIC-class), [86](#)
- accepts, CVXOPT, Problem-method
(CVXOPT-class), [98](#)
- accepts, Dcp2Cone, Problem-method
(Dcp2Cone-class), [101](#)
- accepts, Dgp2Dcp, Problem-method
(Dgp2Dcp-class), [111](#)
- accepts, EliminatePwl, Problem-method
(EliminatePwl-class), [137](#)
- accepts, GUROBI_CONIC, Problem-method
(GUROBI_CONIC-class), [169](#)
- accepts, MOSEK, Problem-method
(MOSEK-class), [233](#)
- accepts, QpSolver, Problem-method
(QpSolver-class), [284](#)
- accepts, Reduction, Problem-method
(Reduction-class), [293](#)
- add_to_solver_blacklist
(installed_solvers), [180](#)
- AddExpression, [12](#)
- AddExpression
(+, Expression, missing-method),
[11](#)
- AddExpression-class
(+, Expression, missing-method),
[11](#)
- AffAtom, [40](#)
- AffAtom (AffAtom-class), [39](#)
- AffAtom-class, [39](#)
- allow_complex, Abs-method (Abs-class), [37](#)
- allow_complex, AffAtom-method
(AffAtom-class), [39](#)
- allow_complex, Atom-method (Atom-class),
[41](#)
- allow_complex, LambdaSumLargest-method
(LambdaSumLargest-class), [192](#)
- allow_complex, MatrixFrac-method
(MatrixFrac-class), [214](#)
- allow_complex, Norm1-method
(Norm1-class), [243](#)
- allow_complex, NormInf-method
(NormInf-class), [247](#)
- allow_complex, NormNuc-method
(NormNuc-class), [249](#)
- allow_complex, Pnorm-method
(Pnorm-class), [263](#)
- allow_complex, QuadForm-method
(QuadForm-class), [285](#)
- allow_complex, QuadOverLin-method
(QuadOverLin-class), [287](#)
- allow_complex, SigmaMax-method
(SigmaMax-class), [306](#)
- are_args_affine, [40](#)
- as.character, Chain-method
(Chain-class), [52](#)
- as.character, Constraint-method
(Constraint-class), [81](#)
- as.character, ExpCone-method
(ExpCone-class), [147](#)
- as.character, Expression-method
(Expression-class), [148](#)
- as.character, SOC-method (SOC-class), [312](#)
- as.character, SOCAxis-method
(SOCAxis-class), [313](#)
- as.character, Solution-method
(Solution-class), [315](#)
- as.character, Variable-method
(Variable-class), [338](#)
- as.Constant (Constant-class), [77](#)
- Atom, [42](#), [43](#), [47](#), [95](#), [96](#), [130](#), [153](#), [199](#), [211](#),
[273](#), [309](#), [328](#), [337](#)
- Atom (Atom-class), [41](#)
- Atom-class, [41](#)
- atoms (expression-parts), [152](#)
- atoms, Atom-method (Atom-class), [41](#)
- atoms, Canonical-method
(Canonical-class), [46](#)
- atoms, Leaf-method (Leaf-class), [196](#)
- atoms, Problem-method (Problem-class),
[270](#)
- AxisAtom (AxisAtom-class), [43](#)
- AxisAtom-class, [43](#)
- BinaryOperator, [44](#)
- BinaryOperator (BinaryOperator-class),
[44](#)

- BinaryOperator-class, [44](#)
- block_format, MOSEK-method
(MOSEK-class), [233](#)
- bmat, [45](#)
- CallbackParam, [46](#)
- CallbackParam (CallbackParam-class), [46](#)
- CallbackParam-class, [46](#)
- Canonical, [47](#), [49](#)
- Canonical-class, [46](#)
- canonical_form (canonicalize), [49](#)
- canonical_form, Canonical-method
(Canonical-class), [46](#)
- Canonicalization, [48](#)
- Canonicalization-class, [48](#)
- canonicalize, [49](#)
- canonicalize, Atom-method (Atom-class),
[41](#)
- canonicalize, Constant-method
(Constant-class), [77](#)
- canonicalize, ExpCone-method
(ExpCone-class), [147](#)
- canonicalize, Maximize-method
(Maximize-class), [222](#)
- canonicalize, Minimize-method
(Minimize-class), [229](#)
- canonicalize, NonPosConstraint-method
(NonPosConstraint-class), [240](#)
- canonicalize, Parameter-method
(Parameter-class), [258](#)
- canonicalize, Problem-method
(Problem-class), [270](#)
- canonicalize, PSDConstraint-method
(%>>%), [350](#)
- canonicalize, SOC-method (SOC-class), [312](#)
- canonicalize, Variable-method
(Variable-class), [338](#)
- canonicalize, ZeroConstraint-method
(ZeroConstraint-class), [344](#)
- canonicalize_expr, Canonicalization-method
(Canonicalization-class), [48](#)
- canonicalize_expr, Dgp2Dcp-method
(Dgp2Dcp-class), [111](#)
- canonicalize_tree, Canonicalization-method
(Canonicalization-class), [48](#)
- CBC_CONIC, [50](#)
- CBC_CONIC (CBC_CONIC-class), [49](#)
- CBC_CONIC-class, [49](#)
- cdiac, [51](#)
- Chain, [52](#), [83](#), [272](#), [317](#), [333](#)
- Chain-class, [52](#)
- CLARABEL, [54](#)
- CLARABEL (CLARABEL-class), [53](#)
- CLARABEL-class, [53](#)
- CLARABEL.dims_to_solver_dict, [55](#)
- CLARABEL.extract_dual_value, [55](#)
- complex-atoms, [56](#)
- complex-methods, [56](#)
- Complex2Real, [57](#)
- Complex2Real (Complex2Real-class), [57](#)
- Complex2Real-class, [57](#)
- Complex2Real.abs_canon, [57](#)
- Complex2Real.add, [58](#)
- Complex2Real.at_least_2D, [58](#)
- Complex2Real.binary_canon, [59](#)
- Complex2Real.canonicalize_expr, [59](#)
- Complex2Real.canonicalize_tree, [60](#)
- Complex2Real.conj_canon, [61](#)
- Complex2Real.constant_canon, [61](#)
- Complex2Real.hermitian_canon, [62](#)
- Complex2Real.imag_canon, [62](#)
- Complex2Real.join, [63](#)
- Complex2Real.lambda_sum_largest_canon,
[64](#)
- Complex2Real.matrix_frac_canon, [64](#)
- Complex2Real.nonpos_canon, [65](#)
- Complex2Real.norm_nuc_canon, [65](#)
- Complex2Real.param_canon, [66](#)
- Complex2Real.pnorm_canon, [67](#)
- Complex2Real.psd_canon, [67](#)
- Complex2Real.quad_canon, [68](#)
- Complex2Real.quad_over_lin_canon, [68](#)
- Complex2Real.real_canon, [69](#)
- Complex2Real.separable_canon, [70](#)
- Complex2Real.soc_canon, [70](#)
- Complex2Real.variable_canon, [71](#)
- Complex2Real.zero_canon, [71](#)
- cone-methods, [72](#)
- cone_sizes (cone-methods), [72](#)
- cone_sizes, ExpCone-method
(ExpCone-class), [147](#)
- cone_sizes, SOC-method (SOC-class), [312](#)
- cone_sizes, SOCAxis-method
(SOCAxis-class), [313](#)
- ConeDims, [55](#), [134](#), [304](#)
- ConeDims-class, [72](#)
- ConeMatrixStuffing, [73](#)

- ConeMatrixStuffing
 - (ConeMatrixStuffing-class), 73
- ConeMatrixStuffing-class, 73
- ConicSolver, 74
- ConicSolver (ConicSolver-class), 73
- ConicSolver-class, 73
- ConicSolver.get_coeff_offset, 74
- ConicSolver.get_spacing_matrix, 75
- Conj, Expression-method (complex-atoms), 56
- Conjugate, 76
- Conjugate (Conjugate-class), 76
- Conjugate-class, 76
- Constant, 47, 62, 77, 78, 153, 199, 273
- Constant (Constant-class), 77
- Constant-class, 77
- constants (expression-parts), 152
- constants, Canonical-method
 - (Canonical-class), 46
- constants, Constant-method
 - (Constant-class), 77
- constants, Leaf-method (Leaf-class), 196
- constants, Problem-method
 - (Problem-class), 270
- ConstantSolver, 80
- ConstantSolver (ConstantSolver-class), 79
- ConstantSolver-class, 79
- constr_value, 84
- constr_value, Constraint-method
 - (Constraint-class), 81
- Constraint, 40, 54, 55, 58–72, 74, 82, 84, 101–111, 131, 133, 137–142, 157, 178, 184, 201, 234–236, 272, 282, 300, 303, 305, 333
- Constraint (Constraint-class), 81
- Constraint-class, 81
- constraints (problem-parts), 274
- constraints, Problem-method
 - (Problem-class), 270
- constraints<- (problem-parts), 274
- constraints<- , Problem-method
 - (Problem-class), 270
- construct_intermediate_chain, Problem, list-method, 83
- construct_solving_chain, 83
- Conv, 85
- Conv (Conv-class), 85
- conv, 84
- Conv-class, 85
- copy, AddExpression-method
 - (+, Expression, missing-method), 11
- copy, GeoMean-method (GeoMean-class), 158
- copy, Power-method (Power-class), 266
- CPLEX_CONIC, 87
- CPLEX_CONIC (CPLEX_CONIC-class), 86
- CPLEX_CONIC-class, 86
- CPLEX_QP, 89
- CPLEX_QP (CPLEX_QP-class), 88
- CPLEX_QP-class, 88
- CumMax, 91
- CumMax (CumMax-class), 90
- cummax (cummax_axis), 91
- cummax, Expression-method (cummax_axis), 91
- CumMax-class, 90
- cummax_axis, 91
- CumSum, 92
- CumSum (CumSum-class), 92
- cumsum (cumsum_axis), 93
- cumsum, Expression-method (cumsum_axis), 93
- CumSum-class, 92
- cumsum_axis, 93
- curvature, 94
- curvature, Expression-method
 - (curvature), 94
- curvature-atom, 94
- curvature-comp, 96
- curvature-methods, 96
- CvxAttr2Constr, 98
- CvxAttr2Constr (CvxAttr2Constr-class), 98
- CvxAttr2Constr-class, 98
- CVXOPT, 99
- CVXOPT-class, 98
- cvxr_norm, 100
- Dcp2Cone, 101
- Dcp2Cone-class, 101
- Dcp2Cone.entr_canon, 101
- Dcp2Cone.exp_canon, 102
- Dcp2Cone.geo_mean_canon, 102
- Dcp2Cone.huber_canon, 103
- Dcp2Cone.indicator_canon, 103
- Dcp2Cone.kl_div_canon, 104

- Dcp2Cone.lambda_max_canon, 104
- Dcp2Cone.lambda_sum_largest_canon, 105
- Dcp2Cone.log1p_canon, 105
- Dcp2Cone.log_canon, 106
- Dcp2Cone.log_det_canon, 107
- Dcp2Cone.log_sum_exp_canon, 107
- Dcp2Cone.logistic_canon, 106
- Dcp2Cone.matrix_frac_canon, 108
- Dcp2Cone.normNuc_canon, 108
- Dcp2Cone.pnorm_canon, 109
- Dcp2Cone.power_canon, 109
- Dcp2Cone.quad_form_canon, 110
- Dcp2Cone.quad_over_lin_canon, 110
- Dcp2Cone.sigma_max_canon, 111
- dgCMatrix-class, 20, 23
- Dgp2Dcp, 112
- Dgp2Dcp (Dgp2Dcp-class), 111
- Dgp2Dcp-class, 111
- Dgp2Dcp.add_canon, 112
- Dgp2Dcp.constant_canon, 113
- Dgp2Dcp.div_canon, 113
- Dgp2Dcp.exp_canon, 114
- Dgp2Dcp.eye_minus_inv_canon, 114
- Dgp2Dcp.geo_mean_canon, 115
- Dgp2Dcp.log_canon, 115
- Dgp2Dcp.mul_canon, 116
- Dgp2Dcp.mulexpression_canon, 116
- Dgp2Dcp.nonpos_constr_canon, 117
- Dgp2Dcp.norm1_canon, 117
- Dgp2Dcp.norm_inf_canon, 118
- Dgp2Dcp.one_minus_pos_canon, 118
- Dgp2Dcp.parameter_canon, 119
- Dgp2Dcp.pf_eigenvalue_canon, 119
- Dgp2Dcp.pnorm_canon, 120
- Dgp2Dcp.power_canon, 120
- Dgp2Dcp.prod_canon, 121
- Dgp2Dcp.quad_form_canon, 121
- Dgp2Dcp.quad_over_lin_canon, 122
- Dgp2Dcp.sum_canon, 122
- Dgp2Dcp.trace_canon, 123
- Dgp2Dcp.zero_constr_canon, 123
- DgpCanonMethods, 124
- DgpCanonMethods-class, 124
- Diag, 124
- diag (diag, Expression-method), 125
- diag, Expression-method, 125
- DiagMat, 126
- DiagMat (DiagMat-class), 125
- DiagMat-class, 125
- DiagVec, 127
- DiagVec (DiagVec-class), 127
- DiagVec-class, 127
- Diff, 128
- diff (diff, Expression-method), 129
- diff, Expression-method, 129
- DiffPos, 130
- dim, Atom-method (Atom-class), 41
- dim, Constant-method (Constant-class), 77
- dim, Constraint-method
(Constraint-class), 81
- dim, EqConstraint-method
(=, Expression, Expression-method),
35
- dim, Expression-method
(Expression-class), 148
- dim, IneqConstraint-method
(<=, Expression, Expression-method),
33
- dim, Leaf-method (Leaf-class), 196
- dim, ZeroConstraint-method
(ZeroConstraint-class), 344
- dim_from_args, 130
- dim_from_args, AddExpression-method
(+, Expression, missing-method),
11
- dim_from_args, Atom-method
(dim_from_args), 130
- dim_from_args, AxisAtom-method
(AxisAtom-class), 43
- dim_from_args, Conjugate-method
(Conjugate-class), 76
- dim_from_args, Conv-method (Conv-class),
85
- dim_from_args, CumMax-method
(CumMax-class), 90
- dim_from_args, CumSum-method
(CumSum-class), 92
- dim_from_args, DiagMat-method
(DiagMat-class), 125
- dim_from_args, DiagVec-method
(DiagVec-class), 127
- dim_from_args, DivExpression-method
(/, Expression, Expression-method),
32
- dim_from_args, Elementwise-method
(Elementwise-class), 136

- dim_from_args, EyeMinusInv-method
(EyeMinusInv-class), [154](#)
- dim_from_args, GeoMean-method
(GeoMean-class), [158](#)
- dim_from_args, HStack-method
(HStack-class), [174](#)
- dim_from_args, Imag-method (Imag-class),
[179](#)
- dim_from_args, Index-method
([, Expression, missing, missing, ANY-method),
[346](#)
- dim_from_args, Kron-method (Kron-class),
[188](#)
- dim_from_args, LambdaMax-method
(LambdaMax-class), [190](#)
- dim_from_args, LogDet-method
(LogDet-class), [205](#)
- dim_from_args, MatrixFrac-method
(MatrixFrac-class), [214](#)
- dim_from_args, MulExpression-method
(%*, Expression, Expression-method),
[348](#)
- dim_from_args, Multiply-method
(Multiply-class), [236](#)
- dim_from_args, NegExpression-method
(-, Expression, missing-method),
[13](#)
- dim_from_args, NormNuc-method
(NormNuc-class), [249](#)
- dim_from_args, OneMinusPos-method
(OneMinusPos-class), [254](#)
- dim_from_args, PfEigenvalue-method
(PfEigenvalue-class), [260](#)
- dim_from_args, Promote-method
(Promote-class), [278](#)
- dim_from_args, QuadForm-method
(QuadForm-class), [285](#)
- dim_from_args, QuadOverLin-method
(QuadOverLin-class), [287](#)
- dim_from_args, Real-method (Real-class),
[292](#)
- dim_from_args, Reshape-method
(Reshape-class), [297](#)
- dim_from_args, SigmaMax-method
(SigmaMax-class), [306](#)
- dim_from_args, SpecialIndex-method
([, Expression, missing, missing, ANY-method),
[346](#)
- dim_from_args, SumLargest-method
(SumLargest-class), [319](#)
- dim_from_args, SymbolicQuadForm-method
(SymbolicQuadForm-class), [325](#)
- dim_from_args, Trace-method
(Trace-class), [328](#)
- dim_from_args, Transpose-method
(Transpose-class), [329](#)
- dim_from_args, UpperTri-method
(UpperTri-class), [335](#)
- dim_from_args, VStack-method
(VStack-class), [342](#)
- dim_from_args, Wrap-method (Wrap-class),
[343](#)
- DivExpression, [33](#)
- DivExpression
(/, Expression, Expression-method),
[32](#)
- DivExpression-class
(/, Expression, Expression-method),
[32](#)
- domain, [131](#)
- domain, Atom-method (Atom-class), [41](#)
- domain, Expression-method
(Expression-class), [148](#)
- domain, Leaf-method (Leaf-class), [196](#)
- dspop, [132](#), [132](#)
- dssamp, [132](#), [132](#)
- dual_value (dual_value-methods), [133](#)
- dual_value, Constraint-method
(Constraint-class), [81](#)
- dual_value-methods, [133](#)
- dual_value<- (dual_value-methods), [133](#)
- dual_value<- , Constraint-method
(Constraint-class), [81](#)
- ECOS, [134](#)
- ECOS (ECOS-class), [133](#)
- ECOS-class, [133](#)
- ECOS.dims_to_solver_dict, [134](#)
- ECOS_BB, [135](#)
- ECOS_BB (ECOS_BB-class), [135](#)
- ECOS_BB-class, [135](#)
- Elementwise, [136](#)
- Elementwise (Elementwise-class), [136](#)
- Elementwise-class, [136](#)
- EliminatePwl, [137](#)
- EliminatePwl-class, [137](#)
- EliminatePwl.abs_canon, [137](#)

- EliminatePwl.cummax_canon, 138
- EliminatePwl.cumsum_canon, 138
- EliminatePwl.max_elemwise_canon, 139
- EliminatePwl.max_entries_canon, 139
- EliminatePwl.min_elemwise_canon, 140
- EliminatePwl.min_entries_canon, 140
- EliminatePwl.norm1_canon, 141
- EliminatePwl.norm_inf_canon, 141
- EliminatePwl.sum_largest_canon, 142
- Entr, 143
- Entr (Entr-class), 143
- entr, 142
- Entr-class, 143
- entropy (entr), 142
- EqConstraint, 36
- EqConstraint-class
 - (==, Expression, Expression-method), 35
- EvalParams, 144
- EvalParams (EvalParams-class), 144
- EvalParams-class, 144
- Exp, 146
- Exp (Exp-class), 145
- exp (exp, Expression-method), 145
- exp, Expression-method, 145
- Exp-class, 145
- ExpCone, 147
- ExpCone (ExpCone-class), 147
- ExpCone-class, 147
- expr, Canonical-method
 - (Canonical-class), 46
- expr, EqConstraint-method
 - (==, Expression, Expression-method), 35
- expr, Expression-method
 - (Expression-class), 148
- expr, IneqConstraint-method
 - (<=, Expression, Expression-method), 33
- Expression, 11–14, 33, 35–38, 45, 48, 56, 58–72, 75–78, 84–86, 90–94, 97, 100–131, 137–146, 151, 155, 156, 159–161, 167, 168, 173, 175–179, 182, 183, 186–196, 200, 202–206, 208–213, 215–232, 236–239, 242–246, 249–251, 254–256, 261, 262, 264–266, 268, 269, 275, 276, 278, 279, 282, 283, 286, 288–290, 292, 293, 298–300, 302, 306–308, 310, 311, 317–327, 329, 331, 333, 335, 336, 338, 340–343, 346–349, 351
- Expression (Expression-class), 148
- Expression-class, 148
- expression-parts, 152
- extract_dual_value, 153
- extract_mip_idx, 154
- eye_minus_inv, 156
- EyeMinusInv, 155
- EyeMinusInv (EyeMinusInv-class), 154
- EyeMinusInv-class, 154
- flatten, Expression-method
 - (Expression-class), 148
- FlipObjective, 157
- FlipObjective (FlipObjective-class), 156
- FlipObjective-class, 156
- format_constr, 157
- format_constr, SOC-method (SOC-class), 312
- format_constr, SOCAxis-method
 - (SOCAxis-class), 313
- geo_mean, 160
- GeoMean, 159
- GeoMean (GeoMean-class), 158
- GeoMean-class, 158
- get_data, 161
- get_data, AxisAtom-method
 - (AxisAtom-class), 43
- get_data, Canonical-method
 - (Canonical-class), 46
- get_data, Constraint-method
 - (Constraint-class), 81
- get_data, CumMax-method (CumMax-class), 90
- get_data, CumSum-method (CumSum-class), 92
- get_data, GeoMean-method
 - (GeoMean-class), 158
- get_data, Huber-method (Huber-class), 176
- get_data, Index-method
 - ([, Expression, missing, missing, ANY-method), 346
- get_data, LambdaSumLargest-method
 - (LambdaSumLargest-class), 192
- get_data, Leaf-method (Leaf-class), 196

- get_data, Norm1-method (Norm1-class), 243
- get_data, NormInf-method (NormInf-class), 247
- get_data, Parameter-method (Parameter-class), 258
- get_data, Pnorm-method (Pnorm-class), 263
- get_data, Power-method (Power-class), 266
- get_data, Promote-method (Promote-class), 278
- get_data, Reshape-method (Reshape-class), 297
- get_data, SOC-method (SOC-class), 312
- get_data, SpecialIndex-method ([, Expression, index, missing, ANY-method), 345
- get_data, SumLargest-method (SumLargest-class), 319
- get_data, SymbolicQuadForm-method (SymbolicQuadForm-class), 325
- get_data, Transpose-method (Transpose-class), 329
- get_dual_values, 162
- get_id, 162, 178
- get_np, 163
- get_problem_data, 163
- get_problem_data, Problem, character, logical-method (Problem-class), 270
- get_problem_data, Problem, character, missing-method (Problem-class), 270
- get_sp, 164
- GLPK, 165
- GLPK (GLPK-class), 164
- GLPK-class, 164
- GLPK_MI, 167
- GLPK_MI (GLPK_MI-class), 166
- GLPK_MI-class, 166
- grad, 167
- grad, Atom-method (Atom-class), 41
- grad, Constant-method (Constant-class), 77
- grad, Expression-method (Expression-class), 148
- grad, Parameter-method (Parameter-class), 258
- grad, Variable-method (Variable-class), 338
- graph_implementation, 168
- graph_implementation, AddExpression-method (+, Expression, missing-method), 11
- graph_implementation, Atom-method (Atom-class), 41
- graph_implementation, Conv-method (Conv-class), 85
- graph_implementation, CumSum-method (CumSum-class), 92
- graph_implementation, DiagMat-method (DiagMat-class), 125
- graph_implementation, DiagVec-method (DiagVec-class), 127
- graph_implementation, DivExpression-method (/ , Expression, Expression-method), 32
- graph_implementation, HStack-method (HStack-class), 174
- graph_implementation, Index-method ([, Expression, missing, missing, ANY-method), 346
- graph_implementation, Kron-method (Kron-class), 188
- graph_implementation, MulExpression-method (%*, Expression, Expression-method), 348
- graph_implementation, Multiply-method (Multiply-class), 236
- graph_implementation, NegExpression-method (-, Expression, missing-method), 13
- graph_implementation, Promote-method (Promote-class), 278
- graph_implementation, Reshape-method (Reshape-class), 297
- graph_implementation, SumEntries-method (SumEntries-class), 318
- graph_implementation, Trace-method (Trace-class), 328
- graph_implementation, Transpose-method (Transpose-class), 329
- graph_implementation, UpperTri-method (UpperTri-class), 335
- graph_implementation, VStack-method (VStack-class), 342
- graph_implementation, Wrap-method (Wrap-class), 343
- group_coeff_offset, ConicSolver-method (ConicSolver-class), 73

- group_constraints, 169
- GUROBI_CONIC, 170
- GUROBI_CONIC (GUROBI_CONIC-class), 169
- GUROBI_CONIC-class, 169
- GUROBI_QP, 172
- GUROBI_QP (GUROBI_QP-class), 171
- GUROBI_QP-class, 171
- harmonic_mean, 173
- HarmonicMean, 172
- HStack, 175
- HStack (HStack-class), 174
- hstack, 173
- HStack-class, 174
- Huber, 177
- Huber (Huber-class), 176
- huber, 175
- Huber-class, 176
- id, 178
- id, Canonical-method (Canonical-class), 46
- id, ListORConstr-method (ListORConstr-class), 201
- Im, Expression-method (complex-atoms), 56
- Imag, 179
- Imag (Imag-class), 179
- Imag-class, 179
- import_solver, 180
- import_solver, CBC_CONIC-method (CBC_CONIC-class), 49
- import_solver, CLARABEL-method (CLARABEL-class), 53
- import_solver, ConstantSolver-method (ConstantSolver-class), 79
- import_solver, CPLEX_CONIC-method (CPLEX_CONIC-class), 86
- import_solver, CPLEX_QP-method (CPLEX_QP-class), 88
- import_solver, CVXOPT-method (CVXOPT-class), 98
- import_solver, ECOS-method (ECOS-class), 133
- import_solver, GLPK-method (GLPK-class), 164
- import_solver, GUROBI_CONIC-method (GUROBI_CONIC-class), 169
- import_solver, GUROBI_QP-method (GUROBI_QP-class), 171
- import_solver, MOSEK-method (MOSEK-class), 233
- import_solver, OSQP-method (OSQP-class), 256
- import_solver, ReductionSolver-method (ReductionSolver-class), 295
- import_solver, SCS-method (SCS-class), 302
- Index, 346, 347
- Index
 - ([, Expression, missing, missing, ANY-method), 346
- Index-class
 - ([, Expression, missing, missing, ANY-method), 346
- IneqConstraint, 35
- IneqConstraint-class
 - (<=, Expression, Expression-method), 33
- installed_solvers, 180
- inv_pos, 182
- InverseData, 48, 57, 74, 89, 112, 172, 181, 257, 260, 272, 333
- InverseData-class, 181
- invert, 181
- invert, Canonicalization, Solution, InverseData-method (Canonicalization-class), 48
- invert, CBC_CONIC, list, list-method (CBC_CONIC-class), 49
- invert, Chain, SolutionORList, list-method (Chain-class), 52
- invert, CLARABEL, list, list-method (CLARABEL-class), 53
- invert, Complex2Real, Solution, InverseData-method (Complex2Real-class), 57
- invert, ConicSolver, Solution, InverseData-method (ConicSolver-class), 73
- invert, ConstantSolver, Solution, list-method (ConstantSolver-class), 79
- invert, CPLEX_CONIC, list, list-method (CPLEX_CONIC-class), 86
- invert, CPLEX_QP, list, InverseData-method (CPLEX_QP-class), 88
- invert, CvxAttr2Constr, Solution, list-method (CvxAttr2Constr-class), 98
- invert, CVXOPT, list, list-method (CVXOPT-class), 98
- invert, Dgp2Dcp, Solution, InverseData-method

- (Dgp2Dcp-class), 111
- invert, ECOS, list, list-method
(ECOS-class), 133
- invert, EvalParams, Solution, list-method
(EvalParams-class), 144
- invert, FlipObjective, Solution, list-method
(FlipObjective-class), 156
- invert, GLPK, list, list-method
(GLPK-class), 164
- invert, GUROBI_CONIC, list, list-method
(GUROBI_CONIC-class), 169
- invert, GUROBI_QP, list, InverseData-method
(GUROBI_QP-class), 171
- invert, MatrixStuffing, Solution, InverseData-method
(MatrixStuffing-class), 215
- invert, MOSEK, ANY, ANY-method
(MOSEK-class), 233
- invert, OSQP, list, InverseData-method
(OSQP-class), 256
- invert, Reduction, Solution, list-method
(Reduction-class), 293
- invert, SCS, list, list-method
(SCS-class), 302
- is.element, ANY, Rdict-method
(Rdict-class), 290
- is_affine (curvature-methods), 96
- is_affine, Expression-method
(Expression-class), 148
- is_atom_affine (curvature-atom), 94
- is_atom_affine, Atom-method
(curvature-atom), 94
- is_atom_concave (curvature-atom), 94
- is_atom_concave, Abs-method (Abs-class), 37
- is_atom_concave, AffAtom-method
(AffAtom-class), 39
- is_atom_concave, Atom-method
(curvature-atom), 94
- is_atom_concave, CumMax-method
(CumMax-class), 90
- is_atom_concave, DivExpression-method
(/, Expression, Expression-method), 32
- is_atom_concave, Entr-method
(Entr-class), 143
- is_atom_concave, Exp-method (Exp-class), 145
- is_atom_concave, EyeMinusInv-method
(EyeMinusInv-class), 154
- is_atom_concave, GeoMean-method
(GeoMean-class), 158
- is_atom_concave, Huber-method
(Huber-class), 176
- is_atom_concave, KLDiv-method
(KLDiv-class), 186
- is_atom_concave, LambdaMax-method
(LambdaMax-class), 190
- is_atom_concave, Log-method (Log-class), 202
- is_atom_concave, LogDet-method
(LogDet-class), 205
- is_atom_concave, Logistic-method
(Logistic-class), 207
- is_atom_concave, LogSumExp-method
(LogSumExp-class), 208
- is_atom_concave, MatrixFrac-method
(MatrixFrac-class), 214
- is_atom_concave, MaxElemwise-method
(MaxElemwise-class), 218
- is_atom_concave, MaxEntries-method
(MaxEntries-class), 220
- is_atom_concave, MinElemwise-method
(MinElemwise-class), 226
- is_atom_concave, MinEntries-method
(MinEntries-class), 227
- is_atom_concave, MulExpression-method
(%*, Expression, Expression-method), 348
- is_atom_concave, Norm1-method
(Norm1-class), 243
- is_atom_concave, NormInf-method
(NormInf-class), 247
- is_atom_concave, NormNuc-method
(NormNuc-class), 249
- is_atom_concave, OneMinusPos-method
(OneMinusPos-class), 254
- is_atom_concave, PfEigenvalue-method
(PfEigenvalue-class), 260
- is_atom_concave, Pnorm-method
(Pnorm-class), 263
- is_atom_concave, Power-method
(Power-class), 266
- is_atom_concave, ProdEntries-method
(ProdEntries-class), 274
- is_atom_concave, QuadForm-method
(QuadForm-class), 285

- `is_atom_concave, QuadOverLin-method`
(QuadOverLin-class), 287
- `is_atom_concave, SigmaMax-method`
(SigmaMax-class), 306
- `is_atom_concave, SumLargest-method`
(SumLargest-class), 319
- `is_atom_concave, SymbolicQuadForm-method`
(SymbolicQuadForm-class), 325
- `is_atom_convex (curvature-atom)`, 94
- `is_atom_convex, Abs-method` (Abs-class), 37
- `is_atom_convex, AffAtom-method`
(AffAtom-class), 39
- `is_atom_convex, Atom-method`
(curvature-atom), 94
- `is_atom_convex, CumMax-method`
(CumMax-class), 90
- `is_atom_convex, DivExpression-method`
(/, Expression, Expression-method), 32
- `is_atom_convex, Entr-method`
(Entr-class), 143
- `is_atom_convex, Exp-method` (Exp-class), 145
- `is_atom_convex, EyeMinusInv-method`
(EyeMinusInv-class), 154
- `is_atom_convex, GeoMean-method`
(GeoMean-class), 158
- `is_atom_convex, Huber-method`
(Huber-class), 176
- `is_atom_convex, KLDiv-method`
(KLDiv-class), 186
- `is_atom_convex, LambdaMax-method`
(LambdaMax-class), 190
- `is_atom_convex, Log-method` (Log-class), 202
- `is_atom_convex, LogDet-method`
(LogDet-class), 205
- `is_atom_convex, Logistic-method`
(Logistic-class), 207
- `is_atom_convex, LogSumExp-method`
(LogSumExp-class), 208
- `is_atom_convex, MatrixFrac-method`
(MatrixFrac-class), 214
- `is_atom_convex, MaxElemwise-method`
(MaxElemwise-class), 218
- `is_atom_convex, MaxEntries-method`
(MaxEntries-class), 220
- `is_atom_convex, MinElemwise-method`
(MinElemwise-class), 226
- `is_atom_convex, MinEntries-method`
(MinEntries-class), 227
- `is_atom_convex, MulExpression-method`
(%*, Expression, Expression-method), 348
- `is_atom_convex, Norm1-method`
(Norm1-class), 243
- `is_atom_convex, NormInf-method`
(NormInf-class), 247
- `is_atom_convex, NormNuc-method`
(NormNuc-class), 249
- `is_atom_convex, OneMinusPos-method`
(OneMinusPos-class), 254
- `is_atom_convex, PfEigenvalue-method`
(PfEigenvalue-class), 260
- `is_atom_convex, Pnorm-method`
(Pnorm-class), 263
- `is_atom_convex, Power-method`
(Power-class), 266
- `is_atom_convex, ProdEntries-method`
(ProdEntries-class), 274
- `is_atom_convex, QuadForm-method`
(QuadForm-class), 285
- `is_atom_convex, QuadOverLin-method`
(QuadOverLin-class), 287
- `is_atom_convex, SigmaMax-method`
(SigmaMax-class), 306
- `is_atom_convex, SumLargest-method`
(SumLargest-class), 319
- `is_atom_convex, SymbolicQuadForm-method`
(SymbolicQuadForm-class), 325
- `is_atom_log_log_affine`
(log_log_curvature-atom), 211
- `is_atom_log_log_affine, Atom-method`
(curvature-atom), 94
- `is_atom_log_log_concave`
(log_log_curvature-atom), 211
- `is_atom_log_log_concave, AddExpression-method`
(+, Expression, missing-method), 11
- `is_atom_log_log_concave, Atom-method`
(curvature-atom), 94
- `is_atom_log_log_concave, DiagMat-method`
(DiagMat-class), 125
- `is_atom_log_log_concave, DiagVec-method`
(DiagVec-class), 127

- `is_atom_log_log_concave`, `DivExpression`-method
(/, `Expression`, `Expression`-method),
32
- `is_atom_log_log_concave`, `Exp`-method
(`Exp`-class), 145
- `is_atom_log_log_concave`, `EyeMinusInv`-method
(`EyeMinusInv`-class), 154
- `is_atom_log_log_concave`, `GeoMean`-method
(`GeoMean`-class), 158
- `is_atom_log_log_concave`, `HStack`-method
(`HStack`-class), 174
- `is_atom_log_log_concave`, `Index`-method
([, `Expression`, `missing`, `missing`, `ANY`-method),
346
- `is_atom_log_log_concave`, `Log`-method
(`Log`-class), 202
- `is_atom_log_log_concave`, `MaxElemwise`-method
(`MaxElemwise`-class), 218
- `is_atom_log_log_concave`, `MaxEntries`-method
(`MaxEntries`-class), 220
- `is_atom_log_log_concave`, `MinElemwise`-method
(`MinElemwise`-class), 226
- `is_atom_log_log_concave`, `MinEntries`-method
(`MinEntries`-class), 227
- `is_atom_log_log_concave`, `MulExpression`-method
(%*, `Expression`, `Expression`-method),
348
- `is_atom_log_log_concave`, `Multiply`-method
(`Multiply`-class), 236
- `is_atom_log_log_concave`, `NormInf`-method
(`NormInf`-class), 247
- `is_atom_log_log_concave`, `OneMinusPos`-method
(`OneMinusPos`-class), 254
- `is_atom_log_log_concave`, `PfEigenvalue`-method
(`PfEigenvalue`-class), 260
- `is_atom_log_log_concave`, `Pnorm`-method
(`Pnorm`-class), 263
- `is_atom_log_log_concave`, `Power`-method
(`Power`-class), 266
- `is_atom_log_log_concave`, `ProdEntries`-method
(`ProdEntries`-class), 274
- `is_atom_log_log_concave`, `Promote`-method
(`Promote`-class), 278
- `is_atom_log_log_concave`, `QuadForm`-method
(`QuadForm`-class), 285
- `is_atom_log_log_concave`, `QuadOverLin`-method
(`QuadOverLin`-class), 287
- `is_atom_log_log_concave`, `Reshape`-method
(`Reshape`-class), 297
- `is_atom_log_log_concave`, `SpecialIndex`-method
([, `Expression`, `index`, `missing`, `ANY`-method),
345
- `is_atom_log_log_concave`, `SumEntries`-method
(`SumEntries`-class), 318
- `is_atom_log_log_concave`, `Trace`-method
(`Trace`-class), 328
- `is_atom_log_log_concave`, `Transpose`-method
(`Transpose`-class), 329
- `is_atom_log_log_concave`, `UpperTri`-method
(`UpperTri`-class), 335
- `is_atom_log_log_concave`, `VStack`-method
(`VStack`-class), 342
- `is_atom_log_log_concave`, `Wrap`-method
(`Wrap`-class), 343
- `is_atom_log_log_convex`
(`log_log_curvature`-atom), 211
- `is_atom_log_log_convex`, `AddExpression`-method
(+, `Expression`, `missing`-method),
11
- `is_atom_log_log_convex`, `Atom`-method
(`curvature`-atom), 94
- `is_atom_log_log_convex`, `DiagMat`-method
(`DiagMat`-class), 125
- `is_atom_log_log_convex`, `DiagVec`-method
(`DiagVec`-class), 127
- `is_atom_log_log_convex`, `DivExpression`-method
(/, `Expression`, `Expression`-method),
32
- `is_atom_log_log_convex`, `Exp`-method
(`Exp`-class), 145
- `is_atom_log_log_convex`, `EyeMinusInv`-method
(`EyeMinusInv`-class), 154
- `is_atom_log_log_convex`, `GeoMean`-method
(`GeoMean`-class), 158
- `is_atom_log_log_convex`, `HStack`-method
(`HStack`-class), 174
- `is_atom_log_log_convex`, `Index`-method
([, `Expression`, `missing`, `missing`, `ANY`-method),
346
- `is_atom_log_log_convex`, `Log`-method
(`Log`-class), 202
- `is_atom_log_log_convex`, `MaxElemwise`-method
(`MaxElemwise`-class), 218
- `is_atom_log_log_convex`, `MaxEntries`-method
(`MaxEntries`-class), 220
- `is_atom_log_log_convex`, `MinElemwise`-method

- (MinElemwise-class), 226
- is_atom_log_log_convex, MinEntries-method
(MinEntries-class), 227
- is_atom_log_log_convex, MulExpression-method
(%*%, Expression, Expression-method),
348
- is_atom_log_log_convex, Multiply-method
(Multiply-class), 236
- is_atom_log_log_convex, NormInf-method
(NormInf-class), 247
- is_atom_log_log_convex, OneMinusPos-method
(OneMinusPos-class), 254
- is_atom_log_log_convex, PfEigenvalue-method
(PfEigenvalue-class), 260
- is_atom_log_log_convex, Pnorm-method
(Pnorm-class), 263
- is_atom_log_log_convex, Power-method
(Power-class), 266
- is_atom_log_log_convex, ProdEntries-method
(ProdEntries-class), 274
- is_atom_log_log_convex, Promote-method
(Promote-class), 278
- is_atom_log_log_convex, QuadForm-method
(QuadForm-class), 285
- is_atom_log_log_convex, QuadOverLin-method
(QuadOverLin-class), 287
- is_atom_log_log_convex, Reshape-method
(Reshape-class), 297
- is_atom_log_log_convex, SpecialIndex-method
([, Expression, index, missing, ANY-method),
345
- is_atom_log_log_convex, SumEntries-method
(SumEntries-class), 318
- is_atom_log_log_convex, Trace-method
(Trace-class), 328
- is_atom_log_log_convex, Transpose-method
(Transpose-class), 329
- is_atom_log_log_convex, UpperTri-method
(UpperTri-class), 335
- is_atom_log_log_convex, VStack-method
(VStack-class), 342
- is_atom_log_log_convex, Wrap-method
(Wrap-class), 343
- is_complex (complex-methods), 56
- is_complex, AffAtom-method
(AffAtom-class), 39
- is_complex, Atom-method (Atom-class), 41
- is_complex, BinaryOperator-method
(BinaryOperator-class), 44
- is_complex, Constant-method
(Constant-class), 77
- is_complex, Constraint-method
(Constraint-class), 81
- is_complex, Expression-method
(Expression-class), 148
- is_complex, Imag-method (Imag-class), 179
- is_complex, Leaf-method (Leaf-class), 196
- is_complex, Real-method (Real-class), 292
- is_concave (curvature-methods), 96
- is_concave, Atom-method (Atom-class), 41
- is_concave, Expression-method
(Expression-class), 148
- is_concave, Leaf-method (Leaf-class), 196
- is_constant (curvature-methods), 96
- is_constant, Expression-method
(Expression-class), 148
- is_constant, Power-method (Power-class),
266
- is_convex (curvature-methods), 96
- is_convex, Atom-method (Atom-class), 41
- is_convex, Expression-method
(Expression-class), 148
- is_convex, Leaf-method (Leaf-class), 196
- is_dcp, 182
- is_dcp, Constraint-method
(Constraint-class), 81
- is_dcp, EqConstraint-method
(==, Expression, Expression-method),
35
- is_dcp, ExpCone-method (ExpCone-class),
147
- is_dcp, Expression-method
(Expression-class), 148
- is_dcp, IneqConstraint-method
(<=, Expression, Expression-method),
33
- is_dcp, Maximize-method
(Maximize-class), 222
- is_dcp, Minimize-method
(Minimize-class), 229
- is_dcp, NonPosConstraint-method
(NonPosConstraint-class), 240
- is_dcp, Problem-method (Problem-class),
270
- is_dcp, PSDConstraint-method (%>>%), 350
- is_dcp, SOC-method (SOC-class), 312

- is_dcp, ZeroConstraint-method
(ZeroConstraint-class), 344
- is_decr (curvature-comp), 96
- is_decr, Abs-method (Abs-class), 37
- is_decr, AffAtom-method (AffAtom-class),
39
- is_decr, Atom-method (curvature-comp), 96
- is_decr, Conjugate-method
(Conjugate-class), 76
- is_decr, Conv-method (Conv-class), 85
- is_decr, CumMax-method (CumMax-class), 90
- is_decr, DivExpression-method
(/, Expression, Expression-method),
32
- is_decr, Entr-method (Entr-class), 143
- is_decr, Exp-method (Exp-class), 145
- is_decr, EyeMinusInv-method
(EyeMinusInv-class), 154
- is_decr, GeoMean-method (GeoMean-class),
158
- is_decr, Huber-method (Huber-class), 176
- is_decr, KLDiv-method (KLDiv-class), 186
- is_decr, Kron-method (Kron-class), 188
- is_decr, LambdaMax-method
(LambdaMax-class), 190
- is_decr, Log-method (Log-class), 202
- is_decr, LogDet-method (LogDet-class),
205
- is_decr, Logistic-method
(Logistic-class), 207
- is_decr, LogSumExp-method
(LogSumExp-class), 208
- is_decr, MatrixFrac-method
(MatrixFrac-class), 214
- is_decr, MaxElemwise-method
(MaxElemwise-class), 218
- is_decr, MaxEntries-method
(MaxEntries-class), 220
- is_decr, MinElemwise-method
(MinElemwise-class), 226
- is_decr, MinEntries-method
(MinEntries-class), 227
- is_decr, MulExpression-method
(%*, Expression, Expression-method),
348
- is_decr, NegExpression-method
(-, Expression, missing-method),
13
- is_decr, Norm1-method (Norm1-class), 243
- is_decr, NormInf-method (NormInf-class),
247
- is_decr, NormNuc-method (NormNuc-class),
249
- is_decr, OneMinusPos-method
(OneMinusPos-class), 254
- is_decr, PfEigenvalue-method
(PfEigenvalue-class), 260
- is_decr, Pnorm-method (Pnorm-class), 263
- is_decr, Power-method (Power-class), 266
- is_decr, ProdEntries-method
(ProdEntries-class), 274
- is_decr, QuadForm-method
(QuadForm-class), 285
- is_decr, QuadOverLin-method
(QuadOverLin-class), 287
- is_decr, SigmaMax-method
(SigmaMax-class), 306
- is_decr, SumLargest-method
(SumLargest-class), 319
- is_decr, SymbolicQuadForm-method
(SymbolicQuadForm-class), 325
- is_dgp, 183
- is_dgp, Constraint-method
(Constraint-class), 81
- is_dgp, EqConstraint-method
(=, Expression, Expression-method),
35
- is_dgp, ExpCone-method (ExpCone-class),
147
- is_dgp, Expression-method
(Expression-class), 148
- is_dgp, IneqConstraint-method
(<=, Expression, Expression-method),
33
- is_dgp, Maximize-method
(Maximize-class), 222
- is_dgp, Minimize-method
(Minimize-class), 229
- is_dgp, NonPosConstraint-method
(NonPosConstraint-class), 240
- is_dgp, Problem-method (Problem-class),
270
- is_dgp, PSDConstraint-method (%>>%), 350
- is_dgp, SOC-method (SOC-class), 312
- is_dgp, ZeroConstraint-method
(ZeroConstraint-class), 344

- `is_hermitian` (matrix_prop-methods), 217
- `is_hermitian`, AddExpression-method
(+, Expression, missing-method), 11
- `is_hermitian`, Conjugate-method
(Conjugate-class), 76
- `is_hermitian`, Constant-method
(Constant-class), 77
- `is_hermitian`, DiagVec-method
(DiagVec-class), 127
- `is_hermitian`, Expression-method
(Expression-class), 148
- `is_hermitian`, Leaf-method (Leaf-class), 196
- `is_hermitian`, NegExpression-method
(-, Expression, missing-method), 13
- `is_hermitian`, Transpose-method
(Transpose-class), 329
- `is_imag` (complex-methods), 56
- `is_imag`, AffAtom-method (AffAtom-class), 39
- `is_imag`, Atom-method (Atom-class), 41
- `is_imag`, BinaryOperator-method
(BinaryOperator-class), 44
- `is_imag`, Constant-method
(Constant-class), 77
- `is_imag`, Constraint-method
(Constraint-class), 81
- `is_imag`, Expression-method
(Expression-class), 148
- `is_imag`, Imag-method (Imag-class), 179
- `is_imag`, Leaf-method (Leaf-class), 196
- `is_imag`, Real-method (Real-class), 292
- `is_incr` (curvature-comp), 96
- `is_incr`, Abs-method (Abs-class), 37
- `is_incr`, AffAtom-method (AffAtom-class), 39
- `is_incr`, Atom-method (curvature-comp), 96
- `is_incr`, Conjugate-method
(Conjugate-class), 76
- `is_incr`, Conv-method (Conv-class), 85
- `is_incr`, CumMax-method (CumMax-class), 90
- `is_incr`, DivExpression-method
(/, Expression, Expression-method), 32
- `is_incr`, Entr-method (Entr-class), 143
- `is_incr`, Exp-method (Exp-class), 145
- `is_incr`, EyeMinusInv-method
(EyeMinusInv-class), 154
- `is_incr`, GeoMean-method (GeoMean-class), 158
- `is_incr`, Huber-method (Huber-class), 176
- `is_incr`, KLDiv-method (KLDiv-class), 186
- `is_incr`, Kron-method (Kron-class), 188
- `is_incr`, LambdaMax-method
(LambdaMax-class), 190
- `is_incr`, Log-method (Log-class), 202
- `is_incr`, LogDet-method (LogDet-class), 205
- `is_incr`, Logistic-method
(Logistic-class), 207
- `is_incr`, LogSumExp-method
(LogSumExp-class), 208
- `is_incr`, MatrixFrac-method
(MatrixFrac-class), 214
- `is_incr`, MaxElemwise-method
(MaxElemwise-class), 218
- `is_incr`, MaxEntries-method
(MaxEntries-class), 220
- `is_incr`, MinElemwise-method
(MinElemwise-class), 226
- `is_incr`, MinEntries-method
(MinEntries-class), 227
- `is_incr`, MulExpression-method
(%*, Expression, Expression-method), 348
- `is_incr`, NegExpression-method
(-, Expression, missing-method), 13
- `is_incr`, Norm1-method (Norm1-class), 243
- `is_incr`, NormInf-method (NormInf-class), 247
- `is_incr`, NormNuc-method (NormNuc-class), 249
- `is_incr`, OneMinusPos-method
(OneMinusPos-class), 254
- `is_incr`, PfEigenvalue-method
(PfEigenvalue-class), 260
- `is_incr`, Pnorm-method (Pnorm-class), 263
- `is_incr`, Power-method (Power-class), 266
- `is_incr`, ProdEntries-method
(ProdEntries-class), 274
- `is_incr`, QuadForm-method
(QuadForm-class), 285
- `is_incr`, QuadOverLin-method

- (QuadOverLin-class), 287
- is_incr, SigmaMax-method
(SigmaMax-class), 306
- is_incr, SumLargest-method
(SumLargest-class), 319
- is_incr, SymbolicQuadForm-method
(SymbolicQuadForm-class), 325
- is_installed, ConstantSolver-method
(ConstantSolver-class), 79
- is_installed, ReductionSolver-method
(ReductionSolver-class), 295
- is_log_log_affine
(log_log_curvature-methods),
212
- is_log_log_affine, Expression-method
(Expression-class), 148
- is_log_log_concave
(log_log_curvature-methods),
212
- is_log_log_concave, Atom-method
(Atom-class), 41
- is_log_log_concave, Expression-method
(Expression-class), 148
- is_log_log_concave, Leaf-method
(Leaf-class), 196
- is_log_log_constant
(log_log_curvature-methods),
212
- is_log_log_constant, Expression-method
(Expression-class), 148
- is_log_log_convex
(log_log_curvature-methods),
212
- is_log_log_convex, Atom-method
(Atom-class), 41
- is_log_log_convex, Expression-method
(Expression-class), 148
- is_log_log_convex, Leaf-method
(Leaf-class), 196
- is_matrix (size-methods), 310
- is_matrix, Expression-method
(Expression-class), 148
- is_mixed_integer, 183
- is_mixed_integer, Problem-method
(Problem-class), 270
- is_neg (leaf-attr), 196
- is_neg, Leaf-method (Leaf-class), 196
- is_nonneg (sign-methods), 308
- is_nonneg, Atom-method (Atom-class), 41
- is_nonneg, Constant-method
(Constant-class), 77
- is_nonneg, Expression-method
(Expression-class), 148
- is_nonneg, Leaf-method (Leaf-class), 196
- is_nonpos (sign-methods), 308
- is_nonpos, Atom-method (Atom-class), 41
- is_nonpos, Constant-method
(Constant-class), 77
- is_nonpos, Expression-method
(Expression-class), 148
- is_nonpos, Leaf-method (Leaf-class), 196
- is_nsd (matrix_prop-methods), 217
- is_nsd, AffAtom-method (AffAtom-class),
39
- is_nsd, Constant-method
(Constant-class), 77
- is_nsd, Expression-method
(Expression-class), 148
- is_nsd, Leaf-method (Leaf-class), 196
- is_nsd, Multiply-method
(Multiply-class), 236
- is_pos (leaf-attr), 196
- is_pos, Constant-method
(Constant-class), 77
- is_pos, Leaf-method (Leaf-class), 196
- is_psd (matrix_prop-methods), 217
- is_psd, AffAtom-method (AffAtom-class),
39
- is_psd, Constant-method
(Constant-class), 77
- is_psd, Expression-method
(Expression-class), 148
- is_psd, Leaf-method (Leaf-class), 196
- is_psd, Multiply-method
(Multiply-class), 236
- is_psd, PSDWrap-method (PSDWrap-class),
279
- is_pwl (curvature-methods), 96
- is_pwl, Abs-method (Abs-class), 37
- is_pwl, AffAtom-method (AffAtom-class),
39
- is_pwl, Expression-method
(Expression-class), 148
- is_pwl, Leaf-method (Leaf-class), 196
- is_pwl, MaxElemwise-method
(MaxElemwise-class), 218

- is_pwl, MaxEntries-method
(MaxEntries-class), 220
- is_pwl, MinElemwise-method
(MinElemwise-class), 226
- is_pwl, MinEntries-method
(MinEntries-class), 227
- is_pwl, Norm1-method (Norm1-class), 243
- is_pwl, NormInf-method (NormInf-class),
247
- is_pwl, Pnorm-method (Pnorm-class), 263
- is_pwl, QuadForm-method
(QuadForm-class), 285
- is_qp, 184
- is_qp, Problem-method (Problem-class),
270
- is_qpwa (curvature-methods), 96
- is_qpwa, AffAtom-method (AffAtom-class),
39
- is_qpwa, DivExpression-method
(/, Expression, Expression-method),
32
- is_qpwa, Expression-method
(Expression-class), 148
- is_qpwa, MatrixFrac-method
(MatrixFrac-class), 214
- is_qpwa, Objective-method
(Objective-class), 253
- is_qpwa, Power-method (Power-class), 266
- is_qpwa, QuadOverLin-method
(QuadOverLin-class), 287
- is_quadratic (curvature-methods), 96
- is_quadratic, AffAtom-method
(AffAtom-class), 39
- is_quadratic, DivExpression-method
(/, Expression, Expression-method),
32
- is_quadratic, Expression-method
(Expression-class), 148
- is_quadratic, Huber-method
(Huber-class), 176
- is_quadratic, Leaf-method (Leaf-class),
196
- is_quadratic, MatrixFrac-method
(MatrixFrac-class), 214
- is_quadratic, Objective-method
(Objective-class), 253
- is_quadratic, Power-method
(Power-class), 266
- is_quadratic, QuadForm-method
(QuadForm-class), 285
- is_quadratic, QuadOverLin-method
(QuadOverLin-class), 287
- is_quadratic, SymbolicQuadForm-method
(SymbolicQuadForm-class), 325
- is_real (complex-methods), 56
- is_real, Constraint-method
(Constraint-class), 81
- is_real, Expression-method
(Expression-class), 148
- is_scalar (size-methods), 310
- is_scalar, Expression-method
(Expression-class), 148
- is_stuffed_cone_constraint, 184
- is_stuffed_cone_objective, 185
- is_stuffed_qp_objective, 185
- is_symmetric (matrix_prop-methods), 217
- is_symmetric, AddExpression-method
(+, Expression, missing-method),
11
- is_symmetric, Conjugate-method
(Conjugate-class), 76
- is_symmetric, Constant-method
(Constant-class), 77
- is_symmetric, DiagVec-method
(DiagVec-class), 127
- is_symmetric, Elementwise-method
(Elementwise-class), 136
- is_symmetric, Expression-method
(Expression-class), 148
- is_symmetric, Imag-method (Imag-class),
179
- is_symmetric, Leaf-method (Leaf-class),
196
- is_symmetric, NegExpression-method
(-, Expression, missing-method),
13
- is_symmetric, Promote-method
(Promote-class), 278
- is_symmetric, Real-method (Real-class),
292
- is_symmetric, Transpose-method
(Transpose-class), 329
- is_vector (size-methods), 310
- is_vector, Expression-method
(Expression-class), 148
- is_zero (sign-methods), 308

- is_zero, Expression-method
(Expression-class), 148
- kl_div, 187
- KLDiv, 186
- KLDiv (KLDiv-class), 186
- KLDiv-class, 186
- Kron, 188
- Kron (Kron-class), 188
- Kron-class, 188
- kronecker
(kronecker, Expression, ANY-method), 189
- kronecker, ANY, Expression-method
(kronecker, Expression, ANY-method), 189
- kronecker, Expression, ANY-method, 189
- lambda_max, 193
- lambda_min, 194
- lambda_sum_largest, 195
- lambda_sum_smallest, 195
- LambdaMax, 191
- LambdaMax (LambdaMax-class), 190
- LambdaMax-class, 190
- LambdaMin, 191
- LambdaSumLargest, 192
- LambdaSumLargest
(LambdaSumLargest-class), 192
- LambdaSumLargest-class, 192
- LambdaSumSmallest, 193
- Leaf, 46, 152, 196, 198, 259, 277, 337, 339
- Leaf (Leaf-class), 196
- leaf-attr, 196
- Leaf-class, 196
- length, Rdict-method (Rdict-class), 290
- linearize, 200
- ListORConstr-class, 201
- Log, 203
- Log (Log-class), 202
- log (log, Expression-method), 201
- log, Expression-method, 201
- Log-class, 202
- log10 (log, Expression-method), 201
- log10, Expression-method
(log, Expression-method), 201
- Log1p, 204
- Log1p (Log1p-class), 204
- log1p (log, Expression-method), 201
- log1p, Expression-method
(log, Expression-method), 201
- Log1p-class, 204
- log2 (log, Expression-method), 201
- log2, Expression-method
(log, Expression-method), 201
- log_det, 210
- log_log_curvature, 211
- log_log_curvature, Expression-method
(log_log_curvature), 211
- log_log_curvature-atom, 211
- log_log_curvature-methods, 212
- log_sum_exp, 212
- LogDet, 206
- LogDet (LogDet-class), 205
- LogDet-class, 205
- Logistic, 208
- Logistic (Logistic-class), 207
- logistic, 206
- Logistic-class, 207
- LogSumExp, 209
- LogSumExp (LogSumExp-class), 208
- LogSumExp-class, 208
- make_sparse_diagonal_matrix, 213
- matrix_frac, 216
- matrix_prop-methods, 217
- matrix_trace, 218
- MatrixFrac, 215
- MatrixFrac (MatrixFrac-class), 214
- MatrixFrac-class, 214
- MatrixStuffing, 216
- MatrixStuffing (MatrixStuffing-class), 215
- MatrixStuffing-class, 215
- max (max_entries), 224
- max_elemwise, 223
- max_entries, 224
- MaxElemwise, 219
- MaxElemwise (MaxElemwise-class), 218
- MaxElemwise-class, 218
- MaxEntries, 221
- MaxEntries (MaxEntries-class), 220
- MaxEntries-class, 220
- Maximize, 185, 222, 253, 272, 273
- Maximize (Maximize-class), 222
- Maximize-class, 222
- mean (mean.Expression), 225
- mean.Expression, 225

- `min(min_entries)`, 230
- `min_elemwise`, 230
- `min_entries`, 230
- `MinElemwise`, 227
- `MinElemwise (MinElemwise-class)`, 226
- `MinElemwise-class`, 226
- `MinEntries`, 228
- `MinEntries (MinEntries-class)`, 227
- `MinEntries-class`, 227
- `Minimize`, 185, 229, 253, 272, 273
- `Minimize (Minimize-class)`, 229
- `Minimize-class`, 229
- `mip_capable`, 231
- `mip_capable, CBC_CONIC-method`
(CBC_CONIC-class), 49
- `mip_capable, CLARABEL-method`
(CLARABEL-class), 53
- `mip_capable, ConstantSolver-method`
(ConstantSolver-class), 79
- `mip_capable, CPLEX_CONIC-method`
(CPLEX_CONIC-class), 86
- `mip_capable, CPLEX_QP-method`
(CPLEX_QP-class), 88
- `mip_capable, CVXOPT-method`
(CVXOPT-class), 98
- `mip_capable, ECOS-method (ECOS-class)`,
133
- `mip_capable, ECOS_BB-method`
(ECOS_BB-class), 135
- `mip_capable, GLPK-method (GLPK-class)`,
164
- `mip_capable, GLPK_MI-method`
(GLPK_MI-class), 166
- `mip_capable, GUROBI_CONIC-method`
(GUROBI_CONIC-class), 169
- `mip_capable, GUROBI_QP-method`
(GUROBI_QP-class), 171
- `mip_capable, MOSEK-method (MOSEK-class)`,
233
- `mip_capable, ReductionSolver-method`
(ReductionSolver-class), 295
- `mip_capable, SCS-method (SCS-class)`, 302
- `mixed_norm`, 232
- `MixedNorm`, 232
- `MOSEK`, 234
- `MOSEK (MOSEK-class)`, 233
- `MOSEK-class`, 233
- `MOSEK.parse_dual_vars`, 235
- `MOSEK.recover_dual_variables`, 235
- `MulExpression`, 349
- `MulExpression`
(`%%`, Expression, Expression-method),
348
- `MulExpression-class`
(`%%`, Expression, Expression-method),
348
- `Multiply`, 237, 348, 349
- `Multiply (Multiply-class)`, 236
- `multiply`, 236
- `Multiply-class`, 236
- `name`, 238
- `name, AddExpression-method`
(`+`, Expression, missing-method),
11
- `name, Atom-method (Atom-class)`, 41
- `name, BinaryOperator-method`
(BinaryOperator-class), 44
- `name, CBC_CONIC-method`
(CBC_CONIC-class), 49
- `name, CLARABEL-method (CLARABEL-class)`,
53
- `name, Constant-method (Constant-class)`,
77
- `name, ConstantSolver-method`
(ConstantSolver-class), 79
- `name, CPLEX_CONIC-method`
(CPLEX_CONIC-class), 86
- `name, CPLEX_QP-method (CPLEX_QP-class)`,
88
- `name, CVXOPT-method (CVXOPT-class)`, 98
- `name, ECOS-method (ECOS-class)`, 133
- `name, ECOS_BB-method (ECOS_BB-class)`, 135
- `name, EqConstraint-method`
(`=`, Expression, Expression-method),
35
- `name, Expression-method`
(Expression-class), 148
- `name, EyeMinusInv-method`
(EyeMinusInv-class), 154
- `name, GeoMean-method (GeoMean-class)`, 158
- `name, GLPK-method (GLPK-class)`, 164
- `name, GLPK_MI-method (GLPK_MI-class)`, 166
- `name, GUROBI_CONIC-method`
(GUROBI_CONIC-class), 169
- `name, GUROBI_QP-method`
(GUROBI_QP-class), 171

- name, IneqConstraint-method
($\leq$, Expression, Expression-method),
[33](#)
- name, MOSEK-method (MOSEK-class), [233](#)
- name, NonPosConstraint-method
(NonPosConstraint-class), [240](#)
- name, Norm1-method (Norm1-class), [243](#)
- name, NormInf-method (NormInf-class), [247](#)
- name, OneMinusPos-method
(OneMinusPos-class), [254](#)
- name, OSQP-method (OSQP-class), [256](#)
- name, Parameter-method
(Parameter-class), [258](#)
- name, PfEigenvalue-method
(PfEigenvalue-class), [260](#)
- name, Pnorm-method (Pnorm-class), [263](#)
- name, Power-method (Power-class), [266](#)
- name, PSDConstraint-method ($\%>\%$), [350](#)
- name, QuadForm-method (QuadForm-class),
[285](#)
- name, ReductionSolver-method
(ReductionSolver-class), [295](#)
- name, SCS-method (SCS-class), [302](#)
- name, SpecialIndex-method
([, Expression, index, missing, ANY-method),
[345](#)
- name, UnaryOperator-method
(UnaryOperator-class), [332](#)
- name, Variable-method (Variable-class),
[338](#)
- name, ZeroConstraint-method
(ZeroConstraint-class), [344](#)
- names, DgpCanonMethods-method
(DgpCanonMethods-class), [124](#)
- ncol, Atom-method (Atom-class), [41](#)
- ncol, Expression-method
(Expression-class), [148](#)
- ndim, Expression-method
(Expression-class), [148](#)
- Neg, [238](#)
- neg, [239](#)
- NegExpression, [14](#)
- NegExpression
(-, Expression, missing-method),
[13](#)
- NegExpression-class
(-, Expression, missing-method),
[13](#)
- NonlinearConstraint
(NonlinearConstraint-class),
[239](#)
- NonlinearConstraint-class, [239](#)
- NonPosConstraint, [240](#)
- NonPosConstraint-class, [240](#)
- Norm, [241](#)
- norm, [100](#)
- norm
(norm, Expression, character-method),
[241](#)
- norm, Expression, character-method, [241](#)
- Norm1, [244](#)
- Norm1 (Norm1-class), [243](#)
- norm1, [242](#)
- Norm1-class, [243](#)
- Norm2, [245](#)
- norm2, [246](#)
- norm_inf, [250](#)
- norm_nuc, [251](#)
- NormInf, [248](#)
- NormInf (NormInf-class), [247](#)
- NormInf-class, [247](#)
- NormNuc, [249](#)
- NormNuc (NormNuc-class), [249](#)
- NormNuc-class, [249](#)
- nrow, Atom-method (Atom-class), [41](#)
- nrow, Expression-method
(Expression-class), [148](#)
- num_cones (cone-methods), [72](#)
- num_cones, ExpCone-method
(ExpCone-class), [147](#)
- num_cones, SOC-method (SOC-class), [312](#)
- num_cones, SOCAxis-method
(SOCAxis-class), [313](#)
- Objective, [185](#), [254](#)
- Objective (Objective-class), [253](#)
- objective (problem-parts), [274](#)
- objective, Problem-method
(Problem-class), [270](#)
- Objective-arith, [252](#)
- Objective-class, [253](#)
- objective<- (problem-parts), [274](#)
- objective<-, Problem-method
(Problem-class), [270](#)
- one_minus_pos, [256](#)
- OneMinusPos, [255](#)
- OneMinusPos (OneMinusPos-class), [254](#)

- OneMinusPos-class, [254](#)
- OSQP, [257](#)
- OSQP (OSQP-class), [256](#)
- OSQP-class, [256](#)
-
- p_norm, [242](#), [282](#)
- Parameter, [47](#), [153](#), [199](#), [238](#), [259](#), [273](#), [338](#)
- Parameter (Parameter-class), [258](#)
- Parameter-class, [258](#)
- parameters (expression-parts), [152](#)
- parameters, Canonical-method (Canonical-class), [46](#)
- parameters, Leaf-method (Leaf-class), [196](#)
- parameters, Parameter-method (Parameter-class), [258](#)
- parameters, Problem-method (Problem-class), [270](#)
- perform, [260](#)
- perform, Canonicalization, Problem-method (Canonicalization-class), [48](#)
- perform, CBC_CONIC, Problem-method (CBC_CONIC-class), [49](#)
- perform, Chain, Problem-method (Chain-class), [52](#)
- perform, CLARABEL, Problem-method (CLARABEL-class), [53](#)
- perform, Complex2Real, Problem-method (Complex2Real-class), [57](#)
- perform, ConstantSolver, Problem-method (ConstantSolver-class), [79](#)
- perform, CPLEX_CONIC, Problem-method (CPLEX_CONIC-class), [86](#)
- perform, CvxAttr2Constr, Problem-method (CvxAttr2Constr-class), [98](#)
- perform, CVXOPT, Problem-method (CVXOPT-class), [98](#)
- perform, Dcp2Cone, Problem-method (Dcp2Cone-class), [101](#)
- perform, Dgp2Dcp, Problem-method (Dgp2Dcp-class), [111](#)
- perform, ECOS, Problem-method (ECOS-class), [133](#)
- perform, ECOS_BB, Problem-method (ECOS_BB-class), [135](#)
- perform, EvalParams, Problem-method (EvalParams-class), [144](#)
- perform, FlipObjective, Problem-method (FlipObjective-class), [156](#)
- perform, GUROBI_CONIC, Problem-method (GUROBI_CONIC-class), [169](#)
- perform, MatrixStuffing, Problem-method (MatrixStuffing-class), [215](#)
- perform, MOSEK, Problem-method (MOSEK-class), [233](#)
- perform, QpSolver, Problem-method (QpSolver-class), [284](#)
- perform, Reduction, Problem-method (Reduction-class), [293](#)
- perform, SCS, Problem-method (SCS-class), [302](#)
- pf_eigenvalue, [262](#)
- PfEigenvalue, [261](#)
- PfEigenvalue (PfEigenvalue-class), [260](#)
- PfEigenvalue-class, [260](#)
- Pnorm, [264](#)
- Pnorm (Pnorm-class), [263](#)
- Pnorm-class, [263](#)
- Pos, [265](#)
- pos, [266](#)
- Power, [268](#)
- Power (Power-class), [266](#)
- power (^, Expression, numeric-method), [351](#)
- Power-class, [266](#)
- prepend, SolvingChain, Chain-method (SolvingChain-class), [316](#)
- Problem, [38](#), [48](#), [50](#), [52](#), [54](#), [57](#), [73](#), [74](#), [80](#), [87](#), [98](#), [99](#), [101](#), [112](#), [134](#), [135](#), [137](#), [144](#), [157](#), [163](#), [170](#), [182–184](#), [216](#), [234](#), [260](#), [270](#), [272](#), [274](#), [280](#), [281](#), [284](#), [293](#), [294](#), [296](#), [303](#), [311](#), [315](#), [333](#), [338](#)
- Problem (Problem-class), [270](#)
- Problem-arith, [269](#)
- Problem-class, [270](#)
- problem-parts, [274](#)
- prod (prod_entries), [276](#)
- prod_entries, [276](#)
- ProdEntries, [275](#)
- ProdEntries (ProdEntries-class), [274](#)
- ProdEntries-class, [274](#)
- project (project-methods), [277](#)
- project, Leaf-method (Leaf-class), [196](#)
- project-methods, [277](#)
- project_and_assign (project-methods), [277](#)
- project_and_assign, Leaf-method

- (Leaf-class), 196
- Promote, 278
- Promote (Promote-class), 278
- Promote-class, 278
- psd_coeff_offset, 280
- PSDConstraint, 351
- PSDConstraint (%>>%), 350
- PSDConstraint-class (%>>%), 350
- PSDWrap, 279
- PSDWrap (PSDWrap-class), 279
- PSDWrap-class, 279
- psolve, 280
- psolve, Problem-method (psolve), 280
- Qp2SymbolicQp-class, 284
- QpMatrixStuffing
 - (QpMatrixStuffing-class), 284
- QpMatrixStuffing-class, 284
- QpSolver, 284
- QpSolver-class, 284
- quad_form, 289
- quad_over_lin, 289
- QuadForm, 286
- QuadForm (QuadForm-class), 285
- QuadForm-class, 285
- QuadOverLin, 288
- QuadOverLin (QuadOverLin-class), 287
- QuadOverLin-class, 287
- Rdict, 291, 292
- Rdict (Rdict-class), 290
- Rdict-class, 290
- Rdictdefault, 291
- Rdictdefault (Rdictdefault-class), 291
- Rdictdefault-class, 291
- Re, Expression-method (complex-atoms), 56
- Real, 292
- Real (Real-class), 292
- Real-class, 292
- reduce, 293, 301
- reduce, Reduction-method
 - (Reduction-class), 293
- Reduction, 38, 181, 260, 293, 294, 300
- Reduction-class, 293
- reduction_format_constr, CLARABEL-method
 - (CLARABEL-class), 53
- reduction_format_constr, ConicSolver-method
 - (ConicSolver-class), 73
- reduction_format_constr, SCS-method
 - (SCS-class), 302
- reduction_solve, ConstantSolver, ANY-method
 - (ConstantSolver-class), 79
- reduction_solve, ReductionSolver, ANY-method
 - (ReductionSolver-class), 295
- reduction_solve, SolvingChain, Problem-method
 - (SolvingChain-class), 316
- reduction_solve_via_data, SolvingChain-method
 - (SolvingChain-class), 316
- ReductionSolver, 180, 231, 296
- ReductionSolver-class, 295
- remove_from_solver_blacklist
 - (installed_solvers), 180
- resetOptions, 297
- Reshape, 298
- Reshape (Reshape-class), 297
- reshape (reshape_expr), 298
- Reshape-class, 297
- reshape_expr, 298
- residual (residual-methods), 300
- residual, Constraint-method
 - (Constraint-class), 81
- residual, EqConstraint-method
 - (=, Expression, Expression-method), 35
- residual, ExpCone-method
 - (ExpCone-class), 147
- residual, IneqConstraint-method
 - (<=, Expression, Expression-method), 33
- residual, NonPosConstraint-method
 - (NonPosConstraint-class), 240
- residual, PSDConstraint-method (%>>%), 350
- residual, SOC-method (SOC-class), 312
- residual, ZeroConstraint-method
 - (ZeroConstraint-class), 344
- residual-methods, 300
- retrieve, 300
- retrieve, Reduction, Solution-method
 - (Reduction-class), 293
- scaled_lower_tri, 301
- scaled_upper_tri, 301
- scalene, 302
- SCS, 303
- SCS (SCS-class), 302
- SCS-class, 302

- SCS.dims_to_solver_dict, [304](#)
- SCS.extract_dual_value, [305](#)
- set_solver_blacklist
(installed_solvers), [180](#)
- setIdCounter, [178](#), [305](#)
- show, Constant-method (Constant-class),
[77](#)
- sigma_max, [307](#)
- SigmaMax, [306](#)
- SigmaMax (SigmaMax-class), [306](#)
- SigmaMax-class, [306](#)
- sign, Expression-method, [308](#)
- sign-methods, [308](#)
- sign_from_args, [309](#)
- sign_from_args, Abs-method (Abs-class),
[37](#)
- sign_from_args, AffAtom-method
(AffAtom-class), [39](#)
- sign_from_args, Atom-method
(sign_from_args), [309](#)
- sign_from_args, BinaryOperator-method
(BinaryOperator-class), [44](#)
- sign_from_args, Conv-method
(Conv-class), [85](#)
- sign_from_args, CumMax-method
(CumMax-class), [90](#)
- sign_from_args, Entr-method
(Entr-class), [143](#)
- sign_from_args, Exp-method (Exp-class),
[145](#)
- sign_from_args, EyeMinusInv-method
(EyeMinusInv-class), [154](#)
- sign_from_args, GeoMean-method
(GeoMean-class), [158](#)
- sign_from_args, Huber-method
(Huber-class), [176](#)
- sign_from_args, KLDiv-method
(KLDiv-class), [186](#)
- sign_from_args, Kron-method
(Kron-class), [188](#)
- sign_from_args, LambdaMax-method
(LambdaMax-class), [190](#)
- sign_from_args, Log-method (Log-class),
[202](#)
- sign_from_args, Log1p-method
(Log1p-class), [204](#)
- sign_from_args, LogDet-method
(LogDet-class), [205](#)
- sign_from_args, Logistic-method
(Logistic-class), [207](#)
- sign_from_args, LogSumExp-method
(LogSumExp-class), [208](#)
- sign_from_args, MatrixFrac-method
(MatrixFrac-class), [214](#)
- sign_from_args, MaxElemwise-method
(MaxElemwise-class), [218](#)
- sign_from_args, MaxEntries-method
(MaxEntries-class), [220](#)
- sign_from_args, MinElemwise-method
(MinElemwise-class), [226](#)
- sign_from_args, MinEntries-method
(MinEntries-class), [227](#)
- sign_from_args, NegExpression-method
(-, Expression, missing-method),
[13](#)
- sign_from_args, Norm1-method
(Norm1-class), [243](#)
- sign_from_args, NormInf-method
(NormInf-class), [247](#)
- sign_from_args, NormNuc-method
(NormNuc-class), [249](#)
- sign_from_args, OneMinusPos-method
(OneMinusPos-class), [254](#)
- sign_from_args, PfEigenvalue-method
(PfEigenvalue-class), [260](#)
- sign_from_args, Pnorm-method
(Pnorm-class), [263](#)
- sign_from_args, Power-method
(Power-class), [266](#)
- sign_from_args, ProdEntries-method
(ProdEntries-class), [274](#)
- sign_from_args, QuadForm-method
(QuadForm-class), [285](#)
- sign_from_args, QuadOverLin-method
(QuadOverLin-class), [287](#)
- sign_from_args, SigmaMax-method
(SigmaMax-class), [306](#)
- sign_from_args, SumLargest-method
(SumLargest-class), [319](#)
- sign_from_args, SymbolicQuadForm-method
(SymbolicQuadForm-class), [325](#)
- size, [310](#)
- size, Constraint-method
(Constraint-class), [81](#)
- size, EqConstraint-method
(=, Expression, Expression-method),

- 35
- size, ExpCone-method (ExpCone-class), 147
- size, Expression-method (Expression-class), 148
- size, IneqConstraint-method ($\leq$, Expression, Expression-method), 33
- size, ListORExpr-method (size), 310
- size, SOC-method (SOC-class), 312
- size, SOCAxis-method (SOCAxis-class), 313
- size, ZeroConstraint-method (Constraint-class), 81
- size-methods, 310
- size_metrics (problem-parts), 274
- size_metrics, Problem-method (Problem-class), 270
- SizeMetrics (SizeMetrics-class), 311
- SizeMetrics-class, 311
- SOC, 313
- SOC (SOC-class), 312
- SOC-class, 312
- SOCAxis, 72, 314
- SOCAxis (SOCAxis-class), 313
- SOCAxis-class, 313
- Solution, 48, 52, 57, 74, 80, 81, 98, 112, 144, 157, 181, 216, 272, 294, 300, 301, 315, 333
- Solution-class, 315
- solve (psolve), 280
- solve, Problem, ANY-method (psolve), 280
- solve_via_data, CBC_CONIC-method (CBC_CONIC-class), 49
- solve_via_data, CLARABEL-method (CLARABEL-class), 53
- solve_via_data, ConstantSolver-method (ConstantSolver-class), 79
- solve_via_data, CPLEX_CONIC-method (CPLEX_CONIC-class), 86
- solve_via_data, CPLEX_QP-method (CPLEX_QP-class), 88
- solve_via_data, CVXOPT-method (CVXOPT-class), 98
- solve_via_data, ECOS-method (ReductionSolver-class), 295
- solve_via_data, ECOS_BB-method (ECOS_BB-class), 135
- solve_via_data, GLPK-method (GLPK-class), 164
- solve_via_data, GLPK_MI-method (GLPK_MI-class), 166
- solve_via_data, GUROBI_CONIC-method (GUROBI_CONIC-class), 169
- solve_via_data, GUROBI_QP-method (GUROBI_QP-class), 171
- solve_via_data, MOSEK-method (MOSEK-class), 233
- solve_via_data, OSQP-method (OSQP-class), 256
- solve_via_data, ReductionSolver-method (ReductionSolver-class), 295
- solve_via_data, SCS-method (SCS-class), 302
- solver_stats, Problem-method (Problem-class), 270
- solver_stats<-, Problem-method (Problem-class), 270
- SolverStats (SolverStats-class), 315
- SolverStats-class, 315
- SolvingChain, 84, 317
- SolvingChain-class, 316
- SpecialIndex ([, Expression, index, missing, ANY-method), 345
- SpecialIndex-class ([, Expression, index, missing, ANY-method), 345
- sqrt (sqrt, Expression-method), 317
- sqrt, Expression-method, 317
- square (square, Expression-method), 318
- square, Expression-method, 318
- status, Problem-method (Problem-class), 270
- status_map, CBC_CONIC-method (CBC_CONIC-class), 49
- status_map, CLARABEL-method (CLARABEL-class), 53
- status_map, CPLEX_CONIC-method (CPLEX_CONIC-class), 86
- status_map, CPLEX_QP-method (CPLEX_QP-class), 88
- status_map, CVXOPT-method (CVXOPT-class), 98
- status_map, ECOS-method (ECOS-class), 133
- status_map, GLPK-method (GLPK-class), 164
- status_map, GLPK_MI-method (GLPK_MI-class), 166

- status_map, GUROBI_CONIC-method
(GUROBI_CONIC-class), 169
- status_map, GUROBI_QP-method
(GUROBI_QP-class), 171
- status_map, OSQP-method (OSQP-class), 256
- status_map, SCS-method (SCS-class), 302
- status_map_lp, CBC_CONIC-method
(CBC_CONIC-class), 49
- status_map_mip, CBC_CONIC-method
(CBC_CONIC-class), 49
- stuffed_objective, ConeMatrixStuffing, Problem, CoeffExtra, and method
(ConeMatrixStuffing-class), 73
- sum (sum_entries), 322
- sum_entries, 322
- sum_largest, 323
- sum_smallest, 324
- sum_squares, 324
- SumEntries, 319
- SumEntries (SumEntries-class), 318
- SumEntries-class, 318
- SumLargest, 320
- SumLargest (SumLargest-class), 319
- SumLargest-class, 319
- SumSmallest, 321
- SumSquares, 321
- SymbolicQuadForm, 326
- SymbolicQuadForm
(SymbolicQuadForm-class), 325
- SymbolicQuadForm-class, 325

- t (t.Expression), 327
- t, Expression-method (t.Expression), 327
- t.Expression, 327
- to_numeric, 328
- to_numeric, Abs-method (Abs-class), 37
- to_numeric, AddExpression-method
(+, Expression, missing-method),
11
- to_numeric, BinaryOperator-method
(BinaryOperator-class), 44
- to_numeric, Conjugate-method
(Conjugate-class), 76
- to_numeric, Conv-method (Conv-class), 85
- to_numeric, CumMax-method
(CumMax-class), 90
- to_numeric, CumSum-method
(CumSum-class), 92
- to_numeric, DiagMat-method
(DiagMat-class), 125
- to_numeric, DiagVec-method
(DiagVec-class), 127
- to_numeric, DivExpression-method
(/, Expression, Expression-method),
32
- to_numeric, Entr-method (Entr-class), 143
- to_numeric, Exp-method (Exp-class), 145
- to_numeric, EyeMinusInv-method
(EyeMinusInv-class), 154
- to_numeric, GeoMean-method
(GeoMean-class), 158
- to_numeric, HStack-method
(HStack-class), 174
- to_numeric, Huber-method (Huber-class),
176
- to_numeric, Imag-method (Imag-class), 179
- to_numeric, Index-method
([, Expression, missing, missing, ANY-method),
346
- to_numeric, KLDiv-method (KLDiv-class),
186
- to_numeric, Kron-method (Kron-class), 188
- to_numeric, LambdaMax-method
(LambdaMax-class), 190
- to_numeric, LambdaSumLargest-method
(LambdaSumLargest-class), 192
- to_numeric, Log-method (Log-class), 202
- to_numeric, Log1p-method (Log1p-class),
204
- to_numeric, LogDet-method
(LogDet-class), 205
- to_numeric, Logistic-method
(Logistic-class), 207
- to_numeric, LogSumExp-method
(LogSumExp-class), 208
- to_numeric, MatrixFrac-method
(MatrixFrac-class), 214
- to_numeric, MaxElemwise-method
(MaxElemwise-class), 218
- to_numeric, MaxEntries-method
(MaxEntries-class), 220
- to_numeric, MinElemwise-method
(MinElemwise-class), 226
- to_numeric, MinEntries-method
(MinEntries-class), 227
- to_numeric, MulExpression-method
(%*, Expression, Expression-method),
348

- to_numeric, Multiply-method
(Multiply-class), [236](#)
- to_numeric, Norm1-method (Norm1-class),
[243](#)
- to_numeric, NormInf-method
(NormInf-class), [247](#)
- to_numeric, NormNuc-method
(NormNuc-class), [249](#)
- to_numeric, OneMinusPos-method
(OneMinusPos-class), [254](#)
- to_numeric, PfEigenvalue-method
(PfEigenvalue-class), [260](#)
- to_numeric, Pnorm-method (Pnorm-class),
[263](#)
- to_numeric, Power-method (Power-class),
[266](#)
- to_numeric, ProdEntries-method
(ProdEntries-class), [274](#)
- to_numeric, Promote-method
(Promote-class), [278](#)
- to_numeric, QuadForm-method
(QuadForm-class), [285](#)
- to_numeric, QuadOverLin-method
(QuadOverLin-class), [287](#)
- to_numeric, Real-method (Real-class), [292](#)
- to_numeric, Reshape-method
(Reshape-class), [297](#)
- to_numeric, SigmaMax-method
(SigmaMax-class), [306](#)
- to_numeric, SpecialIndex-method
([, Expression, missing, missing, ANY-method),
[346](#)
- to_numeric, SumEntries-method
(SumEntries-class), [318](#)
- to_numeric, SumLargest-method
(SumLargest-class), [319](#)
- to_numeric, Trace-method (Trace-class),
[328](#)
- to_numeric, Transpose-method
(Transpose-class), [329](#)
- to_numeric, UnaryOperator-method
(UnaryOperator-class), [332](#)
- to_numeric, UpperTri-method
(UpperTri-class), [335](#)
- to_numeric, VStack-method
(VStack-class), [342](#)
- to_numeric, Wrap-method (Wrap-class), [343](#)
- total_variation (tv), [331](#)
- TotalVariation, [327](#)
- tr (matrix_trace), [218](#)
- Trace, [329](#)
- Trace (Trace-class), [328](#)
- trace (matrix_trace), [218](#)
- Trace-class, [328](#)
- Transpose, [330](#)
- Transpose (Transpose-class), [329](#)
- Transpose-class, [329](#)
- tri_to_full, [331](#)
- triu_to_full, [330](#)
- tv, [331](#)
- UnaryOperator, [332](#)
- UnaryOperator (UnaryOperator-class), [332](#)
- UnaryOperator-class, [332](#)
- unpack_results, [333](#)
- unpack_results, Problem-method
(Problem-class), [270](#)
- updated_scaled_lower_tri, [334](#)
- upper_tri, [336](#)
- UpperTri, [335](#)
- UpperTri (UpperTri-class), [335](#)
- UpperTri-class, [335](#)
- validate_args, [337](#)
- validate_args, Atom-method (Atom-class),
[41](#)
- validate_args, AxisAtom-method
(AxisAtom-class), [43](#)
- validate_args, Conv-method (Conv-class),
[85](#)
- validate_args, Elementwise-method
(Elementwise-class), [136](#)
- validate_args, HStack-method
(HStack-class), [174](#)
- validate_args, Huber-method
(Huber-class), [176](#)
- validate_args, Kron-method (Kron-class),
[188](#)
- validate_args, LambdaMax-method
(LambdaMax-class), [190](#)
- validate_args, LambdaSumLargest-method
(LambdaSumLargest-class), [192](#)
- validate_args, LogDet-method
(LogDet-class), [205](#)
- validate_args, MatrixFrac-method
(MatrixFrac-class), [214](#)

- validate_args, Pnorm-method
(Pnorm-class), [263](#)
- validate_args, QuadForm-method
(QuadForm-class), [285](#)
- validate_args, QuadOverLin-method
(QuadOverLin-class), [287](#)
- validate_args, Reshape-method
(Reshape-class), [297](#)
- validate_args, SumLargest-method
(SumLargest-class), [319](#)
- validate_args, Trace-method
(Trace-class), [328](#)
- validate_args, UpperTri-method
(UpperTri-class), [335](#)
- validate_args, VStack-method
(VStack-class), [342](#)
- validate_val, [337](#)
- validate_val, Leaf-method (Leaf-class),
[196](#)
- value (value-methods), [338](#)
- value, Atom-method (Atom-class), [41](#)
- value, CallbackParam-method
(CallbackParam-class), [46](#)
- value, Constant-method (Constant-class),
[77](#)
- value, Expression-method
(Expression-class), [148](#)
- value, Leaf-method (Leaf-class), [196](#)
- value, Objective-method
(Objective-class), [253](#)
- value, Parameter-method
(Parameter-class), [258](#)
- value, Problem-method (Problem-class),
[270](#)
- value, Variable-method (Variable-class),
[338](#)
- value-methods, [338](#)
- value<- (value-methods), [338](#)
- value<-, Leaf-method (Leaf-class), [196](#)
- value<-, Parameter-method
(Parameter-class), [258](#)
- value<-, Problem-method (Problem-class),
[270](#)
- value_impl, Atom-method (Atom-class), [41](#)
- Variable, [47](#), [153](#), [154](#), [178](#), [198](#), [238](#), [273](#),
[282](#), [333](#), [338](#), [339](#)
- Variable (Variable-class), [338](#)
- Variable-class, [338](#)
- variables (expression-parts), [152](#)
- variables, Canonical-method
(Canonical-class), [46](#)
- variables, Leaf-method (Leaf-class), [196](#)
- variables, Problem-method
(Problem-class), [270](#)
- variables, Variable-method
(Variable-class), [338](#)
- vec, [340](#)
- vectorized_lower_tri_to_mat, [340](#)
- violation (residual-methods), [300](#)
- violation, Constraint-method
(Constraint-class), [81](#)
- VStack, [342](#)
- VStack (VStack-class), [342](#)
- vstack, [341](#)
- VStack-class, [342](#)
- Wrap, [343](#)
- Wrap (Wrap-class), [343](#)
- Wrap-class, [343](#)
- ZeroConstraint, [344](#)
- ZeroConstraint-class, [344](#)