

Package ‘CatEncoders’

July 21, 2025

Type Package

Title Encoders for Categorical Variables

Version 0.1.1

Author nl zhang

Maintainer nl zhang <setseed2016@gmail.com>

Description

Contains some commonly used categorical variable encoders, such as 'LabelEncoder' and 'OneHotEncoder'. Inspired by the encoders implemented in Python 'sklearn.preprocessing' package (see <<http://scikit-learn.org/stable/modules/preprocessing.html>>).

License GPL-2 | GPL-3

LazyData TRUE

Imports Matrix (>= 1.2-6), data.table (>= 1.9.6), methods

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2017-03-08 08:22:03

Contents

inverse.transform	2
LabelEncoder-class	3
LabelEncoder.Character-class	3
LabelEncoder.Factor-class	3
LabelEncoder.fit	4
LabelEncoder.Numeric-class	5
OneHotEncoder-class	5
OneHotEncoder.fit	5
transform	6

Index	8
--------------	----------

inverse.transform	<i>inverse.transform transforms an integer vector back to the original vector</i>
-------------------	---

Description

inverse.transform transforms an integer vector back to the original vector

Usage

```
inverse.transform(enc, z)

## S4 method for signature 'LabelEncoder,numeric'
inverse.transform(enc, z)
```

Arguments

enc	A fitted LabelEncoder
z	A vector of integers

Value

A vector of characters, factors or numerics.

Examples

```
# character vector y
y <- c('a','d','e',NA)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,c('d','d',NA,'f'))
print(z)
inverse.transform(lenc,z)

# factor vector y
y <- factor(c('a','d','e',NA),exclude=NULL)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,factor(c('a','d',NA,'f'))))
inverse.transform(lenc,z)

# numeric vector y
set.seed(123)
y <- c(1:10,NA)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
newy <- sample(c(1:10,NA),5)
print(newy)
z <-transform(lenc,newy)
inverse.transform(lenc, z)
```

LabelEncoder-class	<i>An S4 class to represent a LabelEncoder.</i>
--------------------	---

Description

An S4 class to represent a LabelEncoder.

Slots

type A character to denote the input type, either character, factor or numeric
mapping A data.frame to store the mapping table

LabelEncoder.Character-class	<i>An S4 class to represent a LabelEncoder with character input.</i>
------------------------------	--

Description

An S4 class to represent a LabelEncoder with character input.

Slots

classes A character vector to store the unique values of classes

LabelEncoder.Factor-class	<i>An S4 class to represent a LabelEncoder with factor input.</i>
---------------------------	---

Description

An S4 class to represent a LabelEncoder with factor input.

Slots

classes A factor vector to store the unique values of classes

LabelEncoder.fit	<i>LabelEncoder.fit fits a LabelEncoder object</i>
------------------	--

Description

LabelEncoder.fit fits a LabelEncoder object

Usage

```
LabelEncoder.fit(y)
```

Arguments

y A vector of characters, factors, or numerics, which can include NA as well

Value

Returns an object of S4 class LabelEncoder.

Examples

```
# factor y
y <- factor(c('a','d','e',NA),exclude=NULL)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,factor(c('d','d',NA,'f')))
print(z)

# character y
y <- c('a','d','e',NA)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,c('d','d',NA,'f'))
print(z)

# numeric y
set.seed(123)
y <- sample(c(1:10,NA),5)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,sample(c(1:10,NA),5))
print(z)
```

LabelEncoder.Numeric-class

An S4 class to represent a LabelEncoder with numeric input.

Description

An S4 class to represent a LabelEncoder with numeric input.

Slots

classes A numeric vector to store the unique values of classes

OneHotEncoder-class

An S4 class to represent a OneHotEncoder

Description

An S4 class to represent a OneHotEncoder

Slots

n_columns An integer value to store the number of columns of input data

n_values A numeric vector to store the number of unique values in each column of input data

column_encoders A list that stores the LabelEncoder for each column of input data

OneHotEncoder.fit

OneHotEncoder.fit fits an OneHotEncoder object

Description

OneHotEncoder.fit fits an OneHotEncoder object

Usage

```
OneHotEncoder.fit(X)
```

Arguments

X A matrix or data.frame, which can include NA

Value

Returns an object of S4 class OneHotEncoder

Examples

```
# matrix input
X1 <- matrix(c(0, 1, 0, 1, 0, 1, 2, 0, 3, 0, 1, 2),c(4,3),byrow=FALSE)
oenc <- OneHotEncoder.fit(X1)
z <- transform(oenc,X1,sparse=TRUE)
# return a sparse matrix
print(z)

# data.frame
X2 <- cbind(data.frame(X1),X4=c('a','b','d',NA),X5=factor(c(1,2,3,1)))
oenc <- OneHotEncoder.fit(X2)
z <- transform(oenc,X2,sparse=FALSE)
# return a dense matrix
print(z)
```

transform

*transform transforms a new data set using the fitted encoder***Description**

transform transforms a new data set using the fitted encoder

Usage

```
transform(enc, ...)
```

S4 method for signature 'LabelEncoder.Numeric'

```
transform(enc, y)
```

S4 method for signature 'LabelEncoder.Character'

```
transform(enc, y)
```

S4 method for signature 'LabelEncoder.Factor'

```
transform(enc, y)
```

S4 method for signature 'OneHotEncoder'

```
transform(enc, X, sparse = TRUE,
  new.feature.error = TRUE)
```

Arguments

enc	A fitted encoder, i.e., LabelEncoder or OneHotEncoder
...	Additional argument list
y	A vector of character, factor or numeric values
X	A data.frame or matrix
sparse	If TRUE then return a sparse matrix, default = TRUE

`new.feature.error`

If TRUE then throw an error for new feature values; otherwise the new feature values are ignored, default = TRUE

Value

If `enc` is an `OneHotEncoder`, the returned value is a sparse or dense matrix. If `enc` is a `LabelEncoder`, the returned value is a vector.

Examples

```
# matrix X
X1 <- matrix(c(0, 1, 0, 1, 0, 1, 2, 0, 3, 0, 1, 2),c(4,3),byrow=FALSE)
oenc <- OneHotEncoder.fit(X1)
z <- transform(oenc,X1,sparse=TRUE)
# return a sparse matrix
print(z)

# data.frame X
X2 <- cbind(data.frame(X1),X4=c('a','b','d',NA),X5=factor(c(1,2,3,1)))
oenc <- OneHotEncoder.fit(X2)
z <- transform(oenc,X2,sparse=FALSE)
# return a dense matrix
print(z)

# factor vector y
y <- factor(c('a','d','e',NA),exclude=NULL)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,factor(c('d','d',NA,'f'))))
print(z)

# character vector y
y <- c('a','d','e',NA)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,c('d','d',NA,'f'))
print(z)

# numeric vector y
set.seed(123)
y <- sample(c(1:10,NA),5)
lenc <- LabelEncoder.fit(y)
# new values are transformed to NA
z <- transform(lenc,sample(c(1:10,NA),5))
print(z)
```

Index

`inverse.transform`, [2](#)
`inverse.transform`, `LabelEncoder`, numeric-method
 (`inverse.transform`), [2](#)

`LabelEncoder`-class, [3](#)
`LabelEncoder.Character`, character-method
 (`transform`), [6](#)
`LabelEncoder.Character`-class, [3](#)
`LabelEncoder.Factor`-class, [3](#)
`LabelEncoder.fit`, [4](#)
`LabelEncoder.Numeric`, numeric-method
 (`transform`), [6](#)
`LabelEncoder.Numeric`-class, [5](#)

`OneHotEncoder`-class, [5](#)
`OneHotEncoder.fit`, [5](#)

`transform`, [6](#)
`transform`, (`transform`), [6](#)
`transform`, `LabelEncoder.Character`-method
 (`transform`), [6](#)
`transform`, `LabelEncoder.Factor`, factor-method
 (`transform`), [6](#)
`transform`, `LabelEncoder.Factor`-method
 (`transform`), [6](#)
`transform`, `LabelEncoder.Numeric`-method
 (`transform`), [6](#)
`transform`, `OneHotEncoder`, Any, logical-method
 (`transform`), [6](#)
`transform`, `OneHotEncoder`-method
 (`transform`), [6](#)