

Package ‘CongressData’

July 21, 2025

Type Package

Title A Functional Tool for 'CongressData'

Version 1.5.5

Description A tool that imports, subsets, and exports the 'CongressData' dataset. 'CongressData' contains approximately 800 variables concerning all US congressional districts with data back to 1789. The dataset tracks district characteristics, members of Congress, and the political behavior of those members. Users with only a basic understanding of R can subset this data across multiple dimensions, export their search results, identify the citations associated with their searches, and more.

License GPL-3

Encoding UTF-8

Language en-US

RoxygenNote 7.3.1

Depends R (>= 3.50)

Imports stringr, dplyr, rlang, fst, curl, tidyselect

NeedsCompilation no

Author Caleb Lucas [aut, cre],
Ben Yoel [ctb]

Maintainer Caleb Lucas <calebjlucas@gmail.com>

Repository CRAN

Date/Publication 2025-06-19 10:10:02 UTC

Contents

get_congress_version	2
get_cong_data	2
get_var_info	3

Index	5
--------------	----------

get_congress_version	<i>Get your local version of CongressData</i>
----------------------	---

Description

get_congress_version prints the current version of CongressData available through the package. It takes no arguments.

Usage

```
get_congress_version()
```

Value

No return value, called for side effects.

get_cong_data	<i>Load CongressData into the R environment</i>
---------------	---

Description

get_cong_data loads either a full or subsetting version of the full CongressData dataset into the R environment as a dataframe.

Usage

```
get_cong_data(states = NULL, related_to = "", years = NULL)
```

Arguments

states	Default is NULL. If left blank, returns all states. Takes a string or vector of strings of state names.
related_to	Default is "". Provide a string to search a variable's name, short/long descriptions from the codebook, and its citation for non-exact matches of a search term. For example, searching 'tax' will return variables with words like 'taxes' and 'taxable' in any of those columns.
years	Default is NULL. If left blank, returns all years. Input can be a single year (e.g. 2001) or a two year that represent the first and last that you want in the outputted dataframe (such as c(1989, 2001)).

Value

An object of type tibble containing CongressData. The tibble has columns corresponding to variables in the dataset, and rows corresponding to observations that match the filtering criteria specified by the states, related_to, and years parameters.

get_var_info*Get information regarding CongressData variables*

Description

get_var_info retrieves information regarding variables in the CongressData dataset. The information available includes: the years each variable is observed in the data; a short and long description of each variable; and the source and citation/s for each variable. Citations are available in both bibtex and plain text.

Usage

```
get_var_info(var_names = NULL, related_to = NULL)
```

Arguments

var_names	Default is NULL. Takes a character string. If left blank the function does not subset by variable name. Note that this searches variable names, it does not subset by the specific string you provide. So "over65" will return a variable called 'over65' along with another called 'percent_over65'.
related_to	Default is NULL. Takes a character string. If the user supplies a character string, the function searches the other relevant fields (variable name, short/long description, and source) for string matches. Not case sensitive.

Details

Specifying no arguments returns all the information for all the variables in the CongressData dataset.

Value

A tibble with information about variables in the CongressData dataset. The tibble contains the following columns:

- variable: The name of the variable.
- years: The years the variable is observed.
- short_desc: A short description of the variable.
- long_desc: A long description of the variable.
- source: The source of the data.
- citation: The citation for the data, available in bibtex and plain text.

The tibble is filtered based on the provided var_names and related_to parameters.

Examples

```
# returns all variable information  
get_var_info()
```

```
# match var names that contain "over65" - note this returns multiple variables  
get_var_info(var_names = "over65")
```

```
get_var_info(related_to = c("pop", "femal"))
```

Index

`get_cong_data`, [2](#)
`get_congress_version`, [2](#)
`get_var_info`, [3](#)