

Package ‘DQAgui’

July 21, 2025

Title Graphical User Interface for Data Quality Assessment

Version 0.2.6

Date 2025-02-07

Description A graphical user interface (GUI) to the functions implemented in the R package 'DQAstats'. Publication: Mang et al. (2021) [doi:10.1186/s12911-022-01961-z](https://doi.org/10.1186/s12911-022-01961-z).

License GPL-3

URL <https://github.com/miracum/dqa-dqagui>

BugReports <https://github.com/miracum/dqa-dqagui/issues>

Imports data.table, daterangepicker, DIZtools (>= 1.0.1), DIZutils (>= 0.1.3), DQAstats (>= 0.3.7), DT, jsonlite, knitr, lubridate, magrittr, parsedate, shiny, shinyalert, shinydashboard, shinyFiles, shinyjs, shinyWidgets, utils, waiter

Suggests lintr, testthat (>= 3.0.0)

Config/testthat/edition 3

Config/testthat/parallel false

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Lorenz A. Kapsner [cre, aut] (ORCID: <https://orcid.org/0000-0003-1866-860X>),
Jonathan M. Mang [aut] (ORCID: <https://orcid.org/0000-0003-0518-4710>),
Helene Köster [ctb],
MIRACUM - Medical Informatics in Research and Care in University
Medicine [fnd],
Universitätsklinikum Erlangen [cph]

Maintainer Lorenz A. Kapsner <lorenz.kapsner@gmail.com>

Repository CRAN

Date/Publication 2025-02-07 19:40:05 UTC

Contents

button_send_datamap	2
check_load_data_button	3
feedback_txt	3
get_db_settings	4
launch_app	5
module_atemp_pl_server	6
module_atemp_pl_ui	7
module_completeness_server	7
module_completeness_ui	8
module_config_server	9
module_config_ui	10
module_dashboard_server	11
module_dashboard_ui	12
module_descriptive_server	12
module_descriptive_ui	13
module_differences_server	14
module_differences_ui	15
module_log_server	16
module_log_ui	17
module_mdr_server	17
module_mdr_ui	18
module_report_server	19
module_report_ui	20
module_uniq_plaus_server	21
module_uniq_plaus_ui	22
set_target_equal_to_source	22
show_failure_alert	23
test_connection_button_clicked	23
validate_inputs	24
Index	25

button_send_datamap	<i>button_send_datamap</i>
---------------------	----------------------------

Description

This function is an exported wrapper around the actual function to send the datamap. This actual function can be customized by the user.

Usage

button_send_datamap(rv)

Arguments

rv The global rv object. rv\$datamap needs to be valid.

Value

This functions is used to trigger logic when clicking the "Send Datamap" button on the dashboard (default: triggers the composing of an email by making use of the java-script command `window.open('mailto: ...')`). When customizing DQAgui, the function `button_send_datamap` can be overwritten in the namespace to trigger any other logic, wanted by the user.

Examples

```
if (interactive()) {
  button_send_datamap(rv=rv)
}
```

`check_load_data_button`

Evaluates whether the load-data button needs to be shown or not.

Description

If there is a valid source system and a valid target system (this is also the case if the user set `target == source`), the result of this function will be `TRUE` and the button will be displayed via shinyjs. Otherwise the result is `FALSE` and the button will be hidden. This function also displays (or hides) the variables which can be assessed.

Usage

```
check_load_data_button(rv, session)
```

Arguments

<code>rv</code>	The global 'reactiveValues()' object, defined in <code>server.R</code>
<code>session</code>	Shiny session object

<code>feedback_txt</code>	<i>This function is used in the config-tab and displays the selected system to the user.</i>
---------------------------	--

Description

This function is used in the config-tab and displays the selected system to the user.

Usage

```
feedback_txt(system, type)
```

Arguments

system (String) e.g. "i2b2", "OMOP" or "CSV"
 type (String) "source" or "target"

Value

String containing the input params in a proper manner

get_db_settings	<i>get_db_settings</i>
-----------------	------------------------

Description

get_db_settings

Usage

```
get_db_settings(input, target = TRUE, db_type, displayname_gui, rv)
```

Arguments

input Shiny server input object.
 target A boolean (default: TRUE).
 db_type (String) "postgres" or "oracle".
 displayname_gui (String) "i2b2 (Prod)"
 rv The global 'reactiveValues()' object, defined in server.R

Value

This functions returns a data table of key-value pairs for the database settings, which are parsed from the respective config tab from the shiny application.

Examples

```
if (interactive()) {
  get_db_settings(
    input = input,
    target = TRUE,
    db_type = "postgres"
  )
}
```

launch_app

Launch the DQA graphical user interface (GUI)

Description

Launch the DQA graphical user interface (GUI)

Usage

```
launch_app(
  port = 3838,
  utils_path = system.file("demo_data/utilities", package = "DQAstats"),
  mdr_filename = "mdr_example_data.csv",
  logfile_dir = tempdir(),
  demo_usage = FALSE
)
```

Arguments

port	The port, the MIRACUM DQA Tool is running on (default: 3838)
utils_path	The path to the utilities-folder, containing the metadata repository files (mdr.csv inside the folder MDR), JSON files with SQL statements (inside the folder SQL), config files for the database connection (settings_default.yml) and the email address used for the data map (email.yml), a JSON file containing site names (inside the folder MISC) and a markdown template to create the PDF report (DQA_report.Rmd inside the folder RMD).
mdr_filename	The filename of the mdr (e.g. "mdr_example_data.csv").
logfile_dir	Is the absolute path to the directory where the logfile will be stored. If not path is provided the tempdir() will be used.
demo_usage	A boolean. If TRUE, a box is shown on the dashboard with further instructions on how to use / configure the tool.

Value

Executing this function returns a DQAgui shiny application.

Examples

```
if (interactive()) {
  launch_app()
}
```

`module_atemp_pl_server`*module_atemp_pl_server*

Description`module_atemp_pl_server`**Usage**`module_atemp_pl_server(input, output, session, rv, input_re)`**Arguments**

<code>input</code>	Shiny server input object
<code>output</code>	Shiny server output object
<code>session</code>	Shiny session object
<code>rv</code>	The global 'reactiveValues()' object, defined in server.R
<code>input_re</code>	The Shiny server input object, wrapped into a reactive expression: <code>input_re = reactive({input})</code>

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_atemp_pl_server,  
    "moduleAtemporalPlausibilities",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_atemp_pl_ui	<i>module_atemp_pl_ui</i>
--------------------	---------------------------

Description

module_atemp_pl_ui

Usage

```
module_atemp_pl_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "atemp_plausi",  
      module_atemp_pl_ui(  
        "moduleAtemporalPlausibilities"  
      )  
    )  
  )  
}
```

module_completeness_server	<i>module_completeness_server</i>
----------------------------	-----------------------------------

Description

module_completeness_server

Usage

```
module_completeness_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: <code>input_re = reactive({input})</code>

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_completeness_server,  
    "moduleCompleteness",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_completeness_ui

module_completeness_ui

Description

module_completeness_ui

Usage

```
module_completeness_ui(id)
```

Arguments

id	A character. The identifier of the shiny object
----	---

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "completeness",  
      module_completeness_ui(  
        "moduleCompleteness"  
      )  
    )  
  )  
}
```

module_config_server *module_config_server*

Description

module_config_server

Usage

```
module_config_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_config_server,  
    "moduleConfig",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_config_ui	<i>module_config_ui</i>
------------------	-------------------------

Description

module_config_ui

Usage

```
module_config_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "config",  
      module_config_ui(  
        "moduleConfig"  
      )  
    )  
  )  
}
```

module_dashboard_server
module_dashboard_server

Description

module_dashboard_server

Usage

```
module_dashboard_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_dashboard_server,  
    "moduleDashboard",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_dashboard_ui *module_dashboard_ui*

Description

module_dashboard_ui

Usage

```
module_dashboard_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "dashboard",  
      module_dashboard_ui(  
        "moduleDashboard"  
      )  
    )  
  )  
}
```

module_descriptive_server
 module_descriptive_server

Description

module_descriptive_server

Usage

```
module_descriptive_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_descriptive_server,  
    "moduleDescriptive",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_descriptive_ui *module_descriptive_ui*

Description

module_descriptive_ui

Usage

```
module_descriptive_ui(id)
```

Arguments

id	A character. The identifier of the shiny object
----	---

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "descriptive",  
      module_descriptive_ui(  
        "moduleDescriptive"  
      )  
    )  
  )  
}
```

module_differences_server
module_differences_server

Description

module_differences_server

Usage

module_differences_server(input, output, session, rv, input_re)

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_differences_server,  
    "moduleDifferences",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_differences_ui *module_differences_ui*

Description

module_differences_ui

Usage

```
module_differences_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "differences",  
      module_differences_ui(  
        "moduleDifferences"  
      )  
    )  
  )  
}
```

module_log_server	<i>module_log_server</i>
-------------------	--------------------------

Description

module_log_server

Usage

```
module_log_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_log_server,  
    "moduleLogging",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_log_ui	<i>module_log_ui</i>
---------------	----------------------

Description

module_log_ui

Usage

```
module_log_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {
  shinydashboard::tabItems(
    shinydashboard::tabItem(
      tabName = "logging",
      module_log_ui(
        "moduleLogging"
      )
    )
  )
}
```

module_mdr_server	<i>module_mdr_server</i>
-------------------	--------------------------

Description

module_mdr_server

Usage

```
module_mdr_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {
  rv <- list()
  shiny::callModule(
    module_mdr_server,
    "moduleMDR",
    rv = rv,
    input_re = reactive(input)
  )
}
```

module_mdr_ui

module_mdr_ui

Description

module_mdr_ui

Usage

```
module_mdr_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  shinydashboard::tabItems(  
    shinydashboard::tabItem(  
      tabName = "mdr",  
      module_mdr_ui(  
        "moduleMDR"  
      )  
    )  
  )  
}
```

module_report_server *module_report_server*

Description

module_report_server

Usage

module_report_server(input, output, session, rv, input_re)

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```

if (interactive()) {
  rv <- list()
  shiny::callModule(
    module_report_server,
    "moduleReport",
    rv = rv,
    input_re = reactive(input)
  )
}

```

module_report_ui	<i>module_report_ui</i>
------------------	-------------------------

Description

module_report_ui

Usage

```
module_report_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```

if (interactive()) {
  shinydashboard::tabItems(
    shinydashboard::tabItem(
      tabName = "report",
      module_report_ui(
        "moduleReport"
      )
    )
  )
}

```

```
module_uniq_plaus_server  
  module_uniq_plaus_server
```

Description

module_uniq_plaus_server

Usage

```
module_uniq_plaus_server(input, output, session, rv, input_re)
```

Arguments

input	Shiny server input object
output	Shiny server output object
session	Shiny session object
rv	The global 'reactiveValues()' object, defined in server.R
input_re	The Shiny server input object, wrapped into a reactive expression: input_re = reactive({input})

Value

The function returns a shiny server module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {  
  rv <- list()  
  shiny::callModule(  
    module_uniq_plaus_server,  
    "moduleUniquenessPlausibilities",  
    rv = rv,  
    input_re = reactive(input)  
  )  
}
```

module_uniq_plaus_ui	<i>module_uniq_plaus_ui</i>
----------------------	-----------------------------

Description

module_uniq_plaus_ui

Usage

```
module_uniq_plaus_ui(id)
```

Arguments

id A character. The identifier of the shiny object

Value

The function returns a shiny ui module.

See Also

<https://shiny.rstudio.com/articles/modules.html>

Examples

```
if (interactive()) {
  shinydashboard::tabItems(
    shinydashboard::tabItem(
      tabName = "uniq_plausis",
      module_uniq_plaus_ui(
        "moduleUniquenessPlausibilities"
      )
    )
  )
}
```

set_target_equal_to_source

This function is called when the user clicks on the button

Description

"Set target == source". It sets target settings = source settings.

Usage

```
set_target_equal_to_source(rv)
```

Arguments

rv The global 'reactiveValues()' object, defined in server.R

show_failure_alert *Shows an error alert modal with the hint to look into the logfile.*

Description

See title.

Usage

```
show_failure_alert(what_failed)
```

Arguments

what_failed Short description of what failed. Like: "Getting the data failed." '

Value

Nothing - Just shows the alert modal.

test_connection_button_clicked
Checks if an connection can be established to the system.

Description

After the button "Check connection" is pressed in the GUI, this function will be called and tries to connect to this system and feedbacks the result to the user. If the connection is successfully established, the button will be disabled and this connection will be stored as valid for the given source/target system.

Usage

```
test_connection_button_clicked(
  rv,
  source_target,
  db_type,
  input,
  output,
  session
)
```

Arguments

rv	The global 'reactiveValues()' object, defined in server.R
source_target	(String) "source" or "target"
db_type	(String) "postgres" or "oracle"
input	Shiny server input object
output	Shiny server output object
session	Shiny session object

Value

true if the connection could be established and false otherwise (also if an error occurred)

validate_inputs	<i>This function checks if all necessary input parameters for source and target exist and are valid.</i>
-----------------	--

Description

This function checks if all necessary input parameters for source and target exist and are valid.

Usage

```
validate_inputs(rv, input, output, session)
```

Arguments

rv	The global 'reactiveValues()' object, defined in server.R
input	Shiny server input object
output	Shiny server output object
session	Shiny session object

Index

button_send_datamap, [2](#)

check_load_data_button, [3](#)

feedback_txt, [3](#)

get_db_settings, [4](#)

launch_app, [5](#)

module_atemp_pl_server, [6](#)

module_atemp_pl_ui, [7](#)

module_completeness_server, [7](#)

module_completeness_ui, [8](#)

module_config_server, [9](#)

module_config_ui, [10](#)

module_dashboard_server, [11](#)

module_dashboard_ui, [12](#)

module_descriptive_server, [12](#)

module_descriptive_ui, [13](#)

module_differences_server, [14](#)

module_differences_ui, [15](#)

module_log_server, [16](#)

module_log_ui, [17](#)

module_mdr_server, [17](#)

module_mdr_ui, [18](#)

module_report_server, [19](#)

module_report_ui, [20](#)

module_uniq_plaus_server, [21](#)

module_uniq_plaus_ui, [22](#)

set_target_equal_to_source, [22](#)

show_failure_alert, [23](#)

test_connection_button_clicked, [23](#)

validate_inputs, [24](#)