

Package ‘EcoMetrics’

July 21, 2025

Title Econometrics Model Building

Version 0.1.1

Description An intuitive and user-friendly package designed to aid undergraduate students in understanding and applying econometric methods in their studies,
Tailored specifically for Econometrics and Regression Modeling courses, it provides a practical toolkit for modeling and analyzing econometric data with detailed inference capabilities.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports car, forecast, ggplot2, insight, lmtest, moments, stats,
tibble, tseries

Depends R (>= 2.10)

LazyData true

Suggests knitr

NeedsCompilation no

Author Mutua Kilai [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6290-9728>>)

Maintainer Mutua Kilai <kilaimutua@gmail.com>

Repository CRAN

Date/Publication 2025-01-28 16:30:06 UTC

Contents

ACF_PLOT	2
autocorrelation_assumption	3
best_arma	3
check_model_sig	4
check_stationarity	5
eduperform	5
fit_arma	6
get_coefficients_variance	7
get_confint	7

get_significant_predictors	8
heteroscedasticity_assumption	9
keconomy	10
multicollinearity_assumption	10
normality_assumption	11
ols_model	12
ols_model_sig	12
ols_model_stats	13
PACF_PLOT	14
predict_dep_var	14
select_optimal_model	15
Index	17

ACF_PLOT	<i>Plots ACF of a univariate time series</i>
----------	--

Description

Plots ACF of a univariate time series

Usage

ACF_PLOT(x, lag.max = NULL)

Arguments

- x numeric vector
- lag.max maximum lag to calculate the acf

Value

a plot of the acf vs lag

Author(s)

Mutua Kilai

Examples

```
data(keconomy)
attach(keconomy)
ACF_PLOT(UR)
```

`autocorrelation_assumption`*Check model for residual independence*

Description

Checks model for independence of residuals

Usage

```
autocorrelation_assumption(model)
```

Arguments

`model` A lm object

Value

returns the p-value for the test

Author(s)

Mutua Kilai

Examples

```
model <- lm(pi ~ hs + ps, data = eduperform)
autocorrelation_assumption(model)
```

`best_arima`*Select Optimal Model based on BIC*

Description

Select Optimal Model based on BIC

Usage

```
best_arima(data, max_p = 5, max_d = 2, max_q = 5)
```

Arguments

`data` A univariate ts object
`max_p` Maximum AR order
`max_d` Maximum differencing order
`max_q` Maximum MA order

Value

A list containing the optimal model results and the BIC value

Examples

```
data(keconomy)
attach(keconomy)
best_arima(UR, max_p = 5, max_d = 2, max_q = 5)
```

`check_model_sig`*Checking Overall Model Significance*

Description

Checking Overall Model Significance

Usage

```
check_model_sig(data, y, x)
```

Arguments

<code>data</code>	A data frame containing the variables to use
<code>y</code>	The dependent variable
<code>x</code>	A set of independent variables

Value

p-value with a statement on whether the model is significant or not

Author(s)

Mutua Kilai

Examples

```
check_model_sig(data = eduperform, "pi", c("hs", "ps"))
```

check_stationarity	<i>Check Series for Weak Stationarity</i>
--------------------	---

Description

Check Series for Weak Stationarity

Usage

```
check_stationarity(x)
```

Arguments

x	A numeric vector or time series object
---	--

Value

p-value of the test

Author(s)

Mutua Kilai

Examples

```
data(keconomy)
attach(keconomy)
check_stationarity(UR)
```

eduperform	<i>Student Performance Data</i>
------------	---------------------------------

Description

Student performance dataset is a dataset designed to examine the factors influencing academic student performance.

Usage

```
eduperform
```

Format

eduperform:

A data frame with 10000 rows and 6 columns:

hs hours studied

ps previous score

ea extracurricula activities

sh sleep hours

sppp sample question paper practiced

pi performance Index ...

Source

<https://www.kaggle.com/datasets/nikhil7280/student-performance-multiple-linear-regression?resource=download>

fit_arma

Fit ARIMA models to univariate data

Description

Fit ARIMA models to univariate data

Usage

```
fit_arma(data, p, d, q)
```

Arguments

data	a univariate class object or a vector
p	AR order
d	differencing order
q	MA order

Value

A tibble containing the estimate, SE and p-value

Examples

```
data(keconomy)
attach(keconomy)
fit_arma(UR, p=2,d=0,q=3)
```

`get_coefficients_variance`*Get variance of the model coefficients*

Description

Get variance of the model coefficients

Usage

```
get_coefficients_variance(data, y, x)
```

Arguments

<code>data</code>	A data frame containing the variables to use
<code>y</code>	The dependent variable
<code>x</code>	A set of independent variables

Value

Tibble containing the variances

Author(s)

Mutua Kilai

Examples

```
get_coefficients_variance(data = eduperform, "pi", c("hs", "ps"))
```

`get_confint`*Confidence Intervals of Model Parameters*

Description

Confidence Intervals of Model Parameters

Usage

```
get_confint(data, y, x, level = 0.95)
```

Arguments

data	A data frame containing the variables to use
y	The dependent variable
x	A set of independent variables
level	level of significance can be 0.95, 0.90 etc. default is 0.95

Value

tibble containing the lower and upper confidence intervals

Author(s)

Mutua Kilai

Examples

```
get_confint(data = eduperform, "pi", c("hs", "ps"))
```

```
get_significant_predictors
```

Obtaining only significant predictors from a model

Description

Obtaining only significant predictors from a model

Usage

```
get_significant_predictors(data, y, x, alpha = 0.05)
```

Arguments

data	A data frame containing the variables to use
y	The dependent variable
x	A set of independent variables
alpha	desired alpha level. default is 0.05

Value

A tibble containing the significant predictors

Author(s)

Mutua Kilai

Examples

```
get_significant_predictors(data = eduperform, "pi", c("hs", "ps"))
```

heteroscedasticity_assumption	
<i>Checking heteroscedasticity assumption</i>	

Description

Checking heteroscedasticity assumption

Usage

```
heteroscedasticity_assumption(model)
```

Arguments

model	A lm model object
-------	-------------------

Value

The p-value of the test statistic.

Author(s)

Mutua Kilai

Examples

```
model <- lm(pi ~ hs + ps, data = eduperform)
heteroscedasticity_assumption(model)
```

`keconomy`*Kenya Unemployment Rate and GDP Growth rate for 1999-2023*

Description

Annual Time Series data for Kenyan Economy showing the unemployment rate and GDP Growth Rate.

Usage`keconomy`**Format**`keconomy:`

A data frame with 25 rows and 3 columns:

Year Year; from 1999 to 2023

UR Unemployment Rate

GR GDP Growth Rate

Source

<https://www.statista.com>

`multicollinearity_assumption`*Multicollinearity Assumption*

Description

Multicollinearity Assumption

Usage`multicollinearity_assumption(model)`**Arguments**

`model` A lm object

Value

A tibble containing the VIF and Tolerance values

Author(s)

Mutua Kilai

Examples

```
model <- lm(pi ~ hs + ps, data = eduperform)
multicollinearity_assumption(model)
```

normality_assumption *Checking normality of residuals*

Description

Checking normality of residuals

Usage

```
normality_assumption(model)
```

Arguments

model A lm model object

Value

The p-value of the test statistic.

Author(s)

Mutua Kilai

Examples

```
model <- lm(pi ~ hs + ps, data = eduperform)
normality_assumption(model)
```

`ols_model`*Fitting a simple or multiple linear regression*

Description

Fitting a simple or multiple linear regression

Usage

```
ols_model(data, y, x)
```

Arguments

<code>data</code>	A data frame containing the variables to use
<code>y</code>	The dependent variable
<code>x</code>	Set of independent variables

Value

A tibble of the coefficients, standard errors, t-statistics and p-value

Author(s)

Mutua Kilai

Examples

```
ols_model(data = eduperform, "pi", c("hs", "ps"))
```

`ols_model_sig`*F-statistic attributes*

Description

F-statistic attributes

Usage

```
ols_model_sig(data, y, x)
```

Arguments

<code>data</code>	A data frame containing the variables to use
<code>y</code>	The dependent variable
<code>x</code>	Set of independent variables

Value

A tibble containing the number of observations, F-Statistic, degrees of freedom and p-value

Author(s)

Mutua Kilai

Examples

```
ols_model_sig(data = eduperform, "pi", c("hs", "ps"))
```

ols_model_stats

Model Summary Statistics

Description

Model Summary Statistics

Usage

```
ols_model_stats(data, y, x)
```

Arguments

data	A data frame containing the variables to use
y	The dependent variable
x	The independent variables

Value

A tibble containing model summary stats: R-Squared, Adjusted R-Squared, AIC and BIC

Author(s)

Mutua Kilai

Examples

```
ols_model_stats(data = eduperform, "pi", c("hs", "ps"))
```

PACF_PLOT*Plots PACF of a univariate time series*

Description

Plots PACF of a univariate time series

Usage

```
PACF_PLOT(x, lag.max = NULL)
```

Arguments

x	a numeric vector
lag.max	maximum lag to calculate pacf

Value

a plot of the pacf vs lag

Author(s)

Mutua Kilai

Examples

```
data(keconomy)
attach(keconomy)
PACF_PLOT(UR)
```

predict_dep_var*Prediction from new observations*

Description

Prediction from new observations

Usage

```
predict_dep_var(model, new_data, level = 0.95)
```

Arguments

model	an lm object
new_data	data frame containing the new set of predictors
level	confidence level, default 0.95

Value

A tibble containing the predicted value and the upper and lower CI

Author(s)

Mutua Kilai

Examples

```
model <- lm(pi ~ hs + ps, data = eduperform)
newdata <- data.frame(hs = c(2,3,4), ps = c(23,24,12))
predict_dep_var(model, new_data = newdata, level = 0.95)
```

select_optimal_model	<i>Choosing Best Model Based on AIC, BIC and Adjusted R Squared</i>
----------------------	---

Description

Choosing Best Model Based on AIC, BIC and Adjusted R Squared

Usage

```
select_optimal_model(models, criterion = "AIC")
```

Arguments

models	a list of models
criterion	The criterion to select optimal model. Default AIC

Value

list of the results and best model

Author(s)

Mutua Kilai

Examples

```
data(eduperform)
model1 <- lm(pi ~ hs, data = eduperform)
model2 <- lm(pi ~ hs + ps, data = eduperform)
model3 <- lm(pi ~ hs + ps + sh, data = eduperform)
models <- list(model1, model2, model3)

select_optimal_model(models, criterion= "AIC")
```

Index

* datasets

eduperform, [5](#)

keconomy, [10](#)

ACF_PLOT, [2](#)

autocorrelation_assumption, [3](#)

best_arima, [3](#)

check_model_sig, [4](#)

check_stationarity, [5](#)

eduperform, [5](#)

fit_arima, [6](#)

get_coefficients_variance, [7](#)

get_confint, [7](#)

get_significant_predictors, [8](#)

heteroscedasticity_assumption, [9](#)

keconomy, [10](#)

multicollinearity_assumption, [10](#)

normality_assumption, [11](#)

ols_model, [12](#)

ols_model_sig, [12](#)

ols_model_stats, [13](#)

PACF_PLOT, [14](#)

predict_dep_var, [14](#)

select_optimal_model, [15](#)