

Package ‘FSK2R’

July 21, 2025

Type Package

Title An Interface Between the 'FSKX' Standard and 'R'

Version 0.1.3

Description Functions for importing, creating, editing and exporting 'FSK' files <<https://foodrisklabs.bfr.bund.de/fskx-food-safety-knowledge-exchange-format/>> using the 'R' programming environment. Furthermore, it enables users to run simulations contained in the 'FSK' files and visualize the results.

License GPL-3

Encoding UTF-8

Imports XML (>= 3.98), purrr (>= 0.2.4), dplyr (>= 0.7.8), tibble (>= 2.0.0), tidyr (>= 0.7.2), rlang (>= 0.3.0.1), readxl (>= 1.3.1), readtext (>= 0.7.1), zip (>= 2.0.4), xml2 (>= 1.2.0), rjson (>= 0.2.20), shiny (>= 1.3.2), tools (>= 3.5.3), utils (>= 3.5.3), R.utils (>= 2.9.0)

Suggests knitr (>= 1.9), rmarkdown (>= 1.12), testthat

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Alberto Garre [aut, cre],
Miguel de Alba Aparicio [aut],
Pablo S. Fernandez [aut],
Matthias Filter [aut]

Maintainer Alberto Garre <garre.alberto@gmail.com>

Repository CRAN

Date/Publication 2022-02-25 16:20:02 UTC

Contents

check_manifest_files	3
convert_metadata_to_lists	3

create_fsk	4
dataframe_to_list	5
export_fsk	5
export_manifest	6
export_metadata	6
export_modelmetadata	7
export_otherfiles	7
export_packages	8
export_readme	8
export_R_model	9
export_sbmlModel	9
export_simulation	10
export_visualization	10
find_packages	11
FSK_runner	11
get_background	12
get_general_info	12
get_modelmath	13
get_readme	14
get_scope	14
get_session_info	15
get_simulations	15
import_fsk	16
import_fsk_join	16
is.FSK2R	17
is_fsk_with_r	17
map_FSK_metadata	18
map_metadata_xml_template	18
metadata_list_to_fsk	19
n_simuls_fsk	19
read_fsk_json_metadata	20
read_fsk_manifest	20
read_fsk_metadata_excel	21
read_fsk_model	21
read_fsk_packages	22
read_fsk_rdf_metadata	22
read_fsk_readme	23
read_fsk_sim	23
read_other_files	24
read_R_model	24
read_visualization	25
run_all_simulations	25
run_simulation	26
set_new_simulation	26
set_readme	27
update_manifest	27

check_manifest_files	<i>Checks that the files defined in the manifest exist</i>
----------------------	--

Description

Checks that the files defined in the manifest exist

Usage

```
check_manifest_files(my_manifest, file_dir)
```

Arguments

my_manifest	A list with the contents of the manifest file.
file_dir	Path to the directory where all the files have been extracted.

convert_metadata_to_lists	<i>Fix the metadat so that it is lists</i>
---------------------------	--

Description

Fix the metadat so that it is lists

Usage

```
convert_metadata_to_lists(my_metadata)
```

Arguments

my_metadata	A list with the information in the GoogleSheet as generated by metadata_list_to_fsk.
-------------	--

create_fsk	<i>Creates an FSK model from an existing R script</i>
------------	---

Description

The model includes the R model. If provided as arguments, it also includes the visualization script and the README. Besides, it generates a typical model_metadata, as well as a simulation (without parameters). The manifest is left empty.

Usage

```
create_fsk(  
  r_model,  
  r_visualization = NULL,  
  readme = NULL,  
  other_files = NULL,  
  pkg_frame = NULL  
)
```

Arguments

r_model	character with the path to the R script with the model.
r_visualization	(optional) character with the path to the R script with the visualization.
readme	(optional) path to README file.
other_files	(optional) character vector with the path to additional
pkg_frame	(optional) data.frame with 2 columns 'Package' files required by the model.

Value

An instance of FSK2R.

Examples

```
model_path <- system.file("extdata", "model.r", package = "FSK2R")  
visualization_path <- system.file("extdata", "visualization.r", package = "FSK2R")  
FSK_from_R <- create_fsk(model_path, visualization_path)
```

dataframe_to_list	<i>Converts a dataframe to a list</i>
-------------------	---------------------------------------

Description

This function is needed to convert the output format of rjson to the one used by FSK2R.

Usage

```
dataframe_to_list(this_frame)
```

Arguments

this_frame	data.frame to convert to a list.
------------	----------------------------------

export_fsk	<i>Exports an object of FSK class as an .fskx file</i>
------------	--

Description

Exports an object of FSK class as an .fskx file

Usage

```
export_fsk(fsk_object, out_path, check = TRUE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

Value

None

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
class(my_fsk)
export_fsk(my_fsk, out_path=file.path(tempdir(), "out.fskx"))
```

export_manifest	<i>Functions for exporting the manifest of an FSK2R object</i>
-----------------	--

Description

Functions for exporting the manifest of an FSK2R object

Usage

```
export_manifest(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_metadata	<i>Function for exporting the metadata of an FSK2R object</i>
-----------------	---

Description

Function for exporting the metadata of an FSK2R object

Usage

```
export_metadata(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_modelmetadata *Functions for exporting the model metadata of an FSK2R object*

Description

Functions for exporting the model metadata of an FSK2R object

Usage

```
export_modelmetadata(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_otherfiles *Export other files*

Description

Export other files

Usage

```
export_otherfiles(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_packages	<i>Functions for exporting the packages of an FSK2R object</i>
-----------------	--

Description

Functions for exporting the packages of an FSK2R object

Usage

```
export_packages(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_readme	<i>Functions for exporting the README of an FSK2R object</i>
---------------	--

Description

Functions for exporting the README of an FSK2R object

Usage

```
export_readme(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_R_model	<i>Functions for exporting the R model of an FSK2R object</i>
----------------	---

Description

Functions for exporting the R model of an FSK2R object

Usage

```
export_R_model(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_sbmlModel	<i>Export the model.sbml</i>
------------------	------------------------------

Description

Export the model.sbml

Usage

```
export_sbmlModel(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_simulation	<i>Export the sim.sedml</i>
-------------------	-----------------------------

Description

Export the sim.sedml

Usage

```
export_simulation(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

export_visualization	<i>Functions for exporting the visualization script of an FSK2R object</i>
----------------------	--

Description

Functions for exporting the visualization script of an FSK2R object

Usage

```
export_visualization(fsk_object, out_path, check = FALSE)
```

Arguments

fsk_object	The instance of FSK2R to be exported.
out_path	Path where the file is to be saved.
check	Whether checks are made. TRUE by default.

find_packages	<i>Finds where packages are stored</i>
---------------	--

Description

Finds where packages are stored

Usage

```
find_packages(pckgs)
```

Arguments

pckgs	Character vector with packages names
-------	--------------------------------------

Value

A list of packages locations. If one is not present, a character(0).

FSK_runner	<i>Startup FSK runner</i>
------------	---------------------------

Description

Starts FSK runner within RStudio.

Usage

```
FSK_runner()
```

Value

None

get_background	Returns the background of an FSK object
----------------	---

Description

Returns the background of an FSK object

Usage

```
get_background(fsk_obj)
```

Arguments

fsk_obj	An object of class FSK2R
---------	--------------------------

Value

A nested list with the following entries:

- studyTitle
- studyDescription

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
get_background(my_fsk)
```

get_general_info	Returns the general info of an FSK object
------------------	---

Description

Returns the general info of an FSK object

Usage

```
get_general_info(fsk_obj)
```

Arguments

fsk_obj	An object of class FSK2R
---------	--------------------------

Value

A nested list with the following entries:

- name
- source
- identifier
- creationDate
- rights
- language
- software
- creators
- reference

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
get_general_info(my_fsk)
```

get_modelmath

Returns the model math of an FSK object

Description

Returns the model math of an FSK object

Usage

```
get_modelmath(fsk_obj)
```

Arguments

fsk_obj An object of class FSK2R

Value

A nested list with the following entries:

- parameter

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
get_modelmath(my_fsk)
```

get_readme	<i>Readme of an FSK object</i>
------------	--------------------------------

Description

Readme of an FSK object

Usage

```
get_readme(fsk_obj)
```

Arguments

fsk_obj	An object of class FSK2R
---------	--------------------------

Value

A character vector with the text in the README file.

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
get_readme(my_fsk)
```

get_scope	<i>Returns the scope of an FSK object</i>
-----------	---

Description

Returns the scope of an FSK object

Usage

```
get_scope(fsk_obj)
```

Arguments

fsk_obj	An object of class FSK2R
---------	--------------------------

Value

A nested list with the following entries:

- product
- hazard

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
get_scope(my_fsk)
```

get_session_info	<i>Extract session information</i>
------------------	------------------------------------

Description

Extract session information

Usage

```
get_session_info()
```

Value

A list with 3 elements: `r_version`, `platform` and `pckgs`. The latter is a `data.frame` with two columns: `package` and `version`.

get_simulations	<i>Returns a summary of the simulations of an FSK object (NULL)</i>
-----------------	---

Description

The function is not in-use. It is kept here for compatibility with older versions.

Usage

```
get_simulations(fsk_obj)
```

Arguments

<code>fsk_obj</code>	An object of class FSK2R
----------------------	--------------------------

import_fsk	<i>Import an FSK model into R</i>
------------	-----------------------------------

Description

Importst the file in file_path and transforms it into a list of class FSK2R.

Usage

```
import_fsk(file_path, check = FALSE)
```

Arguments

file_path	Path where the file is located.
check	Whether checks are made. FALSE by default.

Value

An instance of FSK2R.

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
get_general_info(my_fsk)
```

import_fsk_join	<i>Import of FSK with join node</i>
-----------------	-------------------------------------

Description

Join nodes are not yet supported by FSK2R. It just gives an error message when called.

Usage

```
import_fsk_join(file_path, check = TRUE)
```

Arguments

file_path	Path where the file is located.
check	Whether checks are made. FALSE by default.

`is.FSK2R`*Is it an instance of FSK2R?*

Description

Is it an instance of FSK2R?

Usage

```
is.FSK2R(object)
```

Arguments

`object` Object to check

Value

A logical vector

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
is.FSK2R(my_fsk)
```

`is_fsk_with_r`*Does the object have an R model?*

Description

Does the object have an R model?

Usage

```
is_fsk_with_r(fsk_obj)
```

Arguments

`fsk_obj` An object of class FSK2R

Value

A logical vector.

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
is_fsk_with_r(my_fsk)
```

map_FSK_metadata	<i>Map for the contents of the metadata</i>
------------------	---

Description

Maps the location (range) of different pieces of data within the Excel/Google Sheets template. It also includes the names of the sheets.

Usage

```
map_FSK_metadata(type_of_model = "generic", fsk_version = "1.04")
```

Arguments

`type_of_model` Type of model, as defined in the FSK-ML documentation. By default, 'generic'.
`fsk_version` Character stating the version of FSK-ML.

Value

A list with two components: the 'range' where each piece of information is stored and 'ws_name' with the name of the relevant sheet in the GoogleSheet template.

map_metadata_xml_template	<i>Map between the names used in the template and the xml</i>
---------------------------	---

Description

Returns a map of the names used within the sheets of the Excel/GoogleSheets template and the ones in metadata.json.

Usage

```
map_metadata_xml_template()
```

metadata_list_to_fsk	<i>From read_fsk_metadata_XX to FSK2R format</i>
----------------------	--

Description

Converts the contents of the Excel/Google Sheets template into a list with the format of the FSK2R object.

Usage

```
metadata_list_to_fsk(my_metadata, fsk_version = "1.0.5")
```

Arguments

my_metadata	A list generated by
fsk_version	Version of the FSK template.

n_simuls_fsk	<i>Number of simulations in the FSK2R object</i>
--------------	--

Description

Number of simulations in the FSK2R object

Usage

```
n_simuls_fsk(fsk_obj)
```

Arguments

fsk_obj	An instance of FSK2R
---------	----------------------

Value

An integer vector of length one.

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
n_simuls_fsk(my_fsk)
```

`read_fsk_json_metadata`*Read the metadata.json file*

Description

Read the metadata.json file

Usage

```
read_fsk_json_metadata(file_dir, check = FALSE, filename = "metaData.json")
```

Arguments

<code>file_dir</code>	path to the file.
<code>check</code>	Whether to make checks. FALSE by default.
<code>filename</code>	Name of the file with the information (metaData.json by default).

Value

A list with the contents of the metadata file.

`read_fsk_manifest`*Read the manifest of an FSK file and convert it to a data.frame*

Description

Read the manifest of an FSK file and convert it to a data.frame

Usage

```
read_fsk_manifest(file_dir, check = FALSE, filename = "manifest.xml")
```

Arguments

<code>file_dir</code>	path to the file.
<code>check</code>	Whether to make checks. FALSE by default.
<code>filename</code>	Name of the file with the information (manifest.xml by default).

Value

A data.frame with the contents of the xml file.

`read_fsk_metadata_excel`*FSK metadata from local Excel file*

Description

FSK metadata from local Excel file

Usage

```
read_fsk_metadata_excel(  
  fsk_object,  
  path,  
  type_of_model = "generic",  
  fsk_version = "1.0.5"  
)
```

Arguments

<code>fsk_object</code>	FSK2R object where to save the data
<code>path</code>	character describing the path to the file
<code>type_of_model</code>	character identifying the type of model
<code>fsk_version</code>	Character describing the version of FSK-ML ("1.04" by default).

Value

A list with the information in the Excel file as generated by `metadata_list_to_fsk`.

`read_fsk_model`*Read the model.sbml*

Description

Read the model.sbml

Usage

```
read_fsk_model(file_dir, check = FALSE, filename = "model.sbml")
```

Arguments

<code>file_dir</code>	path to the file.
<code>check</code>	Whether to make checks. FALSE by default.
<code>filename</code>	Name of the file with the information (model.sbml by default).

Value

A list with the contents of the .xml file.

read_fsk_packages	<i>Read the packages.json</i>
-------------------	-------------------------------

Description

Read the packages.json

Usage

```
read_fsk_packages(file_dir, check = FALSE, filename = "packages.json")
```

Arguments

file_dir	path to the file.
check	Whether to make checks. FALSE by default.
filename	Name of the file whith the information (packages.json by default).

Value

A list with the contents of the JSON file.

read_fsk_rdf_metadata	<i>Read the metadata.rdf</i>
-----------------------	------------------------------

Description

Read the metadata.rdf

Usage

```
read_fsk_rdf_metadata(file_dir, check = FALSE, filename = "metadata.rdf")
```

Arguments

file_dir	path to the file.
check	Whether to make checks. FALSE by default.
filename	Name of the file whith the information (metadata.rdf by default).

Value

A list with the contents of the .xml file.

read_fsk_readme	<i>Read the README file</i>
-----------------	-----------------------------

Description

Read the README file

Usage

```
read_fsk_readme(file_dir, check = FALSE, filename = "README.txt")
```

Arguments

file_dir	path to the file.
check	Whether to make checks. FALSE by default.
filename	Name of the file whith the information (README.txt by default).

Value

A character string with the content of the README file.

read_fsk_sim	<i>Read the sim.sedml file</i>
--------------	--------------------------------

Description

Read the sim.sedml file

Usage

```
read_fsk_sim(file_dir, check = FALSE, filename = "sim.sedml")
```

Arguments

file_dir	path to the file.
check	Whether to make checks. FALSE by default.
filename	Name of the file whith the information (sim.sedml by default).

Value

A list with the content of the xml file.

read_other_files	<i>Read "other files"</i>
------------------	---------------------------

Description

The R models may require further files that we can not predict. This functions just reads all the "unrecognized" files included in the manifest and copies them to the working directory.

Usage

```
read_other_files(my_tempdir, my_manifest, check = FALSE)
```

Arguments

my_tempdir	Temporary directory to extract contents of the zyp file.
my_manifest	A list with the information in the manifest file
check	Whether checks are made.

read_R_model	<i>Reads the R model in an FSK model</i>
--------------	--

Description

Reads the R model in an FSK model

Usage

```
read_R_model(file_dir, check = FALSE, filename = "model.R")
```

Arguments

file_dir	path to the file.
check	Whether to make checks. FALSE by default.
filename	Name of the file (model.R by default).

Value

A character string with the contents of the R file.

read_visualization	<i>Reads the visualization script in an FSK model</i>
--------------------	---

Description

Reads the visualization script in an FSK model

Usage

```
read_visualization(file_dir, check = FALSE, filename = "visualization.R")
```

Arguments

file_dir	path to the file.
check	Whether to make checks. FALSE by default.
filename	Name of the file with the information (visualization.R by default).

Value

A character string with the contents of the R file.

run_all_simulations	<i>Run every simulation in an FSK object</i>
---------------------	--

Description

Runs every simulation defined in the FSK object. This includes the ones originally included in the FSK container, as well as the ones added using `set_new_simulation()`.

Usage

```
run_all_simulations(fsk_object, run_visualization = FALSE)
```

Arguments

fsk_object	Instance of FSK2R
run_visualization	Whether to call the visualization script. FALSE by default.

Value

None

run_simulation	<i>Run one simulation in an FSK object</i>
----------------	--

Description

Runs the simulation corresponding to index. If defined, it also calls any visualization script.

Usage

```
run_simulation(fsk_object, index, run_visualization = FALSE)
```

Arguments

fsk_object	Instance of FSK2R
index	Index of the simulation
run_visualization	Whether to call the visualization script. FALSE by default.

Value

None

set_new_simulation	<i>Define a new simulation in an FSK2R object</i>
--------------------	---

Description

Sets a new simulation using the parameters defined in simulation_pars. The method updates all the relevant methods.

Usage

```
set_new_simulation(fsk_object, simulation_id, parameters)
```

Arguments

fsk_object	Instance of FSK2R
simulation_id	A character with an id for the new simulation.
parameters	A list whose names are the parameters to modify and their values their values for the simulation.

Value

An instance of FSK2R with the additional simulation data.

set_readme	<i>Readme of an FSK object</i>
------------	--------------------------------

Description

Readme of an FSK object

Usage

```
set_readme(fsk_object, readme_text)
```

Arguments

fsk_object	An instance of FSK2R.
readme_text	A character vector of length 1 with the content of the README file.

Value

An instance of FSK2R.

Examples

```
path_example <- system.file("extdata", "ToyModelv4.fskx", package = "FSK2R")
my_fsk <- import_fsk(path_example)
set_readme(my_fsk, "This is the README.")
```

update_manifest	<i>Updates the manifest file</i>
-----------------	----------------------------------

Description

Updates the manifest file

Usage

```
update_manifest(fsk_object)
```

Arguments

fsk_object	An instance of FSK2R.
------------	-----------------------

Index

check_manifest_files, [3](#)
convert_metadata_to_lists, [3](#)
create_fsk, [4](#)

dataframe_to_list, [5](#)

export_fsk, [5](#)
export_manifest, [6](#)
export_metadata, [6](#)
export_modelmetadata, [7](#)
export_otherfiles, [7](#)
export_packages, [8](#)
export_R_model, [9](#)
export_readme, [8](#)
export_sbmlModel, [9](#)
export_simulation, [10](#)
export_visualization, [10](#)

find_packages, [11](#)
FSK_runner, [11](#)

get_background, [12](#)
get_general_info, [12](#)
get_modelmath, [13](#)
get_readme, [14](#)
get_scope, [14](#)
get_session_info, [15](#)
get_simulations, [15](#)

import_fsk, [16](#)
import_fsk_join, [16](#)
is.FSK2R, [17](#)
is_fsk_with_r, [17](#)

map_FSK_metadata, [18](#)
map_metadata_xml_template, [18](#)
metadata_list_to_fsk, [19](#)

n_simuls_fsk, [19](#)

read_fsk_json_metadata, [20](#)

read_fsk_manifest, [20](#)
read_fsk_metadata_excel, [21](#)
read_fsk_model, [21](#)
read_fsk_packages, [22](#)
read_fsk_rdf_metadata, [22](#)
read_fsk_readme, [23](#)
read_fsk_sim, [23](#)
read_other_files, [24](#)
read_R_model, [24](#)
read_visualization, [25](#)
run_all_simulations, [25](#)
run_simulation, [26](#)

set_new_simulation, [26](#)
set_readme, [27](#)

update_manifest, [27](#)