

Package ‘InterSIM’

July 21, 2025

Type Package

Title Simulation of Inter-Related Genomic Datasets

Version 2.3.0

Date 2025-01-10

Author Prabhakar Chalise [aut, cre],
Rama Raghavan [aut],
Brooke Fridley [aut]

Maintainer Prabhakar Chalise <pchalise@kumc.edu>

Description Generates three inter-related genomic datasets: methylation, gene expression and protein expression having user specified cluster patterns. The simulation utilizes the realistic inter- and intra- relationships from real DNA methylation, mRNA expression and protein expression data from the TCGA ovarian cancer study, Chalise (2016) <[doi:10.1016/j.cmpb.2016.02.011](https://doi.org/10.1016/j.cmpb.2016.02.011)>.

License GPL

Depends R (>= 3.5.0), MASS, NMF, tools

NeedsCompilation no

Repository CRAN

Date/Publication 2025-01-10 23:00:06 UTC

RoxygenNote 6.0.1

Contents

InterSIM-package	2
InterSIM	2
Index	5

InterSIM-package	<i>Simulation of inter-related genomic datasets</i>
------------------	---

Description

Generates three inter-related data set with realistic inter- and intra- relationships based on the DNA methylation, mRNA expression and protein expression from the TCGA ovarian cancer study.

Details

Package: InterSIM
Type: Package
Version: 2.3.0
Date: 2025-01-10
License: GPL>=2

Author(s)

Prabhakar Chalise, Rama Raghavan, Brooke Fridley;
Maintainer: Prabhakar Chalise

InterSIM	<i>InterSIM</i>
----------	-----------------

Description

This function simulates three inter-related genomic datasets : DNA methylation, gene expression and protein expression.

Usage

```
InterSIM(n.sample=500, cluster.sample.prop=c(0.30,0.30,0.40), delta.methyl=2.0,
delta.expr=2.0, delta.protein=2.0, p.DMP=0.2,
p.DEG=NULL, p.DEP=NULL, sigma.methyl=NULL, sigma.expr=NULL, sigma.protein=NULL,
cor.methyl.expr=NULL, cor.expr.protein=NULL, do.plot=FALSE, sample.cluster=TRUE,
feature.cluster=TRUE)
```

Arguments

<code>n.sample</code>	Number of subjects to simulate
<code>cluster.sample.prop</code>	Proportion of samples in the clusters. The number of proportions entered is used to determine the number of clusters in the simulated data. e.g. if (0.3,0.4,0.3) is entered then the number of clusters will be 3.
<code>delta.methyl</code>	Cluster mean shift for methylation data
<code>delta.expr</code>	Cluster mean shift for expression data
<code>delta.protein</code>	Cluster mean shift for protein data
<code>p.DMP</code>	proportion of DE CpGs (DE = Differentially Expressed)
<code>p.DEG</code>	proportion of DE mRNA, if NULL (default) mRNAs mapped by DE CpGs will be selected
<code>p.DEP</code>	proportion of DE protein, if NULL (default) proteins mapped by DE mRNAs will be selected
<code>sigma.methyl</code>	Covariance structure methylation data, if NULL (default) precomputed values will be used. "indep" gives covariance structure with diagonal elements only (Independent features)
<code>sigma.expr</code>	Covariance structure mRNA data, if NULL (default) precomputed values will be used. "indep" gives covariance structure with diagonal elements only (Independent features)
<code>sigma.protein</code>	Covariance structure Protein data, if NULL (default) precomputed values will be used. "indep" gives covariance structure with diagonal elements only (Independent features)
<code>do.plot</code>	TRUE to generate heatmap, default is FALSE
<code>sample.cluster</code>	TRUE (default), if clustering should be done on samples for heatmap. This option will be applicable only if <code>do.plot=TRUE</code> .
<code>feature.cluster</code>	TRUE (default), if clustering should be done on genomic features for heatmap. This option will be applicable only if <code>do.plot=TRUE</code> .
<code>cor.methyl.expr</code>	Correlation between methylation and mRNA, if NULL (default) precomputed values will be used
<code>cor.expr.protein</code>	Correlation between mRNA and protein, if NULL (default) precomputed values will be used

Value

This function returns three interrelated datasets having user specified cluster patterns as matrices - DNA methylation, gene expression and protein expression. It also returns a vector that has true cluster assignment for each subject in the generated data.

Author(s)

Prabhakar Chalise <pchalise@kumc.edu>, Rama Raghavan <rraghavan@kumc.edu>, Brooke Fridley <bfridley@kumc.edu>

References

Chalise P, Raghavan R and Fridley B (2016). InterSIM: Simulation tool for multiple integrative 'omic datasets. *Computer Methods and Programs in Biomedicine*, 128:69-74, <https://doi.org/10.1016/j.cmpb.2016.02.011>

Examples

```
#
prop <- c(0.20,0.30,0.27,0.23)
effect <- 5
sim.data <- InterSIM(n.sample=500, cluster.sample.prop = prop,
delta.methyl=effect, delta.expr=effect, delta.protein=effect,
p.DMP=0.2, p.DEG=NULL, p.DEF=NULL,
sigma.methyl=NULL, sigma.expr=NULL, sigma.protein=NULL,
cor.methyl.expr=NULL, cor.expr.protein=NULL,
do.plot=FALSE, sample.cluster=TRUE, feature.cluster=TRUE)
sim.methyl <- sim.data$dat.methyl
sim.expr <- sim.data$dat.expr
sim.protein <- sim.data$dat.protein
```

Index

`cov.expr (InterSIM)`, [2](#)
`cov.M (InterSIM)`, [2](#)
`cov.protein (InterSIM)`, [2](#)
`CpG.gene.map.for.DEG (InterSIM)`, [2](#)

`InterSIM`, [2](#)
`InterSIM-package`, [2](#)

`logit (InterSIM)`, [2](#)

`mean.expr (InterSIM)`, [2](#)
`mean.M (InterSIM)`, [2](#)
`mean.protein (InterSIM)`, [2](#)
`methyl.gene.level.mean (InterSIM)`, [2](#)

`protein.gene.map.for.DEP (InterSIM)`, [2](#)

`rev.logit (InterSIM)`, [2](#)
`rho.expr.protein (InterSIM)`, [2](#)
`rho.methyl.expr (InterSIM)`, [2](#)