

Package ‘LDNN’

July 21, 2025

Type Package

Title Longitudinal Data Neural Network

Version 1.10

Date 2020-11-25

Author Vasileios Karapoulios

Maintainer Vasileios Karapoulios <billkarap123@gmail.com>

Description This is a Neural Network regression model implementation using 'Keras', consisting of 10 Long Short-Term Memory layers that are fully connected along with the rest of the inputs.

License GNU General Public License

RoxygenNote 7.1.1

LazyData true

Encoding UTF-8

Imports devtools, reticulate, tensorflow

Depends keras

Suggests testthat, knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2020-12-02 10:30:10 UTC

Contents

create_model	2
evaluate_model	3
fit_model	4

Index	7
--------------	-------------------

create_model

Pre-defined Neural Network for Longitudinal Data

Description

Create the Neural Network model (Keras).

Usage

```
create_model(
    rnn_inputs,
    recurrent_dropout,
    inputs,
    layer_dropout,
    n_nodes_hidden_layers,
    loss_function,
    opt,
    metric
)
```

Arguments

rnn_inputs	The number of inputs (integers) per each LSTM (vector of length 10).
recurrent_dropout	The dropout to be applied in the LSTMs (between 0 and 1).
inputs	The number of inputs (integer) to be concatenated with the output of the LSTMs.
layer_dropout	The dropout to be applied between the hidden layers (between 0 and 1).
n_nodes_hidden_layers	The number of nodes in the hidden layers (2 in total).
loss_function	The loss function to be used.
opt	The optimizer to be used.
metric	The metric to be used.

Value

The model object built in Keras.

Examples

```
inp = c(20,24,24,24,16,16,16,16,16,15)
rec_drop = rep(0.1,10)
l_drop = c(0.1,0.1)
## Not run:
create_model(inp,rec_drop,232,c(0.1,0.1),l_drop,'mean_squared_error','adam','mean_absolute_error')

## End(Not run)
```

```
# The functions require to have python installed
# As well as tensorflow, keras and reticulate package.
```

`evaluate_model`*Evaluate the pre-defined Neural Network for Longitudinal Data*

Description

Evaluate the fitted Neural Network model (Keras).

Usage

```
evaluate_model(
  model,
  X1_test,
  X2_test,
  X3_test,
  X4_test,
  X5_test,
  X6_test,
  X7_test,
  X8_test,
  X9_test,
  X10_test,
  Xif_test,
  y_test,
  bsize
)
```

Arguments

<code>model</code>	The fitted model object produced by <code>create_model()</code> .
<code>X1_test</code>	Features as inputs of 1st LSTM.
<code>X2_test</code>	Features as inputs of 2nd LSTM.
<code>X3_test</code>	Features as inputs of 3rd LSTM.
<code>X4_test</code>	Features as inputs of 4th LSTM.
<code>X5_test</code>	Features as inputs of 5th LSTM.
<code>X6_test</code>	Features as inputs of 6th LSTM.
<code>X7_test</code>	Features as inputs of 7th LSTM.
<code>X8_test</code>	Features as inputs of 8th LSTM.
<code>X9_test</code>	Features as inputs of 9th LSTM.
<code>X10_test</code>	Features as inputs of 10th LSTM.
<code>Xif_test</code>	The features to be concatenated with the outputs of the LSTMs.
<code>y_test</code>	The target variable.
<code>bsize</code>	The batch size.

Value

The evaluation results.

Examples

```
X1_test <- matrix(runif(500*20), nrow=500, ncol=20)
X2_test <- matrix(runif(500*24), nrow=500, ncol=24)
X3_test <- matrix(runif(500*24), nrow=500, ncol=24)
X4_test <- matrix(runif(500*24), nrow=500, ncol=24)
X5_test <- matrix(runif(500*16), nrow=500, ncol=16)
X6_test <- matrix(runif(500*16), nrow=500, ncol=16)
X7_test <- matrix(runif(500*16), nrow=500, ncol=16)
X8_test <- matrix(runif(500*16), nrow=500, ncol=16)
X9_test <- matrix(runif(500*16), nrow=500, ncol=16)
X10_test <- matrix(runif(500*15), nrow=500, ncol=15)
Xif_test <- matrix(runif(500*232), nrow=500, ncol=232)
y_test <- matrix(runif(500), nrow=500, ncol=1)
## Not run:
evaluate_model(fitted_model,X1_test,X2_test,X3_test,X4_test,X5_test,X6_test,
X7_test,X8_test,X9_test,X10_test,Xif_test,y_test,32)

## End(Not run)
# The functions require to have python installed
# As well as tensorflow, keras and reticulate package.
```

fit_model

Fit the pre-defined Neural Network for Longitudinal Data

Description

Fit the created Neural Network model (Keras).

Usage

```
fit_model(
  model,
  ver,
  n_epoch,
  bsize,
  X1,
  X2,
  X3,
  X4,
  X5,
  X6,
  X7,
  X8,
  X9,
```

```

    X10,
    Xif,
    y
  )

```

Arguments

model	The model object produced by create_model().
ver	ver=0 to show nothing, ver=1 to show animated progress bar, ver=2 to just mention the number of epoch during training.
n_epoch	The number of epochs to train the model.
bsize	The batch size.
X1	Features as inputs of 1st LSTM.
X2	Features as inputs of 2nd LSTM.
X3	Features as inputs of 3rd LSTM.
X4	Features as inputs of 4th LSTM.
X5	Features as inputs of 5th LSTM.
X6	Features as inputs of 6th LSTM.
X7	Features as inputs of 7th LSTM.
X8	Features as inputs of 8th LSTM.
X9	Features as inputs of 9th LSTM.
X10	Features as inputs of 10th LSTM.
Xif	The features to be concatenated with the outputs of the LSTMs.
y	The target variable.

Value

The fitted model.

Examples

```

X1 <- matrix(runif(500*20), nrow=500, ncol=20)
X2 <- matrix(runif(500*24), nrow=500, ncol=24)
X3 <- matrix(runif(500*24), nrow=500, ncol=24)
X4 <- matrix(runif(500*24), nrow=500, ncol=24)
X5 <- matrix(runif(500*16), nrow=500, ncol=16)
X6 <- matrix(runif(500*16), nrow=500, ncol=16)
X7 <- matrix(runif(500*16), nrow=500, ncol=16)
X8 <- matrix(runif(500*16), nrow=500, ncol=16)
X9 <- matrix(runif(500*16), nrow=500, ncol=16)
X10 <- matrix(runif(500*15), nrow=500, ncol=15)
Xif <- matrix(runif(500*232), nrow=500, ncol=232)
y <- matrix(runif(500), nrow=500, ncol=1)
## Not run:
fitted_model = fit_model(model,0,1,32,X1,X2,X3,X4,X5,X6,X7,X8,X9,X10,Xif,y)

```

```
## End(Not run)
# The functions require to have python installed
# As well as tensorflow, keras and reticulate package.
```

Index

`create_model`, [2](#)

`evaluate_model`, [3](#)

`fit_model`, [4](#)