

Package ‘RJSplot’

July 21, 2025

Type Package

Version 2.7

Date 2021-11-30

Title Interactive Graphs with R

Description Creates interactive graphs with 'R'. It joins the data analysis power of R and the visualization libraries of JavaScript in one package.

URL <https://rjsplot.usal.es>

License CC BY-NC-SA 4.0

Depends R (>= 3.0.0)

Suggests IRdisplay

NeedsCompilation no

Author Carlos Prieto <cprietos@usal.es>,
David Barrios <metal@usal.es>

Maintainer Carlos Prieto <cprietos@usal.es>

Repository CRAN

Date/Publication 2021-12-01 08:40:02 UTC

Contents

barplot_rjs	2
boxplot_rjs	3
bubbles_rjs	4
circularfv_rjs	5
createAssembly	7
dendrogram_rjs	8
densityplot_rjs	9
genomemap_rjs	10
getAssemblyFromFasta	11
GRCh37	12
GRCh37.bands	12
GRCh38	13

GRCh38.bands	13
heatmap_rjs	13
hiveplot_rjs	15
manhattan_rjs	16
NCBI36	17
network_rjs	18
newInput	19
piechart_rjs	20
R4web	21
report_rjs	22
RJSplot	23
scatter3d_rjs	23
scatterplot_rjs	24
surface3d_rjs	26
symheatmap_rjs	27
tables_rjs	28
wordcloud_rjs	29
Index	31

barplot_rjs	<i>Produce interactive bar plot(s).</i>
-------------	---

Description

barplot_rjs produce interactive bar plot(s) of the given values.

Usage

```
barplot_rjs(height, xlab = "", ylab = "", ylim = NULL, cex = 1,
            plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

height	either a vector or matrix of values describing the bars which make up the plot.
xlab	a title for the x axis.
ylab	a title for the y axis.
ylim	a vector with two values which specifies the Y minimun and maximun values in the representation.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive barplot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  barplot_rjs(USArrests, "states", "arrests")
}
```

boxplot_rjs

Produce interactive box-and-whisker plot(s).

Description

boxplot_rjs produce interactive box-and-whisker plot(s) of the given values.

Usage

```
boxplot_rjs(data, xlab = "", ylab = "",
            outline = TRUE, col = NULL, ylim = NULL, cex = 1,
            plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a Data Frame or Matrix from which the data for each box will be taken.
outline	if outline is not true, the outliers are not drawn.
col	if 'col' is non-null it is assumed to contain colors to be used to colour the bodies of the box plots.
xlab	a title for the x axis.
ylab	a title for the y axis.

ylim	a vector with two values which specifies the Y minimum and maximum values in the representation.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive boxplot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  boxplot_rjs(attitude, "attitude", "favourable responses")
}
```

bubbles_rjs	<i>Produce interactive bubble plots.</i>
-------------	--

Description

bubbles_rjs produce interactive bubble plot(s) of the given values.

Usage

```
bubbles_rjs(data, size = NULL, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a numeric Data Frame or Matrix with two columns and one row per bubble which contains represented values for each bubble. Row names will be used as bubble names.
size	a vector giving each bubble size.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive barplot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  bubbles_rjs(scale(mtcars[,c("mpg", "hp")]), FALSE, mtcars$wt)
}
```

circularfv_rjs	<i>Prduce a circular sequence viewer.</i>
----------------	---

Description

circularfv_rjs creates a circular sequence viewer.

Usage

```
circularfv_rjs(sequence, features = FALSE,
               plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

sequence	a "character" string giving the DNA sequence.
features	Data Frame with the segments that will be seen in the viewer. It contains 5 columns which describes the identifier, start coordinate, stop coordinate, segment type and segment color.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
if(interactive()){
## Creates a circular sequence viewer in a temporal directory of your local machine
## Generate test input data
sequence <- paste(sample(c("c","a","t","g"), 10000, replace = TRUE), collapse = "")
data <- matrix(round(runif(12,0,10000)),6,2)
features <- data.frame(id = 0:5, start = data[,1], stop = data[,2],
type = c("voluptate","non","voluptate","sit","et","proident"),
color = c("SandyBrown","Tan","Wheat","SteelBlue","LightSkyBlue","LightBlue"))

## Create the circular sequence viewer
circularfv_rjs(sequence, features)
}
```

createAssembly	<i>Creates a genome assembly for genomemap_rjs or manhattan_rjs.</i>
----------------	--

Description

createAssembly create assemblies for their use as parameter of genomemap_rjs or manhattan_rjs.

Usage

```
createAssembly(name, size)
```

Arguments

name	a vector with the chromosome or scaffold names.
size	a vector with the chromosome or scaffold sizes.

Value

a data frame in BED format to be used as an assembly in genomemap_rjs or manhattan_rjs.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[genomemap_rjs](#).
[manhattan_rjs](#).

Examples

```
## Creates a fake genome assembly for its posterior use as parameter of genomemap or manhattan plot
## Live examples and full tutorial on https://rjsplot.usal.es

## Generate a test assembly with three scaffolds
assembly <- createAssembly(c("scaffold1", "scaffold2", "scaffold3"), c(1000000, 800000, 650000))
```

dendrogram_rjs	<i>Draw a Dendrogram.</i>
----------------	---------------------------

Description

dendrogram_rjs creates a dendrogram.

Usage

```
dendrogram_rjs(data, metadata = NULL, method = "complete", cex = 1,
               plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a dissimilarity object of class dist (p.e. produced by function dist).
metadata	a data frame with metadata information for leaf features (p.e. sample phenotypes). Corresponding Leaf/Sample should be provided as row name.
method	Name of the agglomeration method to be used. It should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC).
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	A "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create a dendrogram in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  dendrogram_rjs(dist(USArrests),USArrests)
}
```

densityplot_rjs	<i>Draw an interactive density plot.</i>
-----------------	--

Description

densityplot_rjs creates density plots.

Usage

```
densityplot_rjs(data, xlab = "", ylab = "", cex = 1,
  plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a data frame from which distribution will be represented for each column.
xlab	a title for the x axis.
ylab	a title for the y axis.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Creates a density plot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  ## Generate test input data
  data <- data.frame(Uni05 = (1:100)/21, Norm = rnorm(100), `5T` = rt(100, df = 5),
    Gam2 = rgamma(100, shape = 2))

  # Create the density plot
  densityplot_rjs(data, "x", "y")
}
```

genomemap_rjs	Create an interactive genome map.
---------------	-----------------------------------

Description

genomemap_rjs creates an interactive genome map.

Usage

```
genomemap_rjs(assembly, track = NULL, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

assembly	a genome assembly data frame. RJSplot provides human assemblies (NCBI36, GRCh37, GRCh38), human assemblies with cytobands (GRCh37.bands or GRCh38.bands), or methods for creating your own assembly from a FASTA file getAssemblyFromFasta .
track	a data frame with values to represent on the genome map (chromosome, position, value).
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with Firefox. If you want to open this file stored in your local machine with other Web browser, please visit the help section on the RJSplot Web site (<https://rjsplot.usal.es>).

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive Genome map in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  # Create test data
  chr <- character()
  pos <- numeric()

  for(i in 1:nrow(GRCh38)){
    chr <- c(chr,as.character(rep(GRCh38[i,"chr"],100)))
    pos <- c(pos,sample(GRCh38[i,"start"]:GRCh38[i,"end"],100))
  }

  value <- round(rexp(length(pos)),2)

  # Create a genome map
  track <- data.frame(chr,pos,pos+1,NA,value)
  genomemap_rjs(GRCh38.bands, track)
}
```

getAssemblyFromFasta	<i>Create an assembly from a FASTA file for its use as parameter of genomemap_rjs or manhattan_rjs.</i>
----------------------	---

Description

getAssemblyFromFasta create assemblies from a FASTA file for their use as parameter of genomemap_rjs or manhattan_rjs.

Usage

```
getAssemblyFromFasta(fasta)
```

Arguments

fasta	a "character" string representing the input Fasta file to be added in the genome browser.
-------	---

Value

a data frame in BED format ready to use as an assembly in genomemap_rjs or manhattan_rjs.

Note

FASTA format is a text-based format for representing either nucleotide sequences or peptide sequences, in which nucleotides or amino acids are represented using single-letter codes.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[genomemap_rjs.](#)
[manhattan_rjs.](#)

Examples

```
## Live examples and full tutorial on https://rjsplot.usal.es
```

GRCh37

Length of human chromosomes based on GRCh37 assembly

Description

Length of human chromosomes based on GRCh37 assembly.

Source

See https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.13/.

GRCh37.bands

Cytoband information based on GRCh37

Description

A Data Frame containing cytobands of GRCh37 assembly.

Source

See http://grch37.ensembl.org/Homo_sapiens/Location/Genome.

GRCh38	<i>Length of human chromosomes based on GRCh38 assembly</i>
--------	---

Description

Length of human chromosomes based on GRCh38 assembly.

Source

See <https://www.ncbi.nlm.nih.gov/assembly/883148/>.

GRCh38.bands	<i>Cytoband information based on GRCh38</i>
--------------	---

Description

A Data Frame containing cytobands of GRCh38 assembly.

Source

See http://www.ensembl.org/Homo_sapiens/Location/Genome.

heatmap_rjs	<i>Produce an interactive heatmap.</i>
-------------	--

Description

heatmap_rjs creates interactive heatmaps.

Usage

```
heatmap_rjs(data, metadata = NULL, scale = c("row", "column", "none"),
  cluster = TRUE, color = c("Reds", "Greens", "Blues", "RdBkGr", "RdWhBu"),
  na.color = "transparent", cex = 1, plot = TRUE, jupyter = FALSE,
  dir = tempdir(), distfun = dist, hclustfun = hclust)
```

Arguments

data	numeric matrix of the values to be plotted.
metadata	a data frame with metadata information for column features (p.e. sample phenotypes). Samples are given in rows and features in columns.
scale	character indicating if the values should be centered and scaled in either the row direction or the column direction, or none. The default value is "none".
cluster	logical value to enable (TRUE) or disable (FALSE) data clustering.
color	character indicating the color scale to paint values. The default value is "Blues".
na.color	character indicating the color to use for missing values. Transparent by default.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.
distfun	function used to compute the distance between rows and columns.
hclustfun	function used to compute the hierarchical clustering.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive heatmap in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  metadata <- data.frame(phenotype1 = sample(c("yes", "no"), ncol(mtcars), TRUE),
                        phenotype2 = sample(1:5, ncol(mtcars), TRUE))

  heatmap_rjs(data.matrix(mtcars), metadata, scale="column")
}
```

hiveplot_rjs	<i>Produce interactive hive plot</i>
--------------	--------------------------------------

Description

hiveplot_rjs creates an interactive hive plot.

Usage

```
hiveplot_rjs(links, nodes = NULL, group = NULL, size = NULL, color = NULL,  
             cex = 1, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

links	an edge list table stored in a data frame with three possible columns (source node id, target node id and link value).
nodes	node attributes stored in a data frame with rownames as node id.
group	column name of nodes data frame which describes visualized axes.
size	column name of nodes data frame which describes each node size.
color	column name of nodes data frame which describes each node color.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive hive plot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  # Prepare data
  x <- 1-cor(t(mtcars))

  source <- rep(rownames(x),nrow(x))
  target <- rep(rownames(x),rep(ncol(x),nrow(x)))
  links <- data.frame(source=source,target=target,value=as.vector(x))

  # Generate the hive plot
  hiveplot_rjs(links, mtcars, group = "cyl", size = "wt", color = "carb")
}
```

manhattan_rjs

Create an interactive manhattan plot

Description

manhattan_rjs creates an interactive Manhattan plot.

Usage

```
manhattan_rjs(data, assembly, axisv, distv, cell = 1e+06,
  outliers = TRUE, ylab = "score", yscale = NULL,
  cex = 1, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a data frame with four columns (identifier, chromosome/scaffold, position, score).
assembly	a data frame with an assembly to be used. It should be one of the following human assemblies data frames provided by RJSplot: NCBI36, GRCh37, GRCh38.
axisv	value for the coordinate of the main horizontal axis.
distv	distance between the main horizontal axis and the secondary axes (which establishes the limit for the outlier representation).
cell	segment size which is represented.
outliers	logical value to enable (TRUE) or disable (FALSE) outliers.
ylab	a title for the y axis.
yscale	a vector with two values which specifies the minimum and maximum limits in the representation. By default maximum and minimum scores are taken as the limits.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive Manhattan plot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  # Create test data
  chr <- character()
  pos <- numeric()

  for(i in 1:nrow(GRCh38)){
    chr <- c(chr, as.character(rep(GRCh38[i, "chr"], 100)))
    pos <- c(pos, sample(GRCh38[i, "start"]:GRCh38[i, "end"], 100))
  }

  value <- round(rexp(length(pos)), 2)

  # Create a manhattan plot
  data <- data.frame(paste0("ProbeSet_", seq_along(pos)), chr, pos, value)
  manhattan_rjs(data, GRCh38, 0, 1, 0, TRUE, "log2Ratio")
}
```

NCBI36

Length of human chromosomes based on NCBI36 assembly

Description

Length of human chromosomes based on NCBI36 assembly.

Source

See https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.12/.

network_rjs

*Produce interactive network graph***Description**

network_rjs creates an interactive network graph.

Usage

```
network_rjs(links, nodes = NULL,
            weight = NULL, linkLabel = NULL, linkColor = NULL,
            group = NULL, size = NULL, color = NULL, label = NULL,
            nodeColorScale = c("RdBk", "RdBkGr"), cex = 1,
            plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

links	an edge list table stored in a data frame with at least two columns (source node id and target node id).
nodes	a node list stored in a data frame object with rownames as node id.
weight	a vector giving the column of links to show as weight. If NULL but third links column is numeric, this one will be used as weight.
linkLabel	a vector giving the column of links to show as link text.
linkColor	a vector giving the column of links to compute link color or directly a vector of colors.
group	a vector giving the column of nodes to show as group.
size	a vector giving the column of nodes to show as size.
color	a vector giving the column of nodes to compute node color or directly a vector of colors.
label	a vector giving the column of nodes to show as label.
nodeColorScale	a "character" string representing the color scale applied to nodes by default.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive network graph in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  # Prepare data
  x <- 1-cor(t(mtcars))

  source <- rep(rownames(x),nrow(x))
  target <- rep(rownames(x),rep(ncol(x),nrow(x)))
  links <- data.frame(source=source,target=target,value=as.vector(x))

  # Generate the network graph
  network_rjs(links[links[,3]>0.1,], mtcars, group = "cyl", size = "hp", color = "mpg")
}
```

newInput

Produce a newInput object for R4web.

Description

newInput produce newInput object for R4web.

Usage

```
newInput(name, type = c("character","numeric","matrix","data.frame","factor"),
         default = "", levels = NULL, multi = FALSE)
```

Arguments

name	character string with the variable name.
type	character string which describes the variable type. Possible values are "character", "numeric", "matrix", "data.frame" or "factor".
default	default value for this input.
levels	a vector with the possible input values. It is described only for factor data type.
multi	boolean value which indicates if multiple selection are enabled for this input. It is described only for factor data type.

Value

Return a newInput object.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

piechart_rjs

Produce interactive pie charts.

Description

piechart_rjs produce interactive pie charts.

Usage

```
piechart_rjs(data, cex = 1, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a Data Frame or Matrix from which the data for each pie will be taken.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive pie chart in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  piechart_rjs(VADeaths)
}
```

R4web

Generate a PHP website which runs an R function.

Description

R4web generate a PHP website which runs an R function.

Usage

```
R4web(..., fnfile, dir)
```

Arguments

...	one or more newInput objects which will be included as form fields. Form values will be used as parameters for the R script.
fnfile	a character string representing the R script file to be executed with the website.
dir	a "character" string representing the directory where the PHP code will be saved.

Value

The function creates a folder in the working directory of your computer with some PHP files. Resulting folder should be added to the Apache applications directory and enable writting permissions.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

report_rjs	<i>Create a report web page.</i>
------------	----------------------------------

Description

report_rjs creates a report web page.

Usage

```
report_rjs(dir = "RJSreport")
addCSS2report(report,css)
addHTML2report(report,HTML)
addParagraph2report(report,p)
addPlot2report(report,plot,height=600)
addImage2report(report,img)
```

Arguments

dir	a "character" string representing the directory where the report will be saved.
report	a RJSreport object produced by the function report_rjs.
css	a character string representing the CSS path to be added.
HTML	a character string giving the HTML code to be added.
p	a character string giving the new paragraph to be added.
plot	a character string representing the plot directory to be added.
height	an integer vector giving a default height of the plot.
img	a character string representing the image path to be added.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the report. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

RJSplot

*Interactive graphs with R***Description**

Create interactive graphs with 'R'.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

scatter3d_rjs

*Produce and interactive 3D Scatter plot (XYZ plot).***Description**

scatter3d_rjs generates an interactive 3D Scatter Plot.

Usage

```
scatter3d_rjs(x, y, z, color="#000", xlab = "x", ylab = "y", zlab = "z",
             plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

x	a vector with the x data of each point.
y	a vector with the y data of each point.
z	a vector with the z data of each point.
xlab	a title for the x axis.
ylab	a title for the y axis.
zlab	a title for the z axis.
color	a vector with the colour of each represented point.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive 3D Scatter plot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

# 3D Scatter plot creation
if(interactive()){
  scatter3d_rjs(iris$Sepal.Width, iris$Sepal.Length, iris$Petal.Width,
    color = iris$Species, xlab = "Sepal Width (cm)", ylab = "Sepal Length (cm)",
    zlab = "Petal Width (cm)")
}
```

scatterplot_rjs

Produce and interactive Scatter plot (XY plot).

Description

scatterplot_rjs generates an interactive Scatter Plot.

Usage

```
scatterplot_rjs(x, y, id = NULL, xlab = "", ylab = "",
  xlim = NULL, ylim = NULL, col = NULL,
  pch = NULL, abline.x = NULL, abline.y = NULL, cex = 1,
  plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

x	a vector with the x data of each point.
y	a vector with the y data of each point.
id	a vector giving the id of each point.
xlab	a title for the x axis.
ylab	a title for the y axis.
xlim	a vector with two values which specifies the X minimum and maximum values in the representation.
ylim	a vector with two values which specifies the Y minimum and maximum values in the representation.
col	a vector with the colour of each represented point.
pch	a character vector with the shape of each point. It should be one of: 1-"circle", 2-"triangle-up", 3-"cross", 4-"square", 5-"diamond", 6-"triangle-down".
abline.x	a numeric vector with x coordinates where a vertical line will be placed.
abline.y	a numeric vector with y coordinates where a horizontal line will be placed.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive Scatter plot in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
# Scatter plot creation
```

```
scatterplot_rjs(iris$Sepal.Width, iris$Sepal.Length,
  abline.x = c(3.4,3.8), abline.y = c(5.8,7),
  col = iris$Species, pch = as.numeric(iris$Species), id = iris$Species,
  xlab = "Sepal Width (cm)", ylab = "Sepal Length (cm)")
}
```

surface3d_rjs

Produce and interactive 3D surface.

Description

surface3d_rjs generates an interactive 3D surface.

Usage

```
surface3d_rjs(x, color = "#fff", xlab = "x", ylab = "y", zlab = "z",
  plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

x	numeric matrix of the values to be plotted.
color	a vector with colors to construct the color scale.
xlab	a title for the x axis.
ylab	a title for the y axis.
zlab	a title for the z axis.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive 3D Surface in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  # 3D surface creation
  surface3d_rjs(volcano,color=c("red","green"))
}
```

symheatmap_rjs	<i>Creates a Symetric Heatmap representation.</i>
----------------	---

Description

symheatmap_rjs creates an interactive symetric heatmap.

Usage

```
symheatmap_rjs(links, nodes = NULL, group = NULL, label = NULL, cex = 1,
  plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

links	an edge list table stored in a data frame with three possible columns (source node id, target node id and a link value).
nodes	a node list stored in a data frame object with rownames as node id.
group	a vector giving the column of nodes to show as group.
label	a vector giving the column of nodes to show as label.
cex	number indicating the amount by which plotting text and symbols should be scaled relative to the default.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive symetric heatmap in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es

if(interactive()){
  # prepare data
  x <- 1-cor(t(mtcars))

  source <- rep(rownames(x),nrow(x))
  target <- rep(rownames(x),rep(ncol(x),nrow(x)))
  links <- data.frame(source=source,target=target,value=as.vector(x))

  # Create symetric heatmap
  symheatmap_rjs(links, mtcars, group = "cyl")
}
```

tables_rjs

Produce interactive html tables.

Description

tables_rjs produce interactive html tables of the given values.

Usage

```
tables_rjs(data, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a Data Frame or Matrix to display.
plot	open resulting table in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the table. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>
[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#),
[scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#),
[piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive html table in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
if(interactive()){
  tables_rjs(swiss)
}
```

wordcloud_rjs

Draw a wordcloud.

Description

wordcloud_rjs creates a wordcloud.

Usage

```
wordcloud_rjs(data, plot = TRUE, jupyter = FALSE, dir = tempdir())
```

Arguments

data	a two column data Frame with the words to display and their frequency.
plot	open resulting graph in your browser.
jupyter	embed the graph as an iframe into a Jupyter Notebook.
dir	a "character" string representing the directory where the graph will be saved.

Value

The function creates a folder in your computer with an HTML document named index.html which contains the graph. This file can be directly opened with your browser.

Author(s)

David Barrios and Carlos Prieto. Bioinformatics Service of Nucleus, University of Salamanca. See <https://bioinfo.usal.es/>

See Also

The 'RJSplot' Website: <https://rjsplot.usal.es>

[dendrogram_rjs](#), [densityplot_rjs](#), [genomemap_rjs](#), [heatmap_rjs](#), [manhattan_rjs](#), [network_rjs](#), [scatterplot_rjs](#), [symheatmap_rjs](#), [wordcloud_rjs](#), [boxplot_rjs](#), [bubbles_rjs](#), [hiveplot_rjs](#), [piechart_rjs](#), [barplot_rjs](#), [tables_rjs](#), [surface3d_rjs](#), [scatter3d_rjs](#).

Examples

```
## Create an interactive heatmap in a temporal directory of your local machine
## Live examples on https://rjsplot.usal.es
```

```
## Format test data
words <- data.frame(word = rownames(USArrests), freq = USArrests[,4])
```

```
# Create WordCloud
if(interactive()){
  wordcloud_rjs(words)
}
```

Index

addCSS2report (report_rjs), 22
addHTML2report (report_rjs), 22
addImage2report (report_rjs), 22
addParagraph2report (report_rjs), 22
addPlot2report (report_rjs), 22

barplot_rjs, 2, 3–6, 8, 9, 11, 14, 15, 17,
19–26, 28–30
boxplot_rjs, 3, 3, 4–6, 8, 9, 11, 14, 15, 17,
19–26, 28–30
bubbles_rjs, 3, 4, 4, 5, 6, 8, 9, 11, 14, 15, 17,
19–26, 28–30

circularfv_rjs, 5
createAssembly, 7

dendrogram_rjs, 3–6, 8, 8, 9, 11, 14, 15, 17,
19–26, 28–30
densityplot_rjs, 3–6, 8, 9, 9, 11, 14, 15, 17,
19–26, 28–30

genomemap_rjs, 3–9, 10, 11, 12, 14, 15, 17,
19–26, 28–30
getAssemblyFromFasta, 10, 11
GRCh37, 12
GRCh37.bands, 12
GRCh38, 13
GRCh38.bands, 13

heatmap_rjs, 3–6, 8, 9, 11, 13, 14, 15, 17,
19–26, 28–30
hiveplot_rjs, 3–6, 8, 9, 11, 14, 15, 15, 17,
19–26, 28–30

manhattan_rjs, 3–9, 11, 12, 14, 15, 16, 17,
19–26, 28–30

NCBI36, 17
network_rjs, 3–6, 8, 9, 11, 14, 15, 17, 18,
19–26, 28–30
newInput, 19

piechart_rjs, 3–6, 8, 9, 11, 14, 15, 17, 19,
20, 20, 21–26, 28–30

R4web, 21
report_rjs, 22
RJSPlot, 23
RJSPlot-package (RJSPlot), 23

scatter3d_rjs, 3–6, 8, 9, 11, 14, 15, 17,
19–23, 23, 24–26, 28–30
scatterplot_rjs, 3–6, 8, 9, 11, 14, 15, 17,
19–24, 24, 25, 26, 28–30
surface3d_rjs, 3–6, 8, 9, 11, 14, 15, 17,
19–26, 26, 28–30
symheatmap_rjs, 3–6, 8, 9, 11, 14, 15, 17,
19–26, 27, 28–30

tables_rjs, 3–6, 8, 9, 11, 14, 15, 17, 19–26,
28, 28, 29, 30

wordcloud_rjs, 3–6, 8, 9, 11, 14, 15, 17,
19–26, 28, 29, 29, 30