

Package ‘RcppFastAD’

July 21, 2025

Type Package

Title 'Rcpp' Bindings to 'FastAD' Auto-Differentiation

Version 0.0.4

Date 2024-09-24

Description The header-only 'C++' template library 'FastAD' for automatic differentiation <<https://github.com/JamesYang007/FastAD>> is provided by this package, along with a few illustrative examples that can all be called from R.

URL <https://github.com/eddelbuettel/rcppfastad>

BugReports <https://github.com/eddelbuettel/rcppfastad/issues>

License GPL (>= 2)

Suggests tinytest

Encoding UTF-8

RoxygenNote 6.0.1

Imports Rcpp

LinkingTo Rcpp, RcppEigen

NeedsCompilation yes

Author Dirk Eddelbuettel [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6419-907X>>),
James Yang [aut] (ORCID: <<https://orcid.org/0000-0002-0015-7812>>)

Maintainer Dirk Eddelbuettel <edd@debian.org>

Repository CRAN

Date/Publication 2024-09-24 12:50:06 UTC

Contents

RcppFastAD-package	2
black_scholes	2
linear_regression	3
quadratic_expression	4

Index**5**

RcppFastAD-package	<i>'Rcpp' Bindings to 'FastAD' Auto-Differentiation</i>
--------------------	---

Description

The header-only 'C++' template library 'FastAD' for automatic differentiation <<https://github.com/JamesYang007/FastAD>> is provided by this package, along with a few illustrative examples that can all be called from R.

Package Content

Index of help topics:

RcppFastAD-package	'Rcpp' Bindings to 'FastAD' Auto-Differentiation
black_scholes	Black-Scholes valuation and first derivatives via Automatic Differentiation
linear_regression	Evaluate a squared-loss linear regression at a given parameter value
quadratic_expression	Compute the value and derivate of a quadratic expression $X' * \text{Sigma} * X$

Maintainer

Dirk Eddebuettel <edd@debian.org>

Author(s)

Dirk Eddebuettel [aut, cre] (<<https://orcid.org/0000-0001-6419-907X>>), James Yang [aut] (<<https://orcid.org/0000-0002-0015-7812>>)

black_scholes	<i>Black-Scholes valuation and first derivatives via Automatic Differentiation</i>
---------------	--

Description

This example illustrate how to use automatic differentiation to calculate the delte of a Black-Scholes call and put. It is based on the same example in the FastAD sources.

Usage

```
black_scholes(spot = 105, strike = 100, vol = 5, r = 1.25/100,
tau = 30/365)
```

Arguments

spot	A double with the spot price, default is 105 as in Boost example
strike	A double with the strike price, default is 100 as in Boost example
vol	A double with the (annualized) volatility (in percent), default is 5 (for 500 per cent) as in Boost example
r	A double with the short-term risk-free rate, default is 0.0125 as in Boost example
tau	A double with the time to expiration (in fractional years), default is 30/365 as in Boost example

Value

A matrix with rows for the call and put variant, and columns for option value, delta and vega

Examples

```
black_scholes()
```

linear_regression	<i>Evaluate a squared-loss linear regression at a given parameter value</i>
-------------------	---

Description

Not that this function does not actually fit the model. Rather it evaluates the squared sum of residuals and ‘gradient’ of parameters.

Usage

```
linear_regression(X, y, theta_hat, initial_lr = 1e-04, max_iter = 100L,
  tol = 1e-07)
```

Arguments

X	Matrix with independent explanatory variables
y	Vector with dependent variable
theta_hat	Vector with initial ‘guess’ of parameter values
initial_lr	[Optional] Scalar with initial step-size value, default is 1e-4
max_iter	[Optional] Scalar with maximum number of iterations, default is 100
tol	[Optional] Scalar with convergence tolerance, default is 1e-7

Value

A list object with the ‘loss’, ‘theta’ (parameters), ‘gradient’ and ‘iter’ for iterations

Examples

```
data(trees) # also used in help(lm)
X <- as.matrix(cbind(const=1, trees[, c("Girth", "Height")]))
y <- trees$Volume
linear_regression(X, y, rep(0, 3), tol=1e-12)
coef(lm(y ~ X - 1)) # for comparison
```

quadratic_expression	<i>Compute the value and derivate of a quadratic expression $X' * \text{Sigma} * X$</i>
----------------------	--

Description

Compute the value and derivate of a quadratic expression $X' * \text{Sigma} * X$

Usage

```
quadratic_expression(X, Sigma)
```

Arguments

X	A 2 element vector
Sigma	A 2 x 2 matrix

Value

A list with two elements for the expression evaluated for X and Sigma as well as

Examples

```
X <- c(0.5, 0.6)
S <- matrix(c(2, 3, 3, 6), 2, 2)
quadratic_expression(X, S)
```

Index

* **package**

RcppFastAD-package, [2](#)

black_scholes, [2](#)

linear_regression, [3](#)

quadratic_expression, [4](#)

RcppFastAD (RcppFastAD-package), [2](#)

RcppFastAD-package, [2](#)