

Package ‘TideCurves’

July 21, 2025

Type Package

Title Analysis and Prediction of Tides

Version 0.0.5

Maintainer Moritz Mueller-Navarra <muellernavarra@gmail.com>

Description Tidal analysis of evenly spaced observed time series (time step 1 to 60 min) with or without shorter gaps using the harmonic representation of inequalities.

The analysis should preferably cover an observation period of at least 19 years.

For shorter periods low frequency constituents are not taken into account, in accordance with the Rayleigh-Criterion.

The main objective of this package is to synthesize or predict a tidal time series.

License GPL-3

LazyData TRUE

Imports chron (>= 2.3-56), data.table (>= 1.14.0), fields (>= 11.6)

Depends R (>= 4.0.0)

RoxygenNote 7.1.1

Suggests testthat (>= 3.0.1)

Config/testthat/edition 3

NeedsCompilation no

Author Moritz Mueller-Navarra [aut, cre],

Sylvin Mueller-Navarra [aut] ((2019)

<<https://doi.org/10.5194/os-15-1363-2019>>),

Andreas Boesch [ctb] ((2019) <<https://doi.org/10.5194/os-15-1363-2019>>)

Repository CRAN

Date/Publication 2021-06-28 16:50:02 UTC

Contents

BuildDesign	2
BuildTC	2
Funcs	3
ResCurve	4

SynTC	5
TideCurve	6
tideObservation	8
Index	9

BuildDesign	<i>Builds the design matrix</i>
-------------	---------------------------------

Description

Builds the xdesign.matrix by calling Funcs. For internal use.

Usage

```
BuildDesign(tdiffa, numma, numme)
```

Arguments

- tdiffa The difference in days as double which stems from the analysis period.
- numma The transit number (start).
- numme The transit number (end).

Value

Returns a matrix

BuildTC	<i>Builds a TideCurve model</i>
---------	---------------------------------

Description

Builds a TideCurve model of class "tidecurve".

Usage

```
BuildTC(  
  dataInput = NULL,  
  otz = 1,  
  astime,  
  asdate,  
  aedate,  
  aetime,  
  km = -1,  
  mindt = 30,  
  keep_data = FALSE  
)
```

Arguments

dataInput	A data frame with the columns observation_date, observation_time and height. See attached data for correct formats.
otz	The time zone of the observations
astime	A string indicating the time you want the analysis to start with. Format: "hh:mm:ss"
asdate	A string indication the date you want the analysis to start with. Format: "yyyy/mm/dd".
aedate	A string indication the date you want the analysis to end with. Format: "yyyy/mm/dd".
aetime	A string indicating the time you want the analysis to end with. Format: "hh:mm:ss".
km	The number of nodes between two consecutive mean moon transits. Shall be less or equal to: $\text{round}(1440 \text{ [min]} / \text{time step [min]})$ Example: Time step 5 min: Use km = 288 or even smaller. Leave on default (km = -1) and supply mindt, when unsure.
mindt	Observation time step in [min]. Default is 30.
keep_data	Indicating whether you want to keep the data for computing residuals later. Default is FALSE which keeps the model footprint small.

Value

A model of class tidecurve, which is a list.

References

https://www.bsh.de/DE/PUBLIKATIONEN/_Anlagen/Downloads/Meer_und_Umwelt/Berichte-des-BSH/Berichte-des-BSH_50_de.pdf?__blob=publicationFile&v=13/
doi: [10.5194/os1513632019](https://doi.org/10.5194/os1513632019)

Examples

```
## Not run: BuildTC(dataInput = tideObservation, asdate = "2015/12/06",
  astime = "00:00:00", aedate = "2015/12/31",
  aetime = "23:30:00")
## End(Not run)
```

Funcs

Returns predictor vector for design matrix

Description

Returns predictor vector for design matrix from 39 astronomical angular velocities.

Usage

```
Funcs(tdiff, xi)
```

Arguments

tdiff	Length of input time series.
xi	Transit index

Value

A list with the selected angular velocities, their ranks and the predictor vector (Values between -1, 1).

ResCurve	<i>Computes the residuum between the observed data and the synthesis</i>
----------	--

Description

This function computes the residuum of the computed lunar and solar synthesis and the observed data

Usage

```
ResCurve(tcData, obsData)
```

Arguments

tcData	The results from TideCurve or BuildTC + SynTC. Warning: The synthesis period must overlap with the analysis period. Must be a data.table object. Please see examples.
obsData	The observation data with the columns observation_date, observation_time and height. See attached data for correct formats.

Value

A list with two data.tables with the joined data input and the computed difference between the observed data and the synthesis (res)

Examples

```
## Not run:
#Using TideCurve
tc <- TideCurve(dataInput = tideObservation, asdate = "2015/12/06",
               astime = "00:00:00", aedate = "2015/12/31",
               aetime = "23:30:00", ssdate = "2015/12/17",
               sstime = "00:00:00", sedate = "2015/12/31",
               setime = "23:30:00")
res_tc <- ResCurve(tc, tideObservation)

#Using BuildTC and SynTC
your_model <- BuildTC(dataInput = tideObservation, asdate = "2015/12/06",
                     astime = "00:00:00", aedate = "2016/12/31",
```

```

aetime = "23:30:00", keep_data = TRUE)

syn_tc <- SynTC(tmodel = your_model, ssdate = "2015/12/17", sstime = "00:00:00",
sedate = "2015/12/31", setime = "23:30:00")

syn_tc$data_matrix <- your_model$data_matrix

res_tc_n <- ResCurve(syn_tc, tideObservation)

## End(Not run)

```

SynTC	<i>Synthesizes a tide curve</i>
-------	---------------------------------

Description

Synthesizes a tide curve; model built with BuildTC().

Usage

```
SynTC(tmodel = NULL, ssdate, sstime, sedate, setime, solar_syn = TRUE)
```

Arguments

tmodel	The model you built with BuildTC(). Please see examples.
ssdate	Synthesis start date. This indicates the date you want your tide curve to start with.
sstime	Synthesis start time. The starting time for your tide table.
sedate	Synthesis end date.
setime	Synthesis end time.
solar_syn	Compute a solar synthesis? Default is TRUE.

Value

Returns a list with two elements, which are of class data.table and data.frame.

synthesis.lunar	The lunar synthesis data as a data.table object in UTC.
tide.curve	The solar tide curve as a data.table or NULL object (time zone of the observations).

References

https://www.bsh.de/DE/PUBLIKATIONEN/_Anlagen/Downloads/Meer_und_Umwelt/Berichte-des-BSH/Berichte-des-BSH_50_de.pdf?__blob=publicationFile&v=13/
doi: 10.5194/os1513632019

Examples

```
## Not run: SynTC(tmodel = your_model, ssdate = "2015/12/17", sstime = "00:00:00",
sedate = "2015/12/31", setime = "23:30:00")
## End(Not run)
```

TideCurve

Computes tide curves

Description

Takes a data frame as input with three columns (see example dataset) and returns a tide curve. Internally the analysis is carried out in lunar days. One mean lunar day lasts 1.0350501 mean solar days. Therefore the analysis time period should start one lunar day after the first observation and end one lunar day before the last observation.

Usage

```
TideCurve(
  dataInput,
  otz = 1,
  km = -1,
  mindt = 30,
  asdate,
  astime,
  aedate,
  aetime,
  ssdate,
  sstime,
  sedate,
  setime
)
```

Arguments

dataInput	A data frame with the columns observation_date, observation_time and height. See attached data for correct formats.
otz	The time zone of the observations
km	The number of nodes between two consecutive mean moon transits. Shall be less or equal to: $\text{round}(1440 [\text{min}] / \text{time step} [\text{min}])$ Example: Time step 5 min: Use km = 288 or even smaller. Leave on default (km = -1) and supply mindt, when unsure.
mindt	Observation time step in [min]. Default is 30.
asdate	A string indication the date you want the analysis to start with. Format: "yyyy/mm/dd".
astime	A string indicating the time you want the analysis to start with. Format: "hh:mm:ss"

aedate	A string indication the date you want the analysis to end with. Format: "yyyy/mm/dd".
aetime	A string indicating the time you want the analysis to end with. Format: "hh:mm:ss"
ssdate	Synthesis start date. This indicates the date you want your tide curve to start with. Format: See above
sstime	Synthesis start time. The starting time for your tide table. Format: See above
sedate	Synthesis end date. Format: See above
setime	Synthesis end time. Format: See above

Value

Returns a list with elements of the analysis, fitting and the tidal curve for given data

synthesis.lunar	The lunar synthesis data as a data.table object in UTC
data.matrix	The data needed for analysis
tide.curve	The solar tide curve as a data.table object (provided time zone)
lm.coeff	Coefficients for the km fitted linear models used in the synthesis as a list of 1-row matrices
diff.analyse	Time in days spanning the analysis

References

Godin, Gabriel (1972) The Analysis of Tides. Toronto, 264pp

doi: [10.5194/os1513632019](https://doi.org/10.5194/os1513632019)

https://www.bsh.de/DE/PUBLIKATIONEN/_Anlagen/Downloads/Meer_und_Umwelt/Berichte-des-BSH/Berichte-des-BSH_50_de.pdf?__blob=publicationFile&v=13

Examples

```
## Not run: TideCurve(dataInput = tideObservation, asdate = "2015/12/06",
  astime = "00:00:00",      aedate = "2015/12/31",
  aetime = "23:30:00",      ssdate = "2015/12/17",
  sstime = "00:00:00",      sedate = "2015/12/31",
  setime = "23:30:00")
## End(Not run)
```

tideObservation	<i>Sample file of high and low water times and heights</i>
-----------------	--

Description

A sample dataset containing observation date, time and height of high and low water

Usage

```
tideObservation
```

Format

A data frame with 10267 rows and 3 variables

observation_date date of observation, character value in "yyyy/mm/dd" format

observation_time time of observation, character value in "hh:mm:ss" format

height observed value, numeric value

Index

* **datasets**

tideObservation, [8](#)

BuildDesign, [2](#)

BuildTC, [2](#)

Funcs, [3](#)

ResCurve, [4](#)

SynTC, [5](#)

TideCurve, [6](#)

tideObservation, [8](#)