

Package ‘bizicount’

July 22, 2025

Title Bivariate Zero-Inflated Count Models Using Copulas

Version 1.3.3

Description Maximum likelihood estimation of copula-based zero-inflated (and non-inflated) Poisson and negative binomial count models, based on the article <[doi:10.18637/jss.v109.i01](https://doi.org/10.18637/jss.v109.i01)>. Supports Frank and Gaussian copulas. Allows for mixed margins (e.g., one margin Poisson, the other zero-inflated negative binomial), and several marginal link functions. Built-in methods for publication-quality tables using 'texreg', post-estimation diagnostics using 'DHARMA', and testing for marginal zero-modification via <[doi:10.1177/0962280217749991](https://doi.org/10.1177/0962280217749991)>. For information on copula regression for count data, see Genest and Nešlehová (2007) <[doi:10.1017/S0515036100014963](https://doi.org/10.1017/S0515036100014963)> as well as Nikoloulopoulos (2013) <[doi:10.1007/978-3-642-35407-6_11](https://doi.org/10.1007/978-3-642-35407-6_11)>. For information on zero-inflated count regression generally, see Lambert (1992) <<https://www.jstor.org/stable/1269547?origin=crossref>>. The author acknowledges support by NSF DMS-1925119 and DMS-212324.

License GPL (>= 3)

Encoding UTF-8

URL <https://github.com/jmniehaus/bizicount>

BugReports <https://github.com/jmniehaus/bizicount/issues>

RoxygenNote 7.3.1

Imports pbivnorm (>= 0.6.0), Formula (>= 1.2-4), rlang (>= 0.4.7), MASS (>= 7.3-54), numDeriv (>= 2016.8-1.1), methods, stats, utils, DHARMA (>= 0.3.4), texreg (>= 1.37.5)

Depends R (>= 4.1.0)

Suggests covr, testthat (>= 3.0.0)

Config/testthat/edition 3

LazyData true

NeedsCompilation no

Author John Niehaus [aut, cre]

Maintainer John Niehaus <jniehaus2257@gmail.com>

Repository CRAN

Date/Publication 2024-05-01 14:02:10 UTC

Contents

bizicount-package	2
bizicount	3
bizicount-class	8
extract.bizicount	10
extract.zicreg	12
make_DHARMa	14
predict.zicreg	16
simulate.bizicount	18
simulate.zicreg	21
terror	23
zic.reg	23
zicreg-class	27
zinb	28
zip	30
zi_test	32
Index	35

bizicount-package	<i>bizicount: Copula-Based Bivariate Zero-Inflated Count Regression Models</i>
-------------------	--

Description

The package provides regression functions for copula-based bivariate count models based on the paper [doi:10.18637/jss.v109.i01](https://doi.org/10.18637/jss.v109.i01), with and without zero-inflation, as well as regression functions for univariate zero-inflated count models. Generic methods from the [texreg-package](#) and [DHARMa](#) are extended to support this package, namely for the purposes of producing professional tables and carrying out post-estimation diagnostics. A generic for He et al. (2019)’s test for zero-modification is provided, with methods for both `bizicount` and `glm`-class objects.

Bivariate Functions

- `bizicount` – The primary function of this package. Carries out copula-based bivariate count regression via maximum likelihood using numerical optimization. Supports both zero-inflated and non-inflated distributions.
- `extract.bizicount` – Method for the `texreg` package’s `extract` generic. Creates a list of `texreg` objects, one for each margin, for use with that package’s other functions.
- `make_DHARMa` – Creates a list of `DHARMa` objects, one for each margin, for `bizicount` models. A wrapper around `createDHARMa`.
- `simulate.bizicount` – Method that simulates observations using the fitted model’s parameters, primarily for use with `DHARMa`.
- `zi_test` – Method for testing for marginal zero-modification using the estimated parameters from the model. This test is preferable to the Vuong, Wald, Score, and LR tests. See He et al. (2019).

Univariate Functions

- `zic.reg` – Univariate zero-inflated count regression models via maximum likelihood.
- `extract.zicreg` – Method for the `texreg` package's `extract` generic. Creates a `texreg` object that interfaces with that package's methods.
- `simulate.zicreg` – Method for simulating from the fitted model. Results are generally used for creating DHARMA objects.
#'
- `zi_test` – Method for testing for univariate zero-modification using the estimated parameters from the model. This test is preferable to the Vuong, Wald, Score, and LR tests. See He et al. (2019).

Author(s)

John Niehaus

References

[doi:10.18637/jss.v109.i01](https://doi.org/10.18637/jss.v109.i01)

bizicount

Bizicount: Maximum likelihood estimation of copula-based bivariate zero-inflated (and non-inflated) count models

Description

The main bivariate regression function of the `bizicount-package` Estimates copula-based bivariate zero-inflated (and non-inflated) count models via maximum likelihood. Supports the Frank and Gaussian copulas, as well as zero-inflated Poisson and negative binomial margins (and their non-inflated counterparts). It's class has associated `simulate` methods for post-estimation diagnostics using the `DHARMA` package, as well as an `extract` method for printing professional tables using `texreg`, and a test for zero-modification using `zi_test`. See the 'See Also' section for links to these methods.

Usage

```
bizicount(
  fmla1,
  fmla2,
  data,
  cop = "gaus",
  margins = c("pois", "pois"),
  link.ct = c("log", "log"),
  link.zi = c("logit", "logit"),
  scaling = "none",
  starts = NULL,
  keep = TRUE,
```

```

subset,
na.action,
weights,
frech.min = 1e-07,
pmf.min = 1e-07,
...
)

```

Arguments

fmla1, fmla2	formulas for the first margin and second margins, respectively. If non-inflated, of the form $y \sim x_{_1} + x_{_2} + \dots + x_{_k}$; if inflated, of the form $y \sim x_1 + x_2 + \dots + x_k z_1 + z_2 + \dots + z_p$, where y is the outcome for the first margin, x are covariates for count parameters, and z are covariates for zero-inflated parameters in each margin. All covariates can be the same.
data	A data.frame containing the response variables, covariates, and offsets for the model. If NULL, these quantities are searched for in the parent environment.
cop	Character string specifying the copula to be used. One of <code>c("gaus", "frank")</code> . Partial matching supported.
margins	Length 2 character vector specifying the marginal distributions for each outcome. Each of the two elements must be one of <code>c("pois", "nbinom", "zip", "zinb")</code> , and must be consistent with its corresponding formula (i.e., zero-inflated margins with zero-inflated formulas).
link.ct	Length 2 character string specifying the link function used for the count portion of each margin. One of <code>c("log", "identity", "sqrt")</code> .
link.zi	Length 2 character string specifying the link function used for the zero-inflation portion of each margin. One of <code>c("logit", "probit", "cauchit", "log", "cloglog")</code> . Ignored if corresponding margins entry is not zero-inflated.
scaling	Deprecated. It is recommended that users scale their covariates if they encounter convergence issues, which can be accomplished using the <code>scale()</code> function on their data before putting it into the <code>bizicount()</code> function.
starts	Numeric vector of starting values for parameter estimates. See 'Details' section regarding the correct order for the values in this vector. If NULL, starting values are obtained automatically by a univariate regression fit.
keep	Logical indicating whether to keep the model matrix in the returned model object. Defaults to TRUE, but can be set to FALSE to conserve memory. NOTE: Must be TRUE to use any post-estimation functions in this package, including <code>zi_test</code> .
subset	A vector indicating the subset of observations to use in estimation.
na.action	Deprecated.
weights	An optional numeric vector of weights for each observation.
frech.min	Lower boundary for Frechet-Hoeffding bounds on copula CDF. Used for computational purposes to prevent over/underflow in likelihood search. Must be in $[0, 1e - 5]$, with 0 imposing the original FH bounds without computational consideration. See 'Details.'

<code>pmf.min</code>	Lower boundary on copula PMF evaluations. Used for computational purposes to prevent over/underflow in likelihood search. Must be in $[0, 1e - 5]$, with 0 imposing no bound. See ‘Details.’
<code>...</code>	Additional arguments to be passed on to the quasi-newton fitting function, <code>nlm</code> . See ‘Details’ for some parameters that may be useful to alter.

Details

- `starts` – Starting values should be organized as follows:

1. count parameters for margin 1
2. count parameters for margin 2
3. zero-inflated parameters for margin 1 (if applicable),
4. zero-inflated parameters for margin 2 (if applicable),
5. inverse dispersion parameter for margin 1 (if applicable),
6. inverse dispersion parameter for margin 2 (if applicable)

Thus, in general count parameters should come first, followed by zero-inflation parameters, and finally inverse dispersion parameters.

- `frech.min` – Changing this argument should almost never be necessary. Frechet (1951) and Hoeffding (1940) showed that copula CDFs have bounds of the form $\max\{u + v - 1, 0\} \leq C(u, v) \leq \min\{u, v\}$, where u and v are uniform realizations derived from the probability integral transform. Due to numerical underflow, very small values of u and v can be rounded to zero. Particularly when evaluating the Gaussian copula CDF this is problematic, ultimately leading to infinite-valued likelihood evaluations. Therefore, we impose Frechet-Hoeffding bounds numerically as $\max\{u + v - 1, \text{frech.min}\} \leq C(u, v) \leq \min\{u, v, 1 - \text{frech.min}\}$. NOTE: Setting this to 0 imposes the original Frechet bounds mentioned above.
- `pmf.min` – Changing this argument should almost never be necessary. Observations can have likelihoods that are extremely close to 0. Numerically, these get rounded to 0 due to underflow. Then, taking logarithms results in an infinite likelihood. To avoid this, we bound PMF evaluations from below at `pmf.min`.
- `...` – Sometimes it may be useful to alter `nlm`’s default parameters. This can be done by simply passing those arguments into `bizicount()`. The two that seem to benefit the fitting process the most are `stepmax` and `steptol`. Readers are referred to the documentation on `nlm` for more details on these parameters. It can be useful to lower `stepmax` particularly when the Hessian is not negative definite at convergence, sometimes to a value between 0 and 1. It can also be beneficial to increase `steptol`.

Value

An S3 `bizicount-class` object, which is a list containing:

- `coef` – Coefficients of the model
- `coef.nid` – Coefficients without margin IDs
- `coef.orig` – Coefficients prior to transformations, for Gaussian dependence and negative binomial dispersion.
- `coef.orig.nid` – Coefficients prior to transforms, no margin IDs.
- `se` – Asymptotic normal-theory standard errors based on observed Fisher Information

- `se.nid` – Standard errors without margin IDs
- `z` – z-scores for parameter estimates
- `z.nid` – z-scores without margin IDs
- `p` – p-values for parameter estimates
- `p.nid` – p-values without margin IDs
- `coefmats` – A list containing coefficient matrices for each margin
- `loglik` – Scalar log-likelihood at convergence
- `grad` – Numerical gradient vector at convergence
- `n.iter` – Number of quasi-newton fitting iterations.
- `covmat` – Covariance matrix of parameter estimates based on observed Fisher Information
- `aic` – Model’s Akaike information
- `bic` – Model’s Bayesian information criterion
- `nobs` – Number of observations
- `margins` – Marginal distributions used in fitting
- `link.zi`, `link.ct` – Names of link functions used in fitting
- `invlink.ct`, `invlink.zi` – Inverse link functions used in fitting (the actual function, not their names)
- `outcomes` – Name of the response vector
- `conv` – Integer telling convergence status in `nlm`. See `?nlm`.
- `cop` – The copula used in fitting
- `starts` – list of starting values used
- `call` – The model’s call
- `model` – List containing model matrices, or `NULL` if `keep = F`.

Author(s)

John Niehaus

References

[doi:10.18637/jss.v109.i01](https://doi.org/10.18637/jss.v109.i01)

Genest C, Nešlehová J (2007). “A primer on copulas for count data.” *ASTIN Bulletin: The Journal of the IAA*, 37(2), 475–515.

Inouye DI, Yang E, Allen GI, Ravikumar P (2017). “A review of multivariate distributions for count data derived from the Poisson distribution.” *Wiley Interdisciplinary Reviews: Computational Statistics*, 9(3).

Joe H (1997). *Multivariate models and multivariate dependence concepts*. CRC Press.

Nikoloulopoulos A (2013). “Copula-Based Models for Multivariate Discrete Response Data.” In P Jaworski, F Durante, WK Härdle (eds.), *Copulae in Mathematical and Quantitative Finance*, chapter 11, pp. 231–250. Springer.

Nelsen RB (2007). *An Introduction to Copulas*. Springer Science & Business Media.

Trivedi P, Zimmer D (2017). “A note on identification of bivariate copulas for discrete countdata.” *Econometrics*, 5(1), 10.

Trivedi PK, Zimmer DM (2007). *Copula modeling: an introduction for practitioners*. NowPublishers Inc.

See Also

[extract.bizicount](#), [make_DHARMa](#), [zi_test](#)

Examples

```
### bizicount example

## SETUP
set.seed(123)
n = 300

# define a function to simulate from a gaussian copula
# first margin is zero-inflated negative binomial (zinb)
# second margin is zero-inflated poisson (zip)
# Note: marginal distributions are hard-coded in function, including
# inverse dispersion parameter for zinb.
gen = function(n,
               b1,
               b2,
               g1,
               g2,
               dep) {

  k1 = length(b1)
  k2 = length(b2)

  X1 = cbind(1, matrix(rbinom(n * (k1 - 1), 1, .5), ncol = k1 - 1))
  X2 = cbind(1, matrix(rexp(n * (k2 - 1), 3), ncol = k2 - 1))

  lam1 = exp(X1 %*% b1)
  lam2 = exp(X2 %*% b2)

  Z1 = cbind(1, matrix(runif(n * (k1 - 1), -1, 1), ncol = k1 - 1))
  Z2 = cbind(1, matrix(rnorm(n * (k2 - 1)), ncol = k2 - 1))

  psi1 = plogis(Z1 %*% g1)
  psi2 = plogis(Z2 %*% g2)

  norm_vars = MASS::mvrnorm(
    n,
    mu = c(0, 0),
    Sigma = matrix(c(1, dep, dep, 1), ncol = 2)
  )

  U = pnorm(norm_vars)
```

```

y1 = qzinb(U[, 1],
           mu = lam1,
           psi = psi1,
           size = .3)
y2 = qzip(U[, 2],
          lambda = lam2,
          psi = psi2)

dat = data.frame(
  X1 = X1[, -1],
  X2 = X2[, -1],
  Z1 = Z1[, -1],
  Z2 = Z2[, -1],
  y1,
  y2,
  lam1,
  lam2,
  psi1,
  psi2
)
return(dat)
}

# define parameters
b1 = c(1, -2, 3)
b2 = c(-1, 3, 1)
g1 = c(2, -1.5, 2)
g2 = c(-1, -3.75, 1.25)
rho = .5

# generate data
dat = gen(n, b1, b2, g1, g2, rho)
f1 = y1 ~ X1.1 + X1.2 | Z1.1 + Z1.2
f2 = y2 ~ X2.1 + X2.2 | Z2.1 + Z2.2

## END SETUP

# estimate model

mod = bizicount(f1, f2, dat, cop = "g", margins = c("zinb", "zip"), keep = TRUE)

print(mod)
summary(mod)

```


Description

Note that bizicount objects are generally S3, and should use S3 syntax. This S4 class is defined only for compatability with `texreg`. However, the contents of bizicount objects is the same in both S3 and S4, so the descriptions below apply in both cases.

Slots

`coef` Coefficients of the model
`coef.nid` Coefficients without margin IDs
`coef.orig` Coefficients prior to transformations, for Gaussian dependence and negative binomial dispersion.
`coef.orig.nid` Coefficients prior to transforms, no margin IDs.
`se` Asymptotic standard errors based on observed Fisher Information
`se.nid` Standard errors without margin IDs
`z` z-scores for parameter estimates
`z.nid` z-scores without margin IDs
`p` p-values for parameter estimates
`p.nid` p-values without margin IDs
`coefmats` A list containing coefficient matrices for each margin
`loglik` Scalar log-likelihood at convergence
`grad` Gradient vector at convergence
`n.iter` Number of quasi-newton fitting iterations.
`covmat` Covariance matrix of parameter estimates based on observed Fisher Information
`aic` Model's Akaike information
`bic` Model's Bayesian information criterion
`nobs` Number of observations
`margins` Marginal distributions used in fitting
`link.zi, link.ct` Names of link functions used in fitting
`invlink.ct, invlink.zi` Inverse link functions used in fitting (the actual function, not their names)
`outcomes` Name of the response vector
`conv` Integer telling convergence status.
`cop` The copula used in fitting
`starts` list of starting values used
`call` The model's call
`model` List containing model matrices, or NULL if keep = F.

extract.bizicount	<i>Texreg for bizicount objects</i>
-------------------	-------------------------------------

Description

This is a method for the [extract](#) generic to be used with objects that are output from the [bizicount](#) function. The results can be used with any of the [texreg-package](#) generics.

Usage

```
## S3 method for class 'bizicount'
extract(model, CI = NULL, id = TRUE, ...)
```

Arguments

model	A bizicount-class model object (S3).
CI	The two-tailed confidence level, if confidence intervals are desired in the texreg object, otherwise NULL.
id	Logical indicating whether to prepend equation identifiers to coefficient names (ct_ for count parameters, zi_ for zero-inflated parameters)
...	Ignored.

Value

A [texreg-class](#) object, as produced by [createTexreg](#), which can interface with all of that package's generics.

Note

Users can typically just call [texreg](#) directly on a [bizicount-class](#) object, instead of first extracting and then calling texreg.

Author(s)

John Niehaus

References

Leifeld, Philip (2013). [texreg](#): Conversion of Statistical Model Output in R to LaTeX and HTML Tables. Journal of Statistical Software, 55(8), 1-24. URL <http://dx.doi.org/10.18637/jss.v055.i08>.

See Also

[extract](#), [createTexreg](#), [bizicount](#)

Examples

```
## SETUP
set.seed(123)
n = 500

# define a function to simulate from a gaussian copula
# first margin is zero-inflated negative binomial (zinb)
# second margin is zero-inflated poisson (zip)
# Note: marginal distributions are hard-coded in function, including
# inverse dispersion parameter for zinb.
gen = function(n,
               b1,
               b2,
               g1,
               g2,
               dep) {

  k1 = length(b1)
  k2 = length(b2)

  X1 = cbind(1, matrix(rbinom(n * (k1 - 1), 1, .5), ncol = k1 - 1))
  X2 = cbind(1, matrix(rexp(n * (k2 - 1), 3), ncol = k2 - 1))

  lam1 = exp(X1 %*% b1)
  lam2 = exp(X2 %*% b2)

  Z1 = cbind(1, matrix(runif(n * (k1 - 1), -1, 1), ncol = k1 - 1))
  Z2 = cbind(1, matrix(rnorm(n * (k2 - 1)), ncol = k2 - 1))

  psi1 = plogis(Z1 %*% g1)
  psi2 = plogis(Z2 %*% g2)

  norm_vars = MASS::mvrnorm(
    n,
    mu = c(0, 0),
    Sigma = matrix(c(1, dep, dep, 1), ncol = 2)
  )

  U = pnorm(norm_vars)

  y1 = qzinb(U[, 1],
             mu = lam1,
             psi = psi1,
             size = .3)
  y2 = qzip(U[, 2],
            lambda = lam2,
            psi = psi2)

  dat = data.frame(
    X1 = X1[, -1],
    X2 = X2[, -1],
    Z1 = Z1[, -1],
```

```

        Z2 = Z2[, -1],
        y1,
        y2,
        lam1,
        lam2,
        psi1,
        psi2
    )
    return(dat)
}

# define parameters
b1 = c(1, -2, 3)
b2 = c(-1, 3, 1)
g1 = c(2, -1.5, 2)
g2 = c(-1, -3.75, 1.25)
rho = .5

# generate data
dat = gen(n, b1, b2, g1, g2, rho)
f1 = y1 ~ X1.1 + X1.2 | Z1.1 + Z1.2
f2 = y2 ~ X2.1 + X2.2 | Z2.1 + Z2.2

## END SETUP

# estimate model

mod = bizicount(f1, f2, dat, cop = "g", margins = c("zinb", "zip"), keep=TRUE)

# extract texreg objects, one with SEs, one with CIs
tr_obj_se = texreg::extract(mod)
tr_obj_ci = texreg::extract(mod, CI = .95)

# output to latex, single table.
# Note use of c(), because tr_obj_se, tr_obj_ci are lists.
texreg::texreg(c(tr_obj_se, tr_obj_ci))

# output as plaintext, two tables
texreg::screenreg(tr_obj_se)
texreg::screenreg(tr_obj_ci)

```

Description

This is a method for the [extract](#) generic to be used with objects that are output from the [zic.reg](#) function. The results can then interface with the [texreg-package](#), as shown in examples below.

Usage

```
## S3 method for class 'zicreg'
extract(model, CI = NULL, id = TRUE, ...)
```

Arguments

model	A zicreg model object, returned by zic.reg .
CI	The two-tailed confidence level, if desired in the resulting texreg object.
id	Logical indicating whether to prepend equation identifiers to coefficient names (ct_ for count parameters, zi_ for zero-inflated parameters)
...	Ignored.

Value

A [texreg-class](#) object, as produced by [createTexreg](#), which can interface with all of that package's generics. See 'Examples.'

Author(s)

John Niehaus

References

Leifeld, Philip (2013). [texreg](#): Conversion of Statistical Model Output in R to LaTeX and HTML Tables. Journal of Statistical Software, 55(8), 1-24. URL <http://dx.doi.org/10.18637/jss.v055.i08>.

See Also

[extract](#), [createTexreg](#), [zic.reg](#)

Examples

```
# Simulate some zip data
n=1000
x = cbind(1, rnorm(n))
z = cbind(1, rbeta(n, 4, 8))
b = c(1, 2.2)
g = c(-1, 1.7)
lam = exp(x %*% b)
psi = plogis(z %*% g)

y = bizicount::rzip(n, lambda = lam, psi=psi)
dat = cbind.data.frame(x = x[,-1], z = z[,-1], y = y)
```

```
# estimate model

mod = zic.reg(y ~ x | z, data = dat)

### Output to table with texreg

# extract information

tr_obj_se = texreg::extract(mod)
tr_obj_ci = texreg::extract(mod, CI = .95)

# output to latex, single table

texreg::texreg(list(tr_obj_se, tr_obj_ci))

# output to plain text, multiple tables

texreg::screenreg(tr_obj_se)
texreg::screenreg(tr_obj_ci)
```

make_DHARMa

DHARMa-class objects from bizicount models

Description

A wrapper around the [DHARMa](#) package's [createDHARMa](#) function. Creates a list of DHARMa objects, one for each margin of a [bizicount-class](#) object, using simulated responses from [simulate.bizicount](#).

Usage

```
make_DHARMa(object, nsim = 250, seed = 123, method = "PIT")
```

Arguments

object	A bizicount-class object, as returned by bizicount .
nsim	Number of simulated responses from the fitted model to use for diagnostics.
seed	Random seed for simulating from fitted model.
method	See createDHARMa .

Value

A list of [DHARMa](#) objects.

Note

This is merely a wrapper around the [createDHARMa](#) function to conveniently get DHARMa objects for each margin of a bizicount model.

Author(s)

John Niehaus

References

Florian Hartig (2022). DHARMA: Residual Diagnostics for Hierarchical (Multi-Level / Mixed) Regression Models. R package version 0.4.5. <https://CRAN.R-project.org/package=DHARMA>

See Also

[DHARMA](#), [createDHARMA](#), [simulate.bizicount](#)

Examples

```
## SETUP
set.seed(123)
n = 100

# define a function to simulate from a gaussian copula
# first margin is zero-inflated negative binomial (zinb)
# second margin is zero-inflated poisson (zip)
# Note: marginal distributions are hard-coded in function, including
# inverse dispersion parameter for zinb.
gen = function(n, b1, b2, g1, g2, dep) {

  k1 = length(b1)
  k2 = length(b2)

  X1 = cbind(1, matrix(rbinom(n * (k1 - 1), 1, .5), ncol = k1 - 1))
  X2 = cbind(1, matrix(rexp(n * (k2 - 1), 3), ncol = k2 - 1))

  lam1 = exp(X1 %*% b1)
  lam2 = exp(X2 %*% b2)

  Z1 = cbind(1, matrix(runif(n * (k1 - 1), -1, 1), ncol = k1 - 1))
  Z2 = cbind(1, matrix(rnorm(n * (k2 - 1)), ncol = k2 - 1))

  psi1 = plogis(Z1 %*% g1)
  psi2 = plogis(Z2 %*% g2)

  norm_vars = MASS::mvrnorm(
    n,
    mu = c(0, 0),
    Sigma = matrix(c(1, dep, dep, 1), ncol = 2)
  )

  U = pnorm(norm_vars)

  y1 = qzinb(U[, 1],
    mu = lam1,
    psi = psi1,
    size = .3)
```

```

    y2 = qzip(U[, 2],
              lambda = lam2,
              psi = psi2)

    dat = data.frame(
      X1 = X1[, -1],
      X2 = X2[, -1],
      Z1 = Z1[, -1],
      Z2 = Z2[, -1],
      y1,
      y2,
      lam1,
      lam2,
      psi1,
      psi2
    )
    return(dat)
  }

# define parameters
b1 = c(1, -2, 3)
b2 = c(-1, 3, 1)
g1 = c(2, -1.5, 2)
g2 = c(-1, -3.75, 1.25)
rho = .5

# generate data
dat = gen(n, b1, b2, g1, g2, rho)
f1 = y1 ~ X1.1 + X1.2 | Z1.1 + Z1.2
f2 = y2 ~ X2.1 + X2.2 | Z2.1 + Z2.2

## END SETUP

# estimate model

mod = bizicount(f1, f2, dat, cop = "g", margins = c("zinb", "zip"), keep=TRUE)

# diagnose model with DHARMA
# see end for simulate.bizicount example.

dharm = make_DHARMA(mod, nsim = 100)

lapply(dharm, DHARMA::testResiduals)

```


Description

Predicts the mean, probability, count mean, or zero-inflation probability for new data using parameters from a fitted zero-inflated count regression model.

Usage

```
## S3 method for class 'zicreg'
predict(object, newdata = NULL, y.new = NULL, type = "mean", ...)
```

Arguments

object	A fitted <code>zic.reg</code> object.
newdata	A <code>data.frame</code> containing new values of the same covariates appearing in fitted model.
y.new	An optional vector of new response values, used only for <code>type = "prob"</code> .
type	String, one of <code>c("mean", "prob", "psi", "lambda")</code> . "mean" will predict the conditional mean of the mixture distribution, "prob" will predict the probability of a new response value, "psi" will predict the probability of zero-inflation, and "lambda" will predict the mean of the count portion of the mixture distribution. NOTE: Setting <code>type = "mean"</code> and leaving <code>newdata = NULL</code> is the same as calling <code>fitted(object)</code> .
...	Ignored.

Value

A numeric vector containing the predictions using the model parameters.

Author(s)

John Niehaus

Examples

```
# Simulate some zip data
n=1000
x = cbind(1, rnorm(n))
z = cbind(1, rbeta(n, 4, 8))
b = c(1, 2.2)
g = c(-1, 1.7)
lam = exp(x %*% b)
psi = plogis(z %*% g)

y = bizicount::rzip(n, lambda = lam, psi=psi)
dat = cbind.data.frame(x = x[,-1], z = z[,-1], y = y)

# estimate model

mod = zic.reg(y ~ x | z, data = dat, keep = TRUE)
```

```

### Predict on observed/training data
# predict conditional mean (fitted values)
predict(mod, type = "mean")

# predict probability Y = y
probs_pred_obs = predict(mod, type = "prob")

# predict mean of count distribution (lambda)
lambda_pred_obs = predict(mod, type = "lambda")

# mse predicted vs true lambda values
mean((lam - lambda_pred_obs)**2)

# predict zero inflation probability (psi)
psi_pred_obs = predict(mod, type = "psi")

# MSE predicted vs true zero-inflation probabilities
mean((psi-psi_pred_obs)**2)

### Predict on test data
# simulate some test data

x = cbind(1, rnorm(n, mean = -0.5, sd = 1.25))
z = cbind(1, rbeta(n, 6, 12))
y = rzip(n, lambda = exp(x %>% coef(mod)[1:2]), psi = plogis(z %>% coef(mod)[3:4]))
dat_new = cbind.data.frame(x = x[, -1], z = z[, -1], y = y)

# predict conditional mean
mean_new = predict(mod, type = "mean", newdata = dat_new)
mean((y - mean_new)**2)

# predict probability of Y = y
probs_new = predict(mod, type = "prob", newdata = dat_new, y.new = y)

# predict lambda
lambda_new = predict(mod, type = "lambda", newdata = dat_new)

# predict zero inflation probability
psi_new = predict(mod, type = "psi", newdata = dat_new)

```

Description

Simulates random response values using the fitted conditional mean function for each margin of a `bizicount-class` object. Primarily for use with the `DHARMA` package.

Usage

```
## S3 method for class 'bizicount'
simulate(object, nsim = 250, seed = 123, ...)
```

Arguments

<code>object</code>	A fitted <code>bizicount-class</code> object, as returned by <code>bizicount</code> .
<code>nsim</code>	Number of simulated response values from the fitted model. E.g., <code>nsim = 250</code> will simulate each observation 250 times, for $n \times 250$ total observations.
<code>seed</code>	Seed used for simulating from fitted model. If <code>NULL</code> , no seed is set.
<code>...</code>	Ignored.

Value

A length 2 list, with each entry containing a numeric $n \times nsim$ matrix for each margin of the `bizicount` model. Rows index the observation, and columns index the simulated dataset number.

Author(s)

John Niehaus

References

Florian Hartig (2022). `DHARMA`: Residual Diagnostics for Hierarchical (Multi-Level / Mixed) Regression Models. R package version 0.4.5. <https://CRAN.R-project.org/package=DHARMA>

See Also

`createDHARMA`, `simulateResiduals`

Examples

```
## SETUP
set.seed(123)
n = 150

# define a function to simulate from a gaussian copula
# first margin is zero-inflated negative binomial (zinb)
# second margin is zero-inflated poisson (zip)
# Note: marginal distributions are hard-coded in function, including
# inverse dispersion parameter for zinb.
gen = function(n,
               b1,
               b2,
               g1,
```

```

      g2,
      dep) {

k1 = length(b1)
k2 = length(b2)

X1 = cbind(1, matrix(rbinom(n * (k1 - 1), 1, .5), ncol = k1 - 1))
X2 = cbind(1, matrix(rexp(n * (k2 - 1), 3), ncol = k2 - 1))

lam1 = exp(X1 %*% b1)
lam2 = exp(X2 %*% b2)

Z1 = cbind(1, matrix(runif(n * (k1 - 1), -1, 1), ncol = k1 - 1))
Z2 = cbind(1, matrix(rnorm(n * (k2 - 1)), ncol = k2 - 1))

psi1 = plogis(Z1 %*% g1)
psi2 = plogis(Z2 %*% g2)

norm_vars = MASS::mvrnorm(
  n,
  mu = c(0, 0),
  Sigma = matrix(c(1, dep, dep, 1), ncol = 2)
)

U = pnorm(norm_vars)

y1 = qzinb(U[, 1],
  mu = lam1,
  psi = psi1,
  size = .3)
y2 = qzip(U[, 2],
  lambda = lam2,
  psi = psi2)

dat = data.frame(
  X1 = X1[, -1],
  X2 = X2[, -1],
  Z1 = Z1[, -1],
  Z2 = Z2[, -1],
  y1,
  y2,
  lam1,
  lam2,
  psi1,
  psi2
)
return(dat)
}

# define parameters
b1 = c(1, -2, 3)
b2 = c(-1, 3, 1)

```

```

g1 = c(2, -1.5, 2)
g2 = c(-1, -3.75, 1.25)
rho = .5

# generate data
dat = gen(n, b1, b2, g1, g2, rho)
f1 = y1 ~ X1.1 + X1.2 | Z1.1 + Z1.2
f2 = y2 ~ X2.1 + X2.2 | Z2.1 + Z2.2

## END SETUP

# estimate model
mod = bizicount(f1, f2, dat, cop = "g", margins = c("zinb", "zip"), keep=TRUE)

# simulate from fitted model
sims = simulate(mod, nsim = 150)

# input sims to DHARMA for diagnostics
# margin 1
d1 = DHARMA::createDHARMA(
  simulatedResponse = sims[[1]],
  observedResponse = dat$y1,
  fittedPredictedResponse = fitted(mod)[,1],
  integerResponse = TRUE,
  method = "PIT"
)

# margin 2
d2 = DHARMA::createDHARMA(
  simulatedResponse = sims[[2]],
  observedResponse = dat$y2,
  fittedPredictedResponse = fitted(mod)[,2],
  integerResponse = TRUE,
  method = "PIT"
)

# test each margin
DHARMA::testResiduals(d1)
DHARMA::testResiduals(d2)

```

Description

Simulates responses using the fitted parameters from a `zicreg-class` object, as returned by `zic.reg`. Primarily useful for methods found in `DHARMA` package. See 'Examples.'

Usage

```
## S3 method for class 'zicreg'
simulate(object, nsim = 250, seed = 123, ...)
```

Arguments

<code>object</code>	A <code>zicreg-class</code> model object, as returned by <code>zic.reg</code> .
<code>nsim</code>	Number of simulated datasets to create.
<code>seed</code>	Random seed for random number generation in simulations. If NULL, no seed is set.
<code>...</code>	Ignored.

Value

A numeric $n \times nsim$ matrix, with rows indexing observations, and columns indexing the simulation number.

Author(s)

John Niehaus

References

Florian Hartig (2022). DHARMA: Residual Diagnostics for Hierarchical (Multi-Level / Mixed) Regression Models. R package version 0.4.5. <https://CRAN.R-project.org/package=DHARMA>

Examples

```
# Simulate some zip data
n=300
x = cbind(1, rnorm(n))
z = cbind(1, rbeta(n, 4, 8))
b = c(1, 2.2)
g = c(-1, 1.7)
lam = exp(x %*% b)
psi = plogis(z %*% g)

y = bizicount::rzip(n, lambda = lam, psi=psi)
dat = cbind.data.frame(x = x[,-1], z = z[,-1], y = y)

# estimate model

mod = zic.reg(y ~ x | z, data = dat, keep = TRUE)

# simulate from fit for use in dharma
```

```

sims = simulate(mod)

### Make dharma object

dharm = DHARMA::createDHARMA(
  simulatedResponse = sims,
  observedResponse = y,
  fittedPredictedResponse = fitted(mod),
  integerResponse = TRUE,
  method = "PIT"
)

### Plot the DHARMA object, do other diagnostics
plot(dharm)
DHARMA::testResiduals(dharm)

```

terror	<i>Nigeria Terrorism Data</i>
--------	-------------------------------

Description

Data on terrorist attacks by Fulani Extremists and Boko Haram in Nigeria, from the year 2014. Attacks data from Global Terrorism Database, other variables from UCDP PRIO-Grid data.

Usage

```
terror
```

Format

terror:

A data frame with 312 rows and 6 columns:

att.ful, att.bok Integer number of attacks by Fulani Extremists and Boko Haram in 2014.

xcoord, ycoord Longitude and Latitude of grid-cell centroid where attack occurs.

pop Population in grid cell.

mtns Proportion of terrain in grid cell that is considered mountainous.

zic.reg	<i>Univariate zero-inflated Poisson and negative binomial regression models</i>
---------	---

Description

This function from the [bizicount](#) package estimates univariate zero-inflated Poisson and negative binomial regression models via maximum likelihood using either the [nlm](#) or [optim](#) optimization functions. It's class has associated [simulate](#) methods for post-estimation diagnostics using the [DHARMA](#) package, as well as an [extract](#) method for printing professional tables using [texreg](#). Visit the 'See Also' section for links to these methods for zicreg objects.

Usage

```

zic.reg(
  fmla = NULL,
  data,
  dist = "pois",
  link.ct = "log",
  link.zi = "logit",
  optimizer = "nlm",
  starts = NULL,
  subset,
  na.action,
  weights = rep(1, length(y)),
  X = NULL,
  z = NULL,
  y = NULL,
  offset.ct = NULL,
  offset.zi = NULL,
  warn.parent = T,
  keep = F,
  ...
)

```

Arguments

fmla	A formula of the form $y \sim x_1 + x_2 + \dots + x_n + \text{offset}(\text{count_var}) \mid z_1 + \dots + z_n + \text{offset}(\text{zero_infl})$ where the x values are covariates in the count portion of the model, and z are in the zero-inflation portion. The z and x variables can be the same. If <code>NULL</code> , design matrices, the response vector, and offsets can be entered directly; see <code>X</code> , <code>z</code> , <code>y</code> , <code>offset.ct</code> , and <code>offset.zi</code> below.
data	A data.frame containing all variables appearing in <code>fmla</code> , including offsets. If not specified, variables are searched for in parent environment.
dist	The distribution used for the count portion of the zero-inflated mixture. One of <code>c("pois", "nbinom")</code> , partial matching supported.
link.ct	String specifying the link function used for the count portion of the mixture distribution. One of <code>c("log", "identity", "sqrt")</code> . See family .
link.zi	Character string specifying the link function used for the zero-inflation portion of the mixture distribution. One of <code>c("logit", "probit", "cauchit", "log", "cloglog")</code> . See family .
optimizer	String specifying the optimizer to be used for fitting, one of <code>c("nlm", "optim")</code> . If <code>"optim"</code> , defaults to <code>method="BFGS"</code> .
starts	Optional vector of starting values used for the numerical optimization procedure. Should have count parameters first (with intercept first, if applicable), followed by zero-inflated parameters (with intercept first, if applicable), and the inverse dispersion parameter last (if applicable).
subset	Vector indicating the subset of observations on which to estimate the model

<code>na.action</code>	A function which indicates what should happen when the data contain NAs. Default is <code>na.omit</code> .
<code>weights</code>	An optional numeric vector of weights for each observation.
<code>X, z</code>	If <code>fmla = NULL</code> , these are the design matrices of covariates for the count and zero-inflation portions, respectively. Both require no missingness. Similar in spirit to <code>glm.fit</code> in that it can be faster for larger datasets because it bypasses model matrix creation.
<code>y</code>	If <code>fmla = NULL</code> , a vector containing the response variable.
<code>offset.ct, offset.zi</code>	If <code>fmla = NULL</code> , vectors containing the (constant) offset for the count and zero-inflated portions, respectively. Must be equal in length to <code>y</code> , and row-dim of <code>X</code> , <code>z</code> . If left <code>NULL</code> , defaults to <code>rep(0, length(y))</code> .
<code>warn.parent</code>	Logical indicating whether to warn about data not being supplied.
<code>keep</code>	Logical indicating whether to keep the model matrices in the returned model object. Must be <code>TRUE</code> to use <code>DHARMA</code> and <code>texreg</code> with the model object, e.g., via <code>simulate.zicreg</code> and <code>extract.zicreg</code> , as well as base generics like <code>fitted</code> and <code>predict</code> .
<code>...</code>	Additional arguments to pass on to the chosen optimizer, either <code>nlm</code> or <code>optim</code> . See 'Examples'.

Value

An S3 `zicreg-class` object, which is a list containing:

- `call` – The original function call
- `obj` – The class of the object
- `coef` – Vector of coefficients, with count, then `zi`, then dispersion.
- `se` – Vector of asymptotic standard errors
- `grad` – Gradient vector at convergence
- `link.ct` – Name of link used for count portion
- `link.zi` – Name of link used for zero-inflated portion
- `dist` – Name of distribution used for count portion
- `optimizer` – Name of optimization package used in fitting
- `coefmat.ct` – Coefficient matrix for count portion
- `coefmat.zi` – Coefficient matrix for zero-inflated portion
- `convergence` – Convergence code from optimization routine.
- `coefmat.all` – Coefficient matrix for both parts of the model
- `theta` – Coefficient matrix for dispersion, if applicable.
- `covmat` – Asymptotic covariance matrix
- `nobs` – Number of observations
- `aic` – Akaike information
- `bic` – Bayes information
- `loglik` – Log-likelihood at convergence
- `model` – List containing model matrices if `keep = TRUE`

Author(s)

John Niehaus

References

Lambert, Diane. "Zero-inflated Poisson regression, with an application to defects in manufacturing." *Technometrics* 34.1 (1992): 1-14.

See Also

[simulate.zicreg](#), [extract.zicreg](#)

Examples

```
## ZIP example
# Simulate some zip data
n=1000
x = cbind(1, rnorm(n))
z = cbind(1, rbeta(n, 4, 8))
b = c(1, 2.2)
g = c(-1, 1.7)
lam = exp(x %*% b)
psi = plogis(z %*% g)

y = bizicount::rzip(n, lambda = lam, psi=psi)
dat = cbind.data.frame(x = x[,-1], z = z[,-1], y = y)

# estimate zip model using NLM, no data.frame

mod = zic.reg(y ~ x[,-1] | z[,-1])

# same model, with dataframe

mod = zic.reg(y ~ x | z, data = dat)

# estimate zip using NLM, adjust stepmax via ... param

mod = zic.reg(y ~ x[,-1] | z[,-1], stepmax = .5)

# estimate zip using optim

mod = zic.reg(y ~ x[,-1] | z[,-1], optimizer = "optim")

# pass different method, reltol to optim using ... param

mod = zic.reg(y ~ x[,-1] | z[,-1],
              optimizer = "optim",
              method = "Nelder-Mead",
              control = list(reltol = 1e-10))
```

```

    )

# No formula, specify design matrices and offsets.
zic.reg(y=y, X=x, z=z)

## ZINB example
# simulate zinb data

disp = .5
y = bizicount::rzinb(n, psi = psi, size = disp, mu=lam)

# zinb model, use keep = TRUE for post-estimation methods

mod = zic.reg(y ~ x[,-1] | z[,-1], dist = "n", keep = TRUE)

print(mod)
summary(mod)

```

zicreg-class

The zicreg S4 Class

Description

Note that zicreg objects are, in general, S3. However, this S4 class is defined for compatability with [texreg](#). Interaction with zicreg objects should generally use S3 syntax, but the below objects have the same name in both the S3 and S4 objects (but are in a list for S3).

Slots

call The original function call
obj The class of the object
coef Vector of coefficients, with count, then zi, then dispersion.
se Vector of asymptotic standard errors
grad Gradient vector at convergence
link.ct Name of link used for count portion
link.zi Name of link used for zero-inflated portion
dist Name of distribution used for count portion
optimizer Name of optimization package used in fitting
coefmat.ct Coefficient matrix for count portion
coefmat.zi Coefficient matrix for zero-inflated portion
convergence Convergence code from optimization routine.

`coefmat.all` Coefficient matrix for both parts of the model
`theta` Coefficient matrix for dispersion, if applicable.
`covmat` Asymptotic covariance matrix
`nobs` Number of observations
`aic` Akaike information
`bic` Bayes information
`loglik` Log-likelihood at convergence
`model` List containing model matrices if `keep = TRUE`

zinb

The zero-inflated negative binomial (ZINB) distribution

Description

These functions are used to evaluate the zero-inflated negative binomial distribution's probability mass function (PMF), cumulative distribution function (CDF), and quantile function (inverse CDF), as well as generate random realizations from the ZINB distribution.

Usage

```
dzinb(
  x,
  size,
  psi,
  mu = NULL,
  prob = NULL,
  lower.tail = TRUE,
  log = FALSE,
  recycle = FALSE
)
```

```
pzinb(
  q,
  size,
  psi,
  mu = NULL,
  prob = NULL,
  lower.tail = TRUE,
  log.p = FALSE,
  recycle = FALSE
)
```

```
qzinb(
  p,
  size,
```

```

    psi,
    mu = NULL,
    prob = NULL,
    lower.tail = TRUE,
    log.p = FALSE,
    recycle = FALSE
  )

  rzinb(n, size, psi, mu = NULL, prob = NULL, recycle = FALSE)

```

Arguments

x, q	Vector of quantiles at which to evaluate the PMF and CDF, respectively. Should be non-negative integers.
size	The inverse dispersion parameter, or number of successful trials, both for the negative binomial portion of the ZINB mixture distribution. See nbinom .
psi	Vector of zero-inflation probabilities.
mu	Vector of means for the count portion of the zero-inflated negative binomial distribution. Only one of mu or prob should be specified, not both. Should be non-negative. NOTE: This is <i>not</i> the mean of the ZINB distribution; it is the mean of the NB component of the mixture distribution. See nbinom .
prob	The probability of success on each trial in the negative binomial portion of the mixture distribution. Only one of mu or prob should be specified, not both. See nbinom .
lower.tail	Logical indicating whether probabilities should be $Pr(X \leq x)$ or $Pr(X > x)$
log, log.p	Logical indicating whether probabilities should be returned on log scale (for dzip and pzip), or are supplied on log-scale (for qzip).
recycle	Logical indicating whether to permit arbitrary recycling of arguments with unequal length. See 'Details' and 'Examples.'
p	Vector of probabilities at which to evaluate the quantile function.
n	Number of realizations to generate from the distribution

Value

dzinb returns the mass function evaluated at x, pzinb returns the CDF evaluated at q, qzinb returns the quantile function evaluated at p, and rzinb returns random realizations with the specified parameters.

Author(s)

John Niehaus

References

Lambert, Diane. "Zero-inflated Poisson regression, with an application to defects in manufacturing." *Technometrics* 34.1 (1992): 1-14.

Examples

```
# zero-inflated negative binomial examples

# two unique lengthed arguments, one is length 1 though. No error.
dzinb(4, size=.25, mu= c(1,2,3), psi=c(.2, .1, .15))

# two unique lengthed arguments, one of them is not length 1
# error
## Not run:

dzinb(5, size=c(.25, .3), mu= c(1,2,3), psi=c(.2, .1, .15))

## End(Not run)

# two unique lengthed arguments, one of them is not length 1, set
# recycle = T, no error but can give innacurate results.
dzinb(5, size=c(.25, .3), mu= c(1,2,3), psi=c(.2, .1, .15), recycle=TRUE)
```

zip

The zero-inflated Poisson (ZIP) distribution

Description

These functions are used to evaluate the zero-inflated Poisson distribution's probability mass function (PMF), cumulative distribution function (CDF), and quantile function (inverse CDF), as well as generate random realizations from the ZIP distribution.

Usage

```
dzip(x, lambda, psi, log = FALSE, recycle = FALSE)

rzip(n, lambda, psi, recycle = FALSE)

pzip(q, lambda, psi, lower.tail = TRUE, log.p = FALSE, recycle = FALSE)

qzip(p, lambda, psi, lower.tail = TRUE, log.p = FALSE, recycle = FALSE)
```

Arguments

x, q	Vector of quantiles at which to evaluate the PMF and CDF, respectively. Should be non-negative integers.
------	--

lambda	Vector of means for the count portion of the zero-inflated Poisson distribution. Should be non-negative. NOTE: This is <i>not</i> the mean of the zero-inflated Poisson distribution; it is the mean of the Poisson component of the mixture distribution. See 'Details.'
psi	Vector of zero-inflation probabilities.
log, log.p	Logical indicating whether probabilities should be returned on log scale (for dzip and pzip), or are supplied on log-scale (for qzip).
recycle	Logical indicating whether to permit arbitrary recycling of arguments with unequal length. See 'Details' and 'Examples.'
n	Number of realizations from the distribution to generate
lower.tail	Logical indicating whether probabilities should be $Pr(X \leq x)$ or $Pr(X > x)$
p	Vector of probabilities at which to evaluate the quantile function.

Details

The zero inflated Poisson distribution is a mixture of a Poisson and a degenerate point-mass at 0. It has the form

$$\psi + (1 - \psi)(\lambda^x e^{-\lambda})/x!$$

, with mean $(1 - \psi)\lambda$. Thus, the parameter lambda above is the mean of the Poisson distribution that forms part of the zero-inflated distribution, *not* the mean of the ZIP distribution.

recycle – If FALSE (default), all arguments must have identical length, there can be two unique lengths for the arguments, provided that one of those lengths is 1. For example, lambda = c(1, 2, 3) and psi=.5 is acceptable because there are two unique lengths, and one of them is length 1. However, lambda=c(1,2,3) and psi=c(.5, .2) would fail, as there are two distinct lengths, none of which is 1. If TRUE, no additional checks (beyond those in base R's functions) are made to ensure that the argument vectors have the same length.

Value

dzip returns the mass function evaluated at x, pzip returns the CDF evaluated at q, qzip returns the quantile function evaluated at p, and rzip returns random variates with the specified parameters.

Author(s)

John Niehaus

References

Lambert, Diane. "Zero-inflated Poisson regression, with an application to defects in manufacturing." Technometrics 34.1 (1992): 1-14.

Examples

```
# Unequal lengths, but one of them is length 1, others are same length (3).
# No error.

x = c(1,2,3)
```

```

lambda = c(3,4,5)
psi = .1

dzip(x, lambda, psi)

# unequal lengths, at least one of them is not length 1,
# error

## Not run:

x = c(1,2,3)
lambda = c(3,4)
psi = .1

dzip(x, lambda, psi)

## End(Not run)

# unequal lengths, at least one of them is not length 1.
# but set recycle = T to permit arbitrary recycling.

x = c(1,2,3)
lambda = c(3,4)
psi = .1

dzip(x, lambda, psi, recycle=TRUE)

```

zi_test

He's (2019) test for zero-modification

Description

This is an implementation of He et al. (2019)'s test for zero-modification (discussed further in Tang & Tang (2019)). This is a test of zero-*modification* instead of *inflation*, because the test is capable of detecting both excessive or lack of zeros, but cannot determine the cause. For example, a mixed data generating process could be generating structural zeros, implying a zero-inflated distribution. However, overdispersion via a negative binomial may also result in excessive zeros. Thus, the test merely determines whether there are excessive (or lacking) zeros, but does not determine the process generating this pattern. That in mind, typical tests in the literature are inappropriate for zero-modified regression models, namely the Vuong, Wald, score, and likelihood ratio tests. See the references below for more information on this claim.

Usage

```
zi_test(model, alternative = "inflated")
```


Arguments

model	A model object of class <code>bizicount</code> or <code>glm</code> . If a <code>bizicount</code> model, then at least one margin must be specified as "pois". If a <code>glm</code> model, then the family must be <code>poisson</code> .
alternative	The alternative hypothesis. One of <code>c("inflated", "deflated", "both")</code> . These correspond to an upper tail, lower tail, or two-tailed test, respectively. Default is "inflated". Partial matching supported.

Details

The test compares the observed proportion of zeros in the data to the expected proportion of zeros under the null hypothesis of a Poisson distribution. This is done using estimating equations to account for the fact that the expected proportion is based on an estimated parameter vector, rather than the true parameter vector. The test statistic is

$$\hat{s} = 1/n \sum_i (r_i - \hat{p}_i)$$

where $r_i = 1$ if $y_i = 0$, otherwise $r_i = 0$, and $\hat{p} = dpois(0, \exp(X\hat{\beta})) = \hat{E}(r_i)$ is the estimated proportion of zeros under the assumption of a Poisson distribution generated with covariates X and parameter vector $\hat{\beta}$.

By the central limit theorem, $\hat{s} \sim AN(0, \sigma_s^2)$. However, estimating $\hat{\sigma}_s$ by a plug-in estimate using $\hat{\beta}$ is inefficient due to $\hat{\beta}$ being an random variable with its own variance. Thus, $\hat{\sigma}$ is estimated via estimating equations in order to account for the variance in $\hat{\beta}$.

See the references below for more discussion and proofs.

Author(s)

John Niehaus

References

- He, H., Zhang, H., Ye, P., & Tang, W. (2019). A test of inflated zeros for Poisson regression models. *Statistical methods in medical research*, 28(4), 1157-1169.
- Tang, Y., & Tang, W. (2019). Testing modified zeros for Poisson regression models. *Statistical Methods in Medical Research*, 28(10-11), 3123-3141.

Examples

```
set.seed(123)
n = 500
u = rpois(n, 3)
y1 = rzip(n, 12, .2) + u
y2 = rpois(n, 8) + u

# Single parameter test, covariates can be added though.
uni1 = glm(y1 ~ 1, family = poisson())
uni2 = glm(y2 ~ 1, family = poisson())

biv = bizicount(y1~1, y2~1, margins = c("pois", "pois"), keep = TRUE)
```

```
zi_test(uni1)
zi_test(uni2)

zi_test(biv)
```

Index

* datasets

terror, 23

bizicount, 2, 3, 10, 14, 19, 23, 33

bizicount-class, 8

bizicount-package, 2

createDHARMA, 2, 14, 15, 19

createTexreg, 10, 13

data.frame, 4, 17, 24

DHARMA, 2, 3, 14, 15, 19, 22, 23, 25

dzinb(zinb), 28

dzip(zip), 30

extract, 2, 3, 10, 13, 23

extract.bizicount, 2, 7, 10

extract.zicreg, 3, 12, 25, 26

family, 24

fitted, 25

formula, 4, 24

glm, 33

glm.fit, 25

make_DHARMA, 2, 7, 14

na.omit, 25

nbinom, 29

nlm, 5, 23, 25

optim, 23, 25

poisson, 33

predict, 25

predict.zicreg, 16

pzinb(zinb), 28

pzip(zip), 30

qzinb(zinb), 28

qzip(zip), 30

rzinb(zinb), 28

rzip(zip), 30

simulate, 3, 23

simulate.bizicount, 2, 14, 15, 18

simulate.zicreg, 3, 21, 25, 26

simulateResiduals, 19

terror, 23

texreg, 3, 9, 10, 13, 23, 25, 27

zi_test, 2, 3, 7, 32

zic.reg, 3, 13, 17, 22, 23

zicreg-class, 27

zinb, 28

zip, 30