

Package ‘disclap’

July 22, 2025

Type Package

Title Discrete Laplace Exponential Family

Version 1.5.1

Author Mikkel Meyer Andersen and Poul Svante Eriksen

Maintainer Mikkel Meyer Andersen <mikl@math.aau.dk>

Description The discrete Laplace exponential family for use in fitting generalized linear models.

License GPL-2

LazyLoad yes

NeedsCompilation no

Repository CRAN

Date/Publication 2022-01-27 12:10:09 UTC

Contents

Discrete Laplace distribution	1
Discrete Laplace exponential family	3
Discrete Laplace package	4
Index	5

Discrete Laplace distribution
Probability mass function, distribution function, and random generation for the discrete Laplace distribution with parameter $0 \leq p < 1$.

Description

Calculates the mass of observations from the discrete Laplace distribution.

Usage

```
ddisclap(x, p)
pdisclap(x, p, lower.tail = TRUE)
rdisclap(n, p)
```

Arguments

x	vector of observations
p	the parameter with $0 \leq p < 1$
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$.
n	number of observations to generate

Details

The probability mass function for the discrete Laplace distribution with parameter $0 < p < 1$ is given by $P(X = x) = \frac{1-p}{1+p}p^{|x|}$ for $x \in \mathbf{Z}$.

If x is a vector, then p must have either length 1 or the same length as x. If p has length 1, then the value will be reused for all values in x.

Value

'ddisclap' gives the probability mass, 'pdisclap' gives the distribution function, and 'rdisclap' generates random deviates.

Author(s)

Mikkel Meyer Andersen <mikl@math.aau.dk> and Poul Svante Eriksen

See Also

[DiscreteLaplace](#)

Examples

```
p <- 0.3
xs <- (-4):4
probd <- ddisclap(xs, p)
data.frame(xs, probd)
plot(xs, probd, type = "l", xlab = "x", ylab = "P(X = x; p)")
```

Discrete Laplace exponential family

Discrete Laplace exponential family

Description

Discrete Laplace exponential family for models such as a generalized linear model.

Usage

`DiscreteLaplace()`

Details

This family can be used in for example fitting a generalized linear model using the [glm](#) or [glm.fit](#) function.

Value

See [binomial](#) or [poisson](#)

Author(s)

Mikkel Meyer Andersen <mikl@math.aau.dk> and Poul Svante Eriksen

See Also

[glm](#) [glm.fit](#) [ddisclap](#) [binomial](#) [poisson](#)

Examples

```
xs <- abs(rdisclap(100, 0.1))
fit <- glm(xs ~ 1, family = DiscreteLaplace())
summary(fit)
theta <- as.numeric(coef(fit)[1])
mu <- DiscreteLaplace()$linkinv(theta)
p <- (sqrt(1 + mu^2) - 1) / mu
p
```

Discrete Laplace package

Discrete Laplace Family

Description

Discrete Laplace Family for models such as a generalized linear model.

Details

`DiscreteLaplace()` `ddisclap(x, p)` `pdisclap(x, p, lower.tail = TRUE)` `rdisclap(n, p)`

Author(s)

Mikkel Meyer Andersen and Poul Svante Eriksen

Maintainer: Mikkel Meyer Andersen <mikl@math.aau.dk>

See Also

[DiscreteLaplace](#) [ddisclap](#) [pdisclap](#) [rdisclap](#)

Index

- * **package**
 - Discrete Laplace package, [4](#)
- binomial, [3](#)
- ddisclap, [3](#), [4](#)
- ddisclap (Discrete Laplace distribution), [1](#)
- disclap (Discrete Laplace package), [4](#)
- disclap-package (Discrete Laplace package), [4](#)
- Discrete Laplace distribution, [1](#)
- Discrete Laplace exponential family, [3](#)
- Discrete Laplace package, [4](#)
- DiscreteLaplace, [2](#), [4](#)
- DiscreteLaplace (Discrete Laplace exponential family), [3](#)
- glm, [3](#)
- glm.fit, [3](#)
- pdisclap, [4](#)
- pdisclap (Discrete Laplace distribution), [1](#)
- poisson, [3](#)
- rdisclap, [4](#)
- rdisclap (Discrete Laplace distribution), [1](#)