

Package ‘edstan’

July 22, 2025

Type Package

Title Stan Models for Item Response Theory

Version 1.1.0

Date 2025-03-24

Maintainer Daniel C. Furr <danielcfurr@berkeley.edu>

Description Streamlines the fitting of common Bayesian item response models using Stan.

License BSD_3_clause + file LICENSE

Depends R (>= 2.10), rstan (>= 2.32.0)

Imports ggplot2, stats

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

LazyData true

RoxygenNote 7.3.2

Encoding UTF-8

NeedsCompilation no

Author Daniel C. Furr [aut, cre]

Repository CRAN

Date/Publication 2025-03-24 22:40:02 UTC

Contents

edstan-package	2
aggression	2
edstan_model_code	3
irt_data	4
irt_stan	5
labelled_integer	7
print_irt_stan	8
rescale_binary	9

rescale_continuous	10
spelling	10
stan_columns_plot	11

Index	13
--------------	-----------

edstan-package	<i>Stan for item response theory</i>
----------------	--------------------------------------

Description

edstan Streamlines the fitting of common Bayesian item response models using Stan.

Details

A typical workflow in fitting a model using **edstan** involves the following sequence:

- 1. [irt_data](#) to format the data,
- 2. [irt_stan](#) to fit a model,
- 3. [stan_columns_plot](#) to view sampling diagnostics, and
- 4. [print_irt_stan](#) to view parameter summaries.

The package includes six Stan item response models (see [irt_stan](#) for a list) and two example datasets ([aggression](#) and [spelling](#)). It is expected that once that a user is comfortable utilizing the preceding workflow with the predefined **edstan** models, they will go on to write their own Stan models.

Author(s)

Maintainer: Daniel C. Furr <danielcfurr@gmail.com>

aggression	<i>Verbal aggression data</i>
------------	-------------------------------

Description

Item response data regarding verbal aggression from 316 persons and 24 items. Participants were instructed to imagine four frustrating scenarios in which either another or oneself is to blame. For each scenario, they responded "yes", "perhaps", or "no" regarding whether they would react by cursing, scolding, and shouting. They also responded whether they would want to engage in those three behaviors, resulting in a total six items per scenario. An example item is, "A bus fails to stop for me. I would want to curse."

Usage

aggression

Format

A long-form data.frame (one row per item response) with the following columns:

person Integer person identifier.

item Integer item identifier.

poly Original, polytomous response. 0 indicates "no", 1 "perhaps", and 3 "yes".

dich Dichotomized response. 0 indicates "no" and 1 indicates "perhaps" or "yes".

description Brief description of the item.

anger Trait anger score for a person.

male Indicator for whether person is male.

do Indicator for whether item concerns actually doing the behavior instead of wanting to do it.

other Indicator for whether item concerns another person being to blame instead of self to blame.

scold Indicator for whether item concerns scolding behavior instead of cursing or shouting.

shout Indicator for whether item concerns shouting behavior instead of cursing or scolding.

Source

Vansteelandt, K. (2000). Formal models for contextualized personality psychology. Unpublished doctoral dissertation. K. U. Leuven, Belgium.

References

De Boeck, P. and Wilson, M. (2004) *Explanatory Item Response Models*. New York: Springer.

edstan_model_code	<i>Read and print the code for an edstan model</i>
-------------------	--

Description

This function reads a Stan file from the 'inst/extdata/' directory of the package, returning its contents invisibly while optionally printing them.

Usage

```
edstan_model_code(filename, print = TRUE)
```

Arguments

filename The name of the stan file.

print Whether to print the stan file contents. Default is 'TRUE'.

Value

Invisibly returns a character vector of the stan file contents.

Examples

```
# View the Stan code for the Rasch model
edstan_model_code("rasch_latent_reg.stan")
```

irt_data	<i>Create a Stan data list from an item response matrix or from long-form data.</i>
----------	---

Description

This function prepares item response data, creating a data list that may be passed to [irt_stan](#).

Usage

```
irt_data(
  response_matrix = matrix(),
  y = integer(),
  ii = integer(),
  jj = integer(),
  covariates = data.frame(),
  formula = NULL,
  integerize = TRUE,
  validate_regression = TRUE
)
```

Arguments

response_matrix	An item response matrix. Columns represent items and rows represent persons. NA may be supplied for missing responses. The lowest score for each item should be 0, with exception to rating scale models. y, ii, and jj should not be supplied if a response matrix is given.
y	A vector of scored responses for long-form data. The lowest score for each item should be 0, with exception to rating scale models. NAs are not permitted, but missing responses may simply be omitted instead. Required if response_matrix is not supplied.
ii	A vector indexing the items in y. This must consist of consecutive integers starting at 1. labelled_integer may be used to create a suitable vector. Required if response_matrix is not supplied.
jj	A vector indexing the persons in y. This must consist of consecutive integers starting at 1. labelled_integer may be used to create a suitable vector. Required if response_matrix is not supplied.
covariates	An optional data frame containing (only) person-covariates. It must contain one row per person or be of the same length as y, ii, and jj. If it contains one row per person, it must be in the same order as the response matrix (or unique(jj)). If it has a number of columns equal to the length of y, ii, and jj, it must be in

	the same order as <code>jj</code> (for example, it may be a subset of columns from the same data frame that contains <code>y</code> , <code>ii</code> , and <code>jj</code>).
<code>formula</code>	An optional formula for the latent regression that is applied to covariates. The left side should be blank (for example, <code>~ v1 + v2</code>). By default it includes only a model intercept, which then represents the mean of the person distribution. If set to <code>NULL</code> (default), then <code>covariates</code> is used directly as the design matrix for the latent regression.
<code>integerize</code>	Whether to apply <code>labelled_integer</code> to <code>ii</code> and <code>jj</code> . Defaults to <code>TRUE</code> , which should be the case unless the inputs are already consecutive integers.
<code>validate_regression</code>	Whether to check the latent regression equation and covariates for compatibility with the prior distributions for the coefficients. Defaults to <code>TRUE</code> and throws a warning if problems are identified.

Value

A data list suitable for `irt_stan`.

See Also

See `labelled_integer` for a means of creating appropriate inputs for `ii` and `jj`. See `irt_stan` to fit a model to the data list.

Examples

```
# For a response matrix ("wide-form" data) with person covariates:
spelling_list <- irt_data(response_matrix = spelling[, 2:5],
                        covariates = spelling[, "male", drop = FALSE],
                        formula = ~ rescale_binary(male))

# For long-form data (one row per item-person pair):
agg_list_1 <- irt_data(y = aggression$poly,
                    ii = aggression$item,
                    jj = aggression$person)

# Add a latent regression and use labelled_integer() with the items
agg_list_2 <- irt_data(y = aggression$poly,
                    ii = labelled_integer(aggression$description),
                    jj = aggression$person,
                    covariates = aggression[, c("male", "anger")],
                    formula = ~ 1 + rescale_continuous(male)*rescale_continuous(anger))
```

irt_stan

Fit an item response model with Stan

Description

This function initiates sampling for an edstan model.

Usage

```
irt_stan(data_list, model = "", ...)
```

Arguments

<code>data_list</code>	A Stan data list created with irt_data .
<code>model</code>	The file name for one of the provided .stan files, or alternatively, a user-created .stan file that accepts <code>data_list</code> as input data. The ".stan" file extension may be omitted. Defaults to either "rasch_latent_reg.stan" or "pcm_latent_reg.stan".
<code>...</code>	Additional options passed to stan . The usual choices are <code>iter</code> for the number of iterations and <code>chains</code> for the number of chains.

Details

The following table lists the models included in **edstan** along with the associated .stan files. These file names are given as the `model` argument.

Model	File
Rasch	<i>rasch_latent_reg.stan</i>
Partial credit	<i>pcm_latent_reg.stan</i>
Rating Scale	<i>rsm_latent_reg.stan</i>
Two-parameter logistic	<i>2pl_latent_reg.stan</i>
Generalized partial credit	<i>gpcm_latent_reg.stan</i>
Generalized rating Scale	<i>grsm_latent_reg.stan</i>

Three simplified models are also available: *rasch_simple.stan*, *pcm_simple.stan*, *rsm_simple.stan*. These are (respectively) the Rasch, partial credit, and rating scale models omitting the latent regression. There is no reason to use these instead of the models listed above, given that the above models allow for rather than require the inclusion of covariates for a latent regression. Instead, the purpose of the simplified models is to provide a straightforward starting point researchers who wish to craft their own Stan models.

Value

A [stanfit-class](#) object.

See Also

See [stan](#), for which this function is a wrapper. See [irt_data](#) for creating the data list. See [rescale_continuous](#) and [rescale_binary](#) for appropriately scaling latent regression covariates. See [print_irt_stan](#) and [print.stanfit](#) for ways of getting tables summarizing parameter posteriors.

Examples

```
## Not run:
# Fit the Rasch and 2PL models on wide-form data with a latent regression
```

```

spelling_list <- irt_data(response_matrix = spelling[, 2:5],
                        covariates = spelling[, "male", drop = FALSE],
                        formula = ~ rescale_binary(male))

rasch_fit <- irt_stan(spelling_list, iter = 2000, chains = 4)
print_irt_stan(rasch_fit, spelling_list)

twopl_fit <- irt_stan(spelling_list, model = "2pl_latent_reg.stan",
                    iter = 2000, chains = 4)
print_irt_stan(twopl_fit, spelling_list)

# Fit the rating scale and partial credit models without a latent regression
agg_list_1 <- irt_data(y = aggression$poly,
                    ii = aggression$description,
                    jj = aggression$person)

fit_rsm <- irt_stan(agg_list_1, model = "rsm_latent_reg.stan",
                  iter = 2000, chains = 4)
print_irt_stan(fit_rsm, agg_list_1)

fit_pcm <- irt_stan(agg_list_1, model = "pcm_latent_reg.stan",
                  iter = 2000, chains = 4)
print_irt_stan(fit_pcm, agg_list_1)

# Fit the generalized rating scale and partial credit models including
# a latent regression
agg_list_2 <- irt_data(y = aggression$poly,
                    ii = aggression$description,
                    jj = aggression$person,
                    covariates = aggression[, c("male", "anger")],
                    formula = ~ rescale_binary(male)*rescale_continuous(anger))

fit_grsm <- irt_stan(agg_list_2, model = "grsm_latent_reg.stan",
                  iter = 2000, chains = 4)
print_irt_stan(fit_grsm, agg_list_2)

fit_gpcm <- irt_stan(agg_list_2, model = "gpcm_latent_reg.stan",
                  iter = 2000, chains = 4)
print_irt_stan(fit_gpcm, agg_list_2)

## End(Not run)

```

Description

This takes vector and transforms it into a vector of consecutive integers, which has a lowest value of one, a maximum value equal to the number of unique values, and no gaps.

Usage

```
labelled_integer(x = vector())
```

Arguments

x A vector, which may be numeric, string, or factor.

Value

A vector of integers corresponding to entries in **x**. The lowest value will be 1, and the greatest value will equal the number of unique elements in **x**. The elements of the recoded vector are named according to the original values of **x**. The result is suitable for the **ii** and **jj** options for [irt_data](#).

Examples

```
x <- c("owl", "cat", "pony", "cat")
labelled_integer(x)

y <- as.factor(x)
labelled_integer(y)

z <- rep(c(22, 57, 13), times = 2)
labelled_integer(z)
```

print_irt_stan	<i>View a table of selected parameter posteriors after using irt_stan</i>
----------------	---

Description

This function prints a table summarizing the parameters for a fitted edstan model.

Usage

```
print_irt_stan(fit, data_list = NULL, ...)
```

Arguments

fit A stanfit-class object created by [irt_stan](#).

data_list An optional Stan data list created with [irt_data](#). If provided, the printed posterior summaries for selected parameters are grouped by item. Otherwise, ungrouped results are provided, which may be preferred, for example, for the Rasch or rating scale models.

... Additional options passed to [print](#).

Examples

```
# Make a suitable data list:
spelling_list <- irt_data(response_matrix = spelling[, 2:5],
                        covariates = spelling[, "male", drop = FALSE],
                        formula = ~ 1 + male)

## Not run:
# Fit a latent regression 2PL
twopl_fit <- irt_stan(spelling_list, model = "2pl_latent_reg.stan",
                    iter = 300, chains = 4)

# Get a table summarizing parameter posteriors
print_irt_stan(twopl_fit, spelling_list)

## End(Not run)
```

rescale_binary	<i>Rescale binary covariates as appropriate for edstan models</i>
----------------	---

Description

This function rescales a covariate to have a mean of zero and range (maximum - minimum) of one

Usage

```
rescale_binary(x)
```

Arguments

x A numeric vector, matrix, or data frame

Value

A numeric vector, matrix, or data frame with rescaled covariates having mean of zero and range (maximum - minimum) of one.

Examples

```
vec <- c(1, 3, 1, 3, 1)
rescale_binary(vec)

mat <- matrix(c(1, 3, 1, 3, 1), nrow = 5, ncol = 5)
rescale_binary(mat)
```

rescale_continuous	<i>Rescale continuous covariates as appropriate for edstan models</i>
--------------------	---

Description

This function scales a covariate to have a mean of zero and standard deviation of 0.5.

Usage

```
rescale_continuous(x)
```

Arguments

x	A numeric vector, matrix, or data frame
---	---

Value

A numeric vector, matrix, or data frame with rescaled covariates having mean of zero and standard deviation of 0.5.

Examples

```
vec <- rnorm(5, 100, 20)
rescale_continuous(vec)

mat <- matrix(rnorm(5*5, 100, 20), ncol = 5)
rescale_continuous(mat)
```

spelling	<i>Spelling data</i>
----------	----------------------

Description

Item response data regarding student spelling performance on four words: *infidelity*, *panoramic*, *succumb*, and *girder*. The sample includes 284 male and 374 female undergraduate students from the University of Kansas. Each item was scored as either correct or incorrect.

Usage

```
spelling
```

Format

A wide-form data.frame (one row per person) with the following columns:

male Indicator for whether person is male.

infidelity Indicator for whether person spelled *infidelity* correctly.

panoramic Indicator for whether person spelled *panoramic* correctly.

succumb Indicator for whether person spelled *succumb* correctly.

girder Indicator for whether person spelled *girder* correctly.

Source

Thissen, D., Steinberg, L. and Wainer, H. (1993). Detection of Differential Item Functioning Using the Parameters of Item Response Models. In *Differential Item Functioning*, edited by Holland. P. and Wainer, H., 67-114. Hillsdale, NJ: Lawrence Erlbaum.

stan_columns_plot	<i>View a plot of summary statistics after using irt_stan</i>
-------------------	---

Description

This function creates a figure summarizing parameter-level diagnostics such as R hat and effective sample size.

Usage

```
stan_columns_plot(fit, stat = "Rhat", ...)
```

Arguments

fit	A stanfit-class object created by irt_stan or stan .
stat	A string for the statistic from the summary method for a stanfit object to plot. The default is "Rhat" but could also be "n_eff" for the effective sample size.
...	Additional options (such as pars), passed to the summary method for a stanfit object. Not required.

Value

A ggplot object.

See Also

See [stan_rhat](#), which provides a histogram of Rhat statistics.

Examples

```
# Make a suitable data list:
spelling_list <- irt_data(response_matrix = spelling[, 2:5],
                          covariates = spelling[, "male", drop = FALSE],
                          formula = ~ 1 + rescale_binary(male))

## Not run:
# Fit a latent regression 2PL
twopl_fit <- irt_stan(spelling_list, model = "2pl_latent_reg.stan",
                     iter = 2000, chains = 4)

# Get a plot showing Rhat statistics
rhat_columns(twopl_fit)

# Get a plot showing number of effective draws
rhat_columns(twopl_fit, stat = "n_eff")

## End(Not run)
```

Index

* datasets

aggression, [2](#)

spelling, [10](#)

aggression, [2](#), [2](#)

edstan (edstan-package), [2](#)

edstan-package, [2](#)

edstan_model_code, [3](#)

irt_data, [2](#), [4](#), [6](#), [8](#)

irt_stan, [2](#), [4](#), [5](#), [5](#), [8](#), [11](#)

labelled_integer, [4](#), [5](#), [7](#)

print, [8](#)

print.stanfit, [6](#)

print_irt_stan, [2](#), [6](#), [8](#)

rescale_binary, [6](#), [9](#)

rescale_continuous, [6](#), [10](#)

spelling, [2](#), [10](#)

stan, [6](#), [11](#)

stan_columns_plot, [2](#), [11](#)

stan_rhat, [11](#)