

Package ‘minimax’

July 22, 2025

Type Package

Title The Minimax Distribution Family

Version 1.1.1

Date 2023-08-20

Author Bill Venables

Maintainer Bill Venables <Bill.Venables@gmail.com>

Description The minimax family of distributions is a two-parameter family like the beta family, but computationally a lot more tractable.

Imports stats

License GPL-2 | GPL-3

LazyLoad yes

NeedsCompilation no

Repository CRAN

Date/Publication 2023-08-20 05:02:32 UTC

Contents

minimax-package	1
minimax	2

Index	4
--------------	----------

minimax-package	<i>Minimax distribution family</i>
-----------------	------------------------------------

Description

Standard functions to calculate probabilities, densities and quantiles for the minimax family, and to generate pseudo-random values.

Author(s)

Bill Venables

Maintainer: Bill Venables <Bill.Venables@gmail.com>

References

See [this document](#) for a detailed discussion.

See Also

[punif](#), [pbeta](#).

Examples

```
p <- pminimax(0:10/10, 1:5, 2)
q <- qminimax(p, 1:5, 2)
(d <- dminimax(matrix(0.5, 2, 2), 1:4, 2:3))

set.seed(123)
r <- rminimax(letters, 2, 3)
```

minimax

Minimax distribution family

Description

Four short functions to provide density, cumulative probability, quantile and random generation computational facilities for the minimax family of distributions.

Usage

```
dminimax(x, a = 1, b = 1, log = FALSE)
pminimax(x, a = 1, b = 1)
qminimax(y, a = 1, b = 1)
rminimax(n, a = 1, b = 1)
```

Arguments

x	Numeric vector giving the values at which the densities or cumulative probabilities are to be calculated.
y	Numeric vector giving the values at which the quantiles are to be calculated. Values must be between 0 and 1.
n	The number of pseudo-random values to be generated. If <code>length(n) = 1</code> , it must be a non-negative number; if <code>length(n) > 1</code> , the value for <code>n</code> is taken to be <code>length(n)</code> .
a, b	Numeric vectors giving the parameters of the distribution. Values must be positive.
log	Logical scalar. Should the log-density be returned rather than the density itself?

Details

The minimax family distributions is a two-parameter with support $[0,1]$. It has properties very like the beta family, though is computationally much more tractable. Both beta and minimax families have the $\text{uniform}(0,1)$ distribution as a special case. For the minimax family, this is the default case.

This package provides the standard four functions for handling the distribution in R using the standard prefix naming convention.

The functions are vectorized with respect to the arguments x , y , a , and b , with short arguments recycled to match the length of any longer ones.

Value

A vector of density, probability, quantile or pseudo-random values, respectively. Shape and name attributes of the first argument are preserved in the result.

Note

The functions are all written in pure R code.

Author(s)

Bill Venables

References

See [this document](#) for a detailed discussion.

See Also

[punif](#), [pbeta](#).

Examples

```
p <- pminimax(0:10/10, 1:5, 2)
q <- qminimax(p, 1:5, 2)
(d <- dminimax(matrix(0.5, 2, 2), 1:4, 2:3))

set.seed(123)
(r <- rminimax(letters, 2, 3))
```

Index

* **distribution**

minimax, [2](#)

minimax-package, [1](#)

dminimax (minimax), [2](#)

minimax, [2](#)

minimax-package, [1](#)

pbeta, [2](#), [3](#)

pminimax (minimax), [2](#)

punif, [2](#), [3](#)

qminimax (minimax), [2](#)

rminimax (minimax), [2](#)