

# Package ‘newsmd’

July 22, 2025

**Title** Creation of NEWS.md File

**Version** 0.5.1

**Date** 2023-04-17

**Description** Adding updates (version or bullet points) to the NEWS.md file.

**License** MIT + file LICENSE

**URL** <https://github.com/Dschaykib/newsmd>

**BugReports** <https://github.com/Dschaykib/newsmd/issues>

**Depends** R (>= 3.3)

**Imports** R6

**Suggests** desc, knitr, lintr, rmarkdown, testthat

**VignetteBuilder** knitr

**Encoding** UTF-8

**Language** en-GB

**RoxygenNote** 7.2.3

**NeedsCompilation** no

**Author** Jakob Gepp [cre, aut]

**Maintainer** Jakob Gepp <jakob.gepp@yahoo.de>

**Repository** CRAN

**Date/Publication** 2023-04-17 21:30:03 UTC

## Contents

combine_dev . . . . .	2
get_version . . . . .	2
news . . . . .	3
newsmd . . . . .	5
<b>Index</b>	<b>6</b>

---

combine_dev	<i>Combining dev-versions into the next version</i>
-------------	---

---

**Description**

Combining dev-versions into the next version

**Usage**

```
combine_dev(text = "")
```

**Arguments**

text                    a string vector with the content of the get\_text method

**Value**

a string vector with the reduced NEWS.md text

---

get_version	<i>Retrieve the version number of a NEWS.md file</i>
-------------	--

---

**Description**

This function tries to extract the version number within a file. There are a few pitfalls:

\* If the word "version" is within the text but denotes a dependency it is still detected. \* If the files has a date before the version it will return the date instead of the version \* It is assumed, that the NEWS.md files is updated from the top. Ergo the latest version is the first one.

**Usage**

```
get_version(file, latest = TRUE)
```

**Arguments**

file                    a path to a file  
latest                   a Boolean, if TRUE (default) only the latest version is returned

**Value**

either a single string or a vector with version numbers

---

news

---

*Manipulate the NEWS.md file***Description**

Manipulate the NEWS.md file.

**Format**

An R6 class.

**Methods****Public methods:**

- `news$new()`
- `news$print()`
- `news$get_text()`
- `news$write()`
- `news$add_version()`
- `news$add_subtitle()`
- `news$add_bullet()`
- `news$clone()`

**Method** `new()`: Create a new news object.

*Usage:*

```
news$new(  
  text = c(paste0("## version ", version), "", "---", "", "### NEWS.md setup", "",  
    "- added NEWS.md creation with [newsmd](https://github.com/Dschaykib/newsmd)", ""),  
  version = "0.0.0.9000",  
  file = NULL  
)
```

*Arguments:*

`text` vector with context for the news.md file.

`version` current version of the package.

`file` a text file with the current news.md file. Use NULL to create new file.

*Returns:* A new 'news' object.

**Method** `print()`: Print a news object.

*Usage:*

```
news$print()
```

**Method** `get_text()`: Get the news object as a text.

*Usage:*

```
news$get_text()
```

*Returns:* The context of the news file.

**Method** write(): Write and save a news object.

*Usage:*

```
news$write(file = "NEWS.md", reduce_dev = FALSE)
```

*Arguments:*

file A path and file to where the news file is saved.

reduce\_dev A boolean, if TRUE dev version's points are combined into the next version

**Method** add\_version(): Adds a version line to a news object.

*Usage:*

```
news$add_version(x)
```

*Arguments:*

x A string with the version number.

**Method** add\_subtitle(): Adds a subtitle line to a news object.

*Usage:*

```
news$add_subtitle(x)
```

*Arguments:*

x A string with the subtitle.

**Method** add\_bullet(): Adds a bullet points to the last subtitle.

*Usage:*

```
news$add_bullet(x)
```

*Arguments:*

x A vector with the bullet points.

**Method** clone(): The objects of this class are cloneable with this method.

*Usage:*

```
news$clone(deep = FALSE)
```

*Arguments:*

deep Whether to make a deep clone.

## See Also

[newsmd](#)

## Examples

```
## Create a template
my_news <- news$new()
my_news$add_subtitle("improved things 1")
my_news$add_bullet("point 1")
my_news$add_bullet("point 2")
```

---

newsmd*Creating a NEWS.md file*

---

## Description

This is a convenience wrapper for `news$new()`. If you already have a NEWS file you can add it's path to `newsmd()`.

## Usage

```
newsmd(  
  file = NULL,  
  text = c(paste0("## version ", version), "", "---", "", "### NEWS.md setup", "",  
    "- added NEWS.md creation with [newsmd](https://github.com/Dschaykib/newsmd)", ""),  
  version = "0.0.0.9000"  
)
```

## Arguments

<code>file</code>	name of the NEWS file to load. If not given a new file <code>NEWS.md</code> is created.
<code>text</code>	a character scalar containing the initial text.
<code>version</code>	a character with the version in the format <code>major.minor.patch.dev</code> .

## Details

This functions creates a news object, which can be saved as the `NEWS.md` file with the internal method `write()`. One can add versions, subtitles and bullet points to the news.

If an existing `NEWS.md` file is given, the version is extracted with `get_version` and the dev part is bumped up.

## Examples

```
newsmd()
```

# Index

`combine_dev`, [2](#)

`get_version`, [2](#)

`news`, [3](#)

`newsmd`, [4](#), [5](#)