

Package ‘pgnorm’

July 23, 2025

Type Package

Title The p-Generalized Normal Distribution

Version 2.0

Date 2015-11-23

Author Steve Kalke

Maintainer Steve Kalke <steve.kalke@gmail.com>

Description Evaluation of the pdf and the cdf of the univariate, noncentral, p-generalized normal distribution. Sampling from the univariate, noncentral, p-generalized normal distribution using either the p-generalized polar method, the p-generalized rejecting polar method, the Monty Python method, the Ziggurat method or the method of Nardon and Pianca. The package also includes routines for the simulation of the bivariate, p-generalized uniform distribution and the simulation of the corresponding angular distribution.

License GPL (>= 2)

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2015-11-24 15:08:34

Contents

pgnorm-package	2
datasetpgnmp1	3
datasetpgnmp2	3
datasetpgnzig	4
dpgnorm	4
ppgnorm	5
rpgangular	6
rpgnorm	7
rpgnorm_montypython	8

rpgnorm_nardonpianca	9
rpgnorm_pgenpolar	9
rpgnorm_pgenpolarrej	10
rpgnorm_ziggurat	11
rpgunif	12
zigsetup	12

Index	14
--------------	-----------

pgnorm-package	<i>The p-Generalized Normal Distribution</i>
----------------	--

Description

The pgnorm-package includes routines to evaluate (cdf,pdf) and simulate the univariate p -generalized normal distribution with form parameter p , expectation $mean$ and standard deviation σ . The pdf of this distribution is given by

$$f(x, p, mean, \sigma) = (\sigma_p/\sigma) C_p \exp \left(- \left(\frac{\sigma_p}{\sigma} \right)^p \frac{|x - mean|^p}{p} \right),$$

where $C_p = p^{1-1/p}/2/\Gamma(1/p)$ and $\sigma_p^2 = p^{2/p} \Gamma(3/p)/\Gamma(1/p)$, which becomes

$$f(x, p, mean, \sigma) = C_p \exp \left(- \frac{|x|^p}{p} \right),$$

if $\sigma = \sigma_p$ and $mean = 0$. The random number generation can be realized with one of five different simulation methods including the p -generalized polar method, the p -generalized rejecting polar method, the Monty Python method, the Ziggurat method and the method of Nardon and Pianca. Additionally to the simulation of the p -generalized normal distribution, the related p -generalized uniform distribution on the p -generalized unit circle and the corresponding angular distribution can be simulated by using the functions "rpgunif" and "rpgangular", respectively.

Details

Package:	pgnorm
Type:	Package
Version:	2.0
Date:	2015-11-23
License:	GPL (>= 2)
LazyLoad:	yes

Author(s)

Steve Kalke <steve.kalke@googlemail.com>

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm(10,3)
```

datasetpgnmp1

Dataset 1 of the Monty Python method

Description

The dataset contains tail algorithm constants for sampling from the tail of the p -generalized normal distribution in context of a simulation of the p -generalized normal distribution with the Monty Python method.

Usage

```
data(datasetpgnmp1)
```

Examples

```
data(datasetpgnmp1)
```

datasetpgnmp2

Dataset 2 of the Monty Python method

Description

The dataset contains optimal rectangle widths in context of a simulation of the p -generalized normal distribution with the Monty Python method.

Usage

```
data(datasetpgnmp2)
```

Examples

```
data(datasetpgnmp2)
```

datasetpgnzig	<i>Dataset of the Ziggurat method</i>
---------------	---------------------------------------

Description

The dataset contains tail algorithm constants for sampling from the tail of the p -generalized normal distribution in context of a simulation of the p -generalized normal distribution with the Ziggurat method.

Usage

```
data(datasetpgnzig)
```

Examples

```
data(datasetpgnzig)
```

dpgnorm	<i>A function to evaluate the p-generalized normal density</i>
---------	---

Description

The function evaluates the density $f(x, p, mean, sigma)$ of the univariate p -generalized normal distribution according to

$$f(x, p, mean, \sigma) = (\sigma_p / \sigma) C_p \exp \left(- \left(\frac{\sigma_p}{\sigma} \right)^p \frac{|x - mean|^p}{p} \right),$$

where $C_p = p^{1-1/p} / 2 / \Gamma(1/p)$ and $\sigma_p^2 = p^{2/p} \Gamma(3/p) / \Gamma(1/p)$.

Usage

```
dpgnorm(y, p, mean, sigma)
```

Arguments

y	The real argument of the function.
p	A positive number expressing the form parameter of the distribution. The default is 2.
mean	A real number expressing the expectation of the distribution. The default is 0.
sigma	A positive number expressing the standard deviation of the distribution. The default is σ_p .

Value

A real number.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p-generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-dpgnorm(0, 3, 1, 2)
```

ppgnorm

*A function to evaluate the p-generalized normal cdf***Description**

The function evaluates the cdf of the univariate p -generalized normal distribution according to the density

$$f(x, p, mean, \sigma) = (\sigma_p/\sigma) C_p \exp \left(- \left(\frac{\sigma_p}{\sigma} \right)^p \frac{|x - mean|^p}{p} \right),$$

where $C_p = p^{1-1/p}/2/\Gamma(1/p)$ and $\sigma_p^2 = p^{2/p} \Gamma(3/p)/\Gamma(1/p)$.

Usage

```
ppgnorm(y, p, mean, sigma)
```

Arguments

- | | |
|-------|--|
| y | A real number, the argument of the function. |
| p | A positive number expressing the form parameter of the distribution. The default is 2. |
| mean | A real number expressing the expectation of the distribution. The default is 0. |
| sigma | A positive number expressing the standard deviation of the distribution. The default is σ_p . |

Value

A real number.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-ppgnorm(2,p=3)
```

rpgangular

A random number generator for the angular distribution

Description

The function simulates the univariate angular distribution corresponding to the p -generalized uniform distribution on the p -generalized unit circle.

Usage

```
rpgangular(n,p)
```

Arguments

n	The natural number of random variables to be simulated.
p	A positive number expressing the form parameter of the distribution. The default is 2.

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgangular(10000,3)
```

rpgnorm

*A random number generator for the p-generalized normal distribution***Description**

The function simulates the univariate p -generalized normal distribution by using one of the following methods: the p -generalized polar method (pgenpolar), the p -generalized rejecting polar method (pgenpolarrej), the Monty Python method (montypython), the Ziggurat method (ziggurat) and the method of Nardon and Pianca (nardonpianca).

Usage

```
rpgnorm(n, p, mean, sigma, method)
```

Arguments

n	The natural number of random variables to be simulated.
p	A positive number expressing the form parameter of the distribution. The default is 2. In case of the Monty Python method and the Ziggurat method, p can be chosen from $(1, \infty) \cup \{0.25, 0.45, 0.5, 0.6, 0.75\}$.
mean	A real number expressing the expectation of the distribution. The default is 0.
sigma	A positive number expressing the standard deviation of the distribution. The default is $\sigma_p = p^{1/p} \sqrt{\Gamma(3/p)/\Gamma(1/p)}$, the natural standard deviation of the p -generalized normal distribution.
method	A string expressing the method to be used for the simulation ("pgenpolar", "pgenpolarrej", "montypython", "ziggurat" or "nardonpianca"). The default is "nardonpianca".

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm(10000,3,method="pgenpolar")
```

rpgnorm_montypython	<i>A random number generator for the p-generalized normal distribution</i>
---------------------	---

Description

The function simulates the univariate, central, p -generalized normal distribution by using the Monty Python method.

Usage

```
rpgnorm_montypython(n,p)
```

Arguments

n	The natural number of random variables to be simulated.
p	A positive number expressing the form parameter of the distribution. The default is 2. In case of the Monty Python method, p can be chosen from $(1, \infty) \cup \{0.25, 0.45, 0.5, 0.6, 0.75\}$.

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm_montypython(10000,3)
```

rpgnorm_nardonpianca *A random number generator for the p -generalized normal distribution*

Description

The function simulates the univariate, central, p -generalized normal distribution by using the method of Nardon and Pianca.

Usage

```
rpgnorm_nardonpianca(n,p)
```

Arguments

<code>n</code>	The natural number of random variables to be simulated.
<code>p</code>	A positive number expressing the form parameter of the distribution. The default is 2.

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm_nardonpianca(10000,3)
```

rpgnorm_pgenpolar *A random number generator for the p -generalized normal distribution*

Description

The function simulates the univariate, central, p -generalized normal distribution by using the p -generalized polar method.

Usage

```
rpgnorm_pgenpolar(n,p)
```

Arguments

- | | |
|---|--|
| n | The natural number of random variables to be simulated. |
| p | A positive number expressing the form parameter of the distribution. The default is 2. |

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm_pgenpolar(10000,3)
```

rpgnorm_pgenpolarrej *A random number generator for the p -generalized normal distribution*

Description

The function simulates the univariate, central, p -generalized normal distribution by using the p -generalized rejecting polar method.

Usage

```
rpgnorm_pgenpolarrej(n,p)
```

Arguments

- | | |
|---|--|
| n | The natural number of random variables to be simulated. |
| p | A positive number expressing the form parameter of the distribution. The default is 2. |

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm_pgenpolarrej(10000,3)
```

rpgnorm_ziggurat	<i>A random number generator for the p-generalized normal distribution</i>
------------------	---

Description

The function simulates the univariate, central, p -generalized normal distribution by using the Ziggurat method.

Usage

```
rpgnorm_ziggurat(n,p,x)
```

Arguments

n	The natural number of random variables to be simulated.
p	A positive number expressing the form parameter of the distribution. The default is 2. In case of the Ziggurat method, p can be chosen from $(1, \infty) \cup \{0.25, 0.45, 0.5, 0.6, 0.75\}$.
x	(optional) A real vector containing the $2^8 - 1$ rightmost endpoints of the 2^8 ziggurat-rectangles.

Value

An n -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgnorm_ziggurat(10000,3)
```

rpgunif

A random number generator for the p -generalized uniform distribution

Description

The function simulates the bivariate, p -generalized uniform distribution on the p -generalized unit circle.

Usage

```
rpgunif(n,p)
```

Arguments

n The natural number of random vectors to be simulated.

p A positive number expressing the form parameter of the distribution. The default is 2.

Value

A real $n \times 2$ matrix.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p -generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-rpgunif(10000,3)
```

zigsetup

A function for setting up the Ziggurat.

Description

The function approximates the rightmost x-coordinates of the first $n-1$ rectangles defining the Ziggurat in case of the central, p -generalized normal distribution.

Usage

```
zigsetup(p, n, tol)
```

Arguments

p	A positive number expressing the form parameter of the distribution. The default is 2. In case of the Ziggurat method, p can be chosen from $(1, \infty) \cup \{0.25, 0.45, 0.5, 0.6, 0.75\}$.
n	The number of rectangles that build up the Ziggurat. The default is 2^8 .
tol	A positive number expressing the approximation accuracy of the function. The default is 10^{-9} .

Value

An $(n - 1)$ -dimensional, real vector.

Author(s)

Steve Kalke

References

S. Kalke and W.-D. Richter (2013). "Simulation of the p-generalized Gaussian distribution." Journal of Statistical Computation and Simulation. Volume 83. Issue 4.

Examples

```
y<-zigsetup(3,20,10^(-6))
```

Index

* **datasets**

- [datasetpgnmp1](#), [3](#)
- [datasetpgnmp2](#), [3](#)
- [datasetpgnzig](#), [4](#)

* **distribution**

- [dpgnorm](#), [4](#)
- [ppgnorm](#), [5](#)
- [rpgangular](#), [6](#)
- [rpgnorm](#), [7](#)
- [rpgnorm_montypython](#), [8](#)
- [rpgnorm_nardonpianca](#), [9](#)
- [rpgnorm_pgenpolar](#), [9](#)
- [rpgnorm_pgenpolarrej](#), [10](#)
- [rpgnorm_ziggurat](#), [11](#)
- [rpgunif](#), [12](#)
- [zigsetup](#), [12](#)

* **package**

- [pgnorm-package](#), [2](#)

[datasetpgnmp1](#), [3](#)

[datasetpgnmp2](#), [3](#)

[datasetpgnzig](#), [4](#)

[dpgnorm](#), [4](#)

[pgnorm \(pgnorm-package\)](#), [2](#)

[pgnorm-package](#), [2](#)

[ppgnorm](#), [5](#)

[rpgangular](#), [6](#)

[rpgnorm](#), [7](#)

[rpgnorm_montypython](#), [8](#)

[rpgnorm_nardonpianca](#), [9](#)

[rpgnorm_pgenpolar](#), [9](#)

[rpgnorm_pgenpolarrej](#), [10](#)

[rpgnorm_ziggurat](#), [11](#)

[rpgunif](#), [12](#)

[zigsetup](#), [12](#)