

Package ‘ukgasapi’

July 22, 2025

Title API for UK Energy Market Information

Version 0.21

Author Timothy Wong [aut, cre]

Maintainer Timothy Wong <timothy.wong@hotmail.co.uk>

Description Allows users to access live UK energy market information via various APIs.

Depends R (>= 3.0.0)

BugReports <https://github.com/timothywong731/ukgasapi/issues>

License GPL-2

Imports httr,XML

LazyData true

Suggests ggplot2, knitr, rmarkdown

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2020-11-06 16:50:02 UTC

Contents

bmrsIndoItsdo	2
dataItemExplorer	3
Index	6

bmrsIndoItsdo

BMRS Initial Demand Outturn API Service

Description

This function connects to the Elexon's BMRS API to retrieve Initial Demand Outturn (INDO) and Initial Transmission System Demand Out-Turn (ITSDO) data. Internet connection must be available.

Usage

```
bmrsIndoItsdo(
  fromdate,
  todate,
  apikey,
  batchsize = 60,
  apiurl = "https://api.bmreports.com/BMRS/INDOITSDO/v1"
)
```

Arguments

fromdate	A character object specifying the start date. Date is inclusive.
todate	A character object specifying the end date. Date is inclusive.
apikey	A character object specifying the API key. This is also known as scripting key on Elexon's website.
batchsize	An interger value indicating the batch size of each API call. (Number of days included in one call)
apiurl	A character object which points to the BMRS INDO/ITSDO API. Under most circumstances users do not have to change this. Default to 'https://api.bmreports.com/BMRS/INDOITSDO/v1'

Details

The function submits a request to the API. The response is in CSV format which function will parse internally and returns a R dataframe object. The data returned by this API is identical to the data displayed on BMRS dashboard <https://www.bmreports.com/bmrs/?q=demand/initialdemandoutturn>.

Value

A dataframe object containing API response data.

Author(s)

Timothy Wong, <timothy.wong@hotmail.co.uk>

References

- BMRS API and Data Push User Guide
<https://www.elexon.co.uk/documents/training-guidance/bsc-guidance-notes/bmrs-api-and-data-push>
- Scripting Guide
<https://www.elexonportal.co.uk/scripting>
- Initial Demand Outturn (INDO)
<https://www.bmreports.com/bmrs/?q=help/glossary#INDO>
- Initial Transmission System Demand Out-Turn (ITSDO)
<https://www.bmreports.com/bmrs/?q=help/glossary#ITSDO>

Examples

```
## Not run:
# Invoke the API (requires internet connection at this step)
response <- bmrsIndoItsdo(fromdate = "2020-01-01",
                          todate = "2020-01-10",
                          apikey = "your api key goes here")

# Visualise the results on a chart
library(ggplot2)
ggplot(response, aes(x=publishtime, y=value, colour=recordtype)) +
  geom_line()

## End(Not run)
```

dataItemExplorer

Data Item Explorer API

Description

This function connects to the UK National Grid's API for Data Item Explorer, which is a major data source for gas-related information. Internet connection must be available.

Usage

```
dataItemExplorer(
  dataitems,
  fromdate,
  todate,
  datatype = "gasday",
  latestflag = "Y",
  applicableforflag = "Y",
  batchsize = -1,
  apiurl = paste0("https://marketinformation.natgrid.co.uk/",
                  "MIPIws-public/public/publicwebservice.asmx")
)
```

Arguments

dataitems	A vector of characters containing data items to enquire via API.
fromdate	A character object specifying the start date. Date is inclusive.
todate	A character object specifying the end date. Date is inclusive.
datatype	A character object specifying the data type. Defaults to gasday
latestflag	A character object with length of one to specify whether to extract the latest data. This can either be Y or N. Defaults to Y.
applicableforflag	A character object with length of one to specify whether dates specified are 'applicable for' or 'applicable on'. This can either be Y or N where Y indicates 'applicable for'. Defaults to Y.
batchsize	An interger value indicating the batch size of each API call. To invoke a single API call, use zero or negative values.
apiurl	A character object which points to National Grid's SOAP API. Under most circumstances users do not have to change this. Default to 'http://marketinformation.natgrid.co.uk/MIPIws-public/public/publicwebservice.asmx'

Details

The function submits a request to the API using XML over SOAP protocol. The response is in XML format which function will parse internally and returns a R dataframe object.

Value

A dataframe object containing API response data.

Author(s)

Timothy Wong, <timothy.wong@hotmail.co.uk>

References

- Graphical User Interface for Data Item Explorer
<https://mip-prd-web.azurewebsites.net/DataItemExplorer>
- API specification
<https://marketinformation.natgrid.co.uk/MIPIws-public/public/publicwebservice.asmx?op=GetPublicationDataWM>

Examples

```
## Not run:
# Specify the data item(s) to enquire from API
dataitems <- c("Storage Injection, Actual",
              "Storage Withdrawal, Actual")

# Invoke the API (requires internet connection at this step)
response <- dataItemExplorer(dataitems,
```

```
                                fromdate = "2020-01-01",  
                                todate="2020-01-31")  
  
# Visualise the results on a chart  
library(ggplot2)  
ggplot(response,aes(x=ApplicableFor,y=Value,colour=PublicationObjectName)) +  
  geom_line()  
  
## End(Not run)
```

Index

`bmrsIndoItsdo`, [2](#)

`dataItemExplorer`, [3](#)