

Package ‘unsystation’

July 22, 2025

Type Package

Title Stationarity Test Based on Unsystematic Sub-Sampling

Version 0.2.1

Maintainer Haeran Cho <haeran.cho@bristol.ac.uk>

Description Performs a test for second-order stationarity of time series based on unsystematic sub-samples.

License GPL-2

Suggests RcppArmadillo

Imports Rcpp (>= 0.12.10), doParallel, foreach, iterators

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 7.3.1

Encoding UTF-8

NeedsCompilation yes

Author Haeran Cho [aut, cre]

Repository CRAN

Date/Publication 2025-04-04 21:30:02 UTC

Contents

unsys.station.test 1

Index 4

unsys.station.test	<i>A second-order stationarity of time series based on unsystematic sub-samples</i>
--------------------	---

Description

The function implements a stationarity test procedure, where the main statistic is obtained from measuring the difference in the second-order structure over pairs of randomly drawn intervals. Maximising the main statistics after AR Sieve bootstrap-based variance stabilisation, the test statistic is obtained which is reported along with the corresponding pair of intervals and the test outcome.

Usage

```
unsys.station.test(
  x,
  M = 2000,
  sig.lev = 0.05,
  max.scale = NULL,
  m = NULL,
  B = 200,
  eps = 5,
  use.all = FALSE,
  do.parallel = 0
)
```

Arguments

x	input time series
M	number of randomly drawn intervals
sig.lev	significance level between 0 and 1
max.scale	number of wavelet scales used for wavelet periodogram computation; max.scale = NULL activates the default choice (max.scale = round(log(log(length(x)), 2), 2))
m	minimum length of a random interval; m = NULL activates the default choice (m = round(sqrt(length(x))))
B	bootstrap sample size
eps	a parameter used for random interval generation, see the supplementary document of Cho (2016)
use.all	if use.all=TRUE, all M*M pairs of random intervals are considered in test statistic computation; if use.all=FALSE, only 10*M pairs are used; regardless, the whole M*M pairs are considered in test criterion generation
do.parallel	number of copies of R running in parallel, if do.parallel = 0, %do% operator is used, see also foreach

Value

intervals	a pair of intervals corresponding to the test statistic, exhibiting the most distinct second-order behaviour
test.stat	test statistic
test.criterion	test criterion
test.res	if test.res=TRUE, the null hypothesis of stationarity is rejected at the given significance level

References

H. Cho (2016) A second-order stationarity of time series based on unsystematic sub-samples. Stat, vol. 5, 262-277.

Examples

```
## Not run:  
x <- rnorm(200)  
unsys.station.test(x, M=1000)  
  
## End(Not run)
```

Index

`foreach`, [2](#)

`unsys.station.test`, [1](#)