

Package ‘wodds’

July 22, 2025

Type Package

Title Calculates Whisker Odds

Version 0.1.0

Description Descriptive statistics for large data tend to be low resolution on the tails. Whisker Odds generate a table of descriptive statistics for large data. This is the same as letter-values, but with an alternative naming of depths which allow for depths beyond 26. For a reference to letter-values see 'Heike Hofmann' and 'Hadley Wickham' and 'Karen Kafadar' (2017) <[doi:10.1080/10618600.2017.1305277](https://doi.org/10.1080/10618600.2017.1305277)>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.1.2

Imports dplyr, stats, magrittr, tibble, glue, purrr

URL <https://github.com/alexhallam/wodds>

BugReports <https://github.com/alexhallam/wodds/issues>

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Alex Hallam [aut, cre],
R. Cody Heimberger [ctb]

Maintainer Alex Hallam <alexhallam6.28@gmail.com>

Repository CRAN

Date/Publication 2022-04-15 10:50:02 UTC

Contents

get_depth_from_n	2
get_n_from_depth	2
make_wodd_name	3
raw_wodd	3
select_wodd_name_from_table	4
wodds	4
wodd_format	5

get_depth_from_n	<i>Get depth from sample size</i>
------------------	-----------------------------------

Description

Calculates the depth given a sample size and alpha level

Usage

```
get_depth_from_n(n, alpha = 0.05)
```

Arguments

n	an integer scalar sample size
alpha	alpha level such as 0.1, 0.05, 0.01. An alpha of 0.05 would be associated with a 95 percent confidence interval

Value

an integer depth

Examples

```
get_depth_from_n(1e4L, 0.05)
```

get_n_from_depth	<i>Get sample size from depth</i>
------------------	-----------------------------------

Description

Calculates the sample size needed given an alpha level and depth

Usage

```
get_n_from_depth(d, alpha = 0.05, conservative = TRUE)
```

Arguments

d	an integer depth
alpha	alpha level such as 0.1, 0.05, 0.01. An alpha of 0.05 would be associated with a 95 percent confidence interval
conservative	a bool. default is FALSE. If TRUE then a conservative (larger) sample size is returned.

Value

a float sample size

Examples

get_n_from_depth(7L, 0.01)

make_wodd_name	<i>make_wodd_name</i>
----------------	-----------------------

Description

make_wodd_name a private function

Usage

make_wodd_name(index)

Arguments

index int

Value

A vector

raw_wodd	<i>raw_wodd</i>
----------	-----------------

Description

raw_wodd a private function

Usage

raw_wodd(index)

Arguments

index int

Value

A vector

```
select_wodd_name_from_table
      select_wodd_name_from_table
```

Description

`select_wodd_name_from_table` a private function

Usage

```
select_wodd_name_from_table(index)
```

Arguments

<code>index</code>	<code>int</code>
--------------------	------------------

Value

A vector

Examples

```
select_wodd_name_from_table(1L)
```

<code>wodds</code>	<i>Calculate whisker odds</i>
--------------------	-------------------------------

Description

makes whisker odds

Usage

```
wodds(
  y,
  alpha = 0.05,
  include_tail_area = FALSE,
  include_outliers = FALSE,
  include_depth = FALSE
)
```

Arguments

- y A vector of values
- alpha the alpha level, such as 0.05 which is the compliment of the confidence interval, such as 0.95
- include_tail_area a binary. If true then include a column of tail area 2^i
- include_outliers a binary. If true include a column of outliers beyond the last wodd depth
- include_depth a binary. If true include a column indicating the depth of the letter value

Value

- A dataframe of wodds
- lower_value lower value
- wodd_name Name of wodd
- upper_value upper value

Examples

```
set.seed(42)
wodds(rnorm(1e4, 0, 1))
```

wodd_format	<i>wodd_format</i>
-------------	--------------------

Description

wodd_format a private function

Usage

```
wodd_format(wodd_name)
```

Arguments

- wodd_name string. "S0", "S1", "M". etc

Value

A string

Index

`get_depth_from_n`, [2](#)

`get_n_from_depth`, [2](#)

`make_wodd_name`, [3](#)

`raw_wodd`, [3](#)

`select_wodd_name_from_table`, [4](#)

`wodd_format`, [5](#)

`wodds`, [4](#)